



- Home
- eSpaces
- Solutions
- Doc API

IERatingEngineUI eSpace

[Back to eSpaces list](#)

1 Index

- 1 – Index
- 2 – Overview
- 3 – Implementation
 - 3.1 – Processes
 - 3.2 – UI Flows
 - 3.2.1 – UI Flows
 - 3.2.2 – Referenced UI Flows
 - 3.3 – Data Model
 - 3.3.1 – Entities
 - 3.3.2 – External Entities
 - 3.3.3 – Structures
 - 3.3.4 – External Structures
 - 3.3.5 – Static Entities
 - 3.4 – Actions
 - 3.4.1 – Client Actions
 - 3.4.2 – Referenced Client Actions
 - 3.4.3 – Server Actions
 - 3.4.4 – Referenced Server Actions
 - 3.4.5 – Service Actions
 - 3.4.6 – Referenced Service Actions
 - 3.5 – Integrations
 - 3.5.1 – SOAP
 - 3.5.2 – REST
 - 3.5.3 – SAP
 - 3.6 – References
 - 3.6.1 – Extensions
 - 3.7 – Runtime
 - 3.7.1 – Client Variables
 - 3.7.2 – Site Properties
 - 3.7.3 – Roles
 - 3.8 – Timers
 - 3.9 – Contents
 - 3.9.1 – Resources
 - 3.9.2 – Images
 - 3.9.3 – Scripts
 - 3.10 – Themes
 - 3.10.1 – Referenced Themes

2 Overview

eSpace Name	IERatingEngineUI
Description	
Database	
Application Server	
Is User Provider	No
User Provider eSpace	Users
Default Theme	
Default Screen	RatingCalculator
Splash Screen	
Global Exception Handler	
Default Transition	Fade
Server Request Timeout	1000

3 Implementation

3.1 Processes

No Processes to show...

3.2 UI Flows

3.2.1 UI Flows

- Layouts

No description available

Theme	–
-------	---

Blocks

	LayoutBase	Allows the creation of a custom layout.
	LayoutBlank	Adds a basic layout with a single placeholder.
	LayoutTopMenu	Adds a layout with the menu on the header, most used in applications with few menu items.
	LayoutSideMenu	Adds a layout with a menu on the side, most used in applications with several menu items.
	LayoutBaseSection	Adds a new section to your custom layout.

 MainFlow

No description available

Theme -

 OnException

No Description

 DocumentAPICheck

Title No title

Screen Actions

	DownloadFileOnClick	No Description
	PostOnClick	No Description
	GetFileUrlOnClick	No Description
	PostJobOnClick	No Description

 H3Test

Title No title

Screen Actions

	CallH3OnClick	No Description
---	---------------	----------------

 RatingCalculator

Title No title

Screen Actions

	Checkbox1OnChange	No Description
	CountryDropdownOnAfterFetch	No Description
	ExcessLibility	No Description
	Dropdown4OnChange	No Description
	WildfireOnChange	No Description
	Input_DALOnChange	No Description
	Flood	No Description
	RefreshFinalPremium	No Description
	WindOnChange	No Description
	SinckholeOnChange	No Description
	Checkbox2OnChange	No Description
	Earthquake	No Description
	PhysicalDamage	No Description

Data Actions

	CountryDropdown	No Description
	GetRating2	No Description
	GetRatingPercentage	No Description
	PhysicalDamagedeductible	No Description
	TypeOfPlan	No Description
	ExcessScheduledBlanket	No Description
	Eathquake	No Description
	StateDropdown	No Description
	AmountOfLiabilityCoverage	No Description
	CoveredLiabilitySelfInsuredRetention	No Description
	Flood	No Description

 Common

Screens and web block common to the whole app

Theme -

 OnException

No Description

 Login

Screen where users login.

Title No title

Screen Actions

	Login	No Description
	ForgotPassword	No Description
	OnInitialize	No Description

 InvalidPermissions

Screen where users will be redirected when they have invalid permissions.

Title	No title
-------	----------

Blocks

	UserInfo	Displays the currently logged in user and allows to log out. If no user is logged in, it links to the login screen.
	Menu	Navigation element with links to the main screens of your application.
	ApplicationTitle	Contains your application's title and logo.
	MenuIcon	Clickable icon that allows opening the menu on small screens.

External Sites

	RedirectToURL
---	---------------

3.3 Data Model

3.3.1 Entities

No items to show...

3.3.2 External Entities

Name	Owner eSpace	Description
	HighchartModules	OutSystemsCharts
	SeriesType	OutSystemsCharts
	LegendPosition	OutSystemsCharts
	ValuesType	OutSystemsCharts
		Set how the chart labels are handled to be displayed on the chart. The type of the values can be: - Integer: the labels will be displayed as integer numbers. - Decimal: the labels will be displayed as decimal numbers. - Datetime: the labels will be displayed as datetimes. - Text: the labels will be displayed as text and treated as categories. By default, the type is Text.
	LegendLayout	OutSystemsCharts
	StackingType	OutSystemsCharts
		The way to plot multiple data series on Area, Bar, or Column charts: - 'NoStacking': plot data series side by side to compare them; - 'Stacked': plot data series stacked to show their contribution to a total; - 'Stacked100Percent': plot data series stacked to show their percentage in a total.
	AxisValuesType	OutSystemsCharts
	Entity_Record	(System)
		Records for each static entity defined in Service Studio. Older records are kept as inactive.
	User	(System)
		End-user of the applications. Shared between eSpaces with the same user provider (defined in Service Studio).
	Entity_Attr	(System)
		Attributes for each entity defined in Service Studio. Old attributes are kept as inactive.
	Entity	(System)
		Entities defined in Service Studio. Older entities defined in Service Studio are kept as inactive.
	Espace_Entity	(System)
		Entities referred by each eSpace as defined in Service Studio add/remove references.
	AnimationType	OutSystemsUI
		Contains different types of element animations.
	Speed	OutSystemsUI
		Sets animation speed settings.
	SideMenuBehavior	OutSystemsUI
		Sets the side menu animation behavior.
	Gradient	OutSystemsUI
		Contains type of gradients to be applied on the Progress patterns.
	Size	OutSystemsUI
		Contains different type of sizes.
	DeviceResponsive	OutSystemsUI
		Contains different responsive behaviors according to device screen size.
	GutterSize	OutSystemsUI
		Contains different sizes of gutter.
	Month	OutSystemsUI
		Contains the list of available months.
	DatePickerLanguage	OutSystemsUI
		Used to define the DatePicker default language.
	Orientation	OutSystemsUI
		Different orientations.
	DatePickerTimeFormat	OutSystemsUI
		Used to configure if the calendar is DateTime 12/24h type or if is Date type.
	AccordionIconType	OutSystemsUI
		Set of icons shown in of the AccordionItem
	Direction	OutSystemsUI
		Sets the direction: left or right.
	BreakColumns	OutSystemsUI
		Different ways of breaking the columns.
	Shape	OutSystemsUI
		Contains different types of shapes.
	StackedCardsPosition	OutSystemsUI
		Sets the position of elements in a Stacked Cards pattern.
	CarouselDirection	OutSystemsUI
		Sets the direction in which the Carousel moves.
	Autoplay	OutSystemsUI
		Contains different autoplay speed settings on elements and animations.
	Position	OutSystemsUI
		Contains different element alignment types.
	Trigger	OutSystemsUI
		Contains different triggers for the patterns behavior.
	Space	OutSystemsUI
		Sets element spacing sizes.
	Alert	OutSystemsUI
		Different types of alert messages
	FloatingPosition	OutSystemsUI
		Contains different element position types.
	BooleanTypes	OutSystemsUI
		Used in the context of Providers Extensibility.
	MenuAction	OutSystemsUI
		Sets the menu behavior for devices with small screens.
	AccordionIconPosition	OutSystemsUI
		Sets the position of the icon in a Accordion Item pattern.
	MessageStatus	OutSystemsUI
		Identify if the message was Received, Sent or Read.
	ScrollbarStyle	OutSystemsUI
		Contains different scrollbar styles.
	Color	OutSystemsUI
		Different colors available.
	ColumnBreak	OutSystemsUI
		Contains different types of column formatting.
	Steps	OutSystemsUI
		Contains different types of status for steps in a sequential process.
	CarouselNavigation	OutSystemsUI
		Sets the navigation type of the Carousel.
	VideoState	OutSystemsUI
		The state of the video.
	DatePickerWeekDay	OutSystemsUI
		Used to define which week day should be displayed first.
	MapErrors	OutSystemsMaps
		Static entity with the available Maps errors.
	Type	OutSystemsMaps
		Set the travel mode to be viewed on the map.

Name	Owner eSpace	Description
		Set the map type to be applied.
 MapEventTriggered	OutSystemsMaps	Static entity with the available Map events that can be triggered.
 Style	OutSystemsMaps	Set the theme to be applied to the map.
Set the theme to be applied to the map.		

3.3.3 Structures

PremiumStructure

No Description

Attributes

Attribute	Description	Type	Length	Decimals	Default	Mandatory
 BasePremium		PremiumValues				
 IncludeWildfire		PremiumValues				
 IncludeWind		PremiumValues				
 IncludeSinkhole		PremiumValues				
 ExcessScheduledBlankedCoveredPL		PremiumValues				
 Earthquake		PremiumValues				
 Flood		PremiumValues				
 ResidentialWorkerNF		PremiumValues				
 SmallScalefarmingEndorsement		PremiumValues				
 LandlordEndorsement		PremiumValues				
 HomeOfficeEndorsement		PremiumValues				
 PolicyFee		PremiumValues				
 PremiumWithoutTaxes		PremiumValues				
 Firetax		PremiumValues				
 OtherThanFireTax		PremiumValues				
 StampingFee		PremiumValues				
 PhysicalDamageDeductible		PremiumValues				
 AmountOfLiability		PremiumValues				
 CoveredLiability		PremiumValues				

PremiumValues

No Description

Attributes

Attribute	Description	Type	Length	Decimals	Default	Mandatory
 BaseValue		Long Integer				
 StandardValue		Long Integer				
 Preferredvalue		Long Integer				

RatingForm

No Description

Attributes

Attribute	Description	Type	Length	Decimals	Default	Mandatory
 State		Text				
 County		Text				
 DAL		Long Integer				
 AppurtenantStructureAssetsLimit		Long Integer				
 PersonalAssetsLimit		Long Integer				
 DwellingOccupancy		Long Integer				
 TotalInsuredValues		Long Integer				
 PhysicalDamageDeductible		Long Integer				
 AmountOfLiabilityCoverage		Long Integer				
 CoveredLiabilitiesselfInsured		Long Integer				
 ExcessScheduledBlanket		Text				
 Earthquake		Text				
 Flood		Text				
 ResidentWorkerNoFault		Text				
 SmallScaleFarmingEndorsement		Text				
 LandlordEndorsement		Text				
 HomeOfficeEndorement		Text				
 PolicyFee		Text				
 PremiumWithoutTaxes		Text				
 CoverageLevel		Integer				

Attribute	Description	Type	Length	Decimals	Default	Mandatory
 FireTax		Text				
 OtherThanFireTax		Text				
 StampingFree		Text				

 Structure1
No Description

Attributes

Attribute	Description	Type	Length	Decimals	Default	Mandatory
 Link		Text				

 HB
No Description

 LimitCoverage
No Description

Attributes

Attribute	Description	Type	Length	Decimals	Default	Mandatory
 DwellingLimit		Text				
 AppurtenantStructure		Text				
 PersonalAssets		Text				
 OccupancyDisruption		Text				
 TotalInsuredValue		Text				
 PhysicaldamageDeductible		Text				
 CoverageLevel		Text				
 AmountOfLiabilityCoverage		Text				

3.3.4 External Structures

Name	Owner eSpace	Description
 XAxisGridLinesStyling	OutSystemsCharts	Define the styles for the vertical lines of the chart.
 SeriesStylingOptionalConfigs	OutSystemsCharts	Define the optional styles for a given serie of the chart.
 ChartExportMenuOptions	OutSystemsCharts	List of options that can be added to the export menu. For each option, it's possible to set if it's part o
 YAxisStyling	OutSystemsCharts	Define the styles for the Y axis of the chart.
 XAxisOptionalConfigs	OutSystemsCharts	Set additional parameters to customize the XAxis behavior and functionality.
 OptionalConfigs	OutSystemsCharts	Set additional parameters to customize the Chart behavior and functionality.
 SeriesStylingMarker	OutSystemsCharts	Define the styles for the marker inside a specific serie of the chart.
 YAxisGridLinesStyling	OutSystemsCharts	Define the styles for the horizontal lines of the chart.
 XAxisStyling	OutSystemsCharts	Define the styles for the X axis of the chart.
 ChartExportOption	OutSystemsCharts	Define the chart export options.
 AxisLabel	OutSystemsCharts	Holds the configurations available for an axis label.
 PropertyValue	OutSystemsCharts	Structure used for charts extensibility with the property path and its value.
 ChartLegendStyling	OutSystemsCharts	Define the styles for the legend of the chart.
 SeriesStyling	OutSystemsCharts	Define the styles for a given series of the chart.
 ChartExportOptionalConfigs	OutSystemsCharts	Define the optional styles for chart export.
 ErrorMessage2	OutSystemsCharts	Return message from actions.
 ChartLegendOptionalConfigs	OutSystemsCharts	Set additional parameters to customize the chart series legend behavior and functionality.
 YAxisOptionalConfigs	OutSystemsCharts	Set additional parameters to customize the YAxis behavior and functionality.
 DataPoint	OutSystemsCharts	Information to plot a data point on the chart.
 ListItems	IERatingEngine	
 HTTPHeader	ardoHTTP	Represents an HTTP header.
 NotificationOptionalConfigs	OutSystemsUI	Group of optional configurations for the Notification block.
 VideoOptionalConfigs	OutSystemsUI	Video optional internal configurations
 VirtualSelectConfigs	OutSystemsUI	Structure with all configs supported by the provider.
 MonthYear	OutSystemsUI	Structure with information about the name month and corresponding year.
 FlatpickrConfigs	OutSystemsUI	Structure with all configs supported by the provider.
 TabsOptionalConfigs	OutSystemsUI	Group of optional configurations for the Tabs block.
 ProgressCircleOptionalConfigs	OutSystemsUI	Group of optional configurations for the ProgressCircle block.
 ProgressBarOptionalConfigs	OutSystemsUI	Group of optional configurations for the ProgressBar block.
 GradientColor	OutSystemsUI	
 ErrorMessage	OutSystemsUI	Return message from actions.
 RangeSliderOptionalConfigs	OutSystemsUI	Group of optional configurations for the RangeSlider block.
 DatePickerOptionalConfigs	OutSystemsUI	DatePicker optional internal configurations
 BulkActions	OutSystemsUI	Supports tables with multiple checkboxes and allows selecting them in bulk.
 VideoCaptions	OutSystemsUI	Video captions information
 TimePickerOptionalConfigs	OutSystemsUI	DatePicker optional internal configurations
 SlideConfigs	OutSystemsUI	Structure with all configs supported by the provider.
 DropdownOptionalConfigs	OutSystemsUI	DropdownSearch optional configurations
 DropdownTagsOptionalConfigs	OutSystemsUI	DropdownTags optional configurations

Name	Owner eSpace	Description
 DeviceConfiguration	OutSystemsUI	Structure used for the customization of the Device Detection.
 DropdownItem	OutSystemsUI	Strcuture used on DropdownSearch and DropdownTag blocks.
 NoUISliderConfigs	OutSystemsUI	Structure with all configs supported by the provider.
 MonthOrderYear	OutSystemsUI	Structure with information about a month and corresponding year. For each month, it contains inform
 CarouselOptionalConfigs	OutSystemsUI	Group of optional configurations for the Carousel block.
 DropdownOption	OutSystemsUI	Structure used on Dropdown option items.
 NoUISliderConfigs_Range	OutSystemsUI	
 DatePickerRangeOptionalConfigs	OutSystemsUI	DatePickerRange optional internal configurations
 SplideProviderClasses	OutSystemsUI	Structure that will help build the classes list in SplideConfigs supported by the provider.
 CarouselItems	OutSystemsUI	Number of visible Carousel items at the same time on each slide.
 SplideProvideri18n	OutSystemsUI	Structure that will allow you to modify all texts used in the carousel for the sake of accessibility in Spl
https://splidejs.com/guides/i18n/		

3.3.5 Static Entities

No Entites to show...

3.4 Actions

3.4.1 Client Actions

This folder is empty.

3.4.2 Referenced Client Actions

Name	Owner	Description
 UpdateChartColorScheme	OutSystemsCharts	A list of color values to use for the chart. Some of the formats accepted are: html, rgb, rgba and he
 SetHighchartsSeriesConfigs	OutSystemsCharts	Extend the properties of a series of a chart with additional Highcharts configurations. Due to security reasons, configurations/properties using callback functions, objects (e.g. arrays) ca Check all Highharts chart properties at: https://api.highcharts.com/highcharts/series
 SetHighchartsXAxisConfigs	OutSystemsCharts	Extend the properties of the x-axis of a chart with additional Highcharts configurations. Due to security reasons, configurations/properties using callback functions, objects (e.g. arrays) ca Check all Highharts chart properties at: https://api.highcharts.com/highcharts/xAxis
 SetHighchartsYAxisConfigs	OutSystemsCharts	Extend the properties of the y-axis of a chart with additional Highcharts configurations. Due to security reasons, configurations/properties using callback functions, objects (e.g. arrays) ca Check all Highharts chart properties at: https://api.highcharts.com/highcharts/yAxis
 SetHighchartsChartConfigs	OutSystemsCharts	Extend the properties of the chart blocks with additional Highcharts configurations. Due to security reasons, configurations/properties using callback functions, objects (e.g. arrays) ca Check all Highcharts chart properties at: https://api.highcharts.com/highcharts/
 ListAll	(System)	Determines if all the elements in the list satisfy the given condition.
 ListFilter	(System)	Returns a new list with the elements from the List parameter satisfying the given condition.
 ListInsert	(System)	Inserts an element in a specific position of a list.
 ListIndexOf	(System)	Returns the position of the first element of the List parameter that satisfies the given condition, or
 ListRemove	(System)	Removes an element from a specific position of a list.
 ListAppend	(System)	Adds an element to the end of a list.
 ListClear	(System)	Removes all elements from a list.
 ListSort	(System)	Sorts the elements of the List parameter by the given criteria.
 ListAppendAll	(System)	Adds the elements of the source list to the end of the destination list.
 ListAny	(System)	Determines if any of the elements in the list satisfies the given condition.
 ListDuplicate	(System)	Duplicates the elements of a list into another list.
 SetCurrentLocale	(System)	Set the locale to change your app's display language.
 SetRangeSliderIntervalValue	OutSystemsUI	Set a value on the RangeSliderInterval.
 AccordionItemExpand	OutSystemsUI	Opens an AccordionItem with a given identifier.
 OverflowMenuOpen	OutSystemsUI	Opens a OverflowMenu with a given identifier.
 VideoJumpToTime	OutSystemsUI	Jump to a specific time of a Video with a given identifier.
 MoveElement	OutSystemsUI	Action that moves elements on the DOM tree. Define the WidgetID of the element to be moved and Example: \$actions.MoveElement(\$parameters.WidgetId, ".active-screen .screen");
 DropdownServerSideClearValidation	OutSystemsUI	Clears the validation style of a DropdownServerSide with a given identifier.
 DropdownTogglePopup	OutSystemsUI	Enables or disables the default behavior of Dropdowns (DropdownTags or DropdownSearch) of ope
 ConfigureOfflineDataSync	OutSystemsUI	Offline data synchronization settings.
 DropdownServerSideClose	OutSystemsUI	Closes the options list of a DropdownServerSide block with a given identifier.
 MenuReady	OutSystemsUI	Pre-defined action to prepare your menu for reactive and native applications.
 SetLang	OutSystemsUI	Use this action to specify the language of the element's content. E.g. "en"
 SetNoUISliderConfigs	OutSystemsUI	Use this action on the Initialized event of the RangeSlider Pattern, to set additional configs support Use this link to check all available configs: https://refreshless.com/nouislider/slider-options/
 IsWebApp	OutSystemsUI	Returns true if using a WebApp Template.
 ToggleTextSpacing	OutSystemsUI	Use this action to increase the letter spacing, word spacing and line-height across the application
 DropdownClearValidation	OutSystemsUI	Clears the validation style of a Dropdown (DropdownTags or DropdownSearch) with a given identifi
 TimePickerUpdateTime	OutSystemsUI	Update the selected time shown in a given TimePicker.
 SetRangeSliderValue	OutSystemsUI	Set a value on the RangeSlider.
 StartOfflineDataSync	OutSystemsUI	This action starts the offline data synchronization in background.
 StackedCardsSwipeTop	OutSystemsUI	Call this action to swipe active card to top. You need to set the Stacked Cards ID (Widget Id).
 SetMenuIcon	OutSystemsUI	Changes the menu icon automatic behavior.
 CarouselGoTo	OutSystemsUI	Set the item that Carousel will go to.

Name	Owner	Description
 NotificationOpen	OutSystemsUI	Shows a Notification with a given identifier.
 RangeSliderEnable	OutSystemsUI	Method that will set RangeSlider with given RangeSlider ID as Enabled.
 CarouselToggleDrag	OutSystemsUI	Enable the drag to navigate between items.
 LayoutDestroy	OutSystemsUI	Pre-defined actions to properly destroy layout for reactive and native applications.
 SidebarToggleSwipe	OutSystemsUI	Use this action to enable/disable the Sidebar swipe actions on Native Apps. By default, the swipe actions are disabled.
 SetCarouselDirection	OutSystemsUI	Set the direction in which the carousel is sliding when it is automatically looping (Loop). By default, the carousel loops in the forward direction.
 SubmenuClose	OutSystemsUI	Action to close the Submenu block.
 SetMenuListeners	OutSystemsUI	Makes the menu accessibility-ready.
 ResetRangeSlider	OutSystemsUI	Resets the RangeSlider value to the StartingValue.
 DropdownServerSideOpen	OutSystemsUI	Opens the options list of a DropdownServerSide block with a given identifier.
 BinaryToURLImage	OutSystemsUI	Generates an image URL from a binary file. This action can be used to generate the URI to be used in the image block.
 AccordionExpandAll	OutSystemsUI	Function to expand all the collapsed items of a given accordion.
 SetMenuAttributes	OutSystemsUI	Supports the items accessible on the menu.
 ResetRangeSliderInterval	OutSystemsUI	Resets the RangeSlider value to the IntervalStart and IntervalEnd values.
 UnsetFlatpickrEvent	OutSystemsUI	Remove an event handler from a given DatePicker block.
 SetProgressBarValue	OutSystemsUI	Set a value on the Progress Bar.
 SetSplideEvent	OutSystemsUI	Use this action on the Initialized event of the Carousel Pattern, to set additional configs supported by Splide.js.
 SetRangeSliderChangeOnDragEnd	OutSystemsUI	Use this link to check all available configs: https://splidejs.com/v3/guides/events/#event-list Use this action on the Initialize event or on the Screen's OnReady event. By using this action, the change events will only be triggered when the user releases the slider. Tip: if you're refreshing a query based on the value of the slider, we recommend using this action.
 SidebarClickOutsideToClose	OutSystemsUI	Use this action to enable/disable the click outside to close the Sidebar.
 FeedbackMessageClose	OutSystemsUI	Closes the FeedbackMessage that is currently open.
 TimePickerOpen	OutSystemsUI	Opens a TimePicker with a given identifier.
 FocusFirstInvalidInput	OutSystemsUI	Set the focus on the first invalid input of the screen. Due to the unsupported scrollend event on Safari, this action is not supported on that browser.
 AccordionCollapseAll	OutSystemsUI	Function to collapse all the expanded items of a given accordion.
 RangeSliderDisable	OutSystemsUI	Method that will set RangeSlider with given RangeSlider ID as Disabled.
 TimePickerClear	OutSystemsUI	Cleans a TimePicker with a given identifier.
 MonthPickerClear	OutSystemsUI	Cleans a MonthPicker with a given identifier.
 CarouselNext	OutSystemsUI	Use to move the Carousel to the next item.
 CarouselDisableOnRender	OutSystemsUI	Prevents the Carousel block from auto-updating every time that there's a change on the Carousel items. This action can be used in combination with the CarouselEnableOnRender action (for instance, before the Carousel is rendered).
 ToggleSideMenu	OutSystemsUI	By default, the Carousel auto-updates itself. Expands the menu.
 AccordionItemCollapse	OutSystemsUI	Closes an AccordionItem with a given identifier.
 OverflowMenuEnable	OutSystemsUI	Sets a OverflowMenu with given identifier as enabled.
 TooltipOpen	OutSystemsUI	Action to open the Tooltip block.
 AddFavicon	OutSystemsUI	Add a favicon to your web application by providing the icon's URL. This action should be used in the Layout OnReady event or on an OnApplicationStart event. Note: This action is only compatible with Chrome, Firefox and Edge.
 FlipContentFront	OutSystemsUI	Shows the front of the FlipContent.
 DatePickerDisableWeekDays	OutSystemsUI	Disable one or more days of the week on a given DatePicker. Note: – Due to a provider issue, when using this action on the DatePickerRange, the component behaves differently than expected.
 ProgressApplyGradient	OutSystemsUI	Use to apply a gradient to the ProgressBar or ProgressCircle.
 SidebarOpen	OutSystemsUI	Action to open the Sidebar block.
 SetVirtualSelectConfigs	OutSystemsUI	Use this action on the Initialized event of the Dropdown (DropdownTags or DropdownSearch) block to set additional configs supported by Virtual Select.
 SetFlatpickrConfigs	OutSystemsUI	Use this link to check all available configs: https://sa-si-dev.github.io/virtual-select/#/properties Use this action on the Initialized event of the DatePicker Pattern, to set additional configs supported by Flatpickr.
 DropdownEnable	OutSystemsUI	Use this link to check all available configs: https://flatpickr.js.org/options/ Sets a Dropdown (DropdownTags or DropdownSearch) with given identifier as enabled.
 DropdownServerSideDisable	OutSystemsUI	Sets a DropdownServerSide with given identifier as disabled.
 SkipToContent	OutSystemsUI	Action used on OutSystems UI layouts, to allow the user to skip the navigation elements on the screen. By default, the MainContentWrapper.Id is used. Use the targetId parameter to set a custom target.
 ListItemHint	OutSystemsUI	Action to hint users that the list item has swipe actions available to use, either on the left or right side of the item.
 GetBrowser	OutSystemsUI	Identifies the browser being used.
 ScrollToElement	OutSystemsUI	Automatically scroll to a given element on the page.
 IsPhone	OutSystemsUI	Check if the current device is phone
 DropdownOpen	OutSystemsUI	Opens the Dropdown (DropdownTags or DropdownSearch) block with a given identifier.
 ResetProgressBar	OutSystemsUI	Resets the ProgressBar value to the Progress value.
 DatePickerDisableDays	OutSystemsUI	Set a list of specific days unavailable for selection on the DatePicker. Note: – Due to a provider issue, when using this action on the DatePickerRange, the component behaves differently than expected.
 SetActiveTab	OutSystemsUI	Action to change to specific TabsHeaderItem.
 DisableTabItem	OutSystemsUI	Disable a TabHeaderItem with a specific identifier.
 IsLayoutNative	OutSystemsUI	Check if the current layout is native.
 SetFocus	OutSystemsUI	Use this action to focus the element.
 FeedbackMessageShow	OutSystemsUI	Shows a FeedbackMessage with a specified message. You can enable HTML encoding, add CSS classes and a timeout.
 SetVirtualSelectEvent	OutSystemsUI	Use this action on the Initialized event of the DropdownTags or DropdownSearch, to set additional configs supported by Virtual Select.

Name	Owner	Description
Use this link to check all available configs: https://sa-si-dev.github.io/virtual-select/#/events		
OverflowMenuDisable	OutSystemsUI	Sets a OverflowMenu with given identifier as disabled.
TimePickerClose	OutSystemsUI	Closes a TimePicker with a given identifier.
SubmenuOpen	OutSystemsUI	Action to open the Submenu block.
SetMenuListeners	OutSystemsUI	Makes the menu navigation accessibility-ready.
IsRTL	OutSystemsUI	Function that exposes if RTL is applied.
DropdownClear	OutSystemsUI	Unselects all selected values of a Dropdown (DropdownTags, DropdownSearch) with a given identifier.
StackedCardsUpdate	OutSystemsUI	This action must be used on list remove action from OS platform. The UpdateStackedCards update

3.4.3 Server Actions

Action1

No Description

Input parameters

Name	Description	DataType	Mandatory
In1		Long Integer	✓

Output parameters

Name	Description	DataType
Out1		Long Integer

Authentication

No Description

DoLogin

No Description

Input parameters

Name	Description	DataType	Mandatory
Username		Text	✓
Password		Text	✓
RememberLogin		Boolean	

DoLogout

No Description

Output parameters

Name	Description	DataType
RedirectURL		Text

3.4.4 Referenced Server Actions

Name	Owner	Description
TextToBinaryData	BinaryData	Converts a Text into binary content. If no encoding is supplied, the system's default ANSI encoding will be used.
HttpBinaryGet	RichMail	Downloads Binary content from the specified URL.
AbortTransaction	(System)	Issues a database ROLLBACK command that undoes all changes performed on the database since the last commit.
Logout	(System)	Logs out a specific user from the application. The 'UserId' and 'Username' session variables are cleared.
ListAll	(System)	Determines if all the elements in the list satisfy the given condition.
LogMessage	(System)	Registers information that can be presented in Service Center in the module general log.
ListIndexOf	(System)	Returns the position of the first element of the List parameter that satisfies the given condition, or -1 if no element satisfies the condition.
ListSort	(System)	Sorts the elements of the List parameter by the given criteria.
ListRemove	(System)	Removes an element from a specific position of a list.
ListFilter	(System)	Returns a new list with the elements from the List parameter satisfying the given condition.
ListInsert	(System)	Inserts an element in a specific position of a list.
SetCurrentLocale	(System)	Sets the language locale of the user session to change the application presentation language.
Login	(System)	Logs a specified user in the application. In case of success, 'UserId' and 'Username' session variables are filled with the user data.
CommitTransaction	(System)	Issues a database COMMIT command that makes effective all changes done on the database since the last commit.
ListAppend	(System)	Adds an element to the end of a list.
ListAny	(System)	Determines if any of the elements in the list satisfies the given condition.
ListClear	(System)	Removes all elements from a list.
ListAppendAll	(System)	Adds the elements of the source list to the end of the destination list.
ListDuplicate	(System)	Duplicates the elements of a list into another list.
HTTPGet	ardoHTTP	Perform an HTTP GET request.
HTTPPost	ardoHTTP	Perform an HTTP POST request.
GetHexcodeFromLatLng	H3Ext	
User_GetName	Users	Returns the name of the logged user.
User_Logout	Users	Logs out the current user. Session variables are cleared during the logout process.
User_GetUnifiedLogoutUrl	Users	Returns the Url used for custom unified logout patterns.
User_GetUnifiedLoginUrl	Users	Returns the Url used for custom unified login patterns. Includes Windows Integrated Authentication pattern.
User_Login	Users	Action to login using username and password as credentials.
GetGoogleMapsServerKey	OutSystemsMaps	Returns the Google Maps API key setup for this component.

Name	Owner	Description
 String_Split	Text	Splits a string into individual elements delimited by any of the characters in Delimiters.

3.4.5 Service Actions

This folder is empty.

3.4.6 Referenced Service Actions

Name	Owner	Description
 DocApiCheck	DocumentGenerationServices	
 GetCounty	CloneOfIERatingEngine	
 GetRatingsValues	CloneOfIERatingEngine	
 ServiceAction1	CloneOfIERatingEngine	
 GetStates	CloneOfIERatingEngine	
 GetRatingsPercentages	CloneOfIERatingEngine	
 ServiceAction2	CloneOfIERatingEngine	

3.5 Integrations

3.5.1 SOAP

3.5.1.1 Consumed Web Services

No SOAP Web Services to show...

3.5.1.2 Exposed Web Services

No Web Services to show...

3.5.2 REST

3.5.2.1 Consumed REST APIs

 ActionsBlobCoreWindows

No Description

Base URL <https://actions.blob.core.windows.net>

REST API Methods:

 GetBwMmHsjcHgaJGQ__

3.5.2.2 Exposed REST APIs

No Exposed REST APIs to show...

3.5.3 SAP

No SAP Connections to show...

3.6 References

3.6.1 Extensions

 BinaryData

For version 11.33.0. Provides Actions to manipulate BinaryData contents, such as retrieving the length or transforming binary content into Text.

Actions:

 TextToBinaryData Converts a Text into binary content. If no encoding is supplied, the system's default ANSI encoding will be used.

 RichMail

For version 11.33.0. The RichMail extension allows retrieval, deletion, creation and sending of email messages, both text and HTML encoded and with optional attachments.

For information about the terms and values used, please refer to the RichMail.chm help file.

Actions:

 HttpBinaryGet Downloads Binary content from the specified URL.

 OutSystemsCharts

This component features the most commonly used chart types to easily generate visual representations of data in Web and Mobile apps.

Version 3.6.1

 (System)

System Objects

Actions:

 AbortTransaction	Issues a database ROLLBACK command that undoes all changes performed on the database since the last commit.
 Logout	Logs out a specific user from the application. The 'UserId' and 'Username' session variables are cleared.
 ListAll	Determines if all the elements in the list satisfy the given condition.
 LogMessage	Registers information that can be presented in Service Center in the module general log.
 ListIndexOf	Returns the position of the first element of the List parameter that satisfies the given condition, or -1 if no element satisfying the condition.
 ListSort	Sorts the elements of the List parameter by the given criteria.
 ListRemove	Removes an element from a specific position of a list.
 ListFilter	Returns a new list with the elements from the List parameter satisfying the given condition.
 ListInsert	Inserts an element in a specific position of a list.
 SetCurrentLocale	Sets the language locale of the user session to change the application presentation language.
 Login	Logs a specified user in the application. In case of success, 'UserId' and 'Username' session variables are filled with the user data.
 CommitTransaction	Issues a database COMMIT command that makes effective all changes done on the database since the last commit.
 ListAppend	Adds an element to the end of a list.
 ListAny	Determines if any of the elements in the list satisfies the given condition.
 ListClear	Removes all elements from a list.
 ListAppendAll	Adds the elements of the source list to the end of the destination list.
 ListDuplicate	Duplicates the elements of a list into another list.

 IERatingEngine

No Description

 ardoHTTP

Version 1.2.5

Set of tools to perform all kinds of HTTP requests, with full control over the request.

Actions:

 HTTPGet	Perform an HTTP GET request.
 HTTPPost	Perform an HTTP POST request.

 H3Ext

No Description

Actions:

 GetHexcodeFromLatLng	No Description
--	----------------

 Users

For version 11.33.0. Backoffice to manage users, groups and roles.

Actions:

 User_GetName	Returns the name of the logged user.
 User_Logout	Logs out the current user. Session variables are cleared during the logout process.
 User_GetUnifiedLogoutUrl	Returns the Url used for custom unified logout patterns.
 User_GetUnifiedLoginUrl	Returns the Url used for custom unified login patterns. Includes Windows Integrated Authentication pattern.
 User_Login	Action to login using username and password as credentials.

 OutSystemsUI

Version 2.21.0

 OutSystemsMaps

Version 2.1.0

Actions:

 GetGoogleMapsServerKey	Returns the Google Maps API key setup for this component.
--	---

 Text

For version 11.33.0. Provides actions to manipulate character strings such as joining, splitting, search and replace using regular expressions, and custom formatting of DateTime expressions.

Actions:

 String_Split	Splits a string into individual elements delimited by any of the characters in Delimiters.
--	--

 DocumentGenerationServices

No Description

CloneOfIERatingEngine

No Description

3.7 Runtime

3.7.1 Client Variables

Name	Description	Type	System
 LastURL		Text	
 Username		Text	

3.7.2 Site Properties

Name	Description	Type	System
 TenantId	Current Tenant identifier generated by the Platform.	Tenant Identifier	✔
 TenantName	Current Tenant name used by Service Center to identify the tenant.	Text	✔

3.7.3 Roles

Name	Description	Persistent	Public
No Roles to show...			

3.8 Timers

Name	Description	Priority	Schedule	Timeout
No Timers to show...				

3.9 Content

3.9.1 Resources

Name	Description	Path
No Resources to show...		

3.9.2 Images

Name	Description	Size
 Logo		12393 Bytes
 User	Placeholder image for logged in users without a picture.	1258 Bytes

3.9.3 Scripts

Name	Description
No Resources to show...	

3.10 Themes

Name	Description	Error Handling Flow	Base Theme
No Themes to show...			

3.10.1 Referenced Themes

Name	Owner eSpace	Description
 OutSystemsUI	OutSystemsUI	OutSystems UI theme for Web and Mobile reactive applications. www.outsystems.com/outsystems-ui

