SAN-Engineer Govindagouda Ranganagoudar

NetApp Usefull Commands Leave a comment

NETWORK To check the network interface/Configuration: ifconfig -a DISKS To assign all disks in one go: netapp1> disk assign all To check what disks are part of which aggr/vol/diskgroup: netapp1> vol status -r or netapp1> aggr status -r To check what disks are spare: netapp1> vol status -s or netapp1> aggr status -s To zero a disk: netapp1> disk zero spares To see what disks are owned by netapp1 netapp1> disk show -o netapp1 To assign the disks to a node in a cluster a. Verify on each filer each disk has 2 paths netapp1> storage show disk -p PRIMARY PORT SECONDARY PORT SHELF BAY switch2:44.126L85 - switch1:12.126L85 - - switch1:12.126L86 - switch2:44.126L86 - - switch2:44.126L87 - switch1:12.126L87 - - switch1:12.126L88 - switch2:44.126L88 - - netapp2> storage show disk -p PRIMARY PORT SECONDARY PORT SHELF BAY switch2:60.126L85 - switch1:28.126L85 - - switch1:28.126L86 - switch2:60.126L86 - - switch2:60.126L87 - switch1:28.126L87 - - -

switch1:28.126L88 - switch2:60.126L88 - - -

1. Find out disks not owned by any filer

netapp1> disk show -n

DISK OWNER POOL SERIAL NUMBER

switch2:44.126L85 Not Owned NONE 6001438005DEAAE00000700004300000 switch1:12.126L86 Not Owned NONE 6001438005DEAAE00000700004360000 switch2:44.126L87 Not Owned NONE 6001438005DEAAE000007000043C0000 switch1:12.126L88 Not Owned NONE 6001438005DEAAE00000700004420000

2. Assign the disk to the filer

netapp1> disk assign switch2:44.126L155 -o netapp1

Sat Aug 7 10:17:15 BST [netapp2: diskown.changingOwner:info]: changing ownership for disk switch1:12.126L155 (S/N 6001438005DEAAE00000700005D40000) from unowned (ID -1) to netapp1 (ID 151735370)

STORAGE PORTS

To check the alias for storage ports/devices a netapp is zoned with:

netapp1> storage alias

Alias Mapping

mc0 WWN[5:005:07630f:0f2601]L1

mc1 WWN[5:005:07630f:0f2611]L1

st0 WWN[5:005:07630f:0f2604]

st1 WWN[5:005:07630f:0f2602]

st10 WWN[5:005:07630f:0f2613]

st11 WWN[5:005:07630f:0f2614]

st12 WWN[5:005:07630f:0f2615]

st13 WWN[5:005:07630f:0f2618]

To unalias the storage port aliases and configrue the correct desired names: netapp1> storage alias st1 WWN[5:005:07630f:0f2601]

If you had several tape drives to be aliased, it is better to put them together in a file under /etc/, say /etc/tape_aliases.dc1. And then source this file using:

netapp1> source /etc/tape_aliases.dc1

netapp1> storage alias

Alias Mapping

mc0 WWN[5:005:07630f:0f2601]L1

mc1 WWN[5:005:07630f:0f2611]L1

st0 WWN[5:005:07630f:0f2604]

st1 WWN[5:005:07630f:0f2602]

st10 WWN[5:005:07630f:0f2613]

USER

To create a user and set its password:

netapp1> useradmin user add backups -g Users -c "Backup user" -m password

New password:

Retype new password:

User added.

To change the login mode (privilege/diag): netapp1> priv set advanced netapp1> priv set diag

VOLUMES

Create a normal flexible volume netapp1> vol create vol1 -l en agg1 1112g

Check the size of volume netapp1> vol size vol1

Find out which aggr a volume is created on netapp1> vol status vol1 -v

AGGREGATES

Create aggregate

Example: 1

netapp1> aggr create agg_1 -r 17 -t raid_dp 51@137104M

-r -> so many disks in one raid group

137104M -> size of disks - get that from vol status -r

This will create an aggregate spanning 3 raid groups each containing 17 disks – if disks were not in use before (assigned to raidgroup) the aggr will be created straightaway. However if they were in use, they will need to be zeroed which will take long time.

Example: 2

In this case we have 36 disks owned by each filer. so we can create 2 aggregates with raid0 and raidgroup having 9 disks (size 874496M obtained from vol status -r) netapp1> aggr create agg_101_fa_2 -r 9 -t raid0 18@874496M
Creation of an aggregate with 18 disks has been initiated. The disks need to be zeroed before addition to the aggregate. The process has been initiated and you will be notified via the system log as disks are added.
Note however, that if system reboots before the disk zeroing is complete, the volume won't exist.

Delete an aggregate
netapp1> aggr status
Aggr State Status Options
vol0 online raid4, trad root
aggr0 online raid_dp, aggr
netapp1> aggr offline aggr0
netapp1> aggr status
Aggr State Status Options
vol0 online raid4, trad root
aggr0 offline raid_dp, aggr lost_write_protect=off
netapp1> aggr destroy aggr0
netapp1> aggr status
Aggr State Status Options
vol0 online raid4, trad root

To set the snap reserve on aggregate

Aggregates are created by default with 5% reserve space. Generally, we don't reserve the space on aggr instead we reserve on per volume. So, disable the snap reserve on aggrs and reduce it to 0%. netapp1> aggr options agg_2

nosnap=off, raidtype=raid_dp, raidsize=16, ignore_inconsistent=off, snapmirrored=off, resyncsnaptime=60, fs_size_fixed=off, snapshot_autodelete=on, lost_write_protect=on netapp1> aggr options agg_2 nosnap 1 netapp1> aggr options agg_2 nosnap=on, raidtype=raid_dp, raidsize=16, ignore_inconsistent=off, snapmirrored=off, resyncsnaptime=60, fs_size_fixed=off, snapshot_autodelete=on, lost_write_protect=on netapp1> snap reserve -A Volume vol0: current snapshot reserve is 20% or 156217696 k-bytes. Aggregate agg_1: current snapshot reserve is 0% or 0 k-bytes. Aggregate agg_2: current snapshot reserve is 5% or 546761940 k-bytes.

netapp1> snap reserve -A agg_2 0

netapp1> snap reserve -A

Volume vol0: current snapshot reserve is 20% or 156217696 k-bytes.

Aggregate agg_1: current snapshot reserve is 0% or 0 k-bytes.

Aggregate agg_2: current snapshot reserve is 0% or 0 k-bytes.

NTP

Options to be set for ntp:

netapp1> options timed.protocol ntp netapp1> options timed.servers ntp1.domain.com,ntp2.domain.com netapp1> options timed.sched 5m

NIS/DNS

To set up NIS

1. Set up nis options

netapp1> options nis.enable on netapp1> options nis.domainname prod.yourdomain.com

2. Set up DNS options

logisnap233a> options dns.enable on logisnap233a> options dns.domainname yourdomain.com

Edit rc file so that it looks something like as below (should have NIS/DNS related info)

netapp1> rdfile /etc/rc

vif create multi vif1 -b ip e4a e3a

vif create multi vif2 -b ip e4b e3b

vif create single vif233a vif1 vif2

ifconfig vifnetapp1 'hostname'-vifnetapp1 netmask 255.255.255.0 partner vifnetapp2

route add default 192.168.1.1 1

routed on

options dns.domainname yourdomain.com

options dns.enable on

options nis.domainname prod.domain.com

options nis.enable on

savecore

timezone Europe/London

4. Set up /etc/resolv.conf file

netapp1> rdfile /etc/resolv.conf nameserver 192.168.1.250 nameserver 192.168.1.251 search yourdomain.com subdomain.yourdomain.com

5. Verify dns is set up correctly netapp1> dns info

6. Verify nis is set up correctly netapp1> nis info

AUTOSUPPORT

Options to be set for autosupport (will require a reboot to take effect)

netapp1> options autosupport.enable on netapp1> options autosupport.from admin@domain.com netapp1> options autosupport.mailhost mailhost.domain.com netapp1> options autosupport.noteto admin@domain.com netapp1> options autosupport.to autosupport@netapp.com,admin@domain.com

To generate autosupport manually:

Suppose node1/node2 are clustered node, and node2 has panicked, and taken over by node1. You are asked to generate autosupport on node2. Follow the steps below:

node1(takeover)> partner
Login to partner shell: node2
node2/node1> Mon Sep 27 11:24:13 BST [node1 (takeover): cf.partner.login:notice]: Login to partner shell: node2
node2/node1> options autosupport
autosupport.cifs.verbose off
autosupport.content complete
autosupport.doit DONT
.

node2/node1> options autosupport.doit DO

SYSTEM

To find the WWN/System related information: netapp1> sysconfig -av -> shows all the information netapp1> sysconfig -av 2 -> shows info about FC Adapter slot 2: FC Host Adapter 2a (QLogic 2432 rev. 3, N-port,)

Board name: QLE2462

Serial Number: RFC0933M00518

Firmware rev: 4.4.0 Host Port Id: 0×614613

FC Node Name: 2:100:001b32:928651

SFF Vendor: FINISAR CORP.

SFF Part Number: FTLF8524E2KNL

SFF Serial Number: PFP45SG SFF Capabilities: 1, 2 or 4 Gbit

Link Data Rate: 2 Gbit

Switch Port: ??

slot 2: FC Host Adapter 2b (QLogic 2432 rev. 3, N-port,)

Board name: QLE2462

Serial Number: RFC0933M00518

Firmware rev: 4.4.0 Host Port Id: 0×614613

FC Node Name: 2:101:001b32:b28651

SFF Vendor: FINISAR CORP.

SFF Part Number: FTLF8524E2KNL

SFF Serial Number: PFP46EP SFF Capabilities: 1, 2 or 4 Gbit

Link Data Rate: 2 Gbit

To use CLI to add disk to the existing aggregation, follow below steps:

1). First check the aggregation that need to be extended:

lab> aggr status aggr1 -v

Aggr State Status Options

aggr1 online raid_dp, aggr nosnap=off, raidtype=raid_dp,

raidsize=16,

ignore_inconsistent=off,

snapmirrored=off,

resyncsnaptime=60,

fs_size_fixed=off,

snapshot_autodelete=on,

lost_write_protect=on

Volumes:

Plex /aggr1/plex0: online, normal, active

RAID group /aggr1/plex0/rg0: normal

lab> df -Am

Aggregate total used avail capacity

aggr0 256MB 244MB 12MB 95%

aggr0/.snapshot 13MB 10MB 2MB 79%

aggr1 128MB 0MB 128MB 0%

aggr1/.snapshot 6MB 0MB 6MB 0%

2). Check the available spares by run sysconfig -r, in this example,

lab> sysconfig -r

Aggregate aggr1 (online, raid_dp) (zoned checksums) Plex /aggr1/plex0 (online, normal, active) RAID group /aggr1/plex0/rg0 (normal) RAID Disk Device HA SHELF BAY CHAN Pool Type RPM Used (MB/blks) Phys (MB/blks) dparity v4.24 v4 1 8 FC:B – FCAL N/A 70/144384 77/158848 parity v4.25 v4 1 9 FC:B – FCAL N/A 70/144384 77/158848 data v4.26 v4 1 10 FC:B - FCAL N/A 70/144384 77/158848 data v4.27 v4 1 11 FC:B - FCAL N/A 70/144384 77/158848 data v4.28 v4 1 12 FC:B - FCAL N/A 70/144384 77/158848 Aggregate aggr0 (online, raid0) (zoned checksums) Plex /aggr0/plex0 (online, normal, active) RAID group /aggr0/plex0/rg0 (normal) RAID Disk Device HA SHELF BAY CHAN Pool Type RPM Used (MB/blks) Phys (MB/blks) data v4.16 v4 1 0 FC:B – FCAL N/A 120/246784 127/261248 data v4.17 v4 1 1 FC:B – FCAL N/A 120/246784 127/261248 data v4.18 v4 1 2 FC:B – FCAL N/A 120/246784 127/261248 Spare disks RAID Disk Device HA SHELF BAY CHAN Pool Type RPM Used (MB/blks) Phys (MB/blks) Spare disks for zoned checksum traditional volumes or aggregates only spare v4.29 v4 1 13 FC:B – FCAL N/A 70/144384 77/158848 spare v4.32 v4 2 0 FC:B – FCAL N/A 70/144384 77/158848 spare v4.33 v4 2 1 FC:B – FCAL N/A 70/144384 77/158848 spare v4.34 v4 2 2 FC:B – FCAL N/A 70/144384 77/158848 spare v4.35 v4 2 3 FC:B – FCAL N/A 70/144384 77/158848 spare v4.36 v4 2 4 FC:B – FCAL N/A 70/144384 77/158848 spare v4.37 v4 2 5 FC:B – FCAL N/A 70/144384 77/158848

```
spare v4.38 v4 2 6 FC:B – FCAL N/A 70/144384 77/158848

spare v4.39 v4 2 7 FC:B – FCAL N/A 70/144384 77/158848

spare v4.40 v4 2 8 FC:B – FCAL N/A 70/144384 77/158848

spare v4.41 v4 2 9 FC:B – FCAL N/A 70/144384 77/158848

spare v4.42 v4 2 10 FC:B – FCAL N/A 70/144384 77/158848

spare v4.43 v4 2 11 FC:B – FCAL N/A 70/144384 77/158848

spare v4.44 v4 2 12 FC:B – FCAL N/A 70/144384 77/158848

spare v4.45 v4 2 13 FC:B – FCAL N/A 70/144384 77/158848

spare v4.19 v4 1 3 FC:B – FCAL N/A 1020/2089984 1027/2104448

spare v4.20 v4 1 4 FC:B – FCAL N/A 1020/2089984 1027/2104448

spare v4.21 v4 1 5 FC:B – FCAL N/A 1020/2089984 1027/2104448
```

3) Next add 15 spare disk to the Aggr1, because the max size of spindle for Raid Group(Raid-DP) is 16 so when 15 new spindles added, a new Raid Group is created with additional 4 disks.

lab> aggr add aggr1 -d v4.29 v4.32 v4.33 v4.34 v4.35 v4.36 v4.37 v4.38 v4.39 v4.40 v4.41 v4.42 v4.43 v4.44 v4.45

Note: preparing to add 13 data disks and 2 parity disks.

Continue? ([y]es, [n]o, or [p]review RAID layout) p

The RAID group configuration will change as follows:

RAID Group Current NEW

/aggr1/plex0/rg0 5 disks 16 disks

/aggr1/plex0/rg1 4 disks

Continue? ([y]es, [n]o, or [p]review RAID layout) yes

Sun Aug 30 17:25:33 GMT [raid.vol.disk.add.done:notice]: Addition of Disk /aggr1/plex0/rg0/v4.41 Shelf 2 Bay 9 [NETAPP VD-50MB 0042] S/N [37981022] to aggregate aggr1 has completed successfully

Sun Aug 30 17:25:33 GMT [raid.vol.disk.add.done:notice]: Addition of Disk /aggr1/plex0/rg0/v4.40 Shelf 2 Bay 8 [NETAPP VD-50MB 0042] S/N [37981021] to aggregate aggr1 has completed successfully

Sun Aug 30 17:25:33 GMT [raid.vol.disk.add.done:notice]: Addition of Disk /aggr1/plex0/rg0/v4.39 Shelf 2 Bay 7 [NETAPP VD-50MB 0042] S/N [37981020] to aggregate aggr1 has completed successfully

Sun Aug 30 17:25:33 GMT [raid.vol.disk.add.done:notice]: Addition of Disk /aggr1/plex0/rg0/v4.38 Shelf 2 Bay 6 [NETAPP VD-50MB 0042] S/N [37981019] to aggregate aggr1 has completed successfully

Sun Aug 30 17:25:33 GMT [raid.vol.disk.add.done:notice]: Addition of Disk /aggr1/plex0/rg0/v4.37 Shelf 2 Bay 5 [NETAPP VD-50MB 0042] S/N [37980918] to aggregate aggr1 has completed successfully

Sun Aug 30 17:25:33 GMT [raid.vol.disk.add.done:notice]: Addition of Disk /aggr1/plex0/rg0/v4.36 Shelf 2 Bay 4 [NETAPP VD-50MB 0042] S/N [37980917] to aggregate aggr1 has completed successfully

Sun Aug 30 17:25:33 GMT [raid.vol.disk.add.done:notice]: Addition of Disk /aggr1/plex0/rg0/v4.35 Shelf 2 Bay 3 [NETAPP VD-50MB 0042] S/N [13292816] to aggregate aggr1 has completed successfully

Sun Aug 30 17:25:33 GMT [raid.vol.disk.add.done:notice]: Addition of Disk /aggr1/plex0/rg0/v4.34 Shelf 2 Bay 2 [NETAPP VD-50MB 0042] S/N [13292715] to aggregate aggr1 has completed successfully

Sun Aug 30 17:25:33 GMT [raid.vol.disk.add.done:notice]: Addition of Disk /aggr1/plex0/rg0/v4.33 Shelf 2 Bay 1 [NETAPP VD-50MB 0042] S/N [13292614] to aggregate aggr1 has completed successfully

Sun Aug 30 17:25:33 GMT [raid.vol.disk.add.done:notice]: Addition of Disk /aggr1/plex0/rg0/v4.32 Shelf 2 Bay 0 [NETAPP VD-50MB 0042] S/N [13292513] to aggregate aggr1 has completed successfully

Sun Aug 30 17:25:33 GMT [raid.vol.disk.add.done:notice]: Addition of Disk /aggr1/plex0/rg0/v4.29 Shelf 1 Bay 13 [NETAPP VD-50MB 0042] S/N [13292512] to aggregate aggr1 has completed successfully

Sun Aug 30 17:25:33 GMT [raid.vol.disk.add.done:notice]: Addition of Disk /aggr1/plex0/rg1/v4.45 Shelf 2 Bay 13 [NETAPP VD-50MB 0042] S/N [37981126] to aggregate aggr1 has completed successfully

Sun Aug 30 17:25:33 GMT [raid.vol.disk.add.done:notice]: Addition of Disk /aggr1/plex0/rg1/v4.44 Shelf 2 Bay 12 [NETAPP VD-50MB 0042] S/N [37981125] to aggregate aggr1 has completed successfully

Sun Aug 30 17:25:33 GMT [raid.vol.disk.add.done:notice]: Addition of Disk /aggr1/plex0/rg1/v4.43 Shelf 2 Bay 11 [NETAPP VD-50MB 0042] S/N [37981124] to aggregate aggr1 has completed successfully

Sun Aug 30 17:25:33 GMT [raid.vol.disk.add.done:notice]: Addition of Disk /aggr1/plex0/rg1/v4.42 Shelf 2 Bay 10 [NETAPP VD-50MB 0042] S/N [37981123] to aggregate aggr1 has completed successfully

Addition of 15 disks to the aggregate has completed.

lab> aggr status aggr1

Aggr State Status Options

aggr1 online raid_dp, aggr

Volumes:

Plex /aggr1/plex0: online, normal, active

RAID group /aggr1/plex0/rg0: normal

RAID group /aggr1/plex0/rg1: normal

4). Next create volume 1 with 200MB of total.

vol create: Containing aggregate 'aggre1' was not found lab> vol create vol1 aggr1 200m Creation of volume 'vol1' with size 200m on containing aggregate 'aggr1' has completed. lab> vol status Volume State Status Options vol0 online raid0, flex root, no_atime_update=on, create_ucode=on, convert_ucode=on, maxdirsize=2621 vol1 online raid_dp, flex create_ucode=on, convert_ucode=on lab> 5). Check the aggregation utilization: lab> df -Am Aggregate total used avail capacity aggr0 256MB 244MB 12MB 95% aggr0/.snapshot 13MB 10MB 2MB 79% aggr1 684MB 201MB 482MB 30% aggr1/.snapshot 36MB 0MB 36MB 0% lab> Posted February 11, 2013 by g6237118

lab> vol create vol1 aggre1 200m

Blog at WordPress.com. Do Not Sell My Personal Information