

---

# SAN-Engineer Govindagouda Ranganagoudar

VMware Leave a comment

## Resolving SCSI reservation conflicts

### Details

- You cannot access a LUN.
- The LUN is zoned, presented and configured properly.
- A vdf command never completes.

### Solution

This article provides instructions for:

- ESX/ESXi 4.x and 5.0 ([http://kb.vmware.com/selfservice/microsites/search.do?language=en\\_US&cmd=displayKC&externalId=1002293#4.x](http://kb.vmware.com/selfservice/microsites/search.do?language=en_US&cmd=displayKC&externalId=1002293#4.x)).
- ESX/ESXi 3.5.x ([http://kb.vmware.com/selfservice/microsites/search.do?language=en\\_US&cmd=displayKC&externalId=1002293#3.5.x](http://kb.vmware.com/selfservice/microsites/search.do?language=en_US&cmd=displayKC&externalId=1002293#3.5.x)).
- ESX 3.0.x ([http://kb.vmware.com/selfservice/microsites/search.do?language=en\\_US&cmd=displayKC&externalId=1002293#3.0.x](http://kb.vmware.com/selfservice/microsites/search.do?language=en_US&cmd=displayKC&externalId=1002293#3.0.x)).

**Note:** For more information about why SCSI reservations occur, see [Analyzing SCSI Reservation conflicts on VMware Infrastructure 3.x and vSphere 4.x \(1005009\)](http://kb.vmware.com/selfservice/microsites/search.do?cmd=displayKC&externalId=1005009).  
(<http://kb.vmware.com/selfservice/microsites/search.do?cmd=displayKC&externalId=1005009>).

## ESX/ESXi 4.x and 5.0

To identify if SCSI reservation conflicts are preventing a LUN from being accessed:

1. Verify that the LUN is detected by the ESX host at boot time. Run the command: `# esxcfg-scsidevs -c`

The output appears similar to:

Device UID	Device Type	Console	Device Size	Plugin Display Name
eui.00000e1100b81bfc	Direct-Access	/dev/sda	70007MB	NMP Local FUJITSU Disk (eui.00000e1100b81bfc)
mpx.vmhba0:C0:T0:L0	CD-ROM	/dev/sr0	0MB	NMP Local HL-DT-ST CD-ROM (mpx.vmhba0:C0:T0:L0)
mpx.vmhba3:C0:T0:L0	Direct-Access	/dev/cciss/c0d0	34727MB	NMP Local VMware Disk (mpx.vmhba3:C0:T0:L0)

- If the LUN is not listed, rescan the storage. For more information, see [Performing a rescan of the storage \(1003988\)](http://kb.vmware.com/selfservice/microsites/search.do?cmd=displayKC&externalId=1003988) (<http://kb.vmware.com/selfservice/microsites/search.do?cmd=displayKC&externalId=1003988>).
- Check the system logs for signs of SCSI Reservation Conflict errors. Look for lines that may provide some information if the LUN is having an issue: **ESX 4.x:** # cat /var/log/dmesg

**ESXi 4.x:** # cat /var/log/messages

**ESXi 5.0:** # cat /var/log/vmkernel.log

Vendor: EMC Model: SYMMETRIX Rev: 5771

Type: Direct-Access ANSI SCSI revision: 03

scsi0 (0,0,52) : RESERVATION CONFLICT

scsi0 (0,0,52) : RESERVATION CONFLICT

scsi0 (0,0,52) : RESERVATION CONFLICT

scsi0 (0,0,52) : RESERVATION CONFLICT

scsi0 (0,0,52) : RESERVATION CONFLICT

scsi0 (0,0,52) : RESERVATION CONFLICT

sdh : READ CAPACITY failed.

status = c, message = 00, host = 0, driver = 00

scsi0 (0,0,52) : RESERVATION CONFLICT

scsi0 (0,0,52) : RESERVATION CONFLICT

scsi0 (0,0,52) : RESERVATION CONFLICT

VMWARE: Device that would have been attached as scsi disk sdh at scsi0, channel 0, id 0, lun 52

Has not been attached because this path could not complete a READ command eventhough a TUR worked.

result = 0x18 key = 0x0, asc = 0x0, ascq = 0x0

VMWARE: Device that would have been attached as scsi disk sdh at scsi0, channel 0, id 0, lun 52

Has not been attached because it is a duplicate path or on a passive path

scan\_scsis starting finish

scan\_scsis done with finish

In this example, LUN 52 is inaccessible in the ESX host cluster. Since it is listed in the output of step one, it was accessible at some point (a host reserved the LUN and never released it, possibly due to a SAN switch reboot in the middle of the reservation operation).

To resolve this:

- Examine all hosts (also applies to hosts for any pending reservations) with the command: # esxcfg-info | egrep -B5 "s Reserved|Pending"

The output appears similar to:

**Note:** Not all of the output is shown.

```
--Console Device...../dev/sdd
|--DevfsPath...../vmfs/devices/disks/vml.
02000000006001c230d8abfe000ff76c51486715db504552432035
|--SCSI Level.....6
|--Queue Depth.....128
|--Is Pseudo.....false
|--Is Reserved.....false
|--Pending Reservations.....0
--
|--Console Device...../dev/sda
|--DevfsPath...../vmfs/devices/disks/vml.
02000000006001c230d8abfe000ff76c198ddbc13e504552432035
|--SCSI Level.....6
|--Queue Depth.....128
|--Is Pseudo.....false
|--Is Reserved.....false
|--Pending Reservations.....1
```

The ESX host that has Pending Reserves with a value that is larger than 0 is holding the lock.

2. Perform a LUN reset to clear the lock with the command:# vmkfstools -lock lunreset /vmfs/devices/disks/vml.02000000006001c230d8abfe000ff76c198ddbc13e504552432035
3. Verify that the LUN no longer has any Pending Reserves with the command:# esxcfg-info -s | egrep -B16 "s Reserved|Pending"

**Note:** If the Pending Reserves is not 0 or Is Reserved is not false, the LUN reset did not succeed.

4. Do a refresh of the storage window on each ESX host.
5. If the datastore is not mounted, perform a rescan. For more information, see [Performing a rescan of the storage \(1003988\)](http://kb.vmware.com/selfservice/microsites/search.do?cmd=displayKC&externalId=1003988) (<http://kb.vmware.com/selfservice/microsites/search.do?cmd=displayKC&externalId=1003988>).

**Note:** Virtual machines housed on a LUN should observe no interruption in service when a LUN reset occurs.

## ESX/ESXi 3.5.x

To identify if SCSI reservation conflicts are preventing a LUN from being accessed:

1. Verify that the LUN is detected by the ESX host at boot time with the commands:# cd /vmfs/devices/disks  
# ls vmh\*

The output appears similar to:

```
vmhba0:0:0:0
vmhba0:0:43:0
vmhba0:0:52:0
```

2. If the LUN is not listed, rescan the storage. For more information, see [Performing a rescan of the storage \(1003988\)](http://kb.vmware.com/selfservice/microsites/search.do?cmd=displayKC&externalId=1003988) (<http://kb.vmware.com/selfservice/microsites/search.do?cmd=displayKC&externalId=1003988>).
3. Checkdmesg. Look for lines that may provide some information if the LUN is having an issue:  
# cd /var/log  
# cat dmesg

Vendor: EMC Model: SYMMETRIX Rev: 5771

Type: Direct-Access ANSI SCSI revision: 03

scsi0 (0,0,52) : RESERVATION CONFLICT

scsi0 (0,0,52) : RESERVATION CONFLICT

scsi0 (0,0,52) : RESERVATION CONFLICT

scsi0 (0,0,52) : RESERVATION CONFLICT

scsi0 (0,0,52) : RESERVATION CONFLICT

scsi0 (0,0,52) : RESERVATION CONFLICT

sdh : READ CAPACITY failed.

status = c, message = 00, host = 0, driver = 00

scsi0 (0,0,52) : RESERVATION CONFLICT

scsi0 (0,0,52) : RESERVATION CONFLICT

scsi0 (0,0,52) : RESERVATION CONFLICT

VMWARE: Device that would have been attached as scsi disk sdh at scsi0,  
channel 0, id 0, lun 52

Has not been attached because this path could not complete a READ  
command eventhough a TUR worked.

result = 0x18 key = 0x0, asc = 0x0, ascq = 0x0

VMWARE: Device that would have been attached as scsi disk sdh at scsi0,  
channel 0, id 0, lun 52

Has not been attached because it is a duplicate path or on a passive  
path

scan\_scsis starting finish

scan\_scsis done with finish

In this example, LUN 52 is inaccessible in the ESX host cluster. Since it is listed in the output of step one, it was accessible at some point (a host reserved the LUN and never released it, possibly due to a SAN switch reboot in the middle of the reservation operation).

To resolve this:

1. Examine all hosts (also applies to hosts for any pending reservations) with the command: # esxcfg-info | egrep -B5 "s Reserved|Pending"

The output appears similar to:

**Note:** Not all of the output is shown.

| --Console Device...../dev/sdd

| --DevfsPath...../vmfs/devices/disks/vml.

02000000006001c230d8abfe000ff76c51486715db504552432035

| --SCSI Level.....6

| --Queue Depth.....128

| --Is Pseudo.....false

| --Is Reserved.....false

| --Pending Reservations.....0

—

```
| --Console Device...../dev/sda
| --DevfsPath...../vmfs/devices/disks/vml.
02000000006001c230d8abfe000ff76c198ddbc13e504552432035
| --SCSI Level.....6
| --Queue Depth.....128
| --Is Pseudo.....false
| --Is Reserved.....false
| --Pending Reservations.....1
```

The ESX host that has Pending Reserves with a value that is larger than 0 is holding the lock.

2. Perform a LUN reset to clear the lock with the command: # vmkfstools -lock lunreset /vmfs/devices/disks/vml.02000000006001c230d8abfe000ff76c198ddbc13e504552432035
3. Verify that the LUN no longer has any Pending Reserves with the command: # esxcfg-info -s | egrep -B5 "s Reserved|Pending"

**Note:** If the Pending Reserves is not 0 or Is Reserved is not false, the LUN reset did not succeed.

4. Do a refresh of the storage window on each ESX host.
5. If the datastore is not mounted, perform a rescan. For more information, see [Performing a rescan of the storage \(1003988\)](http://kb.vmware.com/selfservice/microsites/search.do?cmd=displayKC&externalId=1003988) (<http://kb.vmware.com/selfservice/microsites/search.do?cmd=displayKC&externalId=1003988>).

## ESX 3.0.x

To identify if SCSI reservation conflicts are preventing a LUN from being accessed:

1. Verify that the LUN is detected by the ESX host at boot time. Run the commands: # cd /vmfs/devices/disks  
# ls vmh\*

The output appears similar to:

```
vmhba0:0:0:0
vmhba0:0:43:0
vmhba0:0:52:0
```

2. If the LUN is not listed, rescan the storage. For more information, see [Performing a rescan of the storage \(1003988\)](http://kb.vmware.com/selfservice/microsites/search.do?cmd=displayKC&externalId=1003988) (<http://kb.vmware.com/selfservice/microsites/search.do?cmd=displayKC&externalId=1003988>).
3. Check dmesg. Look for lines that may provide some information if the LUN is having an issue: # cd /var/log  
# cat dmesg

```
Vendor: EMC Model: SYMMETRIX Rev: 5771
Type: Direct-Access ANSI SCSI revision: 03
scsi0 (0,0,52) : RESERVATION CONFLICT
scsi0 (0,0,52) : RESERVATION CONFLICT
scsi0 (0,0,52) : RESERVATION CONFLICT
```

```
scsi0 (0,0,52) : RESERVATION CONFLICT
scsi0 (0,0,52) : RESERVATION CONFLICT
scsi0 (0,0,52) : RESERVATION CONFLICT
sdh : READ CAPACITY failed.
status = c, message = 00, host = 0, driver = 00
scsi0 (0,0,52) : RESERVATION CONFLICT
scsi0 (0,0,52) : RESERVATION CONFLICT
scsi0 (0,0,52) : RESERVATION CONFLICT
VMWARE: Device that would have been attached as scsi disk sdh at scsi0,
channel 0, id 0, lun 52
Has not been attached because this path could not complete a READ
command eventhough a TUR worked.
result = 0x18 key = 0x0, asc = 0x0, ascq = 0x0
VMWARE: Device that would have been attached as scsi disk sdh at scsi0,
channel 0, id 0, lun 52
Has not been attached because it is a duplicate path or on a passive
path
scan_scsis starting finish
scan_scsis done with finish
```

In this example, LUN 52 is inaccessible in the ESX host cluster. Since it is listed in the output of step one, it was accessible at some point (a host reserved the LUN and never released it, possibly due to a SAN switch reboot in the middle of the reservation operation).

To resolve this:

1. Examine all hosts for any pending reservations with the command: `# tail -1 /proc/vmware/scsi/vmhba[0-9]/[0-9]:*`

The output appears similar to:

```
==> /proc/vmware/scsi/vmhba0/0:0 <==
Active: 0 Queued: 0 Reserved: N Pending Reserves: 0

==> /proc/vmware/scsi/vmhba0/0:43 <==
Active: 0 Queued: 0 Reserved: N Pending Reserves: 0

==> /proc/vmware/scsi/vmhba0/0:44 <==
Active: 0 Queued: 0 Reserved: N Pending Reserves: 0

==> /proc/vmware/scsi/vmhba0/0:45 <==
Active: 0 Queued: 0 Reserved: N Pending Reserves: 0

==> /proc/vmware/scsi/vmhba0/0:46 <==
Active: 0 Queued: 0 Reserved: N Pending Reserves: 0

==> /proc/vmware/scsi/vmhba1/0:50 <==
Active: 0 Queued: 0 Reserved: N Pending Reserves: 0

==> /proc/vmware/scsi/vmhba1/0:51 <==
Active: 0 Queued: 0 Reserved: N Pending Reserves: 0

==> /proc/vmware/scsi/vmhba1/0:52 <==
Active: 0 Queued: 0 Reserved: N Pending Reserves: 1
```

```
==> /proc/vmware/scsi/vmhba1/0:53 <==
```

Active: 0 Queued: 0 Reserved: N Pending Reserves: 0

```
==> /proc/vmware/scsi/vmhba1/0:54 <==
```

Active: 0 Queued: 0 Reserved: N Pending Reserves: 0

```
==> /proc/vmware/scsi/vmhba2/0:0 <==
```

Active: 0 Queued: 0 Reserved: N Pending Reserves: 0

The ESX host that has Pending Reserves with a value that is larger than 0 is holding the lock.

2. Perform a LUN reset to clear the lock with the command: # vmkfstools -lock lunreset  
/vmfs/devices/disks/vmhba1\ :0\ :52\ :0

3. Verify that the LUN no longer has any Pending Reserves with the command: # tail -1  
/proc/vmware/scsi/vmhba1/0\ :52

The output appears similar to:

Active: 0 Queued: 0 Reserved: N Pending Reserves: 0

**Note:** If the Pending Reserves is not 0 or Is Reserved is not false, the LUN reset did not succeed.

4. Do a refresh of the storage window on each ESX host.

5. If the datastore is not mounted, perform a rescan. For more information, see [Performing a rescan of the storage \(1003988\)](http://kb.vmware.com/selfservice/microsites/search.do?cmd=displayKC&externalId=1003988) (<http://kb.vmware.com/selfservice/microsites/search.do?cmd=displayKC&externalId=1003988>).

Posted May 11, 2012 by [g6237118](#)

[Blog at WordPress.com.](#) [Do Not Sell My Personal Information](#)