



Full Stack Software Development

Course: Server-Side
Development Using Node.js,
Express.js and MongoDB

Lecture on: Mongoose ODM

Instructor: Rocky Jagtiani

In the previous class, we covered...

- Basics of MongoDB

Poll 1 (15 Sec)

Which MongoDB command is used to **create** a new document?

1. `db.collection.update()`
2. `db.collection.create()`
3. `db.collection.new()`
4. `db.collection.insert()`

Poll 1 (Answer)

Which MongoDB command is used to **create** a new document?

1. `db.collection.update()`
2. `db.collection.create()`
3. `db.collection.new()`
4. **`db.collection.insert()`**

Poll 2 (15 Sec)

Which MongoDB command is used to **delete** a document?

1. `db.collection.remove()`
2. `db.collection.delete()`
3. `db.document.remove()`
4. `db.document.delete()`

Poll 2 (Answer)

Which MongoDB command is used to **delete** a document?

1. **db.collection.remove()**
2. db.collection.delete()
3. db.document.remove()
4. db.document.delete()

Today's Agenda

- JavaScript Promises
- Mongoose ODM
- Helper Methods



JavaScript Promises

```
let promise = new Promise((resolve, reject) => {  
  if(1 >= 0) {  
    resolve("This is working!"); }  
  else {  
    reject(Error("It failed!"));  
  }  
})  
  
promise.then(  
  (result) => console.log(result),  
  (error) => console.log(error)  
);  
  
//This is working!
```

- Let us quickly revisit the concept of promises in JavaScript because Mongoose which is a MongoDB object modelling tool is designed to work in an asynchronous environment and thus, **Mongoose supports both promises and callbacks.**

```
let myPromise = new Promise(function(myResolve, myReject) {  
  // "Producing Code" (May take some time)  
  myResolve(); // when successful  
  myReject(); // when error  
});  
  
// "Consuming Code" (Must wait for a fulfilled Promise)  
myPromise.then(  
  function(value) { /* code if successful */ },  
  function(error) { /* code if some error */ }  
);
```

- A promise is an object that may produce a single value some time in the future: either a resolved value, or a reason that it's not resolved.
- A promise may be in one of 3 possible states:
 - fulfilled
 - rejected
 - pending

```
let myPromise = new Promise(function(myResolve, myReject) {  
  // "Producing Code" (May take some time)  
  myResolve(); // when successful  
  myReject(); // when error  
});  
  
// "Consuming Code" (Must wait for a fulfilled Promise)  
myPromise.then(  
  function(value) { /* code if successful */ },  
  function(error) { /* code if some error */ }  
);
```

When the executing code obtains the result, it should call one of the two callbacks:

Result	Call
Success	myResolve(result value)
Error	myReject(error object)

```
let myPromise = new Promise(function(myResolve, myReject) {  
  // "Producing Code" (May take some time)  
  myResolve(); // when successful  
  myReject(); // when error  
});  
  
// "Consuming Code" (Must wait for a fulfilled Promise)  
myPromise.then(  
  function(value) { /* code if successful */ },  
  function(error) { /* code if some error */ }  
);
```

The Promise object supports two properties: **state** and **result**.

- While a Promise object is "pending" (working), the result is undefined.
- When a Promise object is "fulfilled", the result is a value.
- When a Promise object is "rejected", the result is an error object.

myPromise.state	myPromise.result
"pending"	undefined
"fulfilled"	a result value
"rejected"	an error object

Mongoose

- We know, MongoDB is a schema-less NoSQL document database. It means you can store JSON documents in it, and the structure of these documents can vary as it is not enforced like SQL databases.
- Using NoSQL database speeds up the process of application development and reduces the complexity of deployments.
- Mongoose is an ***Object Document Modeling (ODM)*** layer that sits on top of the Node.js MongoDB API. If you're coming from an SQL background, then Mongoose is similar to an ***Object Relational Mapping (ORM)***.

- **Schemas:** Schemas allow to give a structure to the collection.
- **Built-in validation:** This means you don't have to write the extra code that you had to write with the MongoDB driver. By simply including things like ***required: true*** in your schema definitions, Mongoose provides in-house validations for your collections (including data types).
- **Instance methods:** You can define custom methods on a document with minimal code. While it's possible to do the same in MongoDB, Mongoose makes it easier to create and organise such methods within your schema definition.

- **Returning results:** Returning documents generated by queries is generally easier in Mongoose. One example is the update queries. In MongoDB, this query only returns an object with a success flag and the number of documents modified. Mongoose, on the other hand, provides you the updated document itself so you can easily process the results.

Schemas:

Everything in Mongoose starts with a Schema.

Each schema maps to a MongoDB collection and defines the shape of the documents within that collection.

It has information about properties/field types of documents. Schemas can also store information about validation and default values, and whether a particular property is required. In simple words, they're blueprints for documents.

Model:

A model is a class with which we construct documents.

Install mongoose

Simply install the mongoose module through npm.

```
npm install mongoose
```

Note : *Make a folder **mongoose-pracs** and then do*

```
npm init
```

```
npm install mongoose --S
```

- Create a file **./database.js** under the project root.
- Add a simple class with a method that connects to the database.

Note: The connection string will vary based on your installation.

```
const mongoose = require('mongoose')
mongoose.connect('mongodb://localhost/test', {useNewUrlParser:
true, useUnifiedTopology: true });
```

- In the given example, we're connecting to a database called test. The first parameter is the URL and the second parameter is options.

Note : We would be using a Object Oriented Style of coding in the practical.

Refer To: [mongoose-pracs/database.js](https://mongoose-pracs.com/database.js)

- A Mongoose model is a wrapper on the Mongoose schema.
- Schema defines the structure of the document, default values, validators, etc., whereas a model provides an interface to the database for creating, querying, updating, deleting records.
- Creating a Mongoose model comprises primarily of three parts:
 - **Referencing Mongoose**

```
let mongoose = require('mongoose')
```

- **Defining the Schema**

A schema defines document properties through an object where the key name corresponds to the property name in the collection.

```
let emailSchema = new mongoose.Schema({  
  email: String  
})
```

Here we define a **property called email with a schema type String** which maps to an internal validator that will be triggered when the model is saved to the database. It will fail if the data type of the value is not a string type.

- **Exporting a Model**

We need to call the model constructor on the Mongoose instance and pass it the name of the collection and a reference to the schema definition.

```
module.exports = mongoose.model('Email', emailSchema)
```

We can create an instance of the model we defined above and populate it using the following syntax:

```
let EmailModel = require('./email_model_v1.js')
let msg = new EmailModel({
  email: 'rockyjagtiani@gmail.com'
})
```

The following schema types are permitted:

- Array
- Boolean
- Buffer
- Date
- Mixed (A generic/flexible data type)
- Number
- ObjectId
- String

Mixed and ObjectId are defined under `require('mongoose').Schema.Types`.

Refer To: [email_model_v1.js](#) and [email.js](#)

Hands on Exercise (20 mins)

Enhance the email schema as follows :


- make the email property unique.
- mark email as required field such that it cannot be null.
- convert the email value to lowercase before saving it.
- add a validation function that will ensure that the value is a valid email address.

(hint: use mongoose built-in library called validator library)

Steps :

1. Reuse the [email_model_v1.js](#) file. Edit it to accommodate above properties and save the file as **email_model_v2.js**
2. To use the mongoose validator library, install it as **`npm install validator -S`**
3. Try running the same code twice. On the second run, we should get **duplicate key** error.

CRUD Operations with Mongoose



To create an instance of the email model and save it to the database use .save method.

```
let EmailModel = require('./email_model_v2.js')
let msg = new EmailModel({
  email: 'SREEJITnair@GMAIL.COM'
})

msg.save()
  .then(doc => {
    console.log(doc)
  })
  .catch(err => {
    console.error(err)
  })
```

The following fields are returned (internal fields are prefixed with an underscore) after a CREATE operation , i.e. when using **.save()** :

1. The **_id** field is auto-generated by Mongo and is a primary key of the collection. Its value is a unique identifier for the document.
2. The value of the email field is returned. Notice that it is lower-cased because we specified the **lowercase:true** attribute in the schema.
3. **__v** is the **versionKey** property set on each document when first created by Mongoose. Its value contains the internal revision of the document.

To retrieve the record use find method with some search query.

The model class exposes several static methods and instance methods to perform operations on the database. We will now try to find the record that we created previously using the find method and pass the email as the search term.

```
EmailModel.find({
  email: 'rockyjagtiani@gmail.com'
  // search query
})
.then(doc => {
  console.log(doc)
})
.catch(err => {
  console.error(err)
})
```

Refer To: [fetch-records.js](#)

- To find and modify a record use ***findOneAndUpdate()*** method.
- As the name implies, ***findOneAndUpdate()*** finds the first document that matches a given filter, applies an update, and returns the document.
- By default, ***findOneAndUpdate()*** returns the original document.
- For the program to return the updated document, the `new` option should be set to `true`.

For performance reasons, Mongoose won't return the updated document so we need to pass an additional parameter to ask for it.

```
EmailModel.findOneAndUpdate({
  email: 'akshaykumar@gmail.com'
  // search query
},
{
  email: 'superhero@gmail.com'
  // field:values to update
},
{
  new: true,           // return updated doc
  runValidators: true  // validate before update
}
)
```

- The ***updateMany()*** function is same as ***update()***, in MongoDB.
- It will update all documents that match the given condition. It is often used when the user wishes to update all the documents with specific condition.
- This function has 4 parameters
filter, update, options, callback.
- For example: find all documents matching the condition(**marks >= 99**) and update remark as 'excellent' in all the documents.

```
StudentTestSchema.updateMany(  
  {marks : {$gte:99},  
  {remark : "excellent"}  
).then(doc => {  
  console.log(doc)  
})  
.catch(err => {  
  console.error(err)  
})
```

Refer To: [update-many-records.js](#)

- We can search for documents based on certain conditions and remove it.
- The ***findOneAndRemove()*** or ***findOneAndDelete()*** function is used to find the element according to the condition and then remove the first matched element.

```
StudentTestSchema.findOneAndRemove({
  marks:{$lt:99}
})
.then(doc => {
  console.log(doc)
})
.catch(err => {
  console.error(err)
})
```

Poll 3 (15 Sec)

Models are fancy constructors compiled from Schema definitions. An instance of a model is called a document. Models are responsible for creating and reading documents from the underlying MongoDB database.

1. True
2. False

Poll 3 (Answer)

Models are fancy constructors compiled from Schema definitions. An instance of a model is called a document. Models are responsible for creating and reading documents from the underlying MongoDB database.

1. **True**
2. False

Poll 4 (15 Sec)

Mongoose documents represent a one-to-one mapping to documents as stored in MongoDB. Each document is an instance of its Model.

1. True
2. False

Poll 4 (Answer)

Mongoose documents represent a one-to-one mapping to documents as stored in MongoDB. Each document is an instance of its Model.

1. **True**
2. False

Hands on Exercise (20 mins)

- Create a book Schema with following properties :
 - name
 - author
 - pages
 - Bestprice
 - kindleversion
- Define the Model.
- Insert four book records. (use *insertMany()*)
- Update one of the documents. Like the one which has a **bestprice** more than Rs 2000. Change it to Rs 1999. (use **updateOne()**)
- Delete one document which has no kindle version. (use **deleteOne()**)
- Find all books having kindleVersion as true.

Refer To: [books-CRUD.js](#)

Helper Methods

- We have looked at some of the basic functionality known as CRUD (Create, Read, Update, Delete) operations, but Mongoose also provides the ability to configure several types of helper methods and properties.
- To understand power of helper methods, we would code the following :
 - Instance methods
 - Static methods
 - Hooks (or middleware functions)

- The documents derived from their respective schemas can use these methods.
- For example, with respect to the **UserSchema** we would create a instance method that will provide us with the initials name of the people.

Remember : Instance methods work on the objects and not on the model

```
let userSchema = new mongoose.Schema({
  firstName: String,
  lastName: String
})

userSchema.methods.getInitials = function() {
  return this.firstName[0] + this.lastName[0]
}

// making a Model from the Schema
let UserModel = mongoose.model('User', userSchema)

// Making objects of the Model
let userobject = new UserModel({
  firstName: 'Rocky',
  lastName: 'Jagtiani'
})

let initials = userobject.getInitials()
console.log(initials)
```


Refer To: [instance-method.js](#)

- These are used whenever we don't have a particular object or we don't need it.
- The models derived from their respective schemas can use these methods.
- For example, we would add a static method to find someone by its first-name.

```
userSchema.statics.findByName = function(value){  
  this.find( {firstName : value}, (err, document)=>{  
    console.log(document);  
  })  
}
```

Refer To: [static-method.js](#)

- Middleware are functions that run at specific stages of a pipeline.
- Mongoose supports middleware for the following operations:
 - Aggregate
 - Document
 - Model
 - Query
- For instance, models have **pre and post functions** that take two parameters:
 - Type of event ('init', 'validate', 'save', 'remove')
 - A callback that is executed with ***this*** referencing the model instance.



Refer To: [middleware.js](#)

- When ***model.save()*** is called, there is a `pre('save', ...)` and `post('save', ...)` event that is triggered.
- For the second parameter to `pre()` and `post()`, you can pass a function that is called when the event is triggered. These functions take a parameter to the next function in the middleware chain.
- For example: **pre-save hook** set's values for **createdAt** and **updatedAt** properties.

```
userSchema.pre('save', function (next) {  
  let now = Date.now()  
  
  this.updatedAt = now  
  // Set a value for createdAt only if it is null  
  if (!this.createdAt) {  
    this.createdAt = now  
  }  
  
  // Call the next function in the pre-save chain  
  next()  
})
```

- Suppose that we want to track when a record was created and last updated on every collection in our database.
- Instead of repeating the middleware process i.e. defining a `pre("save", ...)` method on each schema; we can create a plugin and apply it to every schema.

```
let timestampPlugin = require('./plugins/timestamp')  
  
emailSchema.plugin(timestampPlugin)  
userSchema.plugin(timestampPlugin)
```

Refer To: [useplugins.js](#) and [plugins/timestamp.js](#)

Poll 5 (15 Sec)

Middleware (also called pre and post hooks) are functions which are passed control during execution of asynchronous functions. Middleware is specified on the schema level and is useful for writing plugins.

1. True
2. False

Poll 5 (Answer)

Middleware (also called pre and post hooks) are functions which are passed control during execution of asynchronous functions. Middleware is specified on the schema level and is useful for writing plugins.

1. **True**
2. False

Project Work - Checkpoint 4



- Define the Schema according to client requirements. (refer **app/models/tutorial.model.js**)
 - title: String
 - description: String
 - published: Boolean
 - skills : String Array
 - Chapters : String Array
- priceInRupees: Number
keep the default as 5000. Don't allow negative values, means minimum as 0 and maximum as 30000.
- priceAfterDiscount: Number
Don't allow negative values, means minimum as 0 and maximum as 30000.

- category: String
category would get its value through a drop down from React frontend
- imageURL: String
Keep the default as : <https://ik.imagekit.io/upgrad1/marketing-platform-assets/meta-images/home.jpg>
- videoURL: String
Keep the default as : <https://www.youtube.com/watch?v=MTdpHs6HWwM>
- notesURL: String
Keep the default as : <https://www.mongodb.com/mern-stack>

- duration in mins: Number
Set default to 60 and keep minimum as 0 and maximum as 1200 minutes
- popularity: Number
Keep the default as : 4.0

Refer To: app/models/tutorial.model.js

- Define a simple generic USER Schema.
(refer **app/models/user.model.js**)
 - email: String
 - password: String
 - firstName : String
 - lastName : String
 - role: String
- Keep the default as 'user'. There would be only two kinds of user
 - user
 - admin

Refer To: [app/models/user.model.js](#)

- Define a Enrollment Schema.
 - userId: String
 - courseId: String

Refer To: <app/models/enrollment.model.js>

- Under the app/models folder we would need to define a index.js file. This would be executed when we load the app/models folder.
- The app/models/index.js file would load the db.config file, load the mongoose library and make a mongoose object, to be used in the entire project.
- In the server.js when we load /app/models
const db = require("./app/models");
- index.js runs and initializes all the model parameters, needed for backend.
- In the server.js , we would later add more code. For backend programming only below code is needed in **server.js**.


```
const db = require("./app/models");
db.mongoose
  .connect(db.url, {
    useNewUrlParser: true,
    useUnifiedTopology: true
  })
  .then(() => {
    console.log("Connected to the database!");
  })
  .catch(err => {
    console.log("Cannot connect to the database!", err);
    process.exit(1);
  });
```

Refer To: [server.js](#) and [app/models/index.js](#)

Homework

- Create a Movie Schema with following properties :
 - title (define options for required field and unique field)
 - year (define option for required field)
 - actors
- Define the Model.
- Insert 2-3 movie records. (use *insertMany()* method)
- Check at the backend using compass.

Refer: [mongoose_homework_1.js](#)

Doubt Clearance (5 mins)

Key Takeaways

- We understood the advantages of using Mongoose ODM in our applications.

The following tasks are to be completed after today's session:

Homework
MCQs
Coding Questions
Course Project - Checkpoint 5

In the next class, we will discuss...

- Different types of relationships in Mongoose.



Thank you!