

**flask** (version 0.12.2)[index](#)  
[/usr/local/lib/python2.7/dist-packages/flask/\\_\\_\\_init\\_\\_\\_py](/usr/local/lib/python2.7/dist-packages/flask/__init__.py)flask  
~~~~~

A microframework based on Werkzeug. It's extensively documented and follows best practice patterns.

:copyright: (c) 2015 by Armin Ronacher.  
:license: BSD, see LICENSE for more details.

## Package Contents

|                            |                               |                          |                            |
|----------------------------|-------------------------------|--------------------------|----------------------------|
| <a href="#">main</a>       | <a href="#">config</a>        | <a href="#">globals</a>  | <a href="#">signals</a>    |
| <a href="#">compat</a>     | <a href="#">ctx</a>           | <a href="#">helpers</a>  | <a href="#">templating</a> |
| <a href="#">app</a>        | <a href="#">debughelpers</a>  | <a href="#">json</a>     | <a href="#">testing</a>    |
| <a href="#">blueprints</a> | <a href="#">ext (package)</a> | <a href="#">logging</a>  | <a href="#">views</a>      |
| <a href="#">cli</a>        | <a href="#">exthook</a>       | <a href="#">sessions</a> | <a href="#">wrappers</a>   |

## Data

```
__version__ = '0.12.2'  
appcontext_popped = <blinker.base.NamedSignal object at  
0x7f4eb20bb810; 'appcontext-popped'>  
appcontext_pushed = <blinker.base.NamedSignal object at  
0x7f4eb20bb7d0; 'appcontext-pushed'>  
appcontext_tearing_down = <blinker.base.NamedSignal object at  
0x7f4eb20bb790; 'appcontext-tearing-down'>  
before_render_template = <blinker.base.NamedSignal object at  
0x7f4eb20b48d0; 'before-render-template'>  
current_app = <LocalProxy unbound>  
g = <LocalProxy unbound>  
got_request_exception = <blinker.base.NamedSignal object at  
0x7f4eb20bb750; 'got-request-exception'>  
json_available = True  
message_flashed = <blinker.base.NamedSignal object at  
0x7f4eb20bb850; 'message-flashed'>  
request = <LocalProxy unbound>  
request_finished = <blinker.base.NamedSignal object at  
0x7f4eb20bb6d0; 'request-finished'>  
request_started = <blinker.base.NamedSignal object at  
0x7f4eb20bb690; 'request-started'>  
request_tearing_down = <blinker.base.NamedSignal object at  
0x7f4eb20bb710; 'request-tearing-down'>
```

```
session = <LocalProxy unbound>  
signals_available = True  
template_rendered = <blinker.base.NamedSignal object at  
0x7f4eb20b4890; 'template-rendered'>
```