

# Supplementary Material for “Finding Patches for Open Source Software Vulnerabilities”

Anonymous Author(s)

## 1 DATASET ANALYSIS

We analyzed the 1,295 CVEs in our depth dataset with respect to years and programming languages. We determined the programming language of a CVE by analyzing the changed source files in patches. As shown in Fig. 1a, the number of CVEs increases every year, which is consistent with Snyk’s report<sup>1</sup>. As reported in Fig. 1b, these CVEs mainly cover seven programming languages, which demonstrates relatively good coverage of ecosystems. Therefore, we believe that our depth dataset is representative of OSS vulnerabilities.

## 2 ACCURACY ANALYSIS.

We analyzed the intersection between the patches identified by TRACER (denoted as  $P_{\text{TRACER}}$ ) and our manually identified patches (denoted as  $P_{\text{GT}}$ ) for each CVE in our depth dataset. In particular, we classify intersection relationships into six categories, which are used as another indicator of patch accuracy. The results are reported in Table 1, where the first column lists the six categories, the second column shows the number of CVEs belonging to each category, and the last column gives the total number of patches found by TRACER.

It can be observed that TRACER can find patches accurately and completely for 773 (59.7%) CVEs (i.e.,  $P_{\text{TRACER}} = P_{\text{GT}}$ ), with an average of 1.9 found patches for each CVE. TRACER can find patches completely but include some false positives for 128 (9.9%) CVEs (i.e.,  $P_{\text{TRACER}} \supset P_{\text{GT}}$ ). In that sense, 901 (69.6%) CVEs’ patches are completely found by TRACER. Besides, TRACER can find patches accurately but have some false negatives for 139 (10.7%) CVEs (i.e.,  $P_{\text{TRACER}} \subset P_{\text{GT}}$ ). TRACER incurs both false positives and false negatives for 27 (2.1%) CVEs (i.e.,  $P_{\text{TRACER}} \cap P_{\text{GT}} \neq \emptyset$ ), while the patches found for 73 (5.6%) CVEs by TRACER are all false positives (i.e.,  $P_{\text{TRACER}} \cap P_{\text{GT}} = \emptyset$ ). Notice that we analyze the reasons for false positives and false negatives in the submitted paper. These results demonstrate the capability of TRACER in finding patches accurately and completely.

## 3 SENSITIVITY ANALYSIS

TRACER has two configurable parameters, i.e., the network depth limit in the first step of TRACER and the commit span in the third step. The default configuration is 5 and 30, which is used in the evaluation for RQ6, RQ7, RQ8 and RQ9. To evaluate the sensitivity of TRACER to the two parameters, we reconfigured one parameter and fix the other, and reran TRACER against our depth dataset. Specifically, the network depth limit was configured from 3 to 6 by a step of 1, and the commit span was configured from 0 to 60 by a step of 10.

Fig. 2a and 2b show the impact of the two parameters on the accuracy of TRACER, where  $x$ -axis denotes the value of the parameter, and  $y$ -axis denotes the accuracy of TRACER. Overall, as the network depth limit increases, more potential patches are included in our reference network. The number of CVEs that TRACER finds no patch and precision decrease, and recall and F1-score first increase and then decrease. Hence, we believe 5 is a good value for the network depth

Table 1: Intersection between TRACER and Ground Truth

$P_{\text{TRACER}}$ vs. $P_{\text{GT}}$	Number of CVEs	Sum of Found Patches
$P_{\text{TRACER}} = P_{\text{GT}}$	773 (59.7%)	1,451
$P_{\text{TRACER}} \supset P_{\text{GT}}$	128 (9.9%)	708
$P_{\text{TRACER}} \subset P_{\text{GT}}$	139 (10.7%)	289
$P_{\text{TRACER}} \cap P_{\text{GT}} \neq \emptyset$	27 (2.1%)	134
$P_{\text{TRACER}} \cap P_{\text{GT}} = \emptyset$	73 (5.6%)	250
$P_{\text{TRACER}} = \emptyset$	155 (12.0%)	0
Total	1,295	2,832

limit. As the commit span increases, a wider scope of commits are searched. Precision decreases, recall increases, and F1-score first increases and then decreases. Notice that the number of CVEs TRACER finds no patch will not change and thus is not presented in Fig. 2b. Hence, we believe 30 is a good value for the commit span. These results indicate that the sensitivity of the accuracy of TRACER to the two configurable parameters is acceptable.


## 4 APPLICATION ANALYSIS

TRACER is configurable to meet different accuracy requirements of applications. For applications that need **high patch precision**, TRACER can be configured to not construct the reference network in a layered way but simply use the direct references contained in the four advisory sources (i.e., skipping reference analysis in the first step). As shown by our ablation analysis in the submitted paper, this is actually the variant  $v_1^5$ , and achieves the highest precision of 0.918, 6.3% higher than that of the original TRACER.


For applications that need **high patch recall**, TRACER can be configured to not follow the patch selection step in TRACER but select all patches in our reference network. As shown by our ablation analysis in the submitted paper, this is actually the variant  $v_2^1$ , and achieves the highest recall of 0.940, 8.8% higher than that of the original TRACER.

These results demonstrate that the two variants of TRACER can meet the practical requirements of high precision and high recall.

<sup>1</sup>[https://snyk.io/wp-content/uploads/sooss\\_report\\_v2.pdf](https://snyk.io/wp-content/uploads/sooss_report_v2.pdf)




(a) Our Depth Dataset w.r.t. Years




(b) Our Depth Dataset w.r.t. Programming Languages

Figure 1: Our Depth Dataset w.r.t Years and Programming Languages



(a) Network Depth Limit



(b) Commit Span

Figure 2: Sensitivity Analysis Result for Network Depth Limit and Commit Span