

# CS685: DATA MINING

## DATA PREPROCESSING AND DATA CLEANING

Arnab Bhattacharya  
`arnabb@cse.iitk.ac.in`

Computer Science and Engineering,  
Indian Institute of Technology, Kanpur  
<http://web.cse.iitk.ac.in/~cs685/>

1<sup>st</sup> semester, 2020-21  
Mon 1030-1200 (online)

- Data should have the following qualities
  - Accuracy
  - Completeness
  - Consistency
  - Timeliness
  - Reliability
  - Interpretability
  - Availability

# Types of Data

- Data values can be classified as **discrete** or **continuous**

# Types of Data

- Data values can be classified as **discrete** or **continuous**
- *Discrete*
  - Finite or countably infinite set of values
  - Countably infinite sets have a one-to-one correspondence with the set of natural numbers

# Types of Data

- Data values can be classified as **discrete** or **continuous**
- *Discrete*
  - Finite or countably infinite set of values
  - Countably infinite sets have a one-to-one correspondence with the set of natural numbers
- *Continuous*
  - Real numbers
  - Precision of measurement and machine-representation limit possibilities
  - Not continuous in the actual sense

# Types of Data

- Data values can be classified as **discrete** or **continuous**
- *Discrete*
  - Finite or countably infinite set of values
  - Countably infinite sets have a one-to-one correspondence with the set of natural numbers
- *Continuous*
  - Real numbers
  - Precision of measurement and machine-representation limit possibilities
  - Not continuous in the actual sense
- Data can also be classified in other ways

# Categorical Data

- Categorical data is *qualitative*

# Categorical Data

- **Categorical** data is *qualitative*
- **Nominal**
  - Categories
  - Example: color
  - Operations: equal, not equal
- **Binary**
  - Special case of nominal
  - Example: gender, diabetic
  - Symmetric: Two cases are equally important
  - Asymmetric: One case is more important



# Categorical Data

- **Categorical** data is *qualitative*
- **Nominal**
  - Categories
  - Example: color
  - Operations: equal, not equal
- **Binary**
  - Special case of nominal
  - Example: gender, diabetic
  - Symmetric: Two cases are equally important
  - Asymmetric: One case is more important
- **Ordinal** or **Rank** or **Ordered scalar**
  - Can order
  - Example: small, medium, large
  - Operations: equality, lesser, greater

# Categorical Data

- **Categorical** data is *qualitative*
- **Nominal**
  - Categories
  - Example: color
  - Operations: equal, not equal
- **Binary**
  - Special case of nominal
  - Example: gender, diabetic
  - Symmetric: Two cases are equally important
  - Asymmetric: One case is more important
- **Ordinal** or **Rank** or **Ordered scalar**
  - Can order
  - Example: small, medium, large
  - Operations: equality, lesser, greater
  - Difference has no meaning

# Numeric Data

- **Numeric** data is *quantitative*

# Numeric Data

- **Numeric** data is *quantitative*
- **Ratio-scaled**
  - Has a *zero point*: absolute values are ratios of each other
  - Example: temperature in Kelvin, age, mass, length
  - Operations: difference, ratio

# Numeric Data

- **Numeric** data is *quantitative*
- **Ratio-scaled**
  - Has a *zero point*: absolute values are ratios of each other
  - Example: temperature in Kelvin, age, mass, length
  - Operations: difference, ratio
- **Interval-scaled**
  - Measured on equal sized units
  - Example: temperature in Celsius, date
  - No zero point: absolute value has no meaning
  - Operations: difference

# Data Errors and Parameters

- Errors in data due to
  - Measurement error
  - Data collection error
  - **Noise**: probabilistic
  - **Artifact**: deterministic distortions

# Data Errors and Parameters

- Errors in data due to
  - Measurement error
  - Data collection error
  - **Noise**: probabilistic
  - **Artifact**: deterministic distortions
- Parameters to measure the quality of measurements
  - **Precision**: closeness of repeated measurements
  - **Bias**: systematic variation of measurements
  - **Accuracy**: closeness of measurements to true value

# Data Errors and Parameters

- Errors in data due to
  - Measurement error
  - Data collection error
  - **Noise**: probabilistic
  - **Artifact**: deterministic distortions
- Parameters to measure the quality of measurements
  - **Precision**: closeness of repeated measurements
  - **Bias**: systematic variation of measurements
  - **Accuracy**: closeness of measurements to true value
- Data problems
  - Missing values
  - Noise
  - Outliers
  - Inconsistent values
  - Duplicate objects



# Data Errors and Parameters

- Errors in data due to
  - Measurement error
  - Data collection error
  - **Noise**: probabilistic
  - **Artifact**: deterministic distortions
- Parameters to measure the quality of measurements
  - **Precision**: closeness of repeated measurements
  - **Bias**: systematic variation of measurements
  - **Accuracy**: closeness of measurements to true value
- Data problems
  - Missing values
  - Noise
  - Outliers
  - Inconsistent values
  - Duplicate objects
- *Domain knowledge* about data and attributes helps data mining

# Data Preprocessing

- **Data preprocessing** is the process of preparing the data to be fit for data mining algorithms and methods
- Known as **ETL** (Extract, Transform, Load)
- It may involve one or more of the following steps
  - Data cleaning
  - Data reduction/summarization
  - Data integration
  - Data transformation

# Data Cleaning

- Process of handling errors in data
- Different ways
- Filling in missing values
- Handling noise
- Removing outliers
  - One of the main methods in handling noise
- Resolving inconsistent data
  - Out of range
  - Once identified as inconsistent data, handled as missing value
- De-duplicating duplicated objects

# Missing Values

- Ignore the data object

# Missing Values

- Ignore the data object
- Ignore only the missing attribute during analysis

# Missing Values

- Ignore the data object
- Ignore only the missing attribute during analysis
- Estimate the missing value

# Missing Values

- Ignore the data object
- Ignore only the missing attribute during analysis
- Estimate the missing value
- Use a measure of overall *central tendency*
  - Mean or median
- Use a measure of central tendency from only the *neighborhood*

# Missing Values

- Ignore the data object
- Ignore only the missing attribute during analysis
- Estimate the missing value
- Use a measure of overall *central tendency*
  - Mean or median
- Use a measure of central tendency from only the *neighborhood*
- Interpolation
  - Useful for temporal and spatial data



# Missing Values

- Ignore the data object
- Ignore only the missing attribute during analysis
- Estimate the missing value
- Use a measure of overall *central tendency*
  - Mean or median
- Use a measure of central tendency from only the *neighborhood*
- Interpolation
  - Useful for temporal and spatial data
- Use the most probable value
  - Mode

# Noise

- **Noise** is a *random* perturbation in the data
- It is generally assumed that magnitude of noise is smaller than magnitude of attribute of interest
  - **Signal-to-noise** ratio should not be too low
- **White noise**
  - Gaussian distribution with zero mean

# Noise

- **Noise** is a *random* perturbation in the data
- It is generally assumed that magnitude of noise is smaller than magnitude of attribute of interest
  - **Signal-to-noise** ratio should not be too low
- **White noise**
  - Gaussian distribution with zero mean
- As opposed to noise, bias can be corrected since it is deterministic

# Noise

- **Noise** is a *random* perturbation in the data
- It is generally assumed that magnitude of noise is smaller than magnitude of attribute of interest
  - **Signal-to-noise** ratio should not be too low
- **White noise**
  - Gaussian distribution with zero mean
- As opposed to noise, bias can be corrected since it is deterministic
- Histogram binning
  - Bin values are replaced by mean or median
  - Equi-width histograms are more common than equi-depth

- **Noise** is a *random* perturbation in the data
- It is generally assumed that magnitude of noise is smaller than magnitude of attribute of interest
  - **Signal-to-noise** ratio should not be too low
- **White noise**
  - Gaussian distribution with zero mean
- As opposed to noise, bias can be corrected since it is deterministic
- Histogram binning
  - Bin values are replaced by mean or median
  - Equi-width histograms are more common than equi-depth
- Regression
  - Fitting a function to describe the values
  - Small values of noise do not affect the overall fit
  - Noisy value replaced by most likely value predicted by the function

# Noise

- **Noise** is a *random* perturbation in the data
- It is generally assumed that magnitude of noise is smaller than magnitude of attribute of interest
  - **Signal-to-noise** ratio should not be too low
- **White noise**
  - Gaussian distribution with zero mean
- As opposed to noise, bias can be corrected since it is deterministic
- Histogram binning
  - Bin values are replaced by mean or median
  - Equi-width histograms are more common than equi-depth
- Regression
  - Fitting a function to describe the values
  - Small values of noise do not affect the overall fit
  - Noisy value replaced by most likely value predicted by the function
- **Outlier** identification and removal

# Data Duplication

- Same (or almost same) values

# Data Duplication

- Same (or almost same) values
- Duplicate objects may appear during data insertion or data transfer
- Mostly due to data collection errors



# Data Duplication

- Same (or almost same) values
- Duplicate objects may appear during data insertion or data transfer
- Mostly due to data collection errors
- Introduces errors in statistics about the data
- If most attributes are exact copies, then it is easy to remove
- Sometimes one or more attributes are slightly different
- *Domain knowledge* needs to be utilized to identify such cases
- Process is called **de-duplication**

# Data Integration

- **Data integration** is the process of transforming multiple data sources into one single coherent source
- Useful when there are multiple databases about the same set of objects

# Data Integration

- **Data integration** is the process of transforming multiple data sources into one single coherent source
- Useful when there are multiple databases about the same set of objects
- **Schema matching** and **entity identification**
  - Is cust\_id equal to cust\_number?
- Correlation analysis to reduce redundancy
- Chi-square test for categorical data
- De-duplication

# Data Transformation

- Data transformation is useful when

# Data Transformation

- **Data transformation** is useful when
  - Identifying trends
  - Normalizing to correctly get statistics
  - Applying particular data mining algorithms

# Data Transformation

- **Data transformation** is useful when
  - Identifying trends
  - Normalizing to correctly get statistics
  - Applying particular data mining algorithms
- Smoothing of bins using histograms
- Aggregation and summarization
- Generalization
- Normalization

# Normalization

- **Normalization** changes the range of values

# Normalization

- **Normalization** changes the range of values
- **Min-max normalization**

$$x' = \frac{x - \min}{\max - \min}$$

- This puts range to



# Normalization

- **Normalization** changes the range of values
- **Min-max normalization**

$$x' = \frac{x - \min}{\max - \min}$$

- This puts range to (0, 1)
- If new range is (min', max')

# Normalization

- **Normalization** changes the range of values
- **Min-max normalization**

$$x' = \frac{x - \min}{\max - \min}$$

- This puts range to (0, 1)
- If new range is ( $\min'$ ,  $\max'$ )

$$x' = \left( \frac{x - \min}{\max - \min} \right) (\max' - \min') + \min'$$

# Normalization

- **Normalization** changes the range of values
- **Min-max normalization**

$$x' = \frac{x - \min}{\max - \min}$$

- This puts range to (0, 1)
- If new range is ( $\min'$ ,  $\max'$ )

$$x' = \left( \frac{x - \min}{\max - \min} \right) (\max' - \min') + \min'$$

- **Z-score normalization**

$$x' = \frac{x - \mu}{\sigma}$$

where  $\mu$  is the mean and  $\sigma$  is the standard deviation

- This puts range to

# Normalization

- **Normalization** changes the range of values
- **Min-max normalization**

$$x' = \frac{x - \min}{\max - \min}$$

- This puts range to (0, 1)
- If new range is (min', max')

$$x' = \left( \frac{x - \min}{\max - \min} \right) (\max' - \min') + \min'$$

- **Z-score normalization**

$$x' = \frac{x - \mu}{\sigma}$$

where  $\mu$  is the mean and  $\sigma$  is the standard deviation

- This puts range to  $(-\infty, +\infty)$
- Also called **standard score** or **z-score** since it corresponds to the standard normal distribution  $N(0, 1)$