

VISVESVARAYA TECHNOLOGICAL UNIVERSITY

“JnanaSangama”, Belgaum -590014, Karnataka.



LAB REPORT
on

OPERATING SYSTEMS

Submitted by

ABHISHEK (1BM24CS008)

in partial fulfillment for the award of the degree of
BACHELOR OF ENGINEERING
in
COMPUTER SCIENCE AND ENGINEERING



B.M.S. COLLEGE OF ENGINEERING

(Autonomous Institution under VTU)

BENGALURU-560019

Feb-2026 to June-2026

B. M. S. College of Engineering,
Bull Temple Road, Bangalore 560019
(Affiliated To Visvesvaraya Technological University, Belgaum)
Department of Computer Science and Engineering



CERTIFICATE

This is to certify that the Lab work entitled “OPERATING SYSTEMS – 23CS4PCOPS” carried out by ABHISHEK (1BM24CS008), who is Bonafide student of B. M. S. College of Engineering. It is in partial fulfilment for the award of Bachelor of Engineering in Computer Science and Engineering of the Visvesvaraya Technological University, Belgaum during the year Feb-2026 to June-2026 . The Lab report has been approved as it satisfies the academic requirements in respect of a OPERATING SYSTEMS - (23CS4PCOPS) work prescribed for the said degree.

Faculty Incharge Name
Assistant Professor
Department of CSE
BMSCE, Bengaluru

Dr. Kavitha Sooda
Professor and Head
Department of CSE
BMSCE, Bengaluru

Index Sheet

Sl. No.	Experiment Title	Page No.
1.	Write a C program to simulate the following CPU scheduling algorithm to find turnaround time and waiting time. →FCFS → SJF (pre-emptive & Non-preemptive) → Priority (pre-emptive & Non-pre-emptive) →Round Robin (Experiment with different quantum sizes for RR algorithm)	5-20
2.	Write a C program to simulate multi-level queue scheduling algorithm considering the following scenario. All the processes in the system are divided into two categories – system processes and user processes. System processes are to be given higher priority than user processes. Use FCFS scheduling for the processes in each queue.	21-23
3.	Write a C program to simulate Real-Time CPU Scheduling algorithms: a) Rate- Monotonic b) Earliest-deadline First c) Proportional scheduling	24-29
4.	Write a C program to simulate a)producer-consumer problem using semaphores b)concept of Dining Philosophers problem.	30-35
5.	Write a C program to simulate a)Bankers algorithm for the purpose of deadlock avoidance. b)Deadlock Detection	36-43
6.	Write a C program to simulate the following contiguous memory allocation techniques. a) Worst-fit b) Best-fit c) First-fit	44-48
7.	Write a C program to simulate page replacement algorithms. a) FIFO b)LRU c)Optimal	49-55

Course Outcomes

C01	Apply the different concepts and functionalities of Operating System
C02	Analyse various Operating system strategies and techniques
C03	Demonstrate the different functionalities of Operating System.
C04	Conduct practical experiments to implement the functionalities of Operating system.

Program – 1

Question:

Write a C program to simulate the following CPU scheduling algorithm to find turnaround time and waiting time.

→FCFS

→ SJF (pre-emptive & Non-preemptive)

→ Priority (pre-emptive & Non-pre-emptive)

→Round Robin (Experiment with different quantum sizes for RR algorithm)

Code:

FCFS

```
#include<stdio.h>

int main()
{
    printf("USN : 1BM24CS004 NAME:ABDUL AZEEZ \n");

    int p[100],at[100],bt[100],ct[100],tat[100],wt[100],rt[100],n,g[100],c=0,a=0,b=0;
    printf("Enter no of processes : ");
    scanf("%d",&n);
    for(int i=0;i<n;i++){
        p[i]=i;
    }
    printf("Enter Arrival time and Burst time of processes (AT BT) \n ");
    for(int j=0;j<n;j++){
        printf("Process %d \n",j);
        scanf("%d%d",&at[j],&bt[j]);
    }
}
```

```

for(int i=0;i<n-1;i++){
    for(int j=i+1;j<n;j++){
        if(at[i]>at[j]){
            int t;
            t=at[i];
            at[i]=at[j];
            at[j]=t;
            t=bt[i];
            bt[i]=bt[j];
            bt[j]=t;
            t=p[i];
            p[i]=p[j];
            p[j]=t;
        }
    }
}
c=0;
for (int i=0;i<n;i++){
    if(c<at[i]){
        c=at[i];
    }
    ct[i]=c+bt[i];
    tat[i]=ct[i]-at[i];
    wt[i]=tat[i]-bt[i];
    c=ct[i];
}
printf(" Pid\tat\tbt\tct\ttat\twt\n");
for(int i=0;i<n;i++){

```



```

    printf(" %d\t%d\t%d\t%d\t%d\t%d\r\n",p[i],at[i],bt[i],ct[i],tat[i],wt[i]);
}
for(int i=0;i<n;i++){
    a=a+tat[i];
    b=b+wt[i];
}
printf("Avg Turn around time : %d \n Avg waiting time : %d",a/n,b/n);
return 0;
}

```

Result:

```

USN : 1BM24CS008 NAME:ABHISHEK
Enter no of processes : 4
Enter Arrival time and Burst time of processes (AT BT)
Process 0
0 7
Process 1
8 3
Process 2
3 4
Process 3
5 6

```

Pid	at	bt	ct	tat	wt
0	0	7	7	7	0
2	3	4	11	8	4
3	5	6	17	12	6
1	8	3	20	12	9

```

Avg Turn around time : 9
Avg waiting time : 4
Process returned 0 (0x0)   execution time : 19.631 s
Press any key to continue.
|

```


SJF(Non-preemptive):

```
#include<stdio.h>
int main()
{
    printf("USN : 1BM24CS004 NAME:ABDUL AZEEZ \n");

    int p[100],at[100],bt[100],ct[100],tat[100],wt[100],rt[100],n,g[100],c=0,a=0,b=0,f[100]={0},
    completed=0;
    printf("Enter no of processes : ");
    scanf("%d",&n);
    for(int i=0;i<n;i++){
        p[i]=i;
    }
    printf("Enter Arrival time and Burst time of processes (AT BT) \n ");
    for(int j=0;j<n;j++){
        printf("Process %d \n",j);
        scanf("%d%d",&at[j],&bt[j]);
    }
    while(completed<n){
        int Bursttime=1000,index=-1;
        for(int i=0;i<n;i++){
            if(f[i]==0 && at[i]<=c){
                if (bt[i]<Bursttime){
                    Bursttime=bt[i];
                    index=i;
                }
            }
        }
        if(index==-1){
            c++;
        }
        else{
            int i=index;
            ct[i]=c+bt[i];
            tat[i]=ct[i]-at[i];
            wt[i]=tat[i]-bt[i];
            c=ct[i];
            f[i]=1;
            completed++;
        }
    }
}
```


Priority Non-preemptive:

```
#include<stdio.h>
```

```
int main()
```

```
{
```

```
    printf("USN : 1BM24CS004 NAME:ABDUL AZEEZ \n");
```

```
    printf("Lower number ,Higher Priority\n");
```

```
    int
```

```
p[100],at[100],bt[100],ct[100],tat[100],wt[100],comp[100]={0},n,c=0,a=0,b=0,pr[100],completed=0;
```

```
    printf("Enter no of processes : ");
```

```
    scanf("%d",&n);
```

```
    for(int i=0;i<n;i++){
```

```
        p[i]=i+1;
```

```
    }
```

```
    printf("Enter Arrival time,Burst and priority of processes (AT BT PR) \n ");
```

```
    for(int j=0;j<n;j++){
```

```
        printf("Process %d \n",j+1);
```

```
        scanf("%d%d%d",&at[j],&bt[j],&pr[j]);
```

```
    }
```

```
    while(completed<n){
```

```
        int hp=1000,index=-1;
```

```
        for(int i=0;i<n;i++){
```

```
            if(comp[i]==0 && at[i]<=c){
```

```
                if (pr[i]<hp){
```

```
                    hp=pr[i];
```

```
                    index=i;
```

```
                }
```

```
            }
```

```
        }
```

Result:

```
USN : 1BM24CS008 NAME:ABHISHEK
Enter no of processes : 5
Enter Arrival time and Burst time of processes (AT BT)
Process 0
3 1
Process 1
1 4
Process 2
4 2
Process 3
0 6
Process 4
2 3
  Pid      at      bt      ct      tat      wt
  0         3       1       7       4       3
  1         1       4      16      15      11
  2         4       2       9       5       3
  3         0       6       6       6       0
  4         2       3      12      10       7
Avg Turn around time : 8
Avg waiting time : 4
Process returned 0 (0x0)   execution time : 24.670 s
Press any key to continue.
```


SJF(Preemptive):

```
#include<stdio.h>
int main()
{
    printf("USN : 1BM24CS004 NAME:ABDUL AZEEZ \n");

    int
p[100],at[100],bt[100],ct[100],tat[100],wt[100],rt[100],n,g[100],c=0,a=0,b=0,f[100]={0},compl
eted=0;
    printf("Enter no of processes : ");
    scanf("%d",&n);
    for(int i=0;i<n;i++){
        p[i]=i;
    }
    printf("Enter Arrival time and Burst time of processes (AT BT) \n ");
    for(int j=0;j<n;j++){
        printf("Process %d \n",j);
        scanf("%d%d",&at[j],&bt[j]);
        rt[j]=bt[j];
    }
    while(completed<n){
        int Remainingtime=1000,index=-1;
        for(int i=0;i<n;i++){
            if(rt[i]>0 && at[i]<=c){
                if (rt[i]<Remainingtime){
                    Remainingtime=rt[i];
                    index=i;
                }
            }
        }
        if(index==-1){
            c++;
        }
        else{
            int i=index;
            rt[i]--;
            c++;
            if (rt[i]==0){
                ct[i]=c;
                tat[i]=ct[i]-at[i];
            }
        }
    }
}
```


Priority Non-preemptive:

```
#include<stdio.h>
```

```
int main()
```

```
{
```

```
    printf("USN : 1BM24CS004 NAME:ABDUL AZEEZ \n");
```

```
    printf("Lower number ,Higher Priority\n");
```

```
    int
```

```
p[100],at[100],bt[100],ct[100],tat[100],wt[100],comp[100]={0},n,c=0,a=0,b=0,pr[100],completed=0;
```

```
    printf("Enter no of processes : ");
```

```
    scanf("%d",&n);
```

```
    for(int i=0;i<n;i++){
```

```
        p[i]=i+1;
```

```
    }
```

```
    printf("Enter Arrival time,Burst and priority of processes (AT BT PR) \n ");
```

```
    for(int j=0;j<n;j++){
```

```
        printf("Process %d \n",j+1);
```

```
        scanf("%d%d%d",&at[j],&bt[j],&pr[j]);
```

```
    }
```

```
    while(completed<n){
```

```
        int hp=1000,index=-1;
```

```
        for(int i=0;i<n;i++){
```

```
            if(comp[i]==0 && at[i]<=c){
```

```
                if (pr[i]<hp){
```

```
                    hp=pr[i];
```

```
                    index=i;
```

```
                }
```

```
            }
```

```
        }
```

```

    if(index==-1){
        c++;
    }
    else{
        int i=index;
        ct[i]=c+bt[i];
        tat[i]=ct[i]-at[i];
        wt[i]=tat[i]-bt[i];
        c=ct[i];
        comp[i]=1;
        completed++;
    }
}

printf(" Pid\tat\tbt\tpr\tct\ttat\twt\n");
for(int i=0;i<n;i++){
    printf(" %d\t%d\t%d\t%d\t%d\t%d\t%d\n",p[i],at[i],bt[i],pr[i],ct[i],tat[i],wt[i]);
}

for(int i=0;i<n;i++){
    a=a+tat[i];
    b=b+wt[i];
}

printf("Avg Turn around time : %f \n Avg waiting time : %f", (float)a/n, (float)b/n);
return 0;
}

```


Result:

USN : 1BM24CS008 NAME:ABHISHEK

Lower number ,Higher Priority

Enter no of processes : 5

Enter Arrival time,Burst and priority of processes (AT BT PR)

Process 1

0 3 5

Process 2

2 2 3

Process 3

3 5 2

Process 4

4 4 4

Process 5

6 1 1

Pid	at	bt	pr	ct	tat	wt
1	0	3	5	3	3	0
2	2	2	3	11	9	7
3	3	5	2	8	5	0
4	4	4	4	15	11	7
5	6	1	1	9	3	2

Avg Turn around time : 6.200000

Avg waiting time : 3.200000

Process returned 0 (0x0) execution time : 21.853 s

Press any key to continue.

Priority preemptive:

```
#include<stdio.h>
```

```
int main()
```

```
{
```

```
    printf("USN : 1BM24CS004 NAME:ABDUL AZEEZ \n");
```

```
    printf("\nLower number ,Higher Priority\n");
```

```
    int p[100],at[100],bt[100],ct[100],tat[100],wt[100],n,c=0,a=0,b=0,pr[100],completed=0,rt[100];
```

```
    printf("Enter no of processes : ");
```

```
    scanf("%d",&n);
```

```
    for(int i=0;i<n;i++){
```

```
        p[i]=i+1;
```

```
    }
```

```
    printf("Enter Arrival time,Burst and priority of processes (AT BT PR) \n ");
```

```
    for(int j=0;j<n;j++){
```

```
        printf("Process %d \n",j+1);
```

```
        scanf("%d%d%d",&at[j],&bt[j],&pr[j]);
```

```
        rt[j]=bt[j];
```

```
    }
```

```
    while(completed<n){
```

```
        int hp=1000,index=-1;
```

```
        for(int i=0;i<n;i++){
```

```
            if(rt[i]>0 && at[i]<=c){
```

```
                if (pr[i]<hp){
```

```
                    hp=pr[i];
```

```
                    index=i;
```

```
                }
```

```
            }
```

```

    }

    if(index==-1){
        c++;
    }
    else{
        int i=index;
        rt[i]--;
        c++;
        if (rt[i]==0){
            ct[i]=c;
            tat[i]=ct[i]-at[i];
            wt[i]=tat[i]-bt[i];
            completed++;
        }
    }
}

printf(" Pid\tat\tbt\tpr\tct\ttat\twt\n");
for(int i=0;i<n;i++){
    printf(" %d\t%d\t%d\t%d\t%d\t%d\t%d\n",p[i],at[i],bt[i],pr[i],ct[i],tat[i],wt[i]);
}

for(int i=0;i<n;i++){
    a=a+tat[i];
    b=b+wt[i];
}

printf("Avg Turn around time : %f\n Avg waiting time : %f", (float)a/n, (float)b/n);
return 0;
}

```


Result:

```
USN : 1BM24CS008 NAME:ABHISHEK
Enter no of processes : 5
Enter Arrival time and Burst time of processes (AT BT)
Process 0
2 1
Process 1
1 5
Process 2
4 1
Process 3
0 6
Process 4
2 3
  Pid      at      bt      ct      tat      wt
  0         2       1       3       1       0
  1         1       5      11      10       5
  2         4       1       5       1       0
  3         0       6      16      16      10
  4         2       3       7       5       2
Avg Turn around time : 6
Avg waiting time : 3
Process returned 0 (0x0)   execution time : 22.001 s
Press any key to continue.
```


Result:

USN : 1BM24CS008 NAME:ABHISHEK

Lower number ,Higher Priority

Enter no of processes : 5

Enter Arrival time,Burst and priority of processes (AT BT PR)

Process 1

0 3 5

Process 2

2 2 3

Process 3

3 5 2

Process 4

4 4 4

Process 5

6 1 1

Pid	at	bt	pr	ct	tat	wt
1	0	3	5	15	15	12
2	2	2	3	10	8	6
3	3	5	2	9	6	1
4	4	4	4	14	10	6
5	6	1	1	7	1	0

Avg Turn around time : 8.000000

Avg waiting time : 5.000000

Process returned 0 (0x0) execution time : 24.018 s

Press any key to continue.

Round Robin:

```
#include <stdio.h>

int main() {

    printf("USN : 1BM24CS004 NAME:ABDUL AZEEZ \n");

    int n, tq;
    int at[100], bt[100], rt[100];
    int wt[100], tat[100], ct[100];
    int queue[100], front = 0, rear = 0;
    int visited[100] = {0};
    int time = 0, completed = 0;

    printf("Enter number of processes: ");
    scanf("%d", &n);

    printf("Enter Time Quantum: ");
    scanf("%d", &tq);

    printf("Enter Arrival time and Burst time of processes (AT BT) \n ");
    for(int j=0;j<n;j++){
        printf("Process %d \n",j+1);
        scanf("%d%d",&at[j],&bt[j]);
        rt[j]=bt[j];
    }

    for(int i = 0; i < n; i++) {
        if(at[i] <= time && visited[i] == 0) {
            queue[rear++] = i;
            visited[i] = 1;
        }
    }

    while(completed < n) {

        if(front == rear) {
            time++;
            for(int i = 0; i < n; i++) {
                if(at[i] <= time && visited[i] == 0) {
                    queue[rear++] = i;
                }
            }
        }

        if(queue[front] != -1) {
            int i = queue[front];
            int bt = rt[i];
            if(bt > tq) {
                time += tq;
                rt[i] -= tq;
                queue[rear++] = i;
            } else {
                time += bt;
                rt[i] = 0;
                completed++;
            }
            front++;
        }
    }
}
```



```

        visited[i] = 1;

    }
}
continue;
}

int p = queue[front++];

if(rt[p] > tq) {
    time += tq;
    rt[p] -= tq;
} else {
    time += rt[p];
    rt[p] = 0;

    ct[p] = time;
    tat[p] = ct[p] - at[p];
    wt[p] = tat[p] - bt[p];

    completed++;
}

for(int i = 0; i < n; i++) {
    if(at[i] <= time && visited[i] == 0) {
        queue[rear++] = i;
        visited[i] = 1;
    }
}

if(rt[p] > 0) {
    queue[rear++] = p;
}
}

float avg_wt = 0, avg_tat = 0;

printf("\nPID\tAT\tBT\tCT\tTAT\tWT\n");

for(int i = 0; i < n; i++) {
    printf("%d\t%d\t%d\t%d\t%d\t%d\n",
        i + 1, at[i], bt[i], ct[i], tat[i], wt[i]);
}

```


Result:

USN : 1BM24CS008 NAME:ABHISHEK

Enter number of processes: 5

Enter Time Quantum: 2

Enter Arrival time and Burst time of processes (AT BT)

Process 1

0 5

Process 2

1 3

Process 3

2 1

Process 4

3 2

Process 5

4 3

PID	AT	BT	CT	TAT	WT
1	0	5	13	13	8
2	1	3	12	11	8
3	2	1	5	3	2
4	3	2	9	6	4
5	4	3	14	10	7

Average Waiting Time: 5.80

Average Turnaround Time: 8.60

Process returned 0 (0x0) execution time : 19.940 s

Press any key to continue.

Program – 2

Question:

Write a C program to simulate multi-level queue scheduling algorithm considering the following scenario. All the processes in the system are divided into two categories – system processes and user processes. System processes are to be given higher priority than user processes. Use FCFS scheduling for the processes in each queue.

Code:

Multilevel queue scheduling:

```
#include <stdio.h>
struct Process {
    int id;
    int at;
    int bt;
    int ct;
    int tat;
    int wt;
    int type;
    int completed;
};
int main() {
    int n, i;

    printf("USN : 1BM24CS004 NAME:ABDUL AZEEZ \n");

    int completed_count = 0;
    int current_time = 0;
    float total_wt = 0, total_tat = 0;
    printf("Enter the total number of processes: ");
    scanf("%d", &n);
    struct Process p[n];
    for (i = 0; i < n; i++) {
        p[i].id = i + 1;
        printf("\nProcess %d\n", p[i].id);
        printf("Enter Arrival Time: ");
        scanf("%d", &p[i].at);
        printf("Enter Burst Time: ");
        scanf("%d", &p[i].bt);
```



```

printf("Enter Process Type (1 for System, 2 for User): ");
scanf("%d", &p[i].type);
p[i].completed = 0;
}
while (completed_count < n) {
    int selected_process = -1;
    int highest_priority_type = 3;
    int earliest_arrival = 999999;
    for (i = 0; i < n; i++) {
        if (p[i].completed == 0 && p[i].at <= current_time) {
            if (p[i].type < highest_priority_type) {
                highest_priority_type = p[i].type;
                earliest_arrival = p[i].at;
                selected_process = i;
            }

            else if (p[i].type == highest_priority_type && p[i].at < earliest_arrival) {
                earliest_arrival = p[i].at;
                selected_process = i;
            }
        }
    }
    if (selected_process != -1) {
        current_time += p[selected_process].bt;
        p[selected_process].ct = current_time;
        p[selected_process].tat = p[selected_process].ct - p[selected_process].at;
        p[selected_process].wt = p[selected_process].tat - p[selected_process].bt;
        p[selected_process].completed = 1;
        total_tat += p[selected_process].tat;
        total_wt += p[selected_process].wt;
        completed_count++;
    } else {
        current_time++;
    }
}
printf("\n--- Scheduling Results ---\n");
printf("PID\tType\tAT\tBT\tCT\tTAT\tWT\n");
for (i = 0; i < n; i++) {
    printf("%d\t%s\t%d\t%d\t%d\t%d\t%d\n",
        p[i].id,

```


Result:

```
USN : 18M24CS008 NAME:ABHISHEK
Enter the total number of processes: 4

Process 1
Enter Arrival Time: 0
Enter Burst Time: 4
Enter Process Type (1 for System, 2 for User): 1
Process 2
Enter Arrival Time: 0
Enter Burst Time: 3
Enter Process Type (1 for System, 2 for User): 1
Process 3
Enter Arrival Time: 0
Enter Burst Time: 8
Enter Process Type (1 for System, 2 for User): 2
Process 4
Enter Arrival Time: 10
Enter Burst Time: 5
Enter Process Type (1 for System, 2 for User): 1

--- Scheduling Results ---
PID      Type    AT     BT     CT     TAT     WT
1        SYS      0      4      4      4      0
2        SYS      0      3      7      7      4
3        USER     0      8     15     15      7
4        SYS     10      5     20     10      5

Average Turnaround Time: 9.00
Average Waiting Time: 4.00

Process returned 0 (0x0)   execution time : 33.901 s
Press any key to continue.
```

Program – 3

Question:

Write a C program to simulate Real-Time CPU Scheduling algorithms:

- a)Rate- Monotonic
- b)Earliest-deadline First
- c)Proportional scheduling

Code:

Rate-Monotonic Scheduling:

```
#include <stdio.h>
#include <math.h>
int gcd(int a, int b) {
    while (b) {
        int t = b;
        b = a % b;
        a = t;
    }
    return a;
}
int lcm(int a, int b) {
    return (a * b) / gcd(a, b);
}

int main() {

    int n;
    printf("Enter the number of processes:");
    scanf("%d", &n);
    int C[n], P[n];
    printf("Enter the CPU burst times:\n");
    for (int i = 0; i < n; i++)
        scanf("%d", &C[i]);
    printf("Enter the time periods:\n");
    for (int i = 0; i < n; i++)
        scanf("%d", &P[i]);
    for (int i = 0; i < n - 1; i++) {
```



```

    for (int j = i + 1; j < n; j++) {
        if (P[i] > P[j]) {
            int t;
            t = P[i]; P[i] = P[j]; P[j] = t;
            t = C[i]; C[i] = C[j]; C[j] = t;
        }
    }
}
int hp = P[0];
for (int i = 1; i < n; i++)
    hp = lcm(hp, P[i]);

printf("LCM=%d\n\n", hp);
printf("Rate Monotone Scheduling:\n");
printf("PID  Burst  Period\n");
for (int i = 0; i < n; i++)
    printf("%d    %d    %d\n", i + 1, C[i], P[i]);
float u = 0;
for (int i = 0; i < n; i++)
    u += (float)C[i] / P[i];
float b = n * (pow(2, 1.0/n) - 1);
printf("\n%f <= %f =>%s\n", u, b, (u <= b) ? "true" : "false");
printf("Scheduling occurs for %d ms\n\n", hp);

int r[n];
for (int i = 0; i < n; i++)
    r[i] = 0;

int prev = -2;
for (int t = 0; t < hp; t++) {
    for (int i = 0; i < n; i++)
        if (t % P[i] == 0)
            r[i] = C[i];
    int f = -1;
    for (int i = 0; i < n; i++)
        if (r[i] > 0) {
            f = i;
            break;
        }
    if (f != prev) {
        if (f == -1)

```



```

        printf("%dms onwards: CPU is idle\n", t);
    else
        printf("%dms onwards: Process %d running\n", t, f + 1);
    prev = f;
}
if (f != -1)
    r[f]--;
}
return 0;
}

```

Result:

```

Enter the number of processes:2
Enter the CPU burst times:
20
50
Enter the time periods:
50
150
LCM=150

Rate Monotone Scheduling:
PID    Burst    Period
1       20       50
2       50      150

0.733333 <= 0.828427 =>true
Scheduling occurs for 150 ms

0ms onwards: Process 1 running
20ms onwards: Process 2 running
50ms onwards: Process 1 running
70ms onwards: Process 2 running
90ms onwards: CPU is idle
100ms onwards: Process 1 running
120ms onwards: CPU is idle

```

Earliest DeadLine First:

```
#include <stdio.h>

int gcd(int a, int b) {
    while (b) {
        int t = b;
        b = a % b;
        a = t;
    }
    return a;
}

int lcm(int a, int b) {
    return (a * b) / gcd(a, b);
}

int main() {

    int n;
    printf("Enter the number of processes: ");
    scanf("%d", &n);

    int C[n], D[n], P[n], r[n];

    printf("Enter capacities:\n");
    for (int i = 0; i < n; i++) {
        scanf("%d", &C[i]);
        r[i] = 0;
    }

    printf("Enter deadlines:\n");
    for (int i = 0; i < n; i++)
        scanf("%d", &D[i]);
    printf("Enter time periods:\n");
    for (int i = 0; i < n; i++)
        scanf("%d", &P[i]);
    int hp = P[0];
```



```

for (int i = 1; i < n; i++)
    hp = lcm(hp, P[i]);
printf("\nLCM=%d\n\n", hp);
printf("Earliest Deadline First Scheduling:\n");
printf("PID Capacity Deadline Period\n");
for (int i = 0; i < n; i++)
    printf("%d    %d    %d    %d\n", i + 1, C[i], D[i], P[i]);
float u = 0;
for (int i = 0; i < n; i++)
    u += (float)C[i] / P[i];
printf("\nUtilization = %.6f\n", u);
if (u > 1.0)
    printf("Warning: Utilization > 1, schedule may be infeasible.\n");
int time = 0, prev = -2;
printf("\nScheduling:\n");
while (time < hp) {
    for (int i = 0; i < n; i++) {
        if (time % P[i] == 0)
            r[i] = C[i];
    }
    int min_deadline = 1000000;
    int selected = -1;
    for (int i = 0; i < n; i++) {
        if (r[i] > 0) {
            int instances = time / P[i];
            int abs_deadline = instances * P[i] + D[i];
            if (abs_deadline < min_deadline) {
                min_deadline = abs_deadline;
                selected = i;
            }
        }
    }
    if (selected != prev) {
        if (selected == -1)
            printf("%dms onwards: CPU is idle\n", time);
        else
            printf("%dms onwards: Process %d running\n", time, selected + 1);
        prev = selected;
    }
    if (selected != -1)

```



```

        r[selected]--;
        time++;
    }
    printf("\nScheduling completed at %d ms\n", time);
    return 0;
}

```

Result:

```

Enter the number of processes: 3
Enter capacities:
3 2 2
Enter deadlines:
7 4 8
Enter time periods:
20 5 10

LCM=20

Earliest Deadline First Scheduling:
PID    Capacity    Deadline    Period
1       3           7           20
2       2           4           5
3       2           8           10

Utilization = 0.750000

Scheduling:
0ms onwards: Process 2 running
2ms onwards: Process 1 running
5ms onwards: Process 3 running
7ms onwards: Process 2 running
9ms onwards: CPU is idle
10ms onwards: Process 2 running
12ms onwards: Process 3 running
14ms onwards: CPU is idle
15ms onwards: Process 2 running
17ms onwards: CPU is idle

```

Program – 4

Question:

Write a C program to simulate

- a) producer-consumer problem using semaphores
- b) concept of Dining Philosophers problem.

Code:

Producer consumer problem:

```
#include <stdio.h>

int in = 0, out = 0;
int mutex = 1, Full = 0, Empty = 10;
int a[10];

void wait(int *s)
{
    while (*s <= 0)
        ;
    (*s)--;
}

void signal(int *s)
{
    (*s)++;
}

int main()
{
    int p, item, c=0;;

    while (1)
    {
        printf("\n1: Produce\n2: Consume\n3: Exit\nEnter choice: ");
        scanf("%d", &p);
        if (p == 1)
```



```

{
    wait(&Empty);
    wait(&mutex);
    printf("Enter number to produce: ");
    scanf("%d", &item);
    if(c==10){
        printf("Over FLOW");
    }
    a[in] = item;
    in = (in + 1) % 10;
    c++;
    printf("Produced: %d\n", item);
    signal(&mutex);
    signal(&Full);
}
else if (p == 2)
{
    wait(&Full);
    wait(&mutex);
    if(c==0){
        printf("Under FLOW");
    }
    item = a[out];
    out = (out + 1) % 10;
    printf("Consumed: %d\n", item);
    c--;
    signal(&mutex);
    signal(&Empty);
}
else if (p == 3)
{
    break;
}
else
{
    printf("Invalid choice\n");
}
}
return 0;
}

```


Result:

```
1: Produce
2: Consume
3: Exit
Enter choice: 1
Enter number to produce: 15
Produced: 15
```

```
1: Produce
2: Consume
3: Exit
Enter choice: 1
Enter number to produce: 30
Produced: 30
```

```
1: Produce
2: Consume
3: Exit
Enter choice: 1
Enter number to produce: 45
Produced: 45
```

```
1: Produce
2: Consume
3: Exit
Enter choice: 2
Consumed: 15
```

Dining Philosopher:

```
#include <stdio.h>
#include <pthread.h>
#include <unistd.h>

#define N 5

pthread_mutex_t forks[N];
pthread_t philosophers[N];

void *philosopher(void *num)
{
    int id = *(int *)num;
    int left = id;
    int right = (id + 1) % N;
    while (1)
    {
        printf("Philosopher %d is thinking\n", id);
        sleep(1);
        if (id % 2 == 0)
        {
            pthread_mutex_lock(&forks[left]);
            printf("Philosopher %d picked up left fork %d\n", id, left);
            pthread_mutex_lock(&forks[right]);
            printf("Philosopher %d picked up right fork %d\n", id, right);
        }
        else
        {
            pthread_mutex_lock(&forks[right]);
            printf("Philosopher %d picked up right fork %d\n", id, right);

            pthread_mutex_lock(&forks[left]);
            printf("Philosopher %d picked up left fork %d\n", id, left);
        }
        printf("Philosopher %d is eating\n", id);
        sleep(2);
        pthread_mutex_unlock(&forks[left]);
        pthread_mutex_unlock(&forks[right]);
        printf("Philosopher %d put down forks %d and %d\n",
```



```

        id, left, right);
    }
    return NULL;
}

int main()
{
    int i, ids[N];

    for (i = 0; i < N; i++)
    {
        pthread_mutex_init(&forks[i], NULL);
        ids[i] = i;
    }
    for (i = 0; i < N; i++)
    {
        pthread_create(&philosophers[i], NULL,
                      philosopher, &ids[i]);
    }
    for (i = 0; i < N; i++)
    {
        pthread_join(philosophers[i], NULL);
    }

    for (i = 0; i < N; i++)
    {
        pthread_mutex_destroy(&forks[i]);
    }

    return 0;
}

```


Result:

```
Philosopher 1 is thinking
Philosopher 0 is thinking
Philosopher 3 is thinking
Philosopher 2 is thinking
Philosopher 4 is thinking
Philosopher 1 picked up right fork 2
Philosopher 1 picked up left fork 1
Philosopher 1 is eating
Philosopher 0 picked up left fork 0
Philosopher 3 picked up right fork 4
Philosopher 3 picked up left fork 3
Philosopher 3 is eating
Philosopher 1 put down forks 1 and 2
Philosopher 1 is thinking
Philosopher 2 picked up left fork 2
Philosopher 3 put down forks 3 and 4
Philosopher 3 is thinking
Philosopher 0 picked up right fork 1
Philosopher 0 is eating
Philosopher 2 picked up right fork 3
Philosopher 2 is eating
Philosopher 4 picked up left fork 4
Philosopher 0 put down forks 0 and 1
Philosopher 0 is thinking
Philosopher 4 picked up right fork 0
Philosopher 1 picked up right fork 2
Philosopher 1 picked up left fork 1
```

Program – 5

Question:

Write a C program to simulate

- a) Bankers algorithm for the purpose of deadlock avoidance
- b) Deadlock Detection

Code:

Banker's Algorithm:

```
#include <stdio.h>

int main()
{
    int n, m, i, j, k;
    printf("Enter number of processes: ");
    scanf("%d", &n);

    printf("Enter number of resources: ");
    scanf("%d", &m);

    int alloc[n][m], max[n][m], need[n][m], avail[m];

    printf("Enter Allocation Matrix:\n");
    for(i = 0; i < n; i++)
    {
        for(j = 0; j < m; j++)
        {
            scanf("%d", &alloc[i][j]);
        }
    }

    printf("Enter Max Matrix:\n");
    for(i = 0; i < n; i++)
    {
        for(j = 0; j < m; j++)
        {
            scanf("%d", &max[i][j]);
        }
    }
}
```



```

    }
}

printf("Enter Available Resources:\n");
for(i = 0; i < m; i++)
{
    scanf("%d", &avail[i]);
}

for(i = 0; i < n; i++)
{
    for(j = 0; j < m; j++)
    {
        need[i][j] = max[i][j] - alloc[i][j];
    }
}

int finish[n], safeSeq[n], work[m];
int count = 0;

for(i = 0; i < m; i++)
    work[i] = avail[i];

for(i = 0; i < n; i++)
    finish[i] = 0;

while(count < n)
{
    int found = 0;

    for(i = 0; i < n; i++)
    {
        if(finish[i] == 0)
        {
            for(j = 0; j < m; j++)
            {
                if(need[i][j] > work[j])
                    break;
            }

```

```

        if(j == m)
        {
            for(k = 0; k < m; k++)
                work[k] += alloc[i][k];

            safeSeq[count++] = i;
            finish[i] = 1;
            found = 1;
        }
    }
}

if(found == 0)
{
    printf("\nSystem is not in a safe state.\n");
    return 0;
}

printf("\nSystem is in a safe state.\n");
printf("Safe Sequence: ");

for(i = 0; i < n; i++)
{
    printf("P%d", safeSeq[i]);
    if(i != n - 1)
        printf(" -> ");
}

printf("\n");

return 0;
}

```


Result:

```
Enter number of processes: 5
Enter number of resources: 3
Enter Allocation Matrix:
0 1 0
2 0 0
3 0 2
2 1 1
0 0 2
Enter Max Matrix:
7 5 3
3 2 2
9 0 2
2 2 2
4 3 3
Enter Available Resources:
3 3 2

System is in a safe state.
Safe Sequence: P1 -> P3 -> P4 -> P0 -> P2
```

DeadLock Detetion:

```
#include <stdio.h>

int main()
{
    int n, m, i, j, k;
    printf("Enter number of resources: ");
    scanf("%d", &m);

    printf("Enter number of processes: ");
    scanf("%d", &n);

    int alloc[n][m], req[n][m], avail[m];
    int finish[n], work[m], safeSeq[n];
    int count = 0;

    printf("Enter Allocation Matrix:\n");
    for(i = 0; i < n; i++)
    {
        for(j = 0; j < m; j++)
        {
            scanf("%d", &alloc[i][j]);
        }
    }

    printf("Enter Request Matrix:\n");
    for(i = 0; i < n; i++)
    {
        for(j = 0; j < m; j++)
        {
            scanf("%d", &req[i][j]);
        }
    }

    printf("Enter Available Resources:\n");
    for(i = 0; i < m; i++)
    {
        scanf("%d", &avail[i]);
    }
    for(i = 0; i < n; i++)
```



```

    finish[i] = 0;

for(i = 0; i < m; i++)
    work[i] = avail[i];

while(count < n)
{
    int found = 0;

    for(i = 0; i < n; i++)
    {
        if(finish[i] == 0)
        {
            int flag = 1;

            for(j = 0; j < m; j++)
            {
                if(req[i][j] > work[j])
                {
                    flag = 0;
                    break;
                }
            }

            if(flag)
            {
                for(k = 0; k < m; k++)
                {
                    work[k] += alloc[i][k];
                }

                finish[i] = 1;
                safeSeq[count++] = i;
                found = 1;
            }
        }
    }
}

```

```

        if(found == 0)
            break;
    }

    if(count == n)
    {
        printf("\nSystem is in safe state\n");
        printf("Safe Sequence: ");

        for(i = 0; i < n; i++)
        {
            printf("P%d", safeSeq[i]);

            if(i != n - 1)
                printf(" -> ");
        }
    }
    else
    {
        printf("\nDeadlock detected!\n");
        printf("Processes in deadlock are: ");

        for(i = 0; i < n; i++)
        {
            if(finish[i] == 0)
                printf("P%d ", i);
        }
    }

    return 0;
}

```


Result:

```
Enter number of resources: 3
Enter number of processes: 5
Enter Allocation Matrix:
0 1 0
2 0 0
3 0 3
2 1 1
0 0 2
Enter Request Matrix:
0 0 0
2 0 2
0 0 0
1 0 0
0 0 2
Enter Available Resources:
0 0 0

System is in safe state
Safe Sequence: P0 -> P2 -> P3 -> P4 -> P1
```

Program – 6

Question:

Write a C program to simulate the following contiguous memory allocation techniques.

- a) Worst-fit
- b) Best-fit
- c) First-fit

Code:

Continuous Memory Allocation:

```
#include <stdio.h>

void firstFit(int bs[], int b, int ps[], int p)
{
    int a[p];
    int u[b];

    for(int i = 0; i < p; i++)
        a[i] = -1;

    for(int i = 0; i < b; i++)
        u[i] = 0;

    for(int i = 0; i < p; i++)
    {
        for(int j = 0; j < b; j++)
        {
            if(!u[j] && bs[j] >= ps[i])
            {
                a[i] = j;
                u[j] = 1;
                break;
            }
        }
    }
}
```



```

printf("\nFirst Fit\n");
printf("Process\tSize\tBlock\n");

for(int i = 0; i < p; i++)
{
    printf("P%d\t%d\t", i + 1, ps[i]);

    if(a[i] != -1)
        printf("%d\n", a[i] + 1);
    else
        printf("Not Allocated\n");
}
}

void bestFit(int bs[], int b, int ps[], int p)
{
    int a[p];
    int u[b];

    for(int i = 0; i < p; i++)
        a[i] = -1;

    for(int i = 0; i < b; i++)
        u[i] = 0;

    for(int i = 0; i < p; i++)
    {
        int bestIdx = -1;

        for(int j = 0; j < b; j++)
        {
            if(!u[j] && bs[j] >= ps[i])
            {
                if(bestIdx == -1 || bs[j] < bs[bestIdx])
                    bestIdx = j;
            }
        }

        if(bestIdx != -1)
        {

```

```

        a[i] = bestIdx;
        u[bestIdx] = 1;
    }
}

printf("\nBest Fit\n");
printf("Process\tSize\tBlock\n");
for(int i = 0; i < p; i++)
{
    printf("P%d\t%d\t", i + 1, ps[i]);

    if(a[i] != -1)
        printf("%d\n", a[i] + 1);
    else
        printf("Not Allocated\n");
}
}

void worstFit(int bs[], int b, int ps[], int p)
{
    int a[p];
    int u[b];

    for(int i = 0; i < p; i++)
        a[i] = -1;

    for(int i = 0; i < b; i++)
        u[i] = 0;
    for(int i = 0; i < p; i++)
    {
        int worstIdx = -1;

        for(int j = 0; j < b; j++)
        {
            if(!u[j] && bs[j] >= ps[i])
            {
                if(worstIdx == -1 || bs[j] > bs[worstIdx])
                    worstIdx = j;
            }
        }
    }
}

```



```

        if(worstIdx != -1)
        {
            a[i] = worstIdx;
            u[worstIdx] = 1;
        }
    }
    printf("\nWorst Fit\n");
    printf("Process\tSize\tBlock\n");
    for(int i = 0; i < p; i++)
    {
        printf("P%d\t%d\t", i + 1, ps[i]);

        if(a[i] != -1)
            printf("%d\n", a[i] + 1);
        else
            printf("Not Allocated\n");
    }
}
int main()
{
    int blocks, processes;
    printf("Enter number of blocks: ");
    scanf("%d", &blocks);
    int blockSize[blocks];
    printf("Enter block sizes:\n");
    for(int i = 0; i < blocks; i++)
        scanf("%d", &blockSize[i]);
    printf("Enter number of processes: ");
    scanf("%d", &processes);

    int processSize[processes];
    printf("Enter process sizes:\n");
    for(int i = 0; i < processes; i++)
        scanf("%d", &processSize[i]);
    firstFit(blockSize, blocks, processSize, processes);
    bestFit(blockSize, blocks, processSize, processes);
    worstFit(blockSize, blocks, processSize, processes);
    return 0;
}

```

Result:

```
Enter number of blocks: 5
Enter block sizes:
400 700 200 300 600
Enter number of processes: 4
Enter process sizes:
212 512 312 526
```

First Fit

Process	Size	Block
P1	212	1
P2	512	2
P3	312	5
P4	526	Not Allocated

Best Fit

Process	Size	Block
P1	212	4
P2	512	5
P3	312	1
P4	526	2

Worst Fit

Process	Size	Block
P1	212	2
P2	512	5
P3	312	1
P4	526	Not Allocated

Program – 7

Question:

Write a C program to simulate page replacement algorithms.

- a) FIFO
- b) LRU
- c) Optimal

Code:

Page Replacement Algorithms:

```
#include <stdio.h>

void simulate(int p[], int n, int c, int mode)
{
    int f[20], faults = 0, next_fifo = 0;
    int last_used[20];

    for(int i = 0; i < c; i++)
    {
        f[i] = -1;
        last_used[i] = 0;
    }

    printf("\n%s Page Replacement:\n",
        mode == 0 ? "FIFO" :
        mode == 1 ? "Optimal" : "LRU");

    for(int i = 0; i < n; i++)
    {
```

```

int found = -1, empty = -1;

for(int j = 0; j < c; j++)
{
    if(f[j] == p[i])
        found = j;

    if(f[j] == -1 && empty == -1)
        empty = j;
}

if(found != -1)
{
    if(mode == 2)
        last_used[found] = i;
}
else
{
    faults++;

    int rep = empty;

    if(rep == -1)
    {
        if(mode == 0)    /* FIFO */
        {
            rep = next_fifo;
            next_fifo = (next_fifo + 1) % c;

```



```

}
else if(mode == 1) /* Optimal */
{
    int farthest = -1;
    rep = 0;

    for(int j = 0; j < c; j++)
    {
        int next_use = 9999;

        for(int k = i + 1; k < n; k++)
        {
            if(f[j] == p[k])
            {
                next_use = k;
                break;
            }
        }

        if(next_use > farthest)
        {
            farthest = next_use;
            rep = j;
        }
    }
}
else /* LRU */
{

```

```

    rep = 0;

    for(int j = 1; j < c; j++)
    {
        if(last_used[j] < last_used[rep])
            rep = j;
    }
}

f[rep] = p[i];

if(mode == 2)
    last_used[rep] = i;
}

printf("Page %d -> ", p[i]);

for(int j = 0; j < c; j++)
{
    if(f[j] == -1)
        printf("- ");
    else
        printf("%d ", f[j]);
}

if(found == -1)
    printf("(Fault)");

```



```

        printf("\n");
    }

    printf("Total Page Faults: %d\n", faults);
}

int main()
{
    int p[50], n, frames;
    printf("USN : 1BM24CS004 NAME:ABDUL AZEEZ \n");

    printf("Enter number of pages: ");
    scanf("%d", &n);

    printf("Enter reference string:\n");
    for(int i = 0; i < n; i++)
        scanf("%d", &p[i]);

    printf("Enter number of frames: ");
    scanf("%d", &frames);

    for(int m = 0; m < 3; m++)
        simulate(p, n, frames, m);

    return 0;
}

```

Result:

```
Enter number of pages: 12
Enter reference string:
7 0 1 2 0 3 0 4 2 3 0 3
Enter number of frames: 3
```

```
FIFO Page Replacement:
Page 7 -> 7 - - (Fault)
Page 0 -> 7 0 - (Fault)
Page 1 -> 7 0 1 (Fault)
Page 2 -> 2 0 1 (Fault)
Page 0 -> 2 0 1
Page 3 -> 2 3 1 (Fault)
Page 0 -> 2 3 0 (Fault)
Page 4 -> 4 3 0 (Fault)
Page 2 -> 4 2 0 (Fault)
Page 3 -> 4 2 3 (Fault)
Page 0 -> 0 2 3 (Fault)
Page 3 -> 0 2 3
Total Page Faults: 10
```


Optimal Page Replacement:

Page 7 -> 7 - - (Fault)

Page 0 -> 7 0 - (Fault)

Page 1 -> 7 0 1 (Fault)

Page 2 -> 2 0 1 (Fault)

Page 0 -> 2 0 1

Page 3 -> 2 0 3 (Fault)

Page 0 -> 2 0 3

Page 4 -> 2 4 3 (Fault)

Page 2 -> 2 4 3

Page 3 -> 2 4 3

Page 0 -> 0 4 3 (Fault)

Page 3 -> 0 4 3

Total Page Faults: 7

LRU Page Replacement:

Page 7 -> 7 - - (Fault)

Page 0 -> 7 0 - (Fault)

Page 1 -> 7 0 1 (Fault)

Page 2 -> 2 0 1 (Fault)

Page 0 -> 2 0 1

Page 3 -> 2 0 3 (Fault)

Page 0 -> 2 0 3

Page 4 -> 4 0 3 (Fault)

Page 2 -> 4 0 2 (Fault)

Page 3 -> 4 3 2 (Fault)

Page 0 -> 0 3 2 (Fault)

Page 3 -> 0 3 2

Total Page Faults: 9