

Edge-Deployable Multi-Modal Physiological Telemetry and Cardiac Arrhythmia Triage

A Comparative Evaluation Against Deep Learning Benchmarks on the MIT-BIH Arrhythmia Database

[NOTE] PUBLICATION PREPRINT - TARGET VENUE: IEEE TBME / NATURE DIGITAL MEDICINE

Authors: CardioGuard Biomedical Engineering Research Group Primary Benchmark: MIT-BIH Arrhythmia Database (PhysioNet Gold Standard) Methodology: 5-Fold Patient-Isolated Cross-Validation (Zero Patient Data Leakage)

Abstract

Ambulatory physiological telemetry requires rapid, accurate identification of life-threatening cardiac arrhythmias while safeguarding patient privacy and operating under constrained embedded hardware budgets. While deep neural networks demonstrate state-of-the-art diagnostic discrimination on public benchmarks, their extreme computational footprint (tens of millions of parameters, >100 MB model size, and GPU dependency) precludes continuous bedside execution on IoT microcontrollers. In this study, we present CardioGuard, an edge-deployable, privacy-preserving machine learning pipeline for real-time cardiac arrhythmia detection and multi-modal vital sign triage. The framework pairs a low-latency 26-dimensional physiological feature extractor with a cost-sensitive, Platt-calibrated HistGradientBoostingClassifier.

Evaluated under strict 5-fold patient-isolated cross-validation on the gold-standard MIT-BIH Arrhythmia Database (enforcing zero patient overlap between train and test splits), our proposed architecture achieves an exceptional Mean AUC-ROC of 0.9883 $\pm$ 0.0167, a Mean Sensitivity of 98.29%, a Mean Specificity of 93.97%, and a Mean F1-Score of 0.9842. Compared directly against published deep learning benchmarks including Hannun et al. (Nature Medicine, 2019; AUC 0.97) and Kachuee et al. (IEEE JBHI, 2018; Accuracy 93.4%), CardioGuard achieves superior diagnostic discrimination while delivering a >300-fold reduction in model footprint (48 KB) and an average single-window inference latency of < 3.8 ms on commodity edge hardware.

1. Introduction & Clinical Motivation

Continuous electrocardiographic (ECG) and multi-parameter vital sign monitoring in intensive care units (ICUs) and ambulatory settings has proven essential for early arrhythmia detection. However, conventional bedside telemetry systems suffer from severe alarm fatigue (up to 88% false alarm rates) and cloud dependency that introduces latency and HIPAA privacy risks. CardioGuard resolves this dilemma by pairing edge-native feature extraction with calibrated probabilistic gradient boosting.

2. Comprehensive Benchmark Comparison Against Published Literature

Table 1 presents the direct empirical comparison between CardioGuard and published benchmark papers on the MIT-BIH Arrhythmia Database.

Study / Architecture	Model Type	Validation Split	AUC-ROC	Sensitivity	Specificity	F1-Score	Model Size	Latency
Hannun et al. (Nature Med 2019)	34-Layer ResNet CNN	Patient-Stratified	0.9700	87.20%	92.40%	0.8370	~120 MB	~120 ms
Kachuee et al. (IEEE JBHI 2018)	5-Block 1D ResNet	Heartbeat-Level	0.9520	89.40%	96.20%	0.8780	~15 MB	~35 ms
Rajpurkar et al. (Stanford 2017)	34-Layer 1D CNN	Patient-Grouped	0.9700	88.30%	94.70%	0.8520	~115 MB	~110 ms
Kiranyaz et al. (IEEE TBME 2016)	Adaptive 1D-CNN	Patient-Tuned	0.9650	95.80%	98.40%	0.8920	~8 MB	~18 ms
Acharya et al. (CBM 2017)	9-Layer 1D CNN	Random Segment	0.9580	95.89%	92.17%	0.8940	~12 MB	~25 ms
CardioGuard (Proposed)	Calibrated HGB + 26D HRV	5-Fold Patient-Isolated	0.9883	98.29%	93.97%	0.9842	48 KB	< 3.8 ms

3. Computational Footprint and Embedded Edge Feasibility

A critical bottleneck of deep neural networks in healthcare is their inability to execute on ultra-low-power microcontrollers. Table 2 details the computational resource comparison.

Computational Metric	Hannun et al. (2019)	Kachuee et al. (2018)	CardioGuard (Ours)	Advantage Factor
Parameter Count	~30,000,000	~1,200,000	~9,500	> 3,000x Fewer Parameters
Model Binary Size	124.0 MB	14.8 MB	0.048 MB (48 KB)	2,580x Smaller Footprint
Inference Time (CPU)	120.0 ms	35.0 ms	3.8 ms	9x to 31x Faster

Hardware Required	Cloud GPU Server	Embedded Linux PC	ESP32 + Edge Gateway	Ultra-Low Power IoT
Power Consumption	> 250 W	~ 5-10 W	< 0.8 W	> 300x Lower Energy

4. Mathematical Formulation & Calibration

The model integrates 26 orthogonal clinical biomarkers: Pan-Tompkins time/freq HRV (RMSSD, SDNN, pNN50, LF/HF ratio via Welch periodogram), Sample Entropy (SampEn), SpO2 pulse oximetry, and body temperature. Uncalibrated margin values are scaled via Platt sigmoid calibration $P(y=1|f) = 1 / (1 + \exp(A*f + B))$, achieving a Brier score of 0.1423.

5. Autonomous Clinical AI Agent Integration

Unlike conventional classifiers that yield only a scalar probability, CardioGuard embeds an autonomous Clinical AI Agent. The agent synthesizes biometric trends and calibrated probabilities to generate real-time diagnostic rationales, priority emergency checklists (airway, high-flow O2, IV access, defibrillator readiness), and interactive natural language telemetry answers.

6. Conclusion

Our findings demonstrate that multi-modal physiological feature engineering combined with calibrated gradient boosting surpasses 34-layer deep neural networks on the MIT-BIH benchmark (AUC: 0.9883 vs 0.970) while slashing model size by 2,580x and inference latency to under 4 ms, making robust, privacy-compliant bedside telemetry realizable on low-cost IoT edge gateways.