

# On the Contraction Coefficient of the Schrödinger Bridge for Stochastic Linear Systems

Alexis M.H. Teter

Department of Applied Mathematics  
University of California, Santa Cruz

Joint work with




Abhishek Halder  
Iowa State University




Yongxin Chen  
Georgia Institute of Technology

# What is a Schrödinger Bridge Problem (SBP)




$$\mathcal{P}_{01} := \left\{ \rho_0 \rightarrow \rho_1 \right\}$$



Most likely evolution between 2 distributional snapshots

# Classical SBP



$$\begin{aligned} & \underset{(\rho, \mathbf{v}) \in \mathcal{P}_{01} \times \mathcal{V}}{\operatorname{arginf}} \int_{t_0}^{t_1} \int_{\mathbb{R}^n} \frac{1}{2} |\mathbf{v}|^2 \rho(\mathbf{x}, t) d\mathbf{x} dt \\ & \frac{\partial \rho}{\partial t} + \nabla_{\mathbf{x}} \cdot (\rho \mathbf{v}) = \varepsilon \Delta_{\mathbf{x}} \rho, \quad \varepsilon > 0, \\ & \rho(\mathbf{x}, t = t_0) = \rho_0, \quad \rho(\mathbf{x}, t = t_1) = \rho_1, \end{aligned}$$

Controlled sample path dynamics

$$d\mathbf{x} = \mathbf{v}(\mathbf{x}, t) dt + \sqrt{2\varepsilon} d\mathbf{w}(t)$$

# Solution to the Classical SBP

The pair  $(\rho_\varepsilon^{\text{opt}}, \mathbf{v}_\varepsilon^{\text{opt}})$  solves the coupled PDEs

## Value function

$$\frac{\partial \psi_\varepsilon}{\partial t} + \frac{1}{2} |\nabla_x \psi_\varepsilon|^2 + \varepsilon \Delta_x \psi_\varepsilon = 0,$$

$$\frac{\partial \rho_\varepsilon^{\text{opt}}}{\partial t} + \nabla_x \cdot (\rho_\varepsilon^{\text{opt}} \nabla_x \psi_\varepsilon) = \varepsilon \Delta_x \rho_\varepsilon^{\text{opt}}$$

## Hopf-Cole transform

$$\varphi_\varepsilon := \exp\left(\frac{\psi_\varepsilon}{2\varepsilon}\right), \quad \widehat{\varphi}_\varepsilon := \rho_\varepsilon^{\text{opt}} \exp\left(-\frac{\psi_\varepsilon}{2\varepsilon}\right)$$

## Schrödinger factors


Optimally controlled joint state PDF:  $\rho_\varepsilon^{\text{opt}}(\cdot, t) = \widehat{\varphi}_\varepsilon(\cdot, t) \varphi_\varepsilon(\cdot, t)$

Optimal control:  $\mathbf{v}_\varepsilon^{\text{opt}}(\cdot, t) = 2\varepsilon \nabla_x \log \varphi_\varepsilon(\cdot, t)$

  
Schrödinger factors

# Algorithm

Fixed point recursion over pair  $(\varphi_{\varepsilon,1}, \widehat{\varphi}_{\varepsilon,0})$



Schrödinger system

$$\rho_0(\mathbf{x}) = \widehat{\varphi}_{\varepsilon,0}(\mathbf{x}) \int_{\mathbb{R}^n} k(t_0, \mathbf{x}, t_1, \mathbf{y}) \varphi_{\varepsilon,1}(\mathbf{y}) d\mathbf{y}$$

**Markov kernel**

$$\rho_1(\mathbf{x}) = \varphi_{\varepsilon,1}(\mathbf{x}) \int_{\mathbb{R}^n} k(t_0, \mathbf{y}, t_1, \mathbf{x}) \widehat{\varphi}_{\varepsilon,0}(\mathbf{y}) d\mathbf{y}$$

**Coupled nonlinear  
integral equations**

# Contraction Coefficient $\gamma$ in Classical SBP

Let

$$\tilde{\alpha}_B := \max_{\mathbf{x}_0 \in \mathcal{X}_0, \mathbf{x}_1 \in \mathcal{X}_1} |\mathbf{x}_0 - \mathbf{x}_1|^2 \quad \text{and} \quad \tilde{\beta}_B := \min_{\mathbf{x}_0 \in \mathcal{X}_0, \mathbf{x}_1 \in \mathcal{X}_1} |\mathbf{x}_0 - \mathbf{x}_1|^2$$

Then

$$\gamma_B = \tanh^2 \left( \frac{\tilde{\alpha}_B - \tilde{\beta}_B}{8\varepsilon} \right) \in (0, 1)$$

# Linear SBP

$$\arg \inf_{(\rho, \mathbf{v}) \in \mathcal{P}_{01} \times \mathcal{V}} \int_{t_0}^{t_1} \int_{\mathbb{R}^n} \frac{1}{2} |\mathbf{v}|^2 \rho(\mathbf{x}, t) d\mathbf{x} dt$$

$$\frac{\partial \rho}{\partial t} + \nabla_{\mathbf{x}} \cdot (\rho(\mathbf{A}(t)\mathbf{x} + \mathbf{B}(t)\mathbf{v})) = \varepsilon \langle \text{Hess}, \mathbf{B}(t)\mathbf{B}(t)^\top \rho \rangle$$

resp. compact supports  $\mathcal{X}_0, \mathcal{X}_1$

$$\rho(\mathbf{x}, t = t_0) = \rho_0, \quad \rho(\mathbf{x}, t = t_1) = \rho_1$$

## Controlled sample path dynamics

$$d\mathbf{x}(t) = (\mathbf{A}(t)\mathbf{x}(t) + \mathbf{B}(t)\mathbf{v}(\mathbf{x}, t))dt + \sqrt{2\varepsilon} \mathbf{B}(t)d\mathbf{w}(t)$$

State transition matrix  $\Phi_{t\tau} := \Phi(t, \tau) \quad \forall t_0 \leq \tau \leq t \leq t_1$

Assume controllability:  $M_{10} := \int_{t_0}^{t_1} \Phi_{t_1\tau} \mathbf{B}(\tau) \mathbf{B}^\top(\tau) \Phi_{t_1\tau}^\top d\tau \succ 0$

# Structure of the Solution for Linear SBP

Optimally controlled joint state PDF:  $\rho_\varepsilon^{\text{opt}}(\cdot, t) = \widehat{\varphi}_\varepsilon(\cdot, t)\varphi_\varepsilon(\cdot, t)$

Optimal control:  $\mathbf{v}_\varepsilon^{\text{opt}}(\cdot, t) = 2\varepsilon \mathbf{B}(t)^\top \nabla_{\mathbf{x}} \log \varphi_\varepsilon(\cdot, t)$



**Schrödinger factors**

Define:  $\widehat{\varphi}_{\varepsilon,0}(\cdot) := \widehat{\varphi}_\varepsilon(\cdot, t = t_0)$ ,  $\varphi_{\varepsilon,1}(\cdot) := \varphi_\varepsilon(\cdot, t = t_1)$

## Schrödinger system

$$\rho_0(\mathbf{x}) = \widehat{\varphi}_{\varepsilon,0}(\mathbf{x}) \int_{\mathbb{R}^n} k(t_0, \mathbf{x}, t_1, \mathbf{y}) \varphi_{\varepsilon,1}(\mathbf{y}) d\mathbf{y}$$

**Markov kernel**

$$\rho_1(\mathbf{x}) = \varphi_{\varepsilon,1}(\mathbf{x}) \int_{\mathbb{R}^n} k(t_0, \mathbf{y}, t_1, \mathbf{x}) \widehat{\varphi}_{\varepsilon,0}(\mathbf{y}) d\mathbf{y}$$


**Coupled nonlinear  
integral equations**

Here

$$k(t_0, \mathbf{x}_0, t_1, \mathbf{x}_1) := \frac{\exp\left(-\frac{(\Phi_{t_1 t_0} \mathbf{x}_0 - \mathbf{x}_1)^\top \mathbf{M}_{10}^{-1} (\Phi_{t_1 t_0} \mathbf{x}_0 - \mathbf{x}_1)}{4\varepsilon}\right)}{\sqrt{(4\pi\varepsilon)^n \det(\mathbf{M}_{10})}}$$

# Contractive Fixed Point Algorithm

Fixed point recursion over pair  $(\varphi_{\varepsilon,1}, \widehat{\varphi}_{\varepsilon,0})$



Guaranteed linear convergence with contraction rate  $\kappa \in (0, 1)$

But exact rate depends on problem data  $(\mathcal{X}_0, \mathcal{X}_1, \varepsilon, \mathbf{A}(t), \mathbf{B}(t))$

Worst case contraction coefficient  $\gamma := \sup_{\text{Linear SBPs with fixed } (\mathcal{X}_0, \mathcal{X}_1, \varepsilon, \mathbf{A}(t), \mathbf{B}(t))} \kappa$

# Contraction Coefficient $\gamma$ in Linear SBP

Thm. (informal)

Let

State transition matrix

Controllability Gramian

$$\tilde{\alpha}_L := \max_{\mathbf{x}_0 \in \mathcal{X}_0, \mathbf{x}_1 \in \mathcal{X}_1} (\Phi_{t_1 t_0} \mathbf{x}_0 - \mathbf{x}_1)^\top M_{10}^{-1} (\Phi_{t_1 t_0} \mathbf{x}_0 - \mathbf{x}_1)$$

$$\tilde{\beta}_L := \min_{\mathbf{x}_0 \in \mathcal{X}_0, \mathbf{x}_1 \in \mathcal{X}_1} (\Phi_{t_1 t_0} \mathbf{x}_0 - \mathbf{x}_1)^\top M_{10}^{-1} (\Phi_{t_1 t_0} \mathbf{x}_0 - \mathbf{x}_1)$$

Then

$$\gamma_L = \tanh^2 \left( \frac{\tilde{\alpha}_L - \tilde{\beta}_L}{8\varepsilon} \right)$$

# Control-theoretic Interpretation for $\gamma_L$

$$\tilde{\alpha}_L := \max_{\mathbf{x}_0 \in \mathcal{X}_0, \mathbf{x}_1 \in \mathcal{X}_1} (\Phi_{t_1 t_0} \mathbf{x}_0 - \mathbf{x}_1)^\top \mathbf{M}_{10}^{-1} (\Phi_{t_1 t_0} \mathbf{x}_0 - \mathbf{x}_1)$$

$$\tilde{\beta}_L := \min_{\mathbf{x}_0 \in \mathcal{X}_0, \mathbf{x}_1 \in \mathcal{X}_1} (\Phi_{t_1 t_0} \mathbf{x}_0 - \mathbf{x}_1)^\top \mathbf{M}_{10}^{-1} (\Phi_{t_1 t_0} \mathbf{x}_0 - \mathbf{x}_1)$$



$$\underset{\mathbf{v}}{\text{minimum}} \int_{t_0}^{t_1} \frac{1}{2} |\mathbf{v}|^2 dt$$

$$\begin{aligned} \text{subject to } \quad & \dot{\mathbf{x}} = \mathbf{A}(t) \mathbf{x} + \mathbf{B}(t) \mathbf{v} \\ & \mathbf{x}(t = t_0) = \mathbf{x}_0, \mathbf{x}(t = t_1) = \mathbf{x}_1 \end{aligned}$$

Minimum cost for deterministic OCP

# Control-theoretic Interpretation for $\gamma_L$

$$\gamma_L = \tanh^2 \left( \frac{\tilde{\alpha}_L - \tilde{\beta}_L}{8\epsilon} \right)$$

Range of optimal state transfer cost

Process noise

Intuitive:


$$\epsilon \uparrow \quad \Rightarrow \quad \gamma_L \downarrow$$

$$\tilde{\alpha}_L - \tilde{\beta}_L \uparrow \quad \Rightarrow \quad \gamma_L \uparrow$$

# Support Function

The support function  $h_{\mathcal{K}}(\cdot)$  for closed convex set  $\mathcal{K}$  is


$$h_{\mathcal{K}}(\mathbf{y}) := \sup_{\mathbf{x} \in \mathcal{K}} \langle \mathbf{y}, \mathbf{x} \rangle, \quad \mathbf{y} \in \mathbb{R}^n$$



e.g., distance from the origin to a supporting hyperplane of  $\mathcal{K}$  with normal in direction of  $\mathbf{y}$

# Geometric Interpretation for $\gamma_L$

$$\gamma_L = \tanh^2 \left( \frac{\tilde{\alpha}_L - \tilde{\beta}_L}{8\varepsilon} \right)$$




$$\tilde{\alpha}_L = \{ \max_{\mathbf{y} \in \mathcal{S}^{n-1}} (h_{\mathcal{X}_0}(\Phi_{t_1 t_0}^\top \mathbf{M}_{10}^{-1/2} \mathbf{y}) + h_{\mathcal{X}_1}(-\mathbf{M}_{10}^{-1/2} \mathbf{y})) \}^2$$

$$\tilde{\beta}_L = \{ \min_{\mathbf{y} \in \mathcal{S}^{n-1}} (h_{\mathcal{X}_0}(\Phi_{t_1 t_0}^\top \mathbf{M}_{10}^{-1/2} \mathbf{y}) + h_{\mathcal{X}_1}(-\mathbf{M}_{10}^{-1/2} \mathbf{y})) \}^2$$

# Geometric Interpretation for $\gamma_L$

$$\gamma_L = \tanh^2 \left( \frac{\tilde{\alpha}_L - \tilde{\beta}_L}{8\varepsilon} \right)$$

$$\begin{aligned}\tilde{\alpha}_L &:= \max_{\mathbf{x}_0 \in M_{10}^{-1/2} \Phi_{10} \mathcal{X}_0, \mathbf{x}_1 \in M_{10}^{-1/2} \mathcal{X}_1} |\mathbf{x}_0 - \mathbf{x}_1|^2 \\ \tilde{\beta}_L &:= \min_{\mathbf{x}_0 \in M_{10}^{-1/2} \Phi_{10} \mathcal{X}_0, \mathbf{x}_1 \in M_{10}^{-1/2} \mathcal{X}_1} |\mathbf{x}_0 - \mathbf{x}_1|^2\end{aligned}$$



$\tilde{\alpha}_L$  and  $\tilde{\beta}_L$  are the maximum and the minimum separation of the sets

$$M_{10}^{-1/2} \Phi_{t_1 t_0} \mathcal{X}_0 \text{ and } M_{10}^{-1/2} \mathcal{X}_1$$

# Applications to Preconditioning

Preconditioning to improve optimal transport algorithms  
~ Kuang and Tabak, *SIAM J. Scientific Computing*, 2017


Example: Linear SBP:

$$d\mathbf{x}(t) = \begin{bmatrix} 0 & 1 \\ 0 & 0 \end{bmatrix} \mathbf{x}(t) dt + \sqrt{2\varepsilon} \begin{bmatrix} 0 \\ 1 \end{bmatrix} d\mathbf{w}(t)$$

$$\Phi_{t_1 t_0} = \begin{bmatrix} 1 & 1 \\ 0 & 1 \end{bmatrix}, \quad M_{10}^{-1} = \begin{bmatrix} 12 & -6 \\ -6 & 4 \end{bmatrix}.$$

No Preconditioning:

$$\begin{aligned} \tilde{\alpha}_L &= 2 + 2\sqrt{3} &\longrightarrow \gamma_L &= \tanh^2(1) \approx 0.580 \\ \tilde{\beta}_L &= -2 + 2\sqrt{3} \end{aligned}$$




# Applications to Preconditioning

Preconditioning to improve optimal transport algorithms  
~ Kuang and Tabak, *SIAM J. Scientific Computing*, 2017

Example: Linear SBP:

$$d\mathbf{x}(t) = \begin{bmatrix} 0 & 1 \\ 0 & 0 \end{bmatrix} \mathbf{x}(t) dt + \sqrt{2\varepsilon} \begin{bmatrix} 0 \\ 1 \end{bmatrix} d\mathbf{w}(t)$$

$$\Phi_{t_1 t_0} = \begin{bmatrix} 1 & 1 \\ 0 & 1 \end{bmatrix}, \quad M_{10}^{-1} = \begin{bmatrix} 12 & -6 \\ -6 & 4 \end{bmatrix}.$$



With Preconditioning:

$$\tilde{\alpha}_L^{\text{precond}} = 2, \quad \tilde{\beta}_L^{\text{precond}} = 0 \quad \longrightarrow \quad \gamma_L^{\text{precond}} = \tanh^2(0.5) = 0.214$$

# Avenues of Future Research

Preconditioning:

- > Demonstrate effectiveness of proposed methods
- > Inform the construction of new methods

Additional Generalizations of SBP:

- > Current: Quadratic state cost
- > Future: Keplerian state cost

# Thank You

Acknowledgement:



2112755