NextAsk Gateway — Alert Intake API Payload Specification

Complete Single-Table Parameter Specification for **POST /api/alerts** & **POST /api/alerts/intake**

Field Name	Accepted Values / Format	Meaning / Purpose	Effect on Platform / System Behavior
batch_id	String (e.g. "BATCH303", "B-20261102")	Unique identifier for a batch of alerts sent together.	Groups and logs alerts in database (tb_batches).
branch.branch_id	String (e.g. "BR003", "SITE003")	Internal branch or site identifier.	Stored in tb_tickets.branch_id for site tracking.
branch.branch_name	String (e.g. "Dammam Regional Office", "Olaya Branch")	Physical name/location of the site.	Spoken by Text-to-Speech during call: 'This is Shabakkat alert at site [branch_name]'.
branch.site_number	String (e.g. "SITE003", "2040")	Operational site code.	Used as fallback site name if branch_name is empty.
event_id	Unique String (e.g. "EVT303", "INTAKE-INC3001-01")	Unique transaction ID for the event.	Deduplication Key: Suppresses processing if an identical event_id was previously ingested.
event_type	• ASSIGNMENT_CREATED • REASSIGNED • OPERATIONAL_STATUS • ALARM_STATUS • TICKET_CLOSED • SEVERITY_CHANGED	Type of life-cycle event occurring in the helpdesk.	• ASSIGNMENT_CREATED: Creates initial assignment. • REASSIGNED: Replaces technician. • OPERATIONAL_STATUS: Updates movement & cancels reminders. • TICKET_CLOSED: Cancels all live/pending calls.
event_version	Integer (e.g. 1, 2, 3)	Sequence counter for ordering ticket updates.	State Guard: Discards out-of-order stale events if a higher version was already processed.
event_timestamp	ISO-8601 String (e.g. "2026-11-02T14:20:00+03:00")	The exact time this event was generated.	Stored as last_event_time in database and call audit timeline.
alert_id	String (e.g. "ALT3001", "ALM-1002")	Monitoring system alert identifier.	Stored in tb_tickets.alert_id and referenced in WhatsApp alert templates.
ticket.ticket_id	String (e.g. "INC3001", "SR-8849")	Helpdesk/Incident primary tracking number.	Primary Key: Used to group calls, assignments, WhatsApp notifications, and query status.
ticket.alarm_id	String (e.g. "ALM7001")	Source alarm ID from network monitoring.	Persisted in database and logged in call metadata.
ticket.issue_description	String (e.g. "Transmission link failure at Dammam site")	Detailed description of the outage or issue.	Stored in tb_tickets.issue_description and displayed in operator dashboard.
ticket.alarm_type	String (e.g. "Transmission Failure", "Power Down")	Category/classification of the alarm.	Included in WhatsApp notifications and ticket summaries.
ticket.severity	• Critical • Major • High • Medium • Low	Importance/urgency of the incident.	Spoken in phone call: 'This is an automated call for Critical severity ticket...'.

Field Name	Accepted Values / Format	Meaning / Purpose	Effect on Platform / System Behavior
ticket.ticket_status	• Assigned • Open • In Progress • Resolved • Closed	Current helpdesk workflow status.	If set to Closed, immediately terminates any active or queued outbound calls for this ticket.
ticket.alarm_status	• Active • Cleared	Network equipment alarm health.	If Cleared, marks the issue resolved and cancels pending follow-up timers.
ticket.operational_status	• Departed (or En Route) • Arrived • Started (or In Progress) • Completed • Pending (or null)	Field engineer movement tracking.	• Departed, Arrived, Started: Cancels 15-minute follow-up reminder call (technician is active). • Pending: Follow-up reminder will fire on schedule.
assignment.assignment_id	String (e.g. "ASN302")	Unique ID for this specific technician assignment.	Maps call attempts and DTMF acknowledgements to the active assignment in tb_assignments.
assignment.assignment_type	• INITIAL • REASSIGNMENT	Distinguishes first-time dispatch from re-assignment.	Logged in audit history to indicate whether this was initial dispatch or escalation re-assignment.
assignment.assigned_at	ISO-8601 String (e.g. "2026-11-02T14:10:00+03:00")	Timestamp assignment was created.	Stored in tb_assignments.assigned_at.
technician.technician_id	String (e.g. "ENG302")	Technician employee code / badge ID.	Persisted in tb_assignments for technician accountability.
technician.name	String (e.g. "Maloji")	Full name of the technician.	Injected into WhatsApp templates: 'Dear [Name], assignment for ticket...'.
technician.mobile_number	E.164 phone string (e.g. "+9665XXXXXXXX" or "+91XXXXXXXXXX")	Destination mobile number with country code.	Twilio Outbound Dialing & 360dialog WhatsApp: Destination receiving voice calls and WhatsApp alerts.
technician.preferred_language	• English (or en) • Arabic (or ar) • Urdu (or ur) • Hindi (or hi) • ask	Technician preferred spoken/written language.	• Language code: Calls speak in that language immediately. • 'ask': Plays interactive language selection menu first.
team_leader.team_leader_id	String (e.g. "TL301")	Team Leader employee code / badge ID.	Persisted in tb_assignments for supervisor accountability.
team_leader.name	String (e.g. "Pushkraj")	Full name of the Team Leader.	Injected into escalation alerts and WhatsApp templates.
team_leader.mobile_number	E.164 phone string (e.g. "+9665XXXXXXXX" or "+91XXXXXXXXXX")	Team Leader mobile number with country code.	Receives escalation voice calls (if technician rejects/misses) and Emergency WhatsApp alerts.
team_leader.preferred_language	• English (or en) • Arabic (or ar) • Urdu (or ur) • Hindi (or hi) • ask	Team Leader preferred language.	Determines spoken language if supervisor escalation call is triggered.
manager.manager_id	String (e.g. "MGR301")	Manager employee code / badge ID.	Persisted in tb_assignments for management tracking.

Field Name	Accepted Values / Format	Meaning / Purpose	Effect on Platform / System Behavior
manager.name	String (e.g. "Sanket")	Full name of the Manager.	Injected into manager escalation alerts and audit logs.
manager.mobile_number	E.164 phone string (e.g. "+9665XXXXXXXX" or "+91XXXXXXXXXX")	Manager mobile number with country code.	Receives second-level escalation voice calls if Team Leader does not respond.
manager.preferred_language	• English (or en) • Arabic (or ar) • Urdu (or ur) • Hindi (or hi) • ask	Manager preferred language.	Determines spoken language if second-level manager escalation call is triggered.
ack_digit	Single digit string (e.g. "1", "8") [Default: "1"]	DTMF key to accept assignment.	Spoken dynamically: 'Press [ack_digit] to acknowledge'. Sets ticket to ACKNOWLEDGED.
reject_digit	Single digit string (e.g. "9", "1") [Default: "9"]	DTMF key to reject assignment.	Spoken dynamically: 'Press [reject_digit] to reject'. Triggers supervisor escalation.