NextAsk Gateway — API Documentation

Base URL: https://nextaskgw.automationedge.com | **Auth Scheme:** Basic Auth & X-API-Key

Overview: This specification documents the integration for the **Authorization API**, the **Alert Intake API**, and complete **PostgreSQL Data Type Field Mappings** for the NextAsk Gateway. Clients authenticate against /api/authorize using administrative credentials to obtain the active API key, and pass it via the X-API-Key header to ingest batch tickets and initiate outbound Twilio voice alerts.

1. Authorization API (/api/authorize)

Method: POST / GET **Endpoint:** https://nextaskgw.automationedge.com/api/authorize

Request Headers

Header	Example Value	Required	Description
Authorization	Basic <base64_encoded_credentials>	Yes (or body)	Base64 encoded <username>:<password>
Content-Type	application/json	Conditional	Required if passing JSON body

Success Response (200 OK)

```
{
  "status": "success",
  "authorized": true,
  "http_code": 200,
  "message": "User authenticated successfully. Use the provided api_key in the headers of other APIs.",
  "api_key": "<YOUR_API_KEY>",
  "x_api_key": "<YOUR_API_KEY>",
  "token": "<SESSION_BEARER_TOKEN>",
  "token_type": "Bearer",
  "expires_in": 86400,
  "user": {
    "username": "<YOUR_USERNAME>",
    "role": "admin",
    "auth_type": "credentials"
  }
}
```

2. Alert Intake API (/api/alerts)

Method: POST **Endpoint:** https://nextaskgw.automationedge.com/api/alerts

Request Headers

Header	Value	Required	Description
X-API-Key	<YOUR_API_KEY>	Yes	Security key obtained from /api/authorize
Content-Type	application/json	Yes	JSON payload specification

Success Response (200 OK) with Event ID & Event Timestamp


```
{
  "status": "success",
  "mode": "batch",
  "total": 1,
  "successful": 1,
  "failed": 0,
  "authorized": true,
  "auth": {
    "status": "authorized",
    "user": "api_admin",
    "role": "admin",
    "api_key_valid": true,
    "auth_type": "api_key"
  },
  "results": [
    {
      "index": 0,
      "ticket_id": "INC1001",
      "alert_id": "ALT1001",
      "event_id": "EVT001",
      "event_timestamp": "2026-10-30T10:30:00+03:00",
      "timestamp": "2026-10-30T10:30:00+03:00",
      "ack_digit": "1",
      "reject_digit": "9",
      "dtmf_pressed": null,
      "ack_number_pressed": null,
      "acknowledged": false,
      "status": "accepted",
      "http_code": 202,
      "actions": [
        "call workflow -> ASSIGNMENT_REASSIGNED",
        "tech_call #1 scheduled for 2026-10-30T10:30:00+03:00"
      ],
      "alert": {
        "ticket_id": "INC1001",
        "alert_id": "ALT1001",
        "event_id": "EVT001",
        "date_time": "2026-10-30T10:30:00+03:00",
        "site_name": "Riyadh Main Office",
        "site_number": "SITE001",
        "description": "Network connectivity failure",
        "technician_name": "Ali",
        "technician_number": "+9665XXXXXXXX"
      }
    }
  ]
}
```

3. Field Mapping: Previous vs Additional Fields & Data Types

Data types are extracted directly from the production PostgreSQL database schema (FLMHelpdesk.sql: tb_tickets, tb_nextask_events, tb_assignments).

Additional Fields Table (NexTask Architecture)

No.	Additional Field	PostgreSQL Data Type	Sample Value	Purpose
1	batch_id	VARCHAR(50)	BATCH001	Identify a batch of alerts
2	event_timestamp (batch level)	TIMESTAMP WITH TIME ZONE	2026-10-30T10:30:00+03:00	Record the batch timestamp
3	branch.branch_id	VARCHAR(50)	BR001	Identify the branch
4	alert_id	VARCHAR(50)	ALT1001	Separate alert reference
5	assignment. assignment_type	VARCHAR(30)	INITIAL / REASSIGNMENT	Identify assignment type
6	assignment. assigned_at	TIMESTAMP WITH TIME ZONE	2026-10-30T10:20:00+03:00	Record assignment time
7	assignment. previous_assignment_id	VARCHAR(50)	null / ASN001	Identify previous assignment during reassignment

Comparison: Previous Fields vs Additional Fields

Category	Previous Field	Additional Field	Data Type	Sample Value	Purpose
Batch	(none)	batch_id	VARCHAR(50)	BATCH001	Group alerts in single payload
Batch	(none)	event_timestamp	TIMESTAMPTZ	2026-10-30T10:30:00+03:00	Batch creation timestamp
Event	event_id	event_id	VARCHAR(50)	EVT001	Unique event reference
Event	event_type	event_type	VARCHAR(60)	ASSIGNMENT_REASSIGNED	Lifecycle dispatch action
Ticket	ticket_id	ticket.ticket_id	VARCHAR(50)	INC1001	Incident ticket ID
Ticket	alarm_id	ticket.alarm_id	VARCHAR(50)	ALM5001	Alarm sensor reference
Alert	(none)	alert_id	VARCHAR(50)	ALT1001	Dedicated alert ID
Site	site_name	branch.branch_name	VARCHAR(150)	Riyadh Main Office	Physical facility name
Site	site_number	branch.site_number	VARCHAR(50)	SITE001	Branch/site code
Site	(none)	branch.branch_id	VARCHAR(50)	BR001	Branch database ID
Assign	assignment_id	assignment.assignment_id	VARCHAR(50)	ASN002	Current dispatch assignment
Assign	(none)	assignment.assignment_type	VARCHAR(30)	REASSIGNMENT	INITIAL vs REASSIGNMENT
Assign	(none)	assignment.previous_assignment_id	VARCHAR(50)	null / ASN001	Prior assignment reference
Contact	technician_name	technician.name	VARCHAR(150)	Ali	Field engineer name
Contact	technician_mobile	technician.mobile_number	VARCHAR(30)	+9665XXXXXXXX	Technician phone number
Contact	(none)	technician.preferred_language	VARCHAR(20)	English / Arabic	Voice audio language
DTMF	ack_digit	acknowledgement.dtmf_digit	VARCHAR(10)	1	Key to acknowledge call