NextAsk Gateway — API Documentation

Base URL: https://nextaskgw.automationedge.com | **Auth Scheme:** Basic Auth & X-API-Key

Overview: This document specifies the integration for the **Authorization API** and the **Alert Intake API** on the NextAsk Gateway. Clients authenticate against /api/authorize using administrative credentials to obtain the active API key, and pass it via the X-API-Key header to ingest batch tickets and initiate outbound Twilio voice alerts.

1. Authorization API (/api/authorize)

Method: POST / GET **Endpoint:** https://nextaskgw.automationedge.com/api/authorize

Authenticates client credentials and returns the platform api_key. All other endpoints require this key passed in the request header.

Request Headers

Header	Example Value	Required	Description
Authorization	Basic <base64_encoded_credentials>	Yes (or body)	Base64 encoded <username>:<password>
Content-Type	application/json	Conditional	Required if passing JSON body

Request Body (Optional if using HTTP Basic Auth)

```
{
  "username": "<YOUR_USERNAME>",
  "password": "<YOUR_PASSWORD>"
}
```

Success Response (200 OK)

```
{
  "status": "success",
  "authorized": true,
  "http_code": 200,
  "message": "User authenticated successfully. Use the provided api_key in the headers of other APIs.",
  "api_key": "<YOUR_API_KEY>",
  "x_api_key": "<YOUR_API_KEY>",
  "token": "<SESSION_BEARER_TOKEN>",
  "token_type": "Bearer",
  "expires_in": 86400,
  "user": {
    "username": "<YOUR_USERNAME>",
    "role": "admin",
    "auth_type": "credentials"
  }
}
```

Error Responses

HTTP Code	Scenario	Response Body
400 Bad Request	Missing username/password	{"status":"error","http_code":400,"error":"Bad Request: Missing credentials."}
401 Unauthorized	Invalid username/password	{"status":"error","http_code":401,"error":"Unauthorized: Invalid username or password."}

2. Alert Intake API (/api/alerts)

Method: POST **Endpoint:** https://nextaskgw.automationedge.com/api/alerts

Accepts ticket incident alerts (single or batch array). It validates the tickets, schedules escalation timers, and immediately places outbound Twilio automated voice calls to field engineers.

Request Headers

Header	Value	Required	Description
X-API-Key	<YOUR_API_KEY>	Yes	Security key obtained from /api/authorize
Content-Type	application/json	Yes	JSON payload specification

Sample Batch Alert Payload (JSON Body)

```
{
  "batch_id": "BATCH001",
  "event_timestamp": "2026-10-30T10:30:00+03:00",
  "branch": {
    "branch_id": "BR001",
    "branch_name": "Riyadh Main Office",
    "site_number": "SITE001"
  },
  "alerts": [
    {
      "event_id": "EVT001",
      "event_type": "ASSIGNMENT_REASSIGNED",
      "event_version": 2,
      "alert_id": "ALT1001",
      "ticket": {
        "ticket_id": "INC1001",
        "alarm_id": "ALM5001",
        "issue_description": "Network connectivity failure",
        "alarm_type": "Network Failure",
        "severity": "Critical",
        "ticket_status": "Assigned",
        "alarm_status": "Active"
      },
      "assignment": {
        "assignment_id": "ASN002",
        "assignment_type": "REASSIGNMENT",
        "assigned_at": "2026-10-30T10:30:00+03:00"
      },
      "technician": {
        "technician_id": "ENG002",
        "name": "Field Engineer",
        "mobile_number": "+9665XXXXXXXX",
        "preferred_language": "English"
      },
      "team_leader": {
        "team_leader_id": "TL001",
        "name": "Team Leader",
        "mobile_number": "+9665XXXXXXXX",
        "preferred_language": "English"
      },
      "manager": {
        "manager_id": "MGR001",
        "name": "Operations Manager",
        "mobile_number": "+9665XXXXXXXX",
        "preferred_language": "English"
      },
      "acknowledgement": {
        "dtmf_digit": "1"
      }
    }
  ]
}
```


Success Response (200 OK)

```
{
  "status": "success",
  "mode": "batch",
  "total": 1,
  "successful": 1,
  "failed": 0,
  "authorized": true,
  "auth": {
    "status": "authorized",
    "user": "api_admin",
    "role": "admin",
    "api_key_valid": true,
    "auth_type": "api_key"
  },
  "results": [
    {
      "index": 0,
      "ticket_id": "INC1001",
      "alert_id": "ALT1001",
      "ack_digit": "1",
      "reject_digit": "9",
      "acknowledged": false,
      "status": "accepted",
      "http_code": 202,
      "actions": [
        "call workflow -> ASSIGNMENT_REASSIGNED",
        "tech_call #1 scheduled for 2026-10-30T10:30:00+03:00"
      ]
    }
  ]
}
```


Unauthorized Response (401 Unauthorized)


```
{
  "status": "error",
  "authorized": false,
  "http_code": 401,
  "error": "Unauthorized: Missing or invalid API Key.",
  "message": "Please provide 'X-API-Key: <YOUR_API_KEY>' in request headers.",
  "required_header": "X-API-Key"
}
```