

A – reset pedal, single press, reward never held (unsafe-abort case)

pedal held					
reward signal					
terminated (narrow)					
buffer done (wide)					

← reset *PRESSED* here (edge, `consume.reset()`).
terminated and *buffer_done* agree: reward was never held, episode ends with *reward=0*. Verified real example: *buffer index 1335 (online_buffer.cache/c3aeae2b)* has *next.done=True* with *next.original_reward=0.0*.

B – reward pedal held 3 ticks, then released – episode ends on release

pedal held						
reward signal						
terminated (narrow)						
buffer done (wide)						

buffer.done is *True* on *EVERY* tick where the reward signal is *True* (*real.residual.env.py*: *buffer.done = terminated OR truncated OR reward ≥ 1.0*) – not just the terminal one. Verified against the real formula for exactly this 3-tick sequence: stored *next.reward=1.0*, *next.done=True* for all 4 marked transitions, *nonterminal=False* for each – no reward/done desync, no broken bootstrap.

C – reward held continuously through backward motion, then released

pedal held				...		
reward signal				...		
terminated (narrow)				...		
buffer done (wide)				...		

Verified for real: *online_buffer.cache/c3aeae2b*, indices 9493–9527 (35 consecutive steps) – *EVERY* one has *buffer.done=True*, *next.reward=1.0* exactly, *nonterminal=False*. *terminated (narrow)* stays *False* until the true physical release; *buffer.done (wide, §8 fix)* is *True* on every held-reward tick, giving each its own non-bootstrapped, non-inflated target – without the robot physically resetting mid-hold.