DigMitra JCB Site Cleaning App

Terminal Server Manual Startup & Execution Guide

PORT 5050 • OFFLINE GUIDE

PROJECT DIRECTORY	DEFAULT PORT	LOCAL ACCESS URL
`jcb-booking-marketplace-223`	`5050 (host: true)`	`http://localhost:5050`

1 Open Terminal (PowerShell / Command Prompt)

Open any terminal on your Windows machine:

- Press `Win` + `R`, type **powershell** or **cmd**, and press **Enter**.
- *Alternative:* Navigate to the folder in Windows File Explorer, hold `Shift` and right-click on empty space, then select **"Open in Terminal"**.

2 Navigate to Project Folder

Copy and run the following command in your terminal to go to the app directory:

```
cd "C:\Users\Abhishek N\Desktop\site cleaning app\jcb-booking-marketplace-223"
```

Navigate

💡 **Tip:** You can verify your current folder by typing `pwd` and pressing Enter.

3 Start the Development Server

Run any **one** of these commands to launch the server:

COMMAND OPTION	TERMINAL COMMAND	SPEED / NOTE
Option A (Recommended)	`pnpm dev`	Fastest native package runner
Option B (NPM)	`npm run dev`	Standard Node package manager
Option C (Vite Direct)	`npx vite`	Direct bundler execution

When successful, the terminal will display:

```
VITE v8.1.0 ready in 1200 ms
➜ Local: http://localhost:5050/
➜ Network: http://192.168.29.59:5050/
```

Server Active

4 Access the Live Application

DEVICE	URL / ADDRESS	REQUIREMENTS
Computer / Laptop	`http://localhost:5050`	Any browser (Chrome, Edge, Firefox)
Mobile Phone / Tablet	`http://192.168.29.59:5050`	Connected to the same Wi-Fi network

5 How to Switch OFF / Stop the Server

To safely terminate and switch off the server at any time:

- Focus your terminal window where the server is running.
- Press `Ctrl` + `C`.
- If prompted with `Terminate batch job (Y/N)?`, type **Y** and hit **Enter**.

6 Troubleshooting: What if Port 5050 is Busy?

If you see "*Port 5050 is in use*", run this single PowerShell command to immediately release port 5050:

```
Stop-Process -Id (Get-NetTCPConnection -LocalPort 5050 -ErrorAction SilentlyContinue).OwningProcess -Force
```
Kill Port 5050

Or using npm:

```
npx kill-port 5050
```
Free Port

After killing the busy process, run `pnpm dev` or `npm run dev` again.