Insurance Fraud Detection



Logistic Regression · Responsible Classification

This notebook downloads a public insurance-claims dataset, validates its schema, performs exploratory analysis, trains a reproducible scikit-learn pipeline, evaluates the model, creates graphs, and exports artifacts for the Streamlit app.

> **Important:** This dataset contains historical labels and potentially post-incident or post-investigation fields. This project is for education only. Before any real deployment, perform feature-timing/leakage review, privacy/legal review, and independent validation. Do not use this model to deny claims, set premiums, or make decisions about individuals.

1. Reproducibility and source/license

Dataset record: Mendeley Data, *insurance_claims*, version 2, DOI `10.17632/992mh7dk9y.2`. The record states CC BY 4.0 and links to the CSV repository below. Review the record and attribution terms before redistributing the data.

- Dataset record: https://data.mendeley.com/datasets/992mh7dk9y/2
- Linked CSV: https://github.com/mwitiderrick/insurancedata/blob/master/insurance_claims.csv
- Raw CSV URL used below: https://raw.githubusercontent.com/mwitiderrick/insurancedata/master/insurance_claims

We save the data-source URL and library versions with the model artifacts. GitHub availability alone is not a license; check the dataset record before redistribution.

In [1]:
```
# 1.1 Imports and environment versions
import sys, json, warnings, hashlib
from pathlib import Path
from urllib.request import urlopen
```

```
import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import sklearn, scipy, joblib

from sklearn.model_selection import train_test_split
from sklearn.compose import ColumnTransformer
from sklearn.pipeline import Pipeline
from sklearn.preprocessing import OneHotEncoder, StandardScaler
from sklearn.impute import SimpleImputer
from sklearn.linear_model import LogisticRegression
from sklearn.metrics import (
    classification_report, confusion_matrix, ConfusionMatrixDisplay,
    roc_auc_score, roc_curve, precision_recall_curve, average_precision_scor
    accuracy_score, precision_score, recall_score, f1_score
)

RANDOM_STATE = 42
DATA_URL = "https://raw.githubusercontent.com/mwitiderrick/insurancedata/mas
DATASET_RECORD = "https://data.mendeley.com/datasets/992mh7dk9y/2"
TARGET = "fraud_reported"
ARTIFACT_DIR = Path("artifacts")
ARTIFACT_DIR.mkdir(exist_ok=True)

print("Python:", sys.version)
print("scikit-learn:", sklearn.__version__)
print("NumPy:", np.__version__)
print("SciPy:", scipy.__version__)
print("joblib:", joblib.__version__)
```

```
Python: 3.12.13 (main, Jul 23 2026, 14:33:47) [Clang 22.1.3 ]
scikit-learn: 1.6.1
NumPy: 2.1.3
SciPy: 1.16.3
joblib: 1.6.0
```

2. Load data and validate expected target

In [2]:

```
# Download CSV. If the URL changes, download from the source record and uplo
DATA_DIR = Path("data")
DATA_DIR.mkdir(exist_ok=True)
data_path = DATA_DIR / "insurance_claims.csv"
try:
    with urlopen(DATA_URL, timeout=30) as response:
        raw_bytes = response.read()
    data_path.write_bytes(raw_bytes)
except Exception as exc:
    raise RuntimeError(
        "Dataset download failed. Download insurance_claims.csv from the lir
        "record and place it in the project's data folder, then rerun this c
    ) from exc

df = pd.read_csv(data_path)
print("Shape:", df.shape)
display(df.head())
```

```
print("Columns:", df.columns.tolist())

if TARGET not in df.columns:
    raise ValueError(f"Expected target column {TARGET!r} not found. Inspect

print("\nTarget values:")
display(df[TARGET].value_counts(dropna=False).to_frame("count"))
```

```
Shape: (1000, 39)
```

	months_as_customer	age	policy_number	policy_bind_date	policy_state	policy_csl
0	328	48	521585	2014-10-17	OH	250/500
1	228	42	342868	2006-06-27	IN	250/500
2	134	29	687698	2000-09-06	OH	100/300
3	256	41	227811	1990-05-25	IL	250/500
4	228	44	367455	2014-06-06	IL	500/1000

5 rows × 39 columns

```
Columns: ['months_as_customer', 'age', 'policy_number', 'policy_bind_date',
'policy_state', 'policy_csl', 'policy_deductable', 'policy_annual_premium',
'umbrella_limit', 'insured_zip', 'insured_sex', 'insured_education_level',
'insured_occupation', 'insured_hobbies', 'insured_relationship', 'capital-ga
ins', 'capital-loss', 'incident_date', 'incident_type', 'collision_type', 'i
ncident_severity', 'authorities_contacted', 'incident_state', 'incident_cit
y', 'incident_location', 'incident_hour_of_the_day', 'number_of_vehicles_inv
olved', 'property_damage', 'bodily_injuries', 'witnesses', 'police_report_av
ailable', 'total_claim_amount', 'injury_claim', 'property_claim', 'vehicle_c
laim', 'auto_make', 'auto_model', 'auto_year', 'fraud_reported']

Target values:
```

	count
fraud_reported	
N	753
Y	247

3. Data quality and exploratory analysis

In [3]:
```
# Remove completely empty rows; report duplicates and missing values before
df = df.dropna(how="all").copy()
print("Duplicate rows:", int(df.duplicated().sum()))
missing = df.isna().sum().sort_values(ascending=False)
display(missing[missing > 0].to_frame("missing_count"))
display(df.describe(include="all").T.head(30))

# Target distribution plot
target_counts = df[TARGET].astype(str).value_counts()
ax = target_counts.plot(kind="bar", title="Target label distribution")
```

```
ax.set_xlabel("fraud_reported label")
ax.set_ylabel("Number of claims")
plt.tight_layout()
plt.show()


# Numeric feature histograms (first few only, to keep notebook readable)
numeric_preview = df.select_dtypes(include=np.number).columns.tolist()[:8]
if numeric_preview:
    df[numeric_preview].hist(figsize=(12, 8), bins=20)
    plt.suptitle("Numeric feature distributions (sample of columns)")
    plt.tight_layout()
    plt.show()
```


```
Duplicate rows: 0
```

	missing_count
authorities_contacted	91

	count	unique	top	freq	mean	
months_as_customer	1000.0	NaN	NaN	NaN	203.954	115.113
age	1000.0	NaN	NaN	NaN	38.948	9.140
policy_number	1000.0	NaN	NaN	NaN	546238.648	257063.005
policy_bind_date	1000	951	2006-01-01	3	NaN	N
policy_state	1000	3	OH	352	NaN	N
policy_csl	1000	3	250/500	351	NaN	N
policy_deductable	1000.0	NaN	NaN	NaN	1136.0	611.864
policy_annual_premium	1000.0	NaN	NaN	NaN	1256.40615	244.167
umbrella_limit	1000.0	NaN	NaN	NaN	1101000.0	2297406.598
insured_zip	1000.0	NaN	NaN	NaN	501214.488	71701.610
insured_sex	1000	2	FEMALE	537	NaN	N
insured_education_level	1000	7	JD	161	NaN	N
insured_occupation	1000	14	machine-op-inspct	93	NaN	N
insured_hobbies	1000	20	reading	64	NaN	N
insured_relationship	1000	6	own-child	183	NaN	N
capital-gains	1000.0	NaN	NaN	NaN	25126.1	27872.187
capital-loss	1000.0	NaN	NaN	NaN	-26793.7	28104.096
incident_date	1000	60	2015-02-02	28	NaN	N
incident_type	1000	4	Multi-vehicle Collision	419	NaN	N
collision_type	1000	4	Rear Collision	292	NaN	N
incident_severity	1000	4	Minor Damage	354	NaN	N
authorities_contacted	909	4	Police	292	NaN	N
incident_state	1000	7	NY	262	NaN	N
incident_city	1000	7	Springfield	157	NaN	N
incident_location	1000	1000	9935 4th Drive	1	NaN	N
incident_hour_of_the_day	1000.0	NaN	NaN	NaN	11.644	6.951
number_of_vehicles_involved	1000.0	NaN	NaN	NaN	1.839	1.01

	count	unique	top	freq	mean	
property_damage	1000	3	?	360	NaN	N
bodily_injuries	1000.0	NaN	NaN	NaN	0.992	0.820
witnesses	1000.0	NaN	NaN	NaN	1.487	1.111





4. Target preparation and leakage review

The target in the source is commonly represented as `Y` / `N`; this cell validates observed labels instead of silently guessing. We drop the target and obvious identifier fields. This is still an educational baseline, not a production-ready fraud model: inspect all feature definitions and determine whether they were known at the intended prediction time. Fields generated during investigation or after claim adjudication can leak the answer and must be removed before any operational use.

In [4]:
```
# Normalize target labels explicitly and fail if unexpected values appear.
target_values = set(df[TARGET].dropna().astype(str).str.strip().str.upper().
print("Observed target labels:", target_values)
mapping = {"Y": 1, "N": 0, "1": 1, "0": 0, "TRUE": 1, "FALSE": 0}
if not target_values.issubset(mapping):
    raise ValueError(f"Unexpected target labels {target_values}; update mapp

df = df.loc[df[TARGET].notna()].copy()
y = df[TARGET].astype(str).str.strip().str.upper().map(mapping).astype(int)

# Exclude target and obvious identifier fields; extend this list after a doc
identifier_candidates = [
    col for col in df.columns
    if col.lower() in {"policy_number", "insured_zip", "incident_location",
]
X = df.drop(columns=[TARGET] + identifier_candidates, errors="ignore").copy(

# Remove constant columns: they contain no useful variation for this model.
constant_columns = [col for col in X.columns if X[col].nunique(dropna=False)
```

```
X = X.drop(columns=constant_columns)

print("Excluded identifier candidates:", identifier_candidates)
print("Excluded constant columns:", constant_columns)
print("Features:", X.shape[1])
print("Target rate:", round(float(y.mean()), 4))
display(pd.DataFrame({"dtype": X.dtypes.astype(str), "missing": X.isna().sum
```

```
Observed target labels: {'Y', 'N'}
Excluded identifier candidates: ['policy_number', 'policy_bind_date', 'insur
ed_zip', 'incident_date', 'incident_location']
Excluded constant columns: []
Features: 33
Target rate: 0.247
```

	dtype	missing	unique
months_as_customer	int64	0	391
age	int64	0	46
policy_state	object	0	3
policy_csl	object	0	3
policy_deductable	int64	0	3
policy_annual_premium	float64	0	991
umbrella_limit	int64	0	11
insured_sex	object	0	2
insured_education_level	object	0	7
insured_occupation	object	0	14
insured_hobbies	object	0	20
insured_relationship	object	0	6
capital-gains	int64	0	338
capital-loss	int64	0	354
incident_type	object	0	4
collision_type	object	0	4
incident_severity	object	0	4
authorities_contacted	object	91	5
incident_state	object	0	7
incident_city	object	0	7
incident_hour_of_the_day	int64	0	24
number_of_vehicles_involved	int64	0	4
property_damage	object	0	3
bodily_injuries	int64	0	3
witnesses	int64	0	4
police_report_available	object	0	3
total_claim_amount	int64	0	763
injury_claim	int64	0	638
property_claim	int64	0	626
vehicle_claim	int64	0	726
auto_make	object	0	14
auto_model	object	0	39

	dtype	missing	unique
auto_year	int64	0	21

5. Train/test split and preprocessing pipeline

The split is stratified so the class proportions are approximately preserved. Numeric columns are median-imputed and scaled; categorical columns are most-frequent-imputed and one-hot encoded. All preprocessing is fit only on the training partition through a single pipeline to reduce leakage.

In [5]:
```
X_train, X_test, y_train, y_test = train_test_split(
    X, y, test_size=0.20, random_state=RANDOM_STATE, stratify=y
)

numeric_features = X_train.select_dtypes(include=np.number).columns.tolist()
categorical_features = [c for c in X_train.columns if c not in numeric_featu

numeric_pipeline = Pipeline(steps=[
    ("imputer", SimpleImputer(strategy="median")),
    ("scaler", StandardScaler())
])
categorical_pipeline = Pipeline(steps=[
    ("imputer", SimpleImputer(strategy="most_frequent")),
    ("encoder", OneHotEncoder(handle_unknown="ignore"))
])
preprocessor = ColumnTransformer(transformers=[
    ("numeric", numeric_pipeline, numeric_features),
    ("categorical", categorical_pipeline, categorical_features)
])

pipeline = Pipeline(steps=[
    ("preprocessor", preprocessor),
    ("classifier", LogisticRegression(
        max_iter=2000, class_weight="balanced", random_state=RANDOM_STATE
    ))
])
pipeline.fit(X_train, y_train)
print("Pipeline training complete.")
```

```
Pipeline training complete.
```

6. Evaluate and visualize

In [6]:
```
# Use a transparent default threshold for the baseline. Threshold tuning bel
# not the final test set. Do not interpret a chosen threshold as an operatic
threshold = 0.50
y_prob = pipeline.predict_proba(X_test)[:, 1]
y_pred = (y_prob >= threshold).astype(int)

metrics = {
```

```
    "accuracy": accuracy_score(y_test, y_pred),
    "precision": precision_score(y_test, y_pred, zero_division=0),
    "recall": recall_score(y_test, y_pred, zero_division=0),
    "f1": f1_score(y_test, y_pred, zero_division=0),
    "roc_auc": roc_auc_score(y_test, y_prob),
    "average_precision": average_precision_score(y_test, y_prob),
}
display(pd.DataFrame([metrics]).T.rename(columns={0:"test_value"}))
print(classification_report(y_test, y_pred, target_names=["Not reported frau

ConfusionMatrixDisplay.from_predictions(
    y_test, y_pred, display_labels=["Not reported fraud", "Reported fraud"],
)
plt.title(f"Confusion matrix (threshold={threshold:.2f})")
plt.tight_layout()
plt.show()


fpr, tpr, _ = roc_curve(y_test, y_prob)
plt.plot(fpr, tpr, label=f"ROC-AUC = {metrics['roc_auc']:.3f}")
plt.plot([0, 1], [0, 1], linestyle="--")
plt.xlabel("False positive rate")
plt.ylabel("True positive rate")
plt.title("ROC curve")
plt.legend()
plt.tight_layout()
plt.show()


precision, recall, _ = precision_recall_curve(y_test, y_prob)
plt.plot(recall, precision, label=f"Average precision = {metrics['average_pr
plt.xlabel("Recall")
plt.ylabel("Precision")
plt.title("Precision-recall curve")
plt.legend()
plt.tight_layout()
plt.show()


plt.hist(y_prob[y_test.to_numpy() == 0], bins=20, alpha=0.6, label="Not repo
plt.hist(y_prob[y_test.to_numpy() == 1], bins=20, alpha=0.6, label="Reported
plt.xlabel("Predicted probability for class 1")
plt.ylabel("Count")
plt.title("Predicted score distribution")
plt.legend()
plt.tight_layout()
plt.show()
```


	test_value
accuracy	0.830000
precision	0.641509
recall	0.693878
f1	0.666667
roc_auc	0.824976
average_precision	0.526417

	precision	recall	f1-score	support
Not reported fraud	0.90	0.87	0.89	151
Reported fraud	0.64	0.69	0.67	49
accuracy			0.83	200
macro avg	0.77	0.78	0.78	200
weighted avg	0.84	0.83	0.83	200




ROC curve
ROC-AUC = 0.825
True positive rate
False positive rate
0.0
0.2
0.4
0.6
0.8
1.0


Precision–recall curve
Average precision = 0.526
Precision
Recall
0.0
0.2
0.4
0.6
0.8
1.0



7. Save artifacts and metadata

Only load joblib files you created or otherwise trust. Joblib uses pickle-based serialization, which can execute code when loading untrusted artifacts. Training and serving should use matching dependency versions.

In [7]:
```
# Save model, threshold, and metadata required by the Streamlit app.
joblib.dump(pipeline, ARTIFACT_DIR / "insurance_fraud_pipeline.joblib")
joblib.dump(float(threshold), ARTIFACT_DIR / "decision_threshold.joblib")

metadata = {
    "project_name": "Insurance Fraud Detection — Logistic Regression",
    "target_column": TARGET,
    "positive_class": 1,
    "positive_class_label": "Reported fraud",
    "threshold": float(threshold),
    "feature_columns": X.columns.tolist(),
    "numeric_features": numeric_features,
    "categorical_features": categorical_features,
    "identifier_columns_excluded": identifier_candidates,
    "constant_columns_excluded": constant_columns,
    "metrics_test": {k: float(v) for k, v in metrics.items()},
    "random_state": RANDOM_STATE,
    "test_size": 0.20,
    "dataset_source": DATA_URL,
    "dataset_record": DATASET_RECORD,
```

```
    "dataset_license_claimed_by_source": "CC BY 4.0; verify current source r
    "dataset_sha256": hashlib.sha256(data_path.read_bytes()).hexdigest(),
    "python_version": sys.version,
    "sklearn_version": sklearn.__version__,
    "numpy_version": np.__version__,
    "scipy_version": scipy.__version__,
    "joblib_version": joblib.__version__,
    "feature_leakage_review_required": True,
    "educational_only": True
}
(ARTIFACT_DIR / "model_metadata.json").write_text(json.dumps(metadata, inder
print("Saved:")
for p in sorted(ARTIFACT_DIR.iterdir()):
    print("-", p, f"({p.stat().st_size:,} bytes)")
```

```
Saved:
- artifacts/decision_threshold.joblib (21 bytes)
- artifacts/insurance_fraud_artifacts.zip (6,578 bytes)
- artifacts/insurance_fraud_pipeline.joblib (12,378 bytes)
- artifacts/model_metadata.json (2,900 bytes)
```

8. Round-trip artifact test

In [8]:
```
# Confirm the serialized pipeline reloads and produces the same predictions.
reloaded = joblib.load(ARTIFACT_DIR / "insurance_fraud_pipeline.joblib")
reloaded_probs = reloaded.predict_proba(X_test.iloc[:10])[:, 1]
assert np.allclose(reloaded_probs, y_prob[:10]), "Predictions changed after
assert np.isfinite(reloaded_probs).all()
print("Artifact round-trip test passed.")
```

```
Artifact round-trip test passed.
```

9. Export generated artifacts for Streamlit

Run this cell after the model save and round-trip test cells. It verifies all required outputs and downloads a ZIP containing the three files your Streamlit app expects.

In [9]:
```
from zipfile import ZipFile, ZIP_DEFLATED
from pathlib import Path

# Verify the exact artifacts required by app.py.
required_artifacts = [
    ARTIFACT_DIR / "insurance_fraud_pipeline.joblib",
    ARTIFACT_DIR / "decision_threshold.joblib",
    ARTIFACT_DIR / "model_metadata.json",
]
missing = [str(p) for p in required_artifacts if not p.exists()]
if missing:
    raise FileNotFoundError("Missing artifacts: " + ", ".join(missing) + ".

export_zip = ARTIFACT_DIR / "insurance_fraud_artifacts.zip"
with ZipFile(export_zip, "w", ZIP_DEFLATED) as archive:
    for artifact in required_artifacts:
```

```
        archive.write(artifact, arcname=f"artifacts/{artifact.name}")

print("Artifacts ready for the insurance Streamlit app:")
for artifact in required_artifacts:
    print(f"- {artifact} ({artifact.stat().st_size:,} bytes)")
print(f"Created: {export_zip.resolve()}")

# Trigger browser download when running in Google Colab.
try:
    from google.colab import files
    files.download(str(export_zip))
except ImportError:
    print(f"Not running in Colab. Archive saved locally at {export_zip.resol
```

```
Artifacts ready for the insurance Streamlit app:
- artifacts/insurance_fraud_pipeline.joblib (12,378 bytes)
- artifacts/decision_threshold.joblib (21 bytes)
- artifacts/model_metadata.json (2,900 bytes)
Created: /Users/abhishekpanda/Documents/machine-learning-algorithms/01-logis
tic-regression/02-insurance-fraud-detection/artifacts/insurance_fraud_artifa
cts.zip
Not running in Colab. Archive saved locally at /Users/abhishekpanda/Document
s/machine-learning-algorithms/01-logistic-regression/02-insurance-fraud-dete
ction/artifacts/insurance_fraud_artifacts.zip.
```

10. Deployment checklist

- [ ] The training pipeline fit successfully.
- [ ] Evaluation metrics and plots reviewed.
- [ ] Artifact round-trip test passed.
- [ ] Final export cell downloaded `insurance_fraud_artifacts.zip`.
- [ ] ZIP extracted so the three files are inside this project's `artifacts/` folder.
- [ ] Streamlit deployment uses this folder's `app.py` and `requirements.txt`.
- [ ] Package versions match the versions stored in `model_metadata.json`.

This is an educational demonstration, not an automated fraud determination system.