

## Exp 2 - Lexical Analyzer

**Aim:** To implement a lexical analyzer.

### **Algorithm:**

1. Tokenization i.e. Dividing the program into valid tokens.
2. Remove white space characters.
3. Remove comments.
4. It also provides help in generating error messages by providing row numbers and column numbers.

### **Program:**

```
#include <stdio.h>
#include <ctype.h>
#include <string.h>
void keyw(char *p);
int i = 0, id = 0, kw = 0, num = 0, op = 0, sep = 0;
char keys[32][10] = {"auto", "break", "case", "char", "const",
"continue", "default",
"do", "double", "else", "enum", "extern", "float",
"for", "goto",
"if", "int", "long", "register", "return", "short",
"signed",
"sizeof", "static", "struct", "switch", "typedef",
"union",
"unsigned", "void", "volatile", "while"};
main()
{
    char ch, str[25], seps[15] = " \t\n,;(){}[]#\"<>", oper[] = "!%^&*-
+=~|.;<.>/?";
    int j;
    char fname[50] = "C:\\Users\\abhis\\Downloads\\file.txt";
    FILE *f1;

    f1 = fopen(fname, "r");
    if (f1 == NULL)
```

## Exp 2 - Lexical Analyzer

RA1911003010143

Abhishek Kumar

```
{
    printf("file not found");
    exit(0);
}
while ((ch = fgetc(f1)) != EOF)
{
    for (j = 0; j <= 14; j++)
    {
        if (ch == oper[j])
        {
            printf("%c is an operator\n", ch);
            op++;
            str[i] = '\0';
            keyw(str);
        }
    }
    for (j = 0; j <= 14; j++)
    {
        if (i == -1)
            break;
        if (ch == seps[j])
        {
            if (ch == '#')
            {
                while (ch != '>')
                {
                    printf("%c", ch);
                    ch = fgetc(f1);
                }
                printf("%c is a header file\n", ch);
                i = -1;
                break;
            }
            if (ch == ';')
            {
                sep++;
                printf("%c is a seperator\n", ch);
            }
            if (ch == '"')
            {
                do
                {
                    ch = fgetc(f1);
                    printf("%c", ch);
                } while (ch != '"');
                printf("\b is an argument\n");
                i = -1;
                break;
            }
            str[i] = '\0';
            keyw(str);
        }
    }
    if (i != -1)
    {
        str[i] = ch;
```

## Exp 2 - Lexical Analyzer

RA1911003010143

Abhishek Kumar


```
        i++;
    }
    else
        i = 0;
}
printf("Keywords: %d\nIdentifiers: %d\nOperators: %d\nNumbers: %d\nSeperator: %d\n", kw, id, op, num, sep);
//getch();
}
void keyw(char *p)
{
    int k, flag = 0;
    for (k = 0; k <= 31; k++)
    {
        if (strcmp(keys[k], p) == 0)
        {
            printf("%s is a keyword\n", p);
            kw++;
            flag = 1;
            break;
        }
    }
    if (flag == 0)
    {
        if (isdigit(p[0]))
        {
            printf("%s is a number\n", p);
            num++;
        }
        else
        {
            if (p[0] != '\0')
            {
                printf("%s is an identifier\n", p);
                id++;
            }
        }
    }
    i = -1;
}
```

**file.txt:**

a=b+c;

Exp 2 - Lexical Analyzer  
RA1911003010143  
Abhishek Kumar

## Output:



```
lexical_compiler.c X
C: > Users > abhis > Desktop > Study > 6th Semester > Compiler Design > Lab > Exp2 > lexical_compiler.c > ...
1 #include <stdio.h>

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL
PS C:\Users\abhis\Desktop\Study\6th Semester\Compiler Design\Lab\Exp2> cd "c:\Users\abhis\Desktop\Study\6th Semester\Compiler Design\Lab\Exp2" & .\tempCodeRunnerFile
tempCodeRunnerFile.c:11:1: warning: return type defaults to 'int' [-Wimplicit-int]
    main()
    ~~~~
tempCodeRunnerFile.c: In function 'main':
tempCodeRunnerFile.c:24:9: warning: implicit declaration of function 'exit' [-Wimplicit-function-declaration]
    exit(0);
    ~~~~
tempCodeRunnerFile.c:24:9: warning: incompatible implicit declaration of built-in function 'exit'
tempCodeRunnerFile.c:24:9: note: include '<stdlib.h>' or provide a declaration of 'exit'
= is an operator
a is an identifier
+ is an operator
b is an identifier
; is a separator
c is an identifier
Keywords: 0
Identifiers: 3
Operators: 2
Numbers: 0
Separator: 1
PS C:\Users\abhis\Desktop\Study\6th Semester\Compiler Design\Lab\Exp2>
```

**Result:** Program to implement a lexical analyzer was written and executed successfully.