«adapter»
integration::TelegramAdapter

- botToken: String
- httpClient: HttpClient

+ fetchData(): String
+ parseRawTelegramPayload(response: String)
: RawFeedData

Responsibilities
-- Connects to Telegram API to fetch raw
intelligence feeds.

«controller»
service::IntelligenceService

- telegramAdapter: TelegramAdapter
- geminiClient: GeminiClient

+ ingestFeeds(): List<MissionIncident>
+ verifyIncident(incident: MissionIncident)
: boolean

Responsibilities
-- Facade orchestrating data fetching
and parsing workflows.

adapter

client

«interface»
integration::IntelligenceFeed

+ fetchData(): String
+ parseFeed(data: String): List<RawFeedData>

Responsibilities
-- Standardizes heterogeneous
external feeds (Telegram, RSS).

«client»
integration::GeminiClient

- apiKey: String
- modelName: String

+ generate(prompt: String): String
+ extractEntities(rawText: String): String

Responsibilities
-- Communicates with Google Gemini API
for reasoning and extraction.

client

«factory»
engine::TaskFactory

+ createCommand
(commandType: String, parameters: Map<String, Object>): Command

Responsibilities
-- Instantiates concrete command instances from
AI plan payloads.

factory

«controller»
service::PlanOrchestrator

- geminiClient: GeminiClient
- taskFactory: TaskFactory

+ generateTacticalPlan
(incidents: List<MissionIncident>): TacticalPlan

Responsibilities
-- Orchestrates prompt construction
and AI task decomposition.

«database»
database::DatabaseTool

- dbManager: H2DatabaseManager

+ executeToolCall(params: Map<String, Object>)
: ToolResult
+ querySpatialRadius(center: Point, radius: double)
: List<MissionIncident>

Responsibilities
-- -- Exposes spatial database search and
persistence interfaces as an LLM tool.