

Linux & Network Lab

Shell Scripting Proxy Server Web Server

Q. 01 Menu-Based File Management Script

Write a menu-based script which displays the following options. Implement the logic flow as described below:

```
1. Make a file.  
2. Display contents  
3. Copy the file  
4. Rename the file  
5. Delete the file  
6. Exit  
Enter your option: _
```

Implementation Logic:

Option 1: Make a file

- Accept a file name from the user.
- *If file exists:* Display an error message & return to menu.
- *If file does not exist:* Allow user to enter data.
- Pressing should save contents and display the menu.

Option 2: Display contents

- Accept a file name from the user.

- *If exists:* Display the contents of the file.
- *If not exist:* Display suitable error message.
- Display the menu again after this process.

Option 3: Copy the file

- Accept and .
- *If source exists & is readable:* Proceed to target file check.
- *If source does not exist:* Display error message.
- *If target does not exist:* Copy contents from source to target.
- *If target exists:* Display message and go back to menu.

Option 4: Rename the file

Similar logic to Option 3, but perform a **rename** operation instead of copying.

Option 5: Delete the file

- Enter a file name.
- *If exists & is writable:* Ask for confirmation. If yes, delete.
- *If not exist:* Display suitable error message.

Q. 02 Squid Proxy Server Configuration

Install and configure squid proxy server. Configure the server for the following access controls:

✓ Allow Banking & Google

Allow access to specific banking sites and Google:

HDFC Bank SBI Bank Axis Bank
ICICI Bank Google

✓ Allow Development

Allow access to development sites and Google:

Redhat Microsoft Oracle
Python Cisco

✗ Block Keywords

Block sites containing these words for **all** networks:

sports torrent netflix
facebook movies cricket

Default Policy: Block all other websites for the network.

Q. 03 HTTPD Virtual Hosting

Install and configure httpd service to host **2 websites**.

Constraints:

- Both sites must run on the **same IP address**.
- Both sites must run on **Port 8080**.

Target Configuration

Server

IP:
192.168.1.10
Port: 8080

Site A

www.mydemo.com

Site B

www.examplesite.com

Note: Ensure you configure the `/etc/hosts` file or DNS to map both domain names to the server's IP address to test locally.