

Smart App Online UPS

OL1000RTXL2UN

$1,473.00

MSRP

Purchase Online

Check Prices

Find a Solution Provider

Locate a Partner

Capacity:	1000 VA / 900 W
Power Factor (PF):	0.9

Topology:	Double-Conversion
Waveform:	Sine Wave
Output:	100, 110, 115, 120, 125 V ± 2% (configurable)
Plug type & cord:	NEMA 5-15P, 10 ft. cord
Outlet types:	8 × NEMA 5-15R

Show More

Overview +

Product Overview

Prevent business interruptions and safeguard mission-critical enterprise network equipment.

The CyberPower OL1000RTXL2UN is a rack/tower UPS with double conversion topology. It provides sine wave output to critical applications and equipment that require seamless power correction. The Extended Battery Module (EBM) expands runtime, and Fast Charge Technology restores full backup power faster. This model comes with an extendable LCD control panel, Smart Battery Management charging technology, and energy-saving GreenPower UPS™ ECO Mode.

The OL1000RTXL2UN offers generator compatibility and delivers clean AC power with zero transfer time. A factory installed RM card allows remote management and configuration of the UPS via a standard web browser, command line interface (CLI), or network management system (NMS). Its sine wave output keeps sensitive equipment working by preventing unnecessary shutdowns that can occur with simulated sine wave output.

With a $400,000 lifetime connected equipment guarantee and a three-year warranty, you can trust CyberPower's commitment to high quality.

Product Features

- **Double-Conversion Topology**

Provides consistent, clean, and nearly perfect power, regardless of the condition of the incoming power. With the conversion to DC power, the UPS has a zero millisecond transfer time to battery power when utility power is lost. Designed for high-end system components, corporate servers, lab equipment, and other sensitive electronic devices.

- **Sine Wave Output**
  Keeps sensitive equipment with Active PFC working by preventing unnecessary shutdowns caused by gaps from simulated sine waves.

- **PowerPanel® Business Edition Software**
  Provides tools for easy remote monitoring and managing of the UPS and automates shutdown of multiple devices when needed.

- **RMCARD205**
  Is a full-featured network management card. It enables remote management via a standard web browser, command line interface (CLI), or network management system (NMS) connection.

- **LCD Control Panel**
  Displays UPS status data and configures operating settings from up to 10 ft. away (DB26 cable not included). The LCD control panel displays and allows configuration of IP address settings when an RMCARD205 is installed.

- **Extended Battery Module (EBM)**
  Extends runtime by adding up to 10 EBMs.

- **Fast Charge Technology**
  Allows UPS batteries to return to full capacity more rapidly by utilizing a built-in charger. Restores charge from 0-90% within 4 hours regardless of the number of EBMs.

- **Smart Battery Management (SBM)**
  Improves and extends the functional life of a UPS battery and reduces excessive heat during work cycles by using a three-cycle charging process.

- **GreenPower UPS™ ECO Mode**
  Improves UPS efficiency up to 94% reducing electrical and cooling costs.

- **Hot-Swappable Batteries**
  Keep equipment running by eliminating downtime during UPS battery replacement.

- **Upgradeable UPS firmware**
  Manages the unit's features and functions.

- **Critical & Non-Critical Load Banks**
  Maximize the output of the UPS by setting non-critical loads to shut off allowing additional runtime for critical load outlets.

- **Emergency Power Off (EPO)**
  Allows the UPS to be shut off in the event of an emergency, when the EPO port is connected to an EPO switch.

- **Generator Compatible**
  Ensures a stable sine wave output (free of harmonics and distortion) without switching to battery mode when running on generator input power.

- **Converter Mode**
  Provides the flexibility to set the output frequency, regardless of the input frequency, to match connected equipment by selecting 50Hz or 60Hz output on the LCD control panel.

- **USB & Serial Connectivity**
  Enables full integration with built-in power management and auto shutdown features on Windows, Linux, and VMware systems through a HID-compliant USB port and Serial port.

- **EMI/RFI Filters**
  Prevent electromagnetic and radio frequency interference to ensure clean power for connected equipment.

- **Data Line Surge Protection**
  Prevents power surges that travel through telephone and Ethernet lines from causing damage to your equipment

- **Audible Alarms**
  Identify when the model is running on battery power, overloaded, or has a low battery.

- **Resettable Circuit Breaker**
  Interrupts an electric current in a circuit when the current becomes too high.

- **LED Status Lights**
  Indicate Power On, Line Mode, Battery Mode, Bypass Mode, Fault, Replace Battery.

- **Rack/Tower Versatility**
  Allows for horizontal rack or vertical tower installation.

- **Three-Year Warranty**
  Gives you peace of mind knowing we will repair or replace a defective UPS system (including batteries) within three years of the purchase date. See warranty for details.

- **Connected Equipment Guarantee**
  Affirms we will repair or replace properly connected equipment if it is damaged by a power surge.

Typical Applications

- Corporate Servers
- Edge Closets
- Enterprise Servers
- Network and Storage Devices
- PBX and VoIP Installations

Compatible Products



Extended Battery Module
BP36V60ART2U

Extended Warranty
WEXT5YR-U4A



Hardware
DOORSENSOR



Hardware
RELAYIO500



Replacement Batteries
RB1290X3L

Show More

What's In The Box

UPS system, User Manual, Registration Card, (2) Rackmount Rails, (2) Rackmount Ears, (2) Hanging Brackets, phone line, USB Communication Cable, Serial interface Cable (RS-232), (8) M5 x 7L black flat head screws, (12) M5 x 12L black pan head screws, (6) M5 x 6L silver pan head screws, (8) plastic washers, (12) Screw Hole Dust Covers, (12) Rubber Pads, Software Download Card

WARNING

This product can expose you to chemicals including Styrene (ABS), which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to http://www.P65Warnings.ca.gov.

Specifications +

Downloads +

Support +

Series +

Runtime +

Videos +

Stay Connected

Never miss out. Subscribe to our quarterly newsletter for news, updates software releases, and much more.

Sign Up

Company

Careers

Events

Testimonials

Promotions

News

Publications

Power Blog

Newsletters

Resources

How To Buy

FAQs

Product Resources

Glossary

Product Warranty

Advisory Notices

Extended Warranty

Register a Product

Contact Us

General Inquiries

na.info@cyberpower.com

USA/Canada/LATAM Sales

1.855.289.8177
sales@cyberpower.com

Worldwide Sales

Worldwide Contact Details

Technical Support

Support Resources

1.877.297.6937

For the fastest response:

Tech Support

© 2026 Cyber Power Systems (USA), Inc. CyberPower is a registered trademark and brand of Cyber Power Systems (USA), Inc. All rights reserved.

Terms & Conditions

Privacy Policy

Do not sell my personal information (CCPA)

ALSO OF INTEREST

OL1000RTXL2U
OL1500RTXL2UN
OL2200RTXL2UN