Product Description

Technical Specifications

Specifications

Warranty Information	
Warranty	2 Years
Connector(s)	
Input Connector(s)	1 - NEMA 5-15 Power (North America)
Output Connectors	8 - NEMA 5-15 Power (North America)
Environmental	
Operating Temperature	-5°C to 45°C (23°F to 113°F)
Storage Temperature	-25°C to 65°C (-13°F to 149°F)
Humidity	5% to 95% RH non-condencing
Hardware	
Form Factor	Horizontal
Number of Power Outlets	8
Rack-Mountable	Yes
Indicators	
LED Indicators	1 - Surge
	1 - Ground
Packaging Information	
Shipping (Package) Weight	4.9 lb [2.2 kg]
Package Quantity	1
Package Length	9.2 in [23.3 cm]
Package Width	20.5 in [52.1 cm]
Package Height	2.4 in [6.2 cm]
Performance	
Maximum Total Current	15A

Chat
Online

Maximum Total Current Draw per Phase	15A
Regulatory Derated Input Current (North America)	12A
Nominal Input Voltage	120V
Nominal Output Voltage	120V
Maximum Output Voltage	125V
Load Capacity	1800 VA
General Specifications	Surge Protection: 1800 Joules

Physical Characteristics	
Weight of Product	4.3 lb [2.0 kg]
Color	Black
Material	Steel
Cable Length	6.0 ft [1.8 m]
Product Length	19.0 in [48.3 cm]
Product Width	3.8 in [9.6 cm]
Product Height	1.7 in [4.3 cm]
Power	
Input Voltage	120 AC
What's in the Box	
Included in Package	1 - 8 Port Power Distribution Unit 4 - M5 Screws 4 - M5 Cage Nuts 1 - Installation Document

Compliance & Certifications

View downloadable documentation

RoHS Compliant

Drivers & Downloads +

Product Support +

Accessories +

Customer Q&A +

**Product appearance and specifications are subject to change without notice.*

You might also like



RKPW161915

Rackmount PDU with 16 Outlets and Surge Protection - 1U

RKPW247015

Server Rack PDU with 24 outlets - 0U



RK2236BKF

4-Post 22U Server Rack Cabinet, Lockable 19" Data Rack Cabinet for Computer / AV / IT Equipment, Office / Home Network Rack with Casters & Adjustable Mounting Rails

Rackmount PDU with 8 Outlets and Surge Protection - 1U

Product ID: RKPW081915