

# Some Practical Tips And Feature Selection

---

Nipun Batra and teaching staff

IIT Gandhinagar

August 30, 2025

# Ideas for Baselines

- Mean Model:  $\hat{y}$  = Mean of the training set

# Ideas for Baselines

- Mean Model:  $\hat{y}$  = Mean of the training set
- Median or Mode of the training set

# Ideas for Baselines

- Mean Model:  $\hat{y}$  = Mean of the training set
- Median or Mode of the training set
- Random (Min(training set), Max(training set))

# Choosing Best features

To find the best set of features, one can do exhaustive enumeration (brute force) of features.

# Choosing Best features

To find the best set of features, one can do exhaustive enumeration (brute force) of features.

$Feature_1$	$Feature_2$	...	$Feature_d$
True	False	...	False
False	True	...	False
True	True	...	False
$\vdots$	$\vdots$	$\vdots$	
True	True	...	True

# Choosing Best features

To find the best set of features, one can do exhaustive enumeration (brute force) of features.

$Feature_1$	$Feature_2$	...	$Feature_d$
True	False	...	False
False	True	...	False
True	True	...	False
$\vdots$	$\vdots$	$\vdots$	
True	True	...	True

The entries of the table denote if the feature is used for creating a model. In total we have  $2^d$  models: training models using exhaustive enumeration is very expensive!

# Stepwise Forward Selection

$$F = \{\}$$

for  $i = 1$  to  $K$

$$F_i = \operatorname{argmin}_{\text{feature} \notin F} \text{Loss}(F \cup \text{feature})$$

$$F = F \cup F_i$$

$\text{Loss}(\text{features})$  denotes the loss incurred by the model trained with *features*.



# Stepwise Forward Selection for California Housing Data

Now we will be doing SFS on the California Housing Dataset. We will try to predict the median-selling price(in thousands of dollars) for households in the neighbourhood.

## Stepwise Forward Selection for California Housing Data

Iteration	Added Feature	MSE
1	Median Income of block	0.97
2	Avg. number of rooms in the block	0.63
3	Latitude	0.65
4	Longitude	0.66

This shows except the first two features, everything else are unimportant features.

# Stepwise Backward Selection

Same as SFS, but in opposite direction

Remove feature, which reduces the accuracy the least(unimportant).

# Time Complexity Analysis

Both SFS and SBS are  $O(d^2)$  algorithms, where  $d$  is the number of features.

$$\implies (d) + (d-1) + (d-2) + \dots + (1)$$

$$\implies \frac{d(d-1)}{2}$$

$$\implies d(d-1) \implies d^2$$