

# Matrix Factorization for Movie Recommendation Systems

---

Nipun Batra

IIT Gandhinagar

August 30, 2025

# Today's Learning Journey

- **The Problem:** Why do we need recommendation systems?

# Today's Learning Journey

- **The Problem:** Why do we need recommendation systems?
- **Matrix View:** How ratings become a mathematical problem

# Today's Learning Journey

- **The Problem:** Why do we need recommendation systems?
- **Matrix View:** How ratings become a mathematical problem
- **Key Insight:** Matrix factorization as the solution

# Today's Learning Journey

- **The Problem:** Why do we need recommendation systems?
- **Matrix View:** How ratings become a mathematical problem
- **Key Insight:** Matrix factorization as the solution
- **Step-by-Step:** Building intuition with examples

# Today's Learning Journey

- **The Problem:** Why do we need recommendation systems?
- **Matrix View:** How ratings become a mathematical problem
- **Key Insight:** Matrix factorization as the solution
- **Step-by-Step:** Building intuition with examples
- **Algorithms:** ALS vs Gradient Descent

# Today's Learning Journey

- **The Problem:** Why do we need recommendation systems?
- **Matrix View:** How ratings become a mathematical problem
- **Key Insight:** Matrix factorization as the solution
- **Step-by-Step:** Building intuition with examples
- **Algorithms:** ALS vs Gradient Descent
- **Practice:** Hands-on understanding

# Problem Setup



# The Movie Recommendation Challenge

## Real-World Scenario:

- Netflix: 200M+ users, 15K+ titles

# The Movie Recommendation Challenge

## Real-World Scenario:

- Netflix: 200M+ users, 15K+ titles
- Amazon: 300M+ users, millions of products

# The Movie Recommendation Challenge

## Real-World Scenario:

- Netflix: 200M+ users, 15K+ titles
- Amazon: 300M+ users, millions of products
- Spotify: 400M+ users, 70M+ songs

# The Movie Recommendation Challenge

## Real-World Scenario:

- Netflix: 200M+ users, 15K+ titles
- Amazon: 300M+ users, millions of products
- Spotify: 400M+ users, 70M+ songs
- Most ratings are missing!

# The Movie Recommendation Challenge


## Real-World Scenario:

- Netflix: 200M+ users, 15K+ titles
- Amazon: 300M+ users, millions of products
- Spotify: 400M+ users, 70M+ songs
- Most ratings are missing!

# The Movie Recommendation Challenge

## Real-World Scenario:

- Netflix: 200M+ users, 15K+ titles
- Amazon: 300M+ users, millions of products
- Spotify: 400M+ users, 70M+ songs
- Most ratings are missing!



**Sparse Rating Matrix**





## Think About It:

- You've rated 100 movies out of 15,000

# The Movie Recommendation Challenge

## Real-World Scenario:

- Netflix: 200M+ users, 15K+ titles
- Amazon: 300M+ users, millions of products
- Spotify: 400M+ users, 70M+ songs
- Most ratings are missing!

	Users		
Movies	 ?	 ?	?
	 ?	?	?
	?	?	 ?

**Sparse Rating Matrix**


## Think About It:

- You've rated 100 movies out of 15,000
- Your friend has similar but different tastes

# The Movie Recommendation Challenge

## Real-World Scenario:

- Netflix: 200M+ users, 15K+ titles
- Amazon: 300M+ users, millions of products
- Spotify: 400M+ users, 70M+ songs
- Most ratings are missing!



**Sparse Rating Matrix**

## Think About It:

- You've rated 100 movies out of 15,000
- Your friend has similar but different tastes
- How do we predict what



## Pop Quiz 1: Understanding the Scale

### Quick Question

If Netflix has 200 million users and 15,000 movies, how many possible ratings exist?

## Pop Quiz 1: Understanding the Scale

### Quick Question

If Netflix has 200 million users and 15,000 movies, how many possible ratings exist?

**Answer:**  $200 \times 10^6 \times 15 \times 10^3 = 3 \times 10^{12}$  possible ratings!

# Pop Quiz 1: Understanding the Scale

## Quick Question

If Netflix has 200 million users and 15,000 movies, how many possible ratings exist?

**Answer:**  $200 \times 10^6 \times 15 \times 10^3 = 3 \times 10^{12}$  possible ratings!  
But typical users rate only 20-100 movies. What percentage of the matrix is filled?

## Pop Quiz 1: Understanding the Scale

### Quick Question

If Netflix has 200 million users and 15,000 movies, how many possible ratings exist?

**Answer:**  $200 \times 10^6 \times 15 \times 10^3 = 3 \times 10^{12}$  possible ratings!  
But typical users rate only 20-100 movies. What percentage of the matrix is filled?

**Answer:**  $\frac{100}{15000} = 0.67\%$  - extremely sparse!

# Mathematical Problem Setup

**The Rating Matrix  $\mathbf{A} \in \mathbb{R}^{N \times M}$ :**

# Mathematical Problem Setup

**The Rating Matrix  $\mathbf{A} \in \mathbb{R}^{N \times M}$ :**

$$\mathbf{A} = \begin{bmatrix} a_{11} & ? & a_{13} & ? & \cdots \\ ? & a_{22} & ? & a_{24} & \cdots \\ a_{31} & ? & ? & a_{34} & \cdots \\ \vdots & \vdots & \vdots & \vdots & \ddots \end{bmatrix}$$

# Mathematical Problem Setup

**The Rating Matrix  $\mathbf{A} \in \mathbb{R}^{N \times M}$ :**

$$\mathbf{A} = \begin{bmatrix} a_{11} & ? & a_{13} & ? & \cdots \\ ? & a_{22} & ? & a_{24} & \cdots \\ a_{31} & ? & ? & a_{34} & \cdots \\ \vdots & \vdots & \vdots & \vdots & \ddots \end{bmatrix}$$

- **Rows:** Users  $u_1, u_2, \dots, u_N$

# Mathematical Problem Setup

**The Rating Matrix  $\mathbf{A} \in \mathbb{R}^{N \times M}$ :**

$$\mathbf{A} = \begin{bmatrix} a_{11} & ? & a_{13} & ? & \cdots \\ ? & a_{22} & ? & a_{24} & \cdots \\ a_{31} & ? & ? & a_{34} & \cdots \\ \vdots & \vdots & \vdots & \vdots & \ddots \end{bmatrix}$$

- **Rows:** Users  $u_1, u_2, \dots, u_N$
- **Columns:** Movies  $m_1, m_2, \dots, m_M$



# Mathematical Problem Setup

**The Rating Matrix  $\mathbf{A} \in \mathbb{R}^{N \times M}$ :**

$$\mathbf{A} = \begin{bmatrix} a_{11} & ? & a_{13} & ? & \cdots \\ ? & a_{22} & ? & a_{24} & \cdots \\ a_{31} & ? & ? & a_{34} & \cdots \\ \vdots & \vdots & \vdots & \vdots & \ddots \end{bmatrix}$$

- **Rows:** Users  $u_1, u_2, \dots, u_N$
- **Columns:** Movies  $m_1, m_2, \dots, m_M$
- **Entries:**  $a_{ij} \in \{1, 2, 3, 4, 5\}$  (when observed)

# Mathematical Problem Setup

**The Rating Matrix**  $\mathbf{A} \in \mathbb{R}^{N \times M}$ :

$$\mathbf{A} = \begin{bmatrix} a_{11} & ? & a_{13} & ? & \cdots \\ ? & a_{22} & ? & a_{24} & \cdots \\ a_{31} & ? & ? & a_{34} & \cdots \\ \vdots & \vdots & \vdots & \vdots & \ddots \end{bmatrix}$$

- **Rows:** Users  $u_1, u_2, \dots, u_N$
- **Columns:** Movies  $m_1, m_2, \dots, m_M$
- **Entries:**  $a_{ij} \in \{1, 2, 3, 4, 5\}$  (when observed)
- **Challenge:** Predict missing entries ?

# Mathematical Problem Setup

**The Rating Matrix  $\mathbf{A} \in \mathbb{R}^{N \times M}$ :**

$$\mathbf{A} = \begin{bmatrix} a_{11} & ? & a_{13} & ? & \cdots \\ ? & a_{22} & ? & a_{24} & \cdots \\ a_{31} & ? & ? & a_{34} & \cdots \\ \vdots & \vdots & \vdots & \vdots & \ddots \end{bmatrix}$$

- **Rows:** Users  $u_1, u_2, \dots, u_N$
- **Columns:** Movies  $m_1, m_2, \dots, m_M$
- **Entries:**  $a_{ij} \in \{1, 2, 3, 4, 5\}$  (when observed)
- **Challenge:** Predict missing entries ?
- **Notation:**  $\Omega = \{(i, j) : a_{ij} \text{ is observed}\}$

## Concrete Example: Our Movie Dataset

Let's work with a small, concrete example:

## Concrete Example: Our Movie Dataset

Let's work with a small, concrete example:

User	Sholay	Swades	Batman	Interstellar	Shawshank
Alice	5	4	2	3	2
Bob	?	5	1	4	?
Carol	4	?	1	5	?

## Concrete Example: Our Movie Dataset

Let's work with a small, concrete example:

User	Sholay	Swades	Batman	Interstellar	Shawshank
Alice	5	4	2	3	2
Bob	?	5	1	4	?
Carol	4	?	1	5	?

### Observations:

- Alice loves Bollywood films (Sholay, Swades)

# Concrete Example: Our Movie Dataset

Let's work with a small, concrete example:

User	Sholay	Swades	Batman	Interstellar	Shawshank
Alice	5	4	2	3	2
Bob	?	5	1	4	?
Carol	4	?	1	5	?

## Observations:

- Alice loves Bollywood films (Sholay, Swades)
- Carol enjoys Sci-Fi (Interstellar)

# Concrete Example: Our Movie Dataset

Let's work with a small, concrete example:

User	Sholay	Swades	Batman	Interstellar	Shawshank
Alice	5	4	2	3	2
Bob	?	5	1	4	?
Carol	4	?	1	5	?

## Observations:

- Alice loves Bollywood films (Sholay, Swades)
- Carol enjoys Sci-Fi (Interstellar)
- Can we predict Bob's rating for Sholay?



# Concrete Example: Our Movie Dataset

Let's work with a small, concrete example:

User	Sholay	Swades	Batman	Interstellar	Shawshank
Alice	5	4	2	3	2
Bob	?	5	1	4	?
Carol	4	?	1	5	?

## Observations:

- Alice loves Bollywood films (Sholay, Swades)
- Carol enjoys Sci-Fi (Interstellar)
- Can we predict Bob's rating for Sholay?
- Can we predict Carol's rating for Swades?

**Key Insight: Latent  
Features**

## Before We Dive In: A Simple Question

**Why do you like the movies you like?**

## Before We Dive In: A Simple Question

### **Why do you like the movies you like?**

**Maybe because of:**

- Genre (Action, Romance, Comedy)

# Before We Dive In: A Simple Question

## Why do you like the movies you like?

**Maybe because of:**

- Genre (Action, Romance, Comedy)
- Star cast (Shah Rukh Khan, Tom Cruise)

# Before We Dive In: A Simple Question

## Why do you like the movies you like?

**Maybe because of:**

- Genre (Action, Romance, Comedy)
- Star cast (Shah Rukh Khan, Tom Cruise)
- Director (Christopher Nolan, Rajkumar Hirani)

# Before We Dive In: A Simple Question

## Why do you like the movies you like?

**Maybe because of:**

- Genre (Action, Romance, Comedy)
- Star cast (Shah Rukh Khan, Tom Cruise)
- Director (Christopher Nolan, Rajkumar Hirani)
- Language (Hindi, English, Tamil)

# Before We Dive In: A Simple Question

## Why do you like the movies you like?

### Maybe because of:

- Genre (Action, Romance, Comedy)
- Star cast (Shah Rukh Khan, Tom Cruise)
- Director (Christopher Nolan, Rajkumar Hirani)
- Language (Hindi, English, Tamil)
- Era (90s classics, modern CGI)

### Key Insight:

- Your taste = combination of preferences
- Movie appeal = combination of features
- But we don't know these explicitly!



# The Core Insight: Hidden Patterns

**Hypothesis:** User preferences and movie characteristics can be captured by a small number of **latent features**.

# The Core Insight: Hidden Patterns

**Hypothesis:** User preferences and movie characteristics can be captured by a small number of **latent features**.

**Intuition:** Think of latent features as "hidden DNA" of movies and users!

# The Core Insight: Hidden Patterns

**Hypothesis:** User preferences and movie characteristics can be captured by a small number of **latent features**.

**Intuition:** Think of latent features as "hidden DNA" of movies and users!

## For Movies:

- Bollywood vs Hollywood

# The Core Insight: Hidden Patterns

**Hypothesis:** User preferences and movie characteristics can be captured by a small number of **latent features**.

**Intuition:** Think of latent features as "hidden DNA" of movies and users!

## For Movies:

- Bollywood vs Hollywood
- Action vs Drama

# The Core Insight: Hidden Patterns

**Hypothesis:** User preferences and movie characteristics can be captured by a small number of **latent features**.

**Intuition:** Think of latent features as "hidden DNA" of movies and users!

## For Movies:

- Bollywood vs Hollywood
- Action vs Drama
- Comedy vs Serious


# The Core Insight: Hidden Patterns

**Hypothesis:** User preferences and movie characteristics can be captured by a small number of **latent features**.

**Intuition:** Think of latent features as "hidden DNA" of movies and users!

## For Movies:

- Bollywood vs Hollywood
- Action vs Drama
- Comedy vs Serious
- Runtime (Short vs Long)



Latent Features


# The Core Insight: Hidden Patterns

**Hypothesis:** User preferences and movie characteristics can be captured by a small number of **latent features**.

**Intuition:** Think of latent features as "hidden DNA" of movies and users!

## For Movies:

- Bollywood vs Hollywood
- Action vs Drama
- Comedy vs Serious
- Runtime (Short vs Long)
- Year (Classic vs Modern)



Latent Features

## Step 1: Define Movie Features Explicitly

Let's manually define features for our 5 movies:



## Step 1: Define Movie Features Explicitly

Let's manually define features for our 5 movies:

Movie	Bollywood	Sci-Fi	Drama
Sholay	0.95	0.10	0.85
Swades	1.00	0.20	0.90
Batman	0.05	0.80	0.30
Interstellar	0.05	0.95	0.70
Shawshank	0.05	0.15	0.95

## Step 1: Define Movie Features Explicitly

Let's manually define features for our 5 movies:

Movie	Bollywood	Sci-Fi	Drama
Sholay	0.95	0.10	0.85
Swades	1.00	0.20	0.90
Batman	0.05	0.80	0.30
Interstellar	0.05	0.95	0.70
Shawshank	0.05	0.15	0.95

**Movie Feature Matrix  $\mathbf{H} \in \mathbb{R}^{3 \times 5}$ :**

$$\mathbf{H} = \begin{bmatrix} 0.95 & 1.00 & 0.05 & 0.05 & 0.05 \\ 0.10 & 0.20 & 0.80 & 0.95 & 0.15 \\ 0.85 & 0.90 & 0.30 & 0.70 & 0.95 \end{bmatrix}$$

## Step 2: What About User Preferences?

**User Feature Matrix**  $\mathbf{W} \in \mathbb{R}^{3 \times 3}$  represents user preferences:

## Step 2: What About User Preferences?

**User Feature Matrix**  $\mathbf{W} \in \mathbb{R}^{3 \times 3}$  represents user preferences:

$$\mathbf{W} = \begin{bmatrix} w_{11} & w_{12} & w_{13} \\ w_{21} & w_{22} & w_{23} \\ w_{31} & w_{32} & w_{33} \end{bmatrix}$$

## Step 2: What About User Preferences?

**User Feature Matrix**  $\mathbf{W} \in \mathbb{R}^{3 \times 3}$  represents user preferences:

$$\mathbf{W} = \begin{bmatrix} w_{11} & w_{12} & w_{13} \\ w_{21} & w_{22} & w_{23} \\ w_{31} & w_{32} & w_{33} \end{bmatrix}$$

Where row  $i$  represents user  $i$ 's affinity for:

- $w_{i1}$ : Bollywood preference

## Step 2: What About User Preferences?

**User Feature Matrix**  $\mathbf{W} \in \mathbb{R}^{3 \times 3}$  represents user preferences:

$$\mathbf{W} = \begin{bmatrix} w_{11} & w_{12} & w_{13} \\ w_{21} & w_{22} & w_{23} \\ w_{31} & w_{32} & w_{33} \end{bmatrix}$$

Where row  $i$  represents user  $i$ 's affinity for:

- $w_{i1}$ : Bollywood preference
- $w_{i2}$ : Sci-Fi preference

## Step 2: What About User Preferences?

**User Feature Matrix**  $\mathbf{W} \in \mathbb{R}^{3 \times 3}$  represents user preferences:

$$\mathbf{W} = \begin{bmatrix} w_{11} & w_{12} & w_{13} \\ w_{21} & w_{22} & w_{23} \\ w_{31} & w_{32} & w_{33} \end{bmatrix}$$

Where row  $i$  represents user  $i$ 's affinity for:

- $w_{i1}$ : Bollywood preference
- $w_{i2}$ : Sci-Fi preference
- $w_{i3}$ : Drama preference

## Step 2: What About User Preferences?

**User Feature Matrix**  $\mathbf{W} \in \mathbb{R}^{3 \times 3}$  represents user preferences:

$$\mathbf{W} = \begin{bmatrix} w_{11} & w_{12} & w_{13} \\ w_{21} & w_{22} & w_{23} \\ w_{31} & w_{32} & w_{33} \end{bmatrix}$$

Where row  $i$  represents user  $i$ 's affinity for:

- $w_{i1}$ : Bollywood preference
- $w_{i2}$ : Sci-Fi preference
- $w_{i3}$ : Drama preference



## Step 2: What About User Preferences?

**User Feature Matrix**  $\mathbf{W} \in \mathbb{R}^{3 \times 3}$  represents user preferences:

$$\mathbf{W} = \begin{bmatrix} w_{11} & w_{12} & w_{13} \\ w_{21} & w_{22} & w_{23} \\ w_{31} & w_{32} & w_{33} \end{bmatrix}$$

Where row  $i$  represents user  $i$ 's affinity for:

- $w_{i1}$ : Bollywood preference
- $w_{i2}$ : Sci-Fi preference
- $w_{i3}$ : Drama preference

**Key Question:** How do we learn these  $w_{ij}$  values from observed ratings?

## Step 3: The Matrix Factorization Idea

**Core Hypothesis:**  $\text{Rating} = \text{User preferences} \cdot \text{Movie features}$

## Step 3: The Matrix Factorization Idea

**Core Hypothesis:** Rating = User preferences · Movie features

$$a_{ij} \approx \mathbf{w}_i^T \mathbf{h}_j = \sum_{k=1}^r w_{ik} h_{kj}$$

## Step 3: The Matrix Factorization Idea

**Core Hypothesis:** Rating = User preferences · Movie features

$$a_{ij} \approx \mathbf{w}_i^T \mathbf{h}_j = \sum_{k=1}^r w_{ik} h_{kj}$$

**In Matrix Form:**

$$\mathbf{A} \approx \mathbf{WH}$$

## Step 3: The Matrix Factorization Idea

**Core Hypothesis:** Rating = User preferences · Movie features

$$a_{ij} \approx \mathbf{w}_i^T \mathbf{h}_j = \sum_{k=1}^r w_{ik} h_{kj}$$

**In Matrix Form:**

$$\mathbf{A} \approx \mathbf{WH}$$

$$\mathbf{A}_{3 \times 5} = \begin{bmatrix} 5 & 4 & 2 & 3 & 2 \\ ? & 5 & 1 & 4 & ? \\ 4 & ? & 1 & 5 & ? \end{bmatrix} \approx \begin{bmatrix} w_{11} & w_{12} & w_{13} \\ w_{21} & w_{22} & w_{23} \\ w_{31} & w_{32} & w_{33} \end{bmatrix} \begin{bmatrix} 0.95 & 1.00 & 0.05 & 0.05 & 0.05 \\ 0.10 & 0.20 & 0.80 & 0.95 & 0.15 \\ 0.85 & 0.90 & 0.30 & 0.70 & 0.95 \end{bmatrix} = \mathbf{W}_{3 \times 3} \mathbf{H}_{3 \times 5}$$

## Step 4: Understanding the Calculation

**Let's think step by step...**

## Step 4: Understanding the Calculation

**Let's think step by step...**

**Alice's Profile:**

- How much does she like  
Bollywood?  $w_{11}$

## Step 4: Understanding the Calculation

**Let's think step by step...**

**Alice's Profile:**

- How much does she like  
Bollywood?  $w_{11}$
- How much does she like  
Action?  $w_{12}$



## Step 4: Understanding the Calculation

**Let's think step by step...**

### **Alice's Profile:**

- How much does she like Bollywood?  $w_{11}$
- How much does she like Action?  $w_{12}$
- How much does she like Comedy?  $w_{13}$

### **Sholay's DNA:**

- Bollywood-ness: 0.95 (very high!)
- Action-ness: 0.10 (low)
- Comedy-ness: 0.85 (high)

## Step 4: Understanding the Calculation

**Let's think step by step...**

### **Alice's Profile:**

- How much does she like Bollywood?  $w_{11}$
- How much does she like Action?  $w_{12}$
- How much does she like Comedy?  $w_{13}$

### **Sholay's DNA:**

- Bollywood-ness: 0.95 (very high!)
- Action-ness: 0.10 (low)
- Comedy-ness: 0.85 (high)

## Step 4: Understanding the Calculation

**Let's think step by step...**

### **Alice's Profile:**

- How much does she like Bollywood?  $w_{11}$
- How much does she like Action?  $w_{12}$
- How much does she like Comedy?  $w_{13}$

### **Sholay's DNA:**

- Bollywood-ness: 0.95 (very high!)
- Action-ness: 0.10 (low)
- Comedy-ness: 0.85 (high)

### **The Magic Formula:**

Alice's rating = Alice's preferences · Sholay's features

## Step 4: Detailed Calculation Example

Let's compute Alice's predicted rating for Sholay:

## Step 4: Detailed Calculation Example

Let's compute Alice's predicted rating for Sholay:

**Alice's preferences:**  $\mathbf{w}_1 = [w_{11}, w_{12}, w_{13}]$  **Sholay's features:**  
 $\mathbf{h}_1 = [0.95, 0.10, 0.85]^T$

## Step 4: Detailed Calculation Example

Let's compute Alice's predicted rating for Sholay:

**Alice's preferences:**  $\mathbf{w}_1 = [w_{11}, w_{12}, w_{13}]$  **Sholay's features:**  
 $\mathbf{h}_1 = [0.95, 0.10, 0.85]^T$

$$\hat{a}_{11} = \mathbf{w}_1^T \mathbf{h}_1 \quad (1)$$

$$= w_{11} \cdot 0.95 + w_{12} \cdot 0.10 + w_{13} \cdot 0.85 \quad (2)$$

## Step 4: Detailed Calculation Example

Let's compute Alice's predicted rating for Sholay:

**Alice's preferences:**  $\mathbf{w}_1 = [w_{11}, w_{12}, w_{13}]$  **Sholay's features:**  
 $\mathbf{h}_1 = [0.95, 0.10, 0.85]^T$

$$\hat{a}_{11} = \mathbf{w}_1^T \mathbf{h}_1 \quad (1)$$

$$= w_{11} \cdot 0.95 + w_{12} \cdot 0.10 + w_{13} \cdot 0.85 \quad (2)$$

**Goal:** Find  $w_{11}, w_{12}, w_{13}$  such that  $\hat{a}_{11} \approx 5$  (Alice's actual rating)

## Pop Quiz 2: Matrix Dimensions

### Dimension Check

If we have  $N$  users,  $M$  movies, and  $r$  latent features:



## Pop Quiz 2: Matrix Dimensions

### Dimension Check

If we have  $N$  users,  $M$  movies, and  $r$  latent features:

1. What are the dimensions of  $\mathbf{A}$ ?

## Pop Quiz 2: Matrix Dimensions

### Dimension Check

If we have  $N$  users,  $M$  movies, and  $r$  latent features:

1. What are the dimensions of  $\mathbf{A}$ ?
2. What are the dimensions of  $\mathbf{W}$ ?

## Pop Quiz 2: Matrix Dimensions

### Dimension Check

If we have  $N$  users,  $M$  movies, and  $r$  latent features:

1. What are the dimensions of  $\mathbf{A}$ ?
2. What are the dimensions of  $\mathbf{W}$ ?
3. What are the dimensions of  $\mathbf{H}$ ?

## Pop Quiz 2: Matrix Dimensions

### Dimension Check

If we have  $N$  users,  $M$  movies, and  $r$  latent features:

1. What are the dimensions of  $\mathbf{A}$ ?
2. What are the dimensions of  $\mathbf{W}$ ?
3. What are the dimensions of  $\mathbf{H}$ ?
4. How many parameters do we need to learn?

## Pop Quiz 2: Matrix Dimensions

### Dimension Check

If we have  $N$  users,  $M$  movies, and  $r$  latent features:

1. What are the dimensions of  $\mathbf{A}$ ?
2. What are the dimensions of  $\mathbf{W}$ ?
3. What are the dimensions of  $\mathbf{H}$ ?
4. How many parameters do we need to learn?

## Pop Quiz 2: Matrix Dimensions

### Dimension Check

If we have  $N$  users,  $M$  movies, and  $r$  latent features:

1. What are the dimensions of  $\mathbf{A}$ ?
2. What are the dimensions of  $\mathbf{W}$ ?
3. What are the dimensions of  $\mathbf{H}$ ?
4. How many parameters do we need to learn?

### Answers:

1.  $\mathbf{A} \in \mathbb{R}^{N \times M}$
2.  $\mathbf{W} \in \mathbb{R}^{N \times r}$
3.  $\mathbf{H} \in \mathbb{R}^{r \times M}$
4. Total parameters:  $Nr + rM = r(N + M)$

## Pop Quiz 2: Matrix Dimensions

### Dimension Check

If we have  $N$  users,  $M$  movies, and  $r$  latent features:

1. What are the dimensions of  $\mathbf{A}$ ?
2. What are the dimensions of  $\mathbf{W}$ ?
3. What are the dimensions of  $\mathbf{H}$ ?
4. How many parameters do we need to learn?

### Answers:

1.  $\mathbf{A} \in \mathbb{R}^{N \times M}$
2.  $\mathbf{W} \in \mathbb{R}^{N \times r}$
3.  $\mathbf{H} \in \mathbb{R}^{r \times M}$
4. Total parameters:  $Nr + rM = r(N + M)$

**Key Insight:** If  $r \ll \min(N, M)$ , we have huge parameter

# Learning the Factorization



# The Optimization Problem

**Objective:** Minimize prediction error on observed ratings only

# The Optimization Problem

**Objective:** Minimize prediction error on observed ratings only

$$\text{minimize}_{\mathbf{W}, \mathbf{H}} \sum_{(i,j) \in \Omega} (a_{ij} - \mathbf{w}_i^T \mathbf{h}_j)^2$$

# The Optimization Problem

**Objective:** Minimize prediction error on observed ratings only

$$\text{minimize}_{\mathbf{W}, \mathbf{H}} \sum_{(i,j) \in \Omega} (a_{ij} - \mathbf{w}_i^T \mathbf{h}_j)^2$$

**In Matrix Notation:**

$$\text{minimize}_{\mathbf{W}, \mathbf{H}} \|P_{\Omega}(\mathbf{A} - \mathbf{WH})\|_F^2$$

# The Optimization Problem

**Objective:** Minimize prediction error on observed ratings only

$$\text{minimize}_{\mathbf{W}, \mathbf{H}} \sum_{(i,j) \in \Omega} (a_{ij} - \mathbf{w}_i^T \mathbf{h}_j)^2$$

**In Matrix Notation:**

$$\text{minimize}_{\mathbf{W}, \mathbf{H}} \|P_{\Omega}(\mathbf{A} - \mathbf{WH})\|_F^2$$

Where:

- $P_{\Omega}(\cdot)$ : projection onto observed entries

# The Optimization Problem

**Objective:** Minimize prediction error on observed ratings only

$$\text{minimize}_{\mathbf{W}, \mathbf{H}} \sum_{(i,j) \in \Omega} (a_{ij} - \mathbf{w}_i^T \mathbf{h}_j)^2$$

**In Matrix Notation:**

$$\text{minimize}_{\mathbf{W}, \mathbf{H}} \|P_{\Omega}(\mathbf{A} - \mathbf{WH})\|_F^2$$

Where:

- $P_{\Omega}(\cdot)$ : projection onto observed entries
- $\|\cdot\|_F$ : Frobenius norm

# The Optimization Problem

**Objective:** Minimize prediction error on observed ratings only

$$\text{minimize}_{\mathbf{W}, \mathbf{H}} \sum_{(i,j) \in \Omega} (a_{ij} - \mathbf{w}_i^T \mathbf{h}_j)^2$$

**In Matrix Notation:**

$$\text{minimize}_{\mathbf{W}, \mathbf{H}} \|P_{\Omega}(\mathbf{A} - \mathbf{WH})\|_F^2$$

Where:

- $P_{\Omega}(\cdot)$ : projection onto observed entries
- $\|\cdot\|_F$ : Frobenius norm
- $\Omega$ : set of observed  $(i,j)$  pairs

# Why This is Challenging

## Problem Characteristics:

- **Non-convex:** Multiple local minima exist

# Why This is Challenging

## Problem Characteristics:

- **Non-convex:** Multiple local minima exist
- **Bilinear:** Linear in  $\mathbf{W}$  when  $\mathbf{H}$  fixed, and vice versa



# Why This is Challenging

## Problem Characteristics:

- **Non-convex:** Multiple local minima exist
- **Bilinear:** Linear in  $\mathbf{W}$  when  $\mathbf{H}$  fixed, and vice versa
- **Large-scale:** Millions of users and items

# Why This is Challenging

## Problem Characteristics:

- **Non-convex:** Multiple local minima exist
- **Bilinear:** Linear in  $\mathbf{W}$  when  $\mathbf{H}$  fixed, and vice versa
- **Large-scale:** Millions of users and items
- **Sparse:** Only 0.1-1% of entries observed

# Why This is Challenging

## Problem Characteristics:

- **Non-convex:** Multiple local minima exist
- **Bilinear:** Linear in  $\mathbf{W}$  when  $\mathbf{H}$  fixed, and vice versa
- **Large-scale:** Millions of users and items
- **Sparse:** Only 0.1-1% of entries observed

# Why This is Challenging

## Problem Characteristics:

- **Non-convex:** Multiple local minima exist
- **Bilinear:** Linear in  $\mathbf{W}$  when  $\mathbf{H}$  fixed, and vice versa
- **Large-scale:** Millions of users and items
- **Sparse:** Only 0.1-1% of entries observed

**Key Insight:** While non-convex jointly, it's convex in each matrix individually!

# Algorithm 1: Alternating Least Squares (ALS)

# ALS: The Big Picture

## **Alternating Least Squares Strategy:**

# ALS: The Big Picture

## **Alternating Least Squares Strategy:**

1. **Initialize:**  $\mathbf{W}^{(0)}$  and  $\mathbf{H}^{(0)}$  randomly

# ALS: The Big Picture

## **Alternating Least Squares Strategy:**

1. **Initialize:**  $\mathbf{W}^{(0)}$  and  $\mathbf{H}^{(0)}$  randomly
2. **Repeat until convergence:**



# ALS: The Big Picture

## **Alternating Least Squares Strategy:**

1. **Initialize:**  $\mathbf{W}^{(0)}$  and  $\mathbf{H}^{(0)}$  randomly
2. **Repeat until convergence:**
  - 1) **Fix  $\mathbf{H}$ , solve for  $\mathbf{W}$ :** Each row independently

# ALS: The Big Picture

## Alternating Least Squares Strategy:

1. **Initialize:**  $\mathbf{W}^{(0)}$  and  $\mathbf{H}^{(0)}$  randomly
2. **Repeat until convergence:**
  - 1) **Fix  $\mathbf{H}$ , solve for  $\mathbf{W}$ :** Each row independently
  - 2) **Fix  $\mathbf{W}$ , solve for  $\mathbf{H}$ :** Each column independently

# ALS: The Big Picture

## Alternating Least Squares Strategy:

1. **Initialize:**  $\mathbf{W}^{(0)}$  and  $\mathbf{H}^{(0)}$  randomly
2. **Repeat until convergence:**
  - 1) **Fix  $\mathbf{H}$ , solve for  $\mathbf{W}$ :** Each row independently
  - 2) **Fix  $\mathbf{W}$ , solve for  $\mathbf{H}$ :** Each column independently
3. Each subproblem is a standard least squares problem!

# ALS: The Big Picture


## Alternating Least Squares Strategy:

1. **Initialize:**  $\mathbf{W}^{(0)}$  and  $\mathbf{H}^{(0)}$  randomly
2. **Repeat until convergence:**
  - 1) **Fix  $\mathbf{H}$ , solve for  $\mathbf{W}$ :** Each row independently
  - 2) **Fix  $\mathbf{W}$ , solve for  $\mathbf{H}$ :** Each column independently
3. Each subproblem is a standard least squares problem!

# ALS: The Big Picture

## Alternating Least Squares Strategy:

1. **Initialize:**  $\mathbf{W}^{(0)}$  and  $\mathbf{H}^{(0)}$  randomly
2. **Repeat until convergence:**
  - 1) **Fix  $\mathbf{H}$ , solve for  $\mathbf{W}$ :** Each row independently
  - 2) **Fix  $\mathbf{W}$ , solve for  $\mathbf{H}$ :** Each column independently
3. Each subproblem is a standard least squares problem!



## ALS Step 1: Updating User Features

**Fix  $\mathbf{H}$ , solve for each user  $i$  independently:**

## ALS Step 1: Updating User Features

**Fix  $\mathbf{H}$ , solve for each user  $i$  independently:**

$$\text{minimize}_{\mathbf{w}_i} \sum_{j:(i,j) \in \Omega} (a_{ij} - \mathbf{w}_i^T \mathbf{h}_j)^2$$

# ALS Step 1: Updating User Features

**Fix  $\mathbf{H}$ , solve for each user  $i$  independently:**

$$\text{minimize}_{\mathbf{w}_i} \sum_{j:(i,j) \in \Omega} (a_{ij} - \mathbf{w}_i^T \mathbf{h}_j)^2$$

**Matrix Form for User  $i$ :** Let  $\Omega_i = \{j : (i,j) \in \Omega\}$  (movies rated by user  $i$ )



# ALS Step 1: Updating User Features

**Fix  $\mathbf{H}$ , solve for each user  $i$  independently:**

$$\text{minimize}_{\mathbf{w}_i} \sum_{j:(i,j) \in \Omega} (a_{ij} - \mathbf{w}_i^T \mathbf{h}_j)^2$$

**Matrix Form for User  $i$ :** Let  $\Omega_i = \{j : (i,j) \in \Omega\}$  (movies rated by user  $i$ )

$$\mathbf{y}_i = [a_{i,j_1}, a_{i,j_2}, \dots, a_{i,j_{|\Omega_i|}}]^T \quad (3)$$

$$\mathbf{X}_i = [\mathbf{h}_{j_1}, \mathbf{h}_{j_2}, \dots, \mathbf{h}_{j_{|\Omega_i|}}]^T \quad (4)$$

# ALS Step 1: Updating User Features

**Fix  $\mathbf{H}$ , solve for each user  $i$  independently:**

$$\text{minimize}_{\mathbf{w}_i} \sum_{j:(i,j) \in \Omega} (a_{ij} - \mathbf{w}_i^T \mathbf{h}_j)^2$$

**Matrix Form for User  $i$ :** Let  $\Omega_i = \{j : (i,j) \in \Omega\}$  (movies rated by user  $i$ )

$$\mathbf{y}_i = [a_{i,j_1}, a_{i,j_2}, \dots, a_{i,j_{|\Omega_i|}}]^T \quad (3)$$

$$\mathbf{X}_i = [\mathbf{h}_{j_1}, \mathbf{h}_{j_2}, \dots, \mathbf{h}_{j_{|\Omega_i|}}]^T \quad (4)$$

**Least Squares Solution:**

$$\mathbf{w}_i^* = (\mathbf{X}_i^T \mathbf{X}_i)^{-1} \mathbf{X}_i^T \mathbf{y}_i$$

## ALS Step 1: Concrete Example

### **Update Alice's preferences ( $w_1$ ):**

Alice rated: Sholay(5), Swades(4), Batman(2), Interstellar(3),  
Shawshank(2)

## ALS Step 1: Concrete Example

### Update Alice's preferences ( $w_1$ ):

Alice rated: Sholay(5), Swades(4), Batman(2), Interstellar(3), Shawshank(2)

$$y_1 = \begin{bmatrix} 5 \\ 4 \\ 2 \\ 3 \\ 2 \end{bmatrix} \quad (5)$$

$$X_1 = \begin{bmatrix} 0.95 & 0.10 & 0.85 \\ 1.00 & 0.20 & 0.90 \\ 0.05 & 0.80 & 0.30 \\ 0.05 & 0.95 & 0.70 \\ 0.05 & 0.15 & 0.95 \end{bmatrix} \quad (6)$$

## ALS Step 1: Concrete Example

### Update Alice's preferences ( $\mathbf{w}_1$ ):

Alice rated: Sholay(5), Swades(4), Batman(2), Interstellar(3), Shawshank(2)

$$\mathbf{y}_1 = \begin{bmatrix} 5 \\ 4 \\ 2 \\ 3 \\ 2 \end{bmatrix} \quad (5)$$

$$\mathbf{X}_1 = \begin{bmatrix} 0.95 & 0.10 & 0.85 \\ 1.00 & 0.20 & 0.90 \\ 0.05 & 0.80 & 0.30 \\ 0.05 & 0.95 & 0.70 \\ 0.05 & 0.15 & 0.95 \end{bmatrix} \quad (6)$$

**Solution:**  $\mathbf{w}_1^* = (\mathbf{X}_1^T \mathbf{X}_1)^{-1} \mathbf{X}_1^T \mathbf{y}_1$

This gives us Alice's feature preferences!

## ALS Step 2: Updating Movie Features

**Fix  $W$ , solve for each movie  $j$  independently:**

## ALS Step 2: Updating Movie Features

**Fix  $W$ , solve for each movie  $j$  independently:**

$$\text{minimize}_{\mathbf{h}_j} \sum_{i:(i,j) \in \Omega} (a_{ij} - \mathbf{w}_i^T \mathbf{h}_j)^2$$

## ALS Step 2: Updating Movie Features

**Fix  $W$ , solve for each movie  $j$  independently:**

$$\text{minimize}_{\mathbf{h}_j} \sum_{i:(i,j) \in \Omega} (a_{ij} - \mathbf{w}_i^T \mathbf{h}_j)^2$$

**Matrix Form for Movie  $j$ :** Let  $\Omega_j = \{i : (i, j) \in \Omega\}$  (users who rated movie  $j$ )



## ALS Step 2: Updating Movie Features

**Fix  $\mathbf{W}$ , solve for each movie  $j$  independently:**

$$\text{minimize}_{\mathbf{h}_j} \sum_{i:(i,j) \in \Omega} (a_{ij} - \mathbf{w}_i^T \mathbf{h}_j)^2$$

**Matrix Form for Movie  $j$ :** Let  $\Omega_j = \{i : (i, j) \in \Omega\}$  (users who rated movie  $j$ )

$$\mathbf{y}_j = [a_{i_1,j}, a_{i_2,j}, \dots, a_{i_{|\Omega_j|},j}]^T \quad (7)$$

$$\mathbf{X}_j = [\mathbf{w}_{i_1}, \mathbf{w}_{i_2}, \dots, \mathbf{w}_{i_{|\Omega_j|}}]^T \quad (8)$$

## ALS Step 2: Updating Movie Features

**Fix  $\mathbf{W}$ , solve for each movie  $j$  independently:**

$$\text{minimize}_{\mathbf{h}_j} \sum_{i:(i,j) \in \Omega} (a_{ij} - \mathbf{w}_i^T \mathbf{h}_j)^2$$

**Matrix Form for Movie  $j$ :** Let  $\Omega_j = \{i : (i, j) \in \Omega\}$  (users who rated movie  $j$ )

$$\mathbf{y}_j = [a_{i_1,j}, a_{i_2,j}, \dots, a_{i_{|\Omega_j|},j}]^T \quad (7)$$

$$\mathbf{X}_j = [\mathbf{w}_{i_1}, \mathbf{w}_{i_2}, \dots, \mathbf{w}_{i_{|\Omega_j|}}]^T \quad (8)$$

**Least Squares Solution:**

$$\boxed{\mathbf{h}_j^* = (\mathbf{X}_j^T \mathbf{X}_j)^{-1} \mathbf{X}_j^T \mathbf{y}_j}$$

# ALS: Complete Algorithm

## Algorithm 1: [

H] **Input:** Rating matrix  $\mathbf{A}$ , rank  $r$ , max iterations  $T$

1. **Initialize:**  $\mathbf{W}^{(0)} \in \mathbb{R}^{N \times r}$ ,  $\mathbf{H}^{(0)} \in \mathbb{R}^{r \times M}$  randomly

**Output:**  $\mathbf{W}^{(T)}$ ,  $\mathbf{H}^{(T)}$

# ALS: Complete Algorithm

## Algorithm 2: [

H] **Input:** Rating matrix  $\mathbf{A}$ , rank  $r$ , max iterations  $T$

1. **Initialize:**  $\mathbf{W}^{(0)} \in \mathbb{R}^{N \times r}$ ,  $\mathbf{H}^{(0)} \in \mathbb{R}^{r \times M}$  randomly
2. **For**  $t = 1, 2, \dots, T$ :

**Output:**  $\mathbf{W}^{(T)}$ ,  $\mathbf{H}^{(T)}$

# ALS: Complete Algorithm

## Algorithm 3: [

H] **Input:** Rating matrix  $\mathbf{A}$ , rank  $r$ , max iterations  $T$

1. **Initialize:**  $\mathbf{W}^{(0)} \in \mathbb{R}^{N \times r}$ ,  $\mathbf{H}^{(0)} \in \mathbb{R}^{r \times M}$  randomly

2. **For**  $t = 1, 2, \dots, T$ :

1) **Update Users:** For each user  $i = 1, \dots, N$ :

$$\mathbf{w}_i^{(t)} = (\mathbf{X}_i^T \mathbf{X}_i)^{-1} \mathbf{X}_i^T \mathbf{y}_i$$

**Output:**  $\mathbf{W}^{(T)}$ ,  $\mathbf{H}^{(T)}$

# ALS: Complete Algorithm

## Algorithm 4: [

H] **Input:** Rating matrix  $\mathbf{A}$ , rank  $r$ , max iterations  $T$

1. **Initialize:**  $\mathbf{W}^{(0)} \in \mathbb{R}^{N \times r}$ ,  $\mathbf{H}^{(0)} \in \mathbb{R}^{r \times M}$  randomly

2. **For**  $t = 1, 2, \dots, T$ :

1) **Update Users:** For each user  $i = 1, \dots, N$ :

$$\mathbf{w}_i^{(t)} = (\mathbf{X}_i^T \mathbf{X}_i)^{-1} \mathbf{X}_i^T \mathbf{y}_i$$

2) **Update Movies:** For each movie  $j = 1, \dots, M$ :

$$\mathbf{h}_j^{(t)} = (\mathbf{X}_j^T \mathbf{X}_j)^{-1} \mathbf{X}_j^T \mathbf{y}_j$$

**Output:**  $\mathbf{W}^{(T)}$ ,  $\mathbf{H}^{(T)}$

# ALS: Complete Algorithm

## Algorithm 5: [

H] **Input:** Rating matrix  $\mathbf{A}$ , rank  $r$ , max iterations  $T$

1. **Initialize:**  $\mathbf{W}^{(0)} \in \mathbb{R}^{N \times r}$ ,  $\mathbf{H}^{(0)} \in \mathbb{R}^{r \times M}$  randomly

2. **For**  $t = 1, 2, \dots, T$ :

1) **Update Users:** For each user  $i = 1, \dots, N$ :

$$\mathbf{w}_i^{(t)} = (\mathbf{X}_i^T \mathbf{X}_i)^{-1} \mathbf{X}_i^T \mathbf{y}_i$$

2) **Update Movies:** For each movie  $j = 1, \dots, M$ :

$$\mathbf{h}_j^{(t)} = (\mathbf{X}_j^T \mathbf{X}_j)^{-1} \mathbf{X}_j^T \mathbf{y}_j$$

3. **Check Convergence:** Stop if

$$\|\mathbf{W}^{(t)} \mathbf{H}^{(t)} - \mathbf{W}^{(t-1)} \mathbf{H}^{(t-1)}\|_F < \epsilon$$

**Output:**  $\mathbf{W}^{(T)}$ ,  $\mathbf{H}^{(T)}$

# Algorithm 2: Gradient Descent



# Gradient Descent Approach

**Simultaneous Updates:** Update both  $\mathbf{W}$  and  $\mathbf{H}$  together

# Gradient Descent Approach

**Simultaneous Updates:** Update both  $\mathbf{W}$  and  $\mathbf{H}$  together

**Objective Function:**

$$L(\mathbf{W}, \mathbf{H}) = \sum_{(i,j) \in \Omega} (a_{ij} - \mathbf{w}_i^T \mathbf{h}_j)^2$$

# Gradient Descent Approach

**Simultaneous Updates:** Update both  $\mathbf{W}$  and  $\mathbf{H}$  together  
**Objective Function:**

$$L(\mathbf{W}, \mathbf{H}) = \sum_{(i,j) \in \Omega} (a_{ij} - \mathbf{w}_i^T \mathbf{h}_j)^2$$

**Gradients:**

$$\frac{\partial L}{\partial \mathbf{w}_i} = -2 \sum_{j: (i,j) \in \Omega} (a_{ij} - \mathbf{w}_i^T \mathbf{h}_j) \mathbf{h}_j \quad (9)$$

$$\frac{\partial L}{\partial \mathbf{h}_j} = -2 \sum_{i: (i,j) \in \Omega} (a_{ij} - \mathbf{w}_i^T \mathbf{h}_j) \mathbf{w}_i \quad (10)$$

# SGD: Learning Like a Human

**Imagine you're learning someone's taste in movies...**

# SGD: Learning Like a Human

**Imagine you're learning someone's taste in movies...**

## **Your Process:**

1. Make a guess about their rating

# SGD: Learning Like a Human

**Imagine you're learning someone's taste in movies...**

## **Your Process:**

1. Make a guess about their rating
2. See their actual rating

# SGD: Learning Like a Human

**Imagine you're learning someone's taste in movies...**

## **Your Process:**

1. Make a guess about their rating
2. See their actual rating
3. Adjust your understanding

# SGD: Learning Like a Human

**Imagine you're learning someone's taste in movies...**

## **Your Process:**

1. Make a guess about their rating
2. See their actual rating
3. Adjust your understanding
4. Repeat for next movie

## **SGD does exactly this!**

- One rating at a time
- Small adjustments
- Gradually improves



# Stochastic Gradient Descent (SGD)

**For each observed rating  $(i, j) \in \Omega$ :**

# Stochastic Gradient Descent (SGD)

**For each observed rating  $(i, j) \in \Omega$ :**

1. **Predict:**  $\hat{a}_{ij} = \mathbf{w}_i^T \mathbf{h}_j$

# Stochastic Gradient Descent (SGD)

**For each observed rating  $(i, j) \in \Omega$ :**

1. **Predict:**  $\hat{a}_{ij} = \mathbf{w}_i^T \mathbf{h}_j$
2. **Compute Error:**  $e_{ij} = a_{ij} - \hat{a}_{ij}$

# Stochastic Gradient Descent (SGD)

**For each observed rating  $(i, j) \in \Omega$ :**

1. **Predict:**  $\hat{a}_{ij} = \mathbf{w}_i^T \mathbf{h}_j$
2. **Compute Error:**  $e_{ij} = a_{ij} - \hat{a}_{ij}$
3. **Update:**

$$\mathbf{w}_i \leftarrow \mathbf{w}_i + \alpha \cdot e_{ij} \cdot \mathbf{h}_j \quad (11)$$

$$\mathbf{h}_j \leftarrow \mathbf{h}_j + \alpha \cdot e_{ij} \cdot \mathbf{w}_i \quad (12)$$

# Stochastic Gradient Descent (SGD)

**For each observed rating  $(i, j) \in \Omega$ :**

1. **Predict:**  $\hat{a}_{ij} = \mathbf{w}_i^T \mathbf{h}_j$
2. **Compute Error:**  $e_{ij} = a_{ij} - \hat{a}_{ij}$
3. **Update:**

$$\mathbf{w}_i \leftarrow \mathbf{w}_i + \alpha \cdot e_{ij} \cdot \mathbf{h}_j \quad (11)$$

$$\mathbf{h}_j \leftarrow \mathbf{h}_j + \alpha \cdot e_{ij} \cdot \mathbf{w}_i \quad (12)$$

# Stochastic Gradient Descent (SGD)

**For each observed rating  $(i, j) \in \Omega$ :**

1. **Predict:**  $\hat{a}_{ij} = \mathbf{w}_i^T \mathbf{h}_j$
2. **Compute Error:**  $e_{ij} = a_{ij} - \hat{a}_{ij}$
3. **Update:**

$$\mathbf{w}_i \leftarrow \mathbf{w}_i + \alpha \cdot e_{ij} \cdot \mathbf{h}_j \quad (11)$$

$$\mathbf{h}_j \leftarrow \mathbf{h}_j + \alpha \cdot e_{ij} \cdot \mathbf{w}_i \quad (12)$$

**Intuition:**

- If  $e_{ij} > 0$ : Predicted rating too low  $\rightarrow$  Increase similarity

# Stochastic Gradient Descent (SGD)

**For each observed rating  $(i, j) \in \Omega$ :**

1. **Predict:**  $\hat{a}_{ij} = \mathbf{w}_i^T \mathbf{h}_j$
2. **Compute Error:**  $e_{ij} = a_{ij} - \hat{a}_{ij}$
3. **Update:**

$$\mathbf{w}_i \leftarrow \mathbf{w}_i + \alpha \cdot e_{ij} \cdot \mathbf{h}_j \quad (11)$$

$$\mathbf{h}_j \leftarrow \mathbf{h}_j + \alpha \cdot e_{ij} \cdot \mathbf{w}_i \quad (12)$$

**Intuition:**

- If  $e_{ij} > 0$ : Predicted rating too low  $\rightarrow$  Increase similarity
- If  $e_{ij} < 0$ : Predicted rating too high  $\rightarrow$  Decrease similarity

# Stochastic Gradient Descent (SGD)

**For each observed rating  $(i, j) \in \Omega$ :**

1. **Predict:**  $\hat{a}_{ij} = \mathbf{w}_i^T \mathbf{h}_j$
2. **Compute Error:**  $e_{ij} = a_{ij} - \hat{a}_{ij}$
3. **Update:**

$$\mathbf{w}_i \leftarrow \mathbf{w}_i + \alpha \cdot e_{ij} \cdot \mathbf{h}_j \quad (11)$$

$$\mathbf{h}_j \leftarrow \mathbf{h}_j + \alpha \cdot e_{ij} \cdot \mathbf{w}_i \quad (12)$$

**Intuition:**

- If  $e_{ij} > 0$ : Predicted rating too low  $\rightarrow$  Increase similarity
- If  $e_{ij} < 0$ : Predicted rating too high  $\rightarrow$  Decrease similarity
- Learning rate  $\alpha$  controls step size



## SGD: Step-by-Step Example

**Example:** Alice rates Sholay as 5, but we predict 3.2

## SGD: Step-by-Step Example

**Example:** Alice rates Sholay as 5, but we predict 3.2

$$\text{Current: } \mathbf{w}_1 = [0.4, 0.2, 0.3], \quad \mathbf{h}_1 = [0.95, 0.10, 0.85] \quad (13)$$

$$\text{Prediction: } \hat{a}_{11} = 0.4 \times 0.95 + 0.2 \times 0.10 + 0.3 \times 0.85 = 0.655 \quad (14)$$

$$\text{Error: } e_{11} = 5 - 0.655 = 4.345 \quad (15)$$

## SGD: Step-by-Step Example

**Example:** Alice rates Sholay as 5, but we predict 3.2

$$\text{Current: } \mathbf{w}_1 = [0.4, 0.2, 0.3], \quad \mathbf{h}_1 = [0.95, 0.10, 0.85] \quad (13)$$

$$\text{Prediction: } \hat{a}_{11} = 0.4 \times 0.95 + 0.2 \times 0.10 + 0.3 \times 0.85 = 0.655 \quad (14)$$

$$\text{Error: } e_{11} = 5 - 0.655 = 4.345 \quad (15)$$

**Updates with  $\alpha = 0.01$ :**

$$\mathbf{w}_1 \leftarrow [0.4, 0.2, 0.3] + 0.01 \times 4.345 \times [0.95, 0.10, 0.85] \quad (16)$$

$$= [0.4413, 0.2043, 0.3369] \quad (17)$$

$$\mathbf{h}_1 \leftarrow [0.95, 0.10, 0.85] + 0.01 \times 4.345 \times [0.4, 0.2, 0.3] \quad (18)$$

$$= [0.9674, 0.1087, 0.8631] \quad (19)$$

## Pop Quiz 3: SGD Understanding

### Quick Check

A user gives a rating of 2 to a movie, but our model predicts 4.5.

## Pop Quiz 3: SGD Understanding

### Quick Check

A user gives a rating of 2 to a movie, but our model predicts 4.5.

1. What is the error  $e_{ij}$ ?

## Pop Quiz 3: SGD Understanding

### Quick Check

A user gives a rating of 2 to a movie, but our model predicts 4.5.

1. What is the error  $e_{ij}$ ?
2. Should we increase or decrease the user-movie similarity?

## Pop Quiz 3: SGD Understanding

### Quick Check

A user gives a rating of 2 to a movie, but our model predicts 4.5.

1. What is the error  $e_{ij}$ ?
2. Should we increase or decrease the user-movie similarity?
3. If  $\alpha = 0.1$ ,  $\mathbf{w}_i = [0.8, 0.3]$ ,  $\mathbf{h}_j = [0.6, 0.9]$ , what are the updates?

## Pop Quiz 3: SGD Understanding

### Quick Check

A user gives a rating of 2 to a movie, but our model predicts 4.5.

1. What is the error  $e_{ij}$ ?
2. Should we increase or decrease the user-movie similarity?
3. If  $\alpha = 0.1$ ,  $\mathbf{w}_i = [0.8, 0.3]$ ,  $\mathbf{h}_j = [0.6, 0.9]$ , what are the updates?



## Pop Quiz 3: SGD Understanding

### Quick Check

A user gives a rating of 2 to a movie, but our model predicts 4.5.

1. What is the error  $e_{ij}$ ?
2. Should we increase or decrease the user-movie similarity?
3. If  $\alpha = 0.1$ ,  $\mathbf{w}_i = [0.8, 0.3]$ ,  $\mathbf{h}_j = [0.6, 0.9]$ , what are the updates?

### Answers:

1.  $e_{ij} = 2 - 4.5 = -2.5$
2. Decrease similarity (negative error)
3.  $\mathbf{w}_i \leftarrow [0.8, 0.3] + 0.1 \times (-2.5) \times [0.6, 0.9] = [0.65, 0.075]$
4.  $\mathbf{h}_j \leftarrow [0.6, 0.9] + 0.1 \times (-2.5) \times [0.8, 0.3] = [0.4, 0.825]$

# Algorithm Comparison and Practical Considerations

# ALS vs SGD: Head-to-Head Comparison

Aspect	ALS	SGD
<b>Updates</b>	Alternating	Simultaneous
<b>Convergence</b>	Faster, more stable	Slower, can oscillate
<b>Parallelization</b>	Excellent	Limited
<b>Memory</b>	Higher	Lower
<b>Implementation</b>	Complex	Simple
<b>Hyperparameters</b>	Few (rank $r$ )	Many ( $\alpha$ , schedule)
<b>Scalability</b>	Very good	Good

# ALS vs SGD: Head-to-Head Comparison

Aspect	ALS	SGD
Updates	Alternating	Simultaneous
Convergence	Faster, more stable	Slower, can oscillate
Parallelization	Excellent	Limited
Memory	Higher	Lower
Implementation	Complex	Simple
Hyperparameters	Few (rank $r$ )	Many ( $\alpha$ , schedule)
Scalability	Very good	Good

## When to Use Which?

- **ALS:** Large-scale, production systems (Spark, distributed)

# ALS vs SGD: Head-to-Head Comparison

Aspect	ALS	SGD
<b>Updates</b>	Alternating	Simultaneous
<b>Convergence</b>	Faster, more stable	Slower, can oscillate
<b>Parallelization</b>	Excellent	Limited
<b>Memory</b>	Higher	Lower
<b>Implementation</b>	Complex	Simple
<b>Hyperparameters</b>	Few (rank $r$ )	Many ( $\alpha$ , schedule)
<b>Scalability</b>	Very good	Good

## When to Use Which?

- **ALS:** Large-scale, production systems (Spark, distributed)
- **SGD:** Online learning, real-time updates, research

# Advanced Practical Considerations

**Regularization:** Prevent overfitting

$$\text{minimize}_{\mathbf{W}, \mathbf{H}} \sum_{(i,j) \in \Omega} (a_{ij} - \mathbf{w}_i^T \mathbf{h}_j)^2 + \lambda (\|\mathbf{W}\|_F^2 + \|\mathbf{H}\|_F^2)$$

# Advanced Practical Considerations

**Regularization:** Prevent overfitting

$$\text{minimize}_{\mathbf{W}, \mathbf{H}} \sum_{(i,j) \in \Omega} (a_{ij} - \mathbf{w}_i^T \mathbf{h}_j)^2 + \lambda (\|\mathbf{W}\|_F^2 + \|\mathbf{H}\|_F^2)$$

**Bias Terms:** Account for global, user, and item biases

$$\hat{a}_{ij} = \mu + b_i + b_j + \mathbf{w}_i^T \mathbf{h}_j$$

# Advanced Practical Considerations

**Regularization:** Prevent overfitting

$$\text{minimize}_{\mathbf{W}, \mathbf{H}} \sum_{(i,j) \in \Omega} (a_{ij} - \mathbf{w}_i^T \mathbf{h}_j)^2 + \lambda (\|\mathbf{W}\|_F^2 + \|\mathbf{H}\|_F^2)$$

**Bias Terms:** Account for global, user, and item biases

$$\hat{a}_{ij} = \mu + b_i + b_j + \mathbf{w}_i^T \mathbf{h}_j$$

**Implicit Feedback:** Binary observations (clicks, views)

$$\text{Confidence: } c_{ij} = 1 + \alpha \cdot \text{frequency}_{ij}$$



# Advanced Practical Considerations

**Regularization:** Prevent overfitting

$$\text{minimize}_{\mathbf{W}, \mathbf{H}} \sum_{(i,j) \in \Omega} (a_{ij} - \mathbf{w}_i^T \mathbf{h}_j)^2 + \lambda (\|\mathbf{W}\|_F^2 + \|\mathbf{H}\|_F^2)$$

**Bias Terms:** Account for global, user, and item biases

$$\hat{a}_{ij} = \mu + b_i + b_j + \mathbf{w}_i^T \mathbf{h}_j$$

**Implicit Feedback:** Binary observations (clicks, views)

$$\text{Confidence: } c_{ij} = 1 + \alpha \cdot \text{frequency}_{ij}$$

**Cold Start Problem:** New users/items with no ratings

- Content-based features

# Advanced Practical Considerations

**Regularization:** Prevent overfitting

$$\text{minimize}_{\mathbf{W}, \mathbf{H}} \sum_{(i,j) \in \Omega} (a_{ij} - \mathbf{w}_i^T \mathbf{h}_j)^2 + \lambda (\|\mathbf{W}\|_F^2 + \|\mathbf{H}\|_F^2)$$

**Bias Terms:** Account for global, user, and item biases

$$\hat{a}_{ij} = \mu + b_i + b_j + \mathbf{w}_i^T \mathbf{h}_j$$

**Implicit Feedback:** Binary observations (clicks, views)

$$\text{Confidence: } c_{ij} = 1 + \alpha \cdot \text{frequency}_{ij}$$

**Cold Start Problem:** New users/items with no ratings

- Content-based features
- Demographic information

# Advanced Practical Considerations

**Regularization:** Prevent overfitting

$$\text{minimize}_{\mathbf{W}, \mathbf{H}} \sum_{(i,j) \in \Omega} (a_{ij} - \mathbf{w}_i^T \mathbf{h}_j)^2 + \lambda (\|\mathbf{W}\|_F^2 + \|\mathbf{H}\|_F^2)$$

**Bias Terms:** Account for global, user, and item biases

$$\hat{a}_{ij} = \mu + b_i + b_j + \mathbf{w}_i^T \mathbf{h}_j$$

**Implicit Feedback:** Binary observations (clicks, views)

$$\text{Confidence: } c_{ij} = 1 + \alpha \cdot \text{frequency}_{ij}$$

**Cold Start Problem:** New users/items with no ratings

- Content-based features
- Demographic information
- Hybrid approaches

# Hands-On Understanding

# Let's Build Intuition: Small Example

**Our 3×3 rating matrix:**

$$\mathbf{A} = \begin{bmatrix} 5 & ? & 2 \\ 4 & 4 & ? \\ ? & 5 & 1 \end{bmatrix}$$

# Let's Build Intuition: Small Example

**Our 3×3 rating matrix:**

$$\mathbf{A} = \begin{bmatrix} 5 & ? & 2 \\ 4 & 4 & ? \\ ? & 5 & 1 \end{bmatrix}$$

**Goal:** Find  $\mathbf{W} \in \mathbb{R}^{3 \times 2}$  and  $\mathbf{H} \in \mathbb{R}^{2 \times 3}$  such that:

$$\mathbf{A} \approx \mathbf{WH} = \begin{bmatrix} w_{11} & w_{12} \\ w_{21} & w_{22} \\ w_{31} & w_{32} \end{bmatrix} \begin{bmatrix} h_{11} & h_{12} & h_{13} \\ h_{21} & h_{22} & h_{23} \end{bmatrix}$$

# Let's Build Intuition: Small Example

**Our  $3 \times 3$  rating matrix:**

$$\mathbf{A} = \begin{bmatrix} 5 & ? & 2 \\ 4 & 4 & ? \\ ? & 5 & 1 \end{bmatrix}$$

**Goal:** Find  $\mathbf{W} \in \mathbb{R}^{3 \times 2}$  and  $\mathbf{H} \in \mathbb{R}^{2 \times 3}$  such that:

$$\mathbf{A} \approx \mathbf{WH} = \begin{bmatrix} w_{11} & w_{12} \\ w_{21} & w_{22} \\ w_{31} & w_{32} \end{bmatrix} \begin{bmatrix} h_{11} & h_{12} & h_{13} \\ h_{21} & h_{22} & h_{23} \end{bmatrix}$$

**Constraint:** Only minimize error on observed entries!

# Step-by-Step ALS Solution

**Iteration 1:** Initialize randomly

$$\mathbf{W}^{(0)} = \begin{bmatrix} 0.5 & 0.3 \\ 0.4 & 0.6 \\ 0.2 & 0.8 \end{bmatrix}, \quad \mathbf{H}^{(0)} = \begin{bmatrix} 1.0 & 0.5 & 0.2 \\ 0.3 & 1.2 & 0.8 \end{bmatrix}$$



# Step-by-Step ALS Solution

**Iteration 1:** Initialize randomly

$$\mathbf{W}^{(0)} = \begin{bmatrix} 0.5 & 0.3 \\ 0.4 & 0.6 \\ 0.2 & 0.8 \end{bmatrix}, \quad \mathbf{H}^{(0)} = \begin{bmatrix} 1.0 & 0.5 & 0.2 \\ 0.3 & 1.2 & 0.8 \end{bmatrix}$$

**Update User 1:** Only use observed ratings (positions 1,3)

$$\mathbf{y}_1 = [5, 2]^T \quad (20)$$

$$\mathbf{X}_1 = \begin{bmatrix} 1.0 & 0.3 \\ 0.2 & 0.8 \end{bmatrix} \text{ (columns 1,3 of } \mathbf{H}^{(0)T}) \quad (21)$$

# Step-by-Step ALS Solution

**Iteration 1:** Initialize randomly

$$\mathbf{W}^{(0)} = \begin{bmatrix} 0.5 & 0.3 \\ 0.4 & 0.6 \\ 0.2 & 0.8 \end{bmatrix}, \quad \mathbf{H}^{(0)} = \begin{bmatrix} 1.0 & 0.5 & 0.2 \\ 0.3 & 1.2 & 0.8 \end{bmatrix}$$

**Update User 1:** Only use observed ratings (positions 1,3)

$$\mathbf{y}_1 = [5, 2]^T \quad (20)$$

$$\mathbf{X}_1 = \begin{bmatrix} 1.0 & 0.3 \\ 0.2 & 0.8 \end{bmatrix} \text{ (columns 1,3 of } \mathbf{H}^{(0)T} \text{)} \quad (21)$$

**Solve:**  $\mathbf{w}_1^{(1)} = (\mathbf{X}_1^T \mathbf{X}_1)^{-1} \mathbf{X}_1^T \mathbf{y}_1$

Continue for all users and movies...

## Pop Quiz 4: Final Challenge

### Master Check

You're Netflix's lead ML engineer. You have:

- 200M users, 15K movies
- 20B ratings (0.67% filled)
- Need real-time recommendations
- New users/movies arrive daily

## Pop Quiz 4: Final Challenge

### Master Check

You're Netflix's lead ML engineer. You have:

- 200M users, 15K movies
- 20B ratings (0.67% filled)
- Need real-time recommendations
- New users/movies arrive daily

Design your recommendation system:

1. Which algorithm: ALS or SGD? Why?

## Pop Quiz 4: Final Challenge

### Master Check

You're Netflix's lead ML engineer. You have:

- 200M users, 15K movies
- 20B ratings (0.67% filled)
- Need real-time recommendations
- New users/movies arrive daily

Design your recommendation system:

1. Which algorithm: ALS or SGD? Why?
2. What rank  $r$  would you choose?

## Pop Quiz 4: Final Challenge

### Master Check

You're Netflix's lead ML engineer. You have:

- 200M users, 15K movies
- 20B ratings (0.67% filled)
- Need real-time recommendations
- New users/movies arrive daily

Design your recommendation system:

1. Which algorithm: ALS or SGD? Why?
2. What rank  $r$  would you choose?
3. How to handle new users?

## Pop Quiz 4: Final Challenge

### Master Check

You're Netflix's lead ML engineer. You have:

- 200M users, 15K movies
- 20B ratings (0.67% filled)
- Need real-time recommendations
- New users/movies arrive daily

Design your recommendation system:

1. Which algorithm: ALS or SGD? Why?
2. What rank  $r$  would you choose?
3. How to handle new users?
4. How to handle the scale?

## Pop Quiz 4: Final Challenge

### Master Check

You're Netflix's lead ML engineer. You have:

- 200M users, 15K movies
- 20B ratings (0.67% filled)
- Need real-time recommendations
- New users/movies arrive daily

Design your recommendation system:

1. Which algorithm: ALS or SGD? Why?
2. What rank  $r$  would you choose?
3. How to handle new users?
4. How to handle the scale?



## Pop Quiz 4: Final Challenge

### Master Check

You're Netflix's lead ML engineer. You have:

- 200M users, 15K movies
- 20B ratings (0.67% filled)
- Need real-time recommendations
- New users/movies arrive daily

Design your recommendation system:

1. Which algorithm: ALS or SGD? Why?
2. What rank  $r$  would you choose?
3. How to handle new users?
4. How to handle the scale?

**Suggested Solution:**

# Summary and Key Takeaways

# Key Insights Summary

1. **Sparsity**  $\Rightarrow$  **Factorization**: Sparse rating matrices can be approximated by low-rank factorizations

# Key Insights Summary

1. **Sparsity  $\Rightarrow$  Factorization**: Sparse rating matrices can be approximated by low-rank factorizations
2. **Latent Features**: Users and items are characterized by latent factors (not manually defined!)

# Key Insights Summary

1. **Sparsity  $\Rightarrow$  Factorization**: Sparse rating matrices can be approximated by low-rank factorizations
2. **Latent Features**: Users and items are characterized by latent factors (not manually defined!)
3. **Bilinear Problem**: Non-convex jointly, but convex individually  $\rightarrow$  Alternating optimization works well

# Key Insights Summary

1. **Sparsity  $\Rightarrow$  Factorization**: Sparse rating matrices can be approximated by low-rank factorizations
2. **Latent Features**: Users and items are characterized by latent factors (not manually defined!)
3. **Bilinear Problem**: Non-convex jointly, but convex individually  $\rightarrow$  Alternating optimization works well
4. **Scale Matters**: Algorithm choice depends on data size and computational constraints

# Key Insights Summary

1. **Sparsity  $\Rightarrow$  Factorization:** Sparse rating matrices can be approximated by low-rank factorizations
2. **Latent Features:** Users and items are characterized by latent factors (not manually defined!)
3. **Bilinear Problem:** Non-convex jointly, but convex individually  $\rightarrow$  Alternating optimization works well
4. **Scale Matters:** Algorithm choice depends on data size and computational constraints
5. **Real-World Complexity:** Regularization, bias terms, cold start, implicit feedback all matter

# Key Insights Summary

1. **Sparsity  $\Rightarrow$  Factorization:** Sparse rating matrices can be approximated by low-rank factorizations
2. **Latent Features:** Users and items are characterized by latent factors (not manually defined!)
3. **Bilinear Problem:** Non-convex jointly, but convex individually  $\rightarrow$  Alternating optimization works well
4. **Scale Matters:** Algorithm choice depends on data size and computational constraints
5. **Real-World Complexity:** Regularization, bias terms, cold start, implicit feedback all matter



# Key Insights Summary

1. **Sparsity  $\Rightarrow$  Factorization:** Sparse rating matrices can be approximated by low-rank factorizations
2. **Latent Features:** Users and items are characterized by latent factors (not manually defined!)
3. **Bilinear Problem:** Non-convex jointly, but convex individually  $\rightarrow$  Alternating optimization works well
4. **Scale Matters:** Algorithm choice depends on data size and computational constraints
5. **Real-World Complexity:** Regularization, bias terms, cold start, implicit feedback all matter

## The Mathematical Beauty:

Collaborative Filtering = Matrix Factorization = Dimensionality Reduction

# Extensions and Advanced Topics

## **Beyond Basic Matrix Factorization:**

# Extensions and Advanced Topics

## Beyond Basic Matrix Factorization:

- **Non-negative Matrix Factorization (NMF):** Interpretable factors

# Extensions and Advanced Topics

## Beyond Basic Matrix Factorization:

- **Non-negative Matrix Factorization (NMF):** Interpretable factors
- **Deep Matrix Factorization:** Neural networks for non-linear patterns

# Extensions and Advanced Topics

## Beyond Basic Matrix Factorization:

- **Non-negative Matrix Factorization (NMF):** Interpretable factors
- **Deep Matrix Factorization:** Neural networks for non-linear patterns
- **Factorization Machines:** Handle multi-way interactions

# Extensions and Advanced Topics

## Beyond Basic Matrix Factorization:

- **Non-negative Matrix Factorization (NMF):** Interpretable factors
- **Deep Matrix Factorization:** Neural networks for non-linear patterns
- **Factorization Machines:** Handle multi-way interactions
- **Variational Autoencoders:** Probabilistic approach to recommendations

# Extensions and Advanced Topics

## Beyond Basic Matrix Factorization:

- **Non-negative Matrix Factorization (NMF):** Interpretable factors
- **Deep Matrix Factorization:** Neural networks for non-linear patterns
- **Factorization Machines:** Handle multi-way interactions
- **Variational Autoencoders:** Probabilistic approach to recommendations
- **Graph Neural Networks:** Leverage user-item interaction graphs

# Extensions and Advanced Topics

## Beyond Basic Matrix Factorization:

- **Non-negative Matrix Factorization (NMF):** Interpretable factors
- **Deep Matrix Factorization:** Neural networks for non-linear patterns
- **Factorization Machines:** Handle multi-way interactions
- **Variational Autoencoders:** Probabilistic approach to recommendations
- **Graph Neural Networks:** Leverage user-item interaction graphs
- **Multi-armed Bandits:** Exploration vs exploitation in recommendations



# Extensions and Advanced Topics

## Beyond Basic Matrix Factorization:

- **Non-negative Matrix Factorization (NMF):** Interpretable factors
- **Deep Matrix Factorization:** Neural networks for non-linear patterns
- **Factorization Machines:** Handle multi-way interactions
- **Variational Autoencoders:** Probabilistic approach to recommendations
- **Graph Neural Networks:** Leverage user-item interaction graphs
- **Multi-armed Bandits:** Exploration vs exploitation in recommendations

# Extensions and Advanced Topics

## Beyond Basic Matrix Factorization:

- **Non-negative Matrix Factorization (NMF):** Interpretable factors
- **Deep Matrix Factorization:** Neural networks for non-linear patterns
- **Factorization Machines:** Handle multi-way interactions
- **Variational Autoencoders:** Probabilistic approach to recommendations
- **Graph Neural Networks:** Leverage user-item interaction graphs
- **Multi-armed Bandits:** Exploration vs exploitation in recommendations

## Applications Beyond Movies:

- E-commerce (Amazon, eBay)

# Extensions and Advanced Topics

## Beyond Basic Matrix Factorization:

- **Non-negative Matrix Factorization (NMF):** Interpretable factors
- **Deep Matrix Factorization:** Neural networks for non-linear patterns
- **Factorization Machines:** Handle multi-way interactions
- **Variational Autoencoders:** Probabilistic approach to recommendations
- **Graph Neural Networks:** Leverage user-item interaction graphs
- **Multi-armed Bandits:** Exploration vs exploitation in recommendations

## Applications Beyond Movies:

- E-commerce (Amazon, eBay)
- Music streaming (Spotify, Apple Music)

# Extensions and Advanced Topics

## Beyond Basic Matrix Factorization:

- **Non-negative Matrix Factorization (NMF):** Interpretable factors
- **Deep Matrix Factorization:** Neural networks for non-linear patterns
- **Factorization Machines:** Handle multi-way interactions
- **Variational Autoencoders:** Probabilistic approach to recommendations
- **Graph Neural Networks:** Leverage user-item interaction graphs
- **Multi-armed Bandits:** Exploration vs exploitation in recommendations

## Applications Beyond Movies:

- E-commerce (Amazon, eBay)
- Music streaming (Spotify, Apple Music)
- Social media (Facebook, LinkedIn)

# Extensions and Advanced Topics

## Beyond Basic Matrix Factorization:

- **Non-negative Matrix Factorization (NMF):** Interpretable factors
- **Deep Matrix Factorization:** Neural networks for non-linear patterns
- **Factorization Machines:** Handle multi-way interactions
- **Variational Autoencoders:** Probabilistic approach to recommendations
- **Graph Neural Networks:** Leverage user-item interaction graphs
- **Multi-armed Bandits:** Exploration vs exploitation in recommendations

## Applications Beyond Movies:

- E-commerce (Amazon, eBay)
- Music streaming (Spotify, Apple Music)
- Social media (Facebook, LinkedIn)

# Final Pop Quiz: Comprehensive Understanding

## Mastery Test

**True or False? Explain your reasoning:**

# Final Pop Quiz: Comprehensive Understanding

## Mastery Test

**True or False? Explain your reasoning:**

1. Matrix factorization can only work with explicit ratings

# Final Pop Quiz: Comprehensive Understanding

## Mastery Test

### **True or False? Explain your reasoning:**

1. Matrix factorization can only work with explicit ratings
2. ALS always converges to the global optimum



# Final Pop Quiz: Comprehensive Understanding

## Mastery Test

### **True or False? Explain your reasoning:**

1. Matrix factorization can only work with explicit ratings
2. ALS always converges to the global optimum
3. A rank-1 factorization means all users have identical preferences

# Final Pop Quiz: Comprehensive Understanding

## Mastery Test

### **True or False? Explain your reasoning:**

1. Matrix factorization can only work with explicit ratings
2. ALS always converges to the global optimum
3. A rank-1 factorization means all users have identical preferences
4. Adding regularization always improves recommendations

# Final Pop Quiz: Comprehensive Understanding

## Mastery Test

### **True or False? Explain your reasoning:**

1. Matrix factorization can only work with explicit ratings
2. ALS always converges to the global optimum
3. A rank-1 factorization means all users have identical preferences
4. Adding regularization always improves recommendations
5. SGD is better than ALS for all applications

# Final Pop Quiz: Comprehensive Understanding

## Mastery Test

### **True or False? Explain your reasoning:**

1. Matrix factorization can only work with explicit ratings
2. ALS always converges to the global optimum
3. A rank-1 factorization means all users have identical preferences
4. Adding regularization always improves recommendations
5. SGD is better than ALS for all applications

# Final Pop Quiz: Comprehensive Understanding

## Mastery Test

### True or False? Explain your reasoning:

1. Matrix factorization can only work with explicit ratings
2. ALS always converges to the global optimum
3. A rank-1 factorization means all users have identical preferences
4. Adding regularization always improves recommendations
5. SGD is better than ALS for all applications

### Answers:

1. **False** - Works with implicit feedback too (clicks, views)
2. **False** - Converges to local optimum (problem is