CH402 Capstone Project – Atmospheric Distillation of Crude Oil

Objectives

(1) Cadets design a process that separates a specified crude oil into light ends, light naphtha, heavy naphtha, kerosene, gas oils, and vacuum gas oil.
(2) Cadets develop realistic constraints for the maximum allowed sulfur and water content in refined products and implement these constraints in their design.
(3) Cadets revise their design to reduce or eliminate redundant equipment through consolidation of process steps.
(4) Cadets optimize the design to reduce overall energy consumption through integration of heat exchangers for energy recovery.
(5) Cadets will determine the number and diameter of distillation trays, the diameter and thickness of column shells, the size of the reflux drums, the heat transfer areas of the condensers and reboilers, pump capacities, and pipeline dimensions.
(6) Cadets develop a strategy for safe control of the process by identifying major control points and implementing key relief devices.
(7) Cadets will produce a table of purchased equipment including costs.
(8) Cadets will perform an economic analysis of the process based on PBP, ROI, NPW, and IRR (DCFR).
(9) Cadets will prepare a safety and environmental impact assessment of the process as well as a preliminary process specification and management of change proposal (PC/MOC).
(10) Cadets will produce a detailed design report for the project that meets specifications in Chapter 11 and includes research into regional political and economic impact on sustainability of the source crude oil.

Introduction

Crude oil is an extremely important raw material that forms over millions of years from the remains of plants and animals. This “fossil fuel” is pumped from the ground in oil fields located in the Middle East, West Africa, North and South America, Asia, as well as various offshore locations such as the Gulf of Mexico and the North Sea. It is then transported by pipeline, railroad, and ocean-going tanker ships to refineries all over the world, where it is converted into fuels and basic chemicals. The Energy Information Administration estimates that that 38% of the energy used in the United States comes from petroleum and its refined products.[1] Worldwide this percentage is 34%.[2] Furthermore, almost all synthetic chemicals used on a commercial scale originate from molecules derived from crude oil.

Crude oil is a mixture of many hundreds of hydrocarbon molecules.[3] The hydrocarbon molecules range in size from the smallest, methane, with one carbon atom, to large compounds containing 300 or more carbon atoms. The major fraction of these compounds are alkanes, such as n-butane and i-butane, n-pentane, n-octane, and so on. Most of the remaining hydrocarbons are either cyclic alkanes or aromatics. Only the simplest molecules are purified on a commercial scale. Generally, in a refining process, isolation of pure products is restricted to those compounds lighter than C7's. Most hydrocarbon molecules present in crude oil have been isolated but only under laboratory conditions. Because of the large number of molecules involved, refined products are characterized by boiling point ranges and not molecular structure. For example, a major product in a refinery is light naphtha, which would be identified as a "15 to 75°C cut." The light naphtha itself contains many molecules.

Not all compounds in crude oil are hydrocarbons. Small quantities of sulfur, nitrogen, and metals are also present. By far, the most important of these is sulfur. Sulfur is present in the form of hydrogen sulfide and organic compounds of sulfur. These organic compounds are present through the entire boiling range of the hydrocarbons in the crude. They are similar in structure to the hydrocarbons themselves, but with the addition of one or more sulfur atoms to the structure. The simplest of these is methyl mercaptan, which has a structure like methanol, but with the oxygen atom replaced by sulfur. The higher carbon-number ranges of these compounds are thiophenes, which are found mostly in the heavy residuum ranges, and disulfides, which are found in the middle distillate range of the crude oil. The sulfur from these heavier compounds can only be removed by converting the sulfur to H_2S in a hydrotreating process operating under severe conditions of temperature and pressure and in the presence of a suitable catalyst. The lighter sulfur compounds are usually removed by extraction with caustic soda or other proprietary solvents.

Organic chloride compounds are also present in crude oil. These are not removed as such, but the process equipment must be designed to withstand attack by HCl, specifically in the primary distillation processes. This protection is in the form of monel lining in the sections of the process most susceptible to chloride attack. Ammonia injection is also used to neutralize the HCl in those sections.

The most common metal impurities found in crude oils are nickel, vanadium, and sodium. These are not volatile and usually end up in the residuum or fuel oil products of the crude oil. These are typically not removed from the oil, and normally they are only a nuisance if they

affect further processing of the oil or if they are a deterrent to sales. For example, these metals are known to cause a reduction in catalyst life in the catalytic sections of the refinery, in which case they would need to be removed to the extent possible. As another example, high concentrations of nickel and vanadium are unacceptable in fuel oils used in the production of certain steels.

Although most hydrocarbons found in crude oil are alkanes, cyclic alkanes and aromatics, there is a fourth group of compounds also present. These are the unsaturated or “olefinic” hydrocarbons. They are not naturally present in any great quantities in most crude oils but are often produced in significant quantities during the processing of the crude oil to refined products. This occurs in those processes that subject the oil to high temperature for a relatively long period of time. Under these conditions, the saturated hydrocarbon molecules break down or “crack,” losing one or more of the atoms attached to quadrivalent carbon. The remaining atoms are rearranged to form unsaturated compounds. An example is the thermal cracking of n-butane to form ethane and ethene (ethylene):

$$\underset{\text{(n-butane)}}{CH_3\text{-}CH_2\text{-}CH_2\text{-}CH_3} + \text{heat} \rightarrow \underset{\text{(ethane)}}{CH_3\text{-}CH_3} + \underset{\text{(ethylene)}}{CH_2{=}CH_2}$$

Since crude oil is extracted from underground reservoirs in the oil field, it also contains water and suspended solids. The water content can vary greatly from field to field and may be present in large quantities if oil extraction is enhanced using water injection technology. Most of the water and suspended solids are separated at the field to minimize the amount that would otherwise need to be transported to refineries. However, there will always be residual amount of these unwanted impurities. Refiners deal with this by purchasing crude oil with a specification on the allowed content of water and suspended solids, and they will have process units that reduce the quantities to acceptable limits.[4]

Finally, methane is also present in oil field crude oil and can be as high as 65% of the material coming out of the well.[5] The vast majority of methane is removed in the field. As the crude oil emerges from the well, there is a significant decrease in pressure causing the dissolved gases to flash off. The gas is either collected for processing and sales or is flared in the field.[6] However, a residual amount of dissolved methane will always be present in the oil entering the refinery.

Although all crude oils contain the types of compounds and impurities described above, rarely are there two crude oils with the same characteristics. This is because crude oils from different

geographic locations contain different quantities of the various compounds and minerals described earlier. Crude oils produced in Nigeria, for example, contain high amounts of cyclic alkanes. On the other hand, crude oil from Venezuela has somewhat lower amounts of materials boiling below 350°C. The difference in the character of the various crudes enables refiners to improve their operation by selecting the best crude or crudes that meet their product marketing requirements.

To simplify this project, we will not consider chlorides, alkenes, metals, water, or suspended solids in the crude oil. The crude oil being processed in your design can be considered to have been "pretreated" to remove these components. The sulfur compounds will be modeled collectively as hydrogen sulfide only to simplify your design work. That is, mercaptans such as ethyl and methyl mercaptan are not present in the oil by assumption.

To model the crude oil, cadets will be provided with specific crude oil, specified by its name. Cadets will then use the published assay for their oil with CHEMCAD to calculate a list of "pseudo-components" from the boiling point curve in the assay. The output of this calculation will enable CHEMCAD model the fluid, including the fluid traffic through the process. Cadets will then use this "pseudo-fluid" to model and size the various equipment in the process, calculate heat duties, determine process economics, etc.

<u>Assignment Specifics</u>:

Each cadet team will be assigned one crude oil and design a process that separates 10,000 BPSD of the assigned crude oil into the fractions or "cuts" listed in Table 1. Your team is also required to separate sulfur and methane and/or ethane from the light ends.

As mentioned above, cadets will use CHEMCAD's *thermophysical* tools to create the "pseudocomponents" that model the properties of the crude oil. This is accomplished in "Thermophysical" section in CHEMCAD, in the "Petroleum Assay" section. A procedure with more specifics will be provided by the instructor. The idea is to step through the menus until you come to specific properties that you must enter that are taken from the published assays. CHEMCAD will calculate all other physical properties needed. A boiling point curve with experimental data for comparison must be included in your final report. More details are provided in the procedure.

In addition to the cuts specified in Table 1, you are also responsible for further processing the light ends into purified methane, ethane, and LPG. Purified propane and butane should be blended to produce

liquefied petroleum gas (LPG). Purified ethane and methane that result from producing LPG can be blended to produce fuel for the fired heaters as needed, or you may take a credit for these products in your economic analysis.

Table 1. Approximate carbon number and boiling range for products.		
Component	Composition	Normal Boiling Range
	(Carbon Number)	(°C, approximate[a])
Light ends[b]	C1 to C4	<15
Light Naphtha	C5 to C6	15 to 75
Heavy Naphtha	C6 to C12	75 to 165
Kerosene	C6 to C16	165 to 250
Gas oils (Diesel)	C12 to C20	250 to 345
Vacuum Gas Oil[c]	C20 and up	345 to +540
Notes: a: Ranges vary and specific ranges are found in the assays. b: Light ends include tail gas and liquid petroleum gas (LPG) c: Also known as reduced crude oil (RCO) or topped crude oil (TCO).		

Purified hydrogen sulfide is normally processed into sulfuric acid and sulfur, but a detailed design of that plant is not required for this project. However, hydrogen sulfide must be purified to the extent possible in a separate stream.

The light hydrocarbons in the “light-ends” of the crude oil must be entered manually into CHEMCAD before you enter the assay data. For this project, these components include methane, ethane, propane, i-butane, n-butane. The amounts of these compounds are found in the assay.

Water and hydrogen sulfide are not part of the light-ends but must also be entered manually. The water and H_2S can be entered as zero when creating the pseudo-components and later added to the feed in the amount specified for your crude oil.

Please be aware of the design heuristics in Appendix E of the Peters, Timmerhaus, and West textbook, especially pumps, heat exchangers, and distillation columns. Use of typical design conditions specified in these heuristics, especially for distillation columns, is strongly encouraged. You may also use heuristics for preliminary design of heat exchangers, subject to the comments below.

You are responsible to determine sufficient pipe pressure drops to size all pumps. You must also design all condensers, reflux drums and reboilers for each distillation column. You are also required to design any ancillary equipment such as fired heaters, dewatering vessels, etc. The 3-step design method is required for each heat exchanger. In the even that you cannot get the 3-step method to work, or as a preliminary design, you may assume that the heat transfer coefficient (U) for entry into CHEMCAD is 850 $W/(m^2 \cdot K)$ for all condensers and 1100 $W/(m^2 \cdot K)$ for all reboilers. Cooling water for the condensers is available at 5°C and 5 atm and must be returned to central facilities no higher than 65 °C. Reboilers are to be heated with steam, and saturated steam is available from an existing steam plant at pressures of 150, 790, or 3550 kPa. All utilities available in the colorful worksheet may be assumed to be available for use in your design.

You must complete an economic analysis using the "Economics" tools in CHEMCAD like the analysis in design problem 5. The timeline for your evaluation is 10 years with MACRS depreciation and with 1% inflation. You must evaluate the return on investment (ROI), payback period (PBP), net present worth (NPW) and internal rate of return (IRR) for the project. A table showing a summary of purchased equipment costs is required and must be included in your report (see DP3 for a simplified example). All equipment pricing must be in May 2026. Pricing of raw materials and finished products can be obtained from current internet sources and must be documented carefully. Pricing of utilities is available in the colorful worksheet.

Costs for raw materials and products are determined as follows: Costs of products (LPG, naphtha, and gas oil) should be 90% of current market values (since products are not quite finished) at the refinery location. Crude oil (raw material) is determined from international market values and must include transportation costs. Transportation costs by sea (tanker) are $1.00 per barrel per 1000 miles. Railroad shipping costs are $5.50 per barrel per 1000 miles. Pipeline shipping costs are $0.75 per barrel per 1000 miles.

You must complete a socio-economic analysis of the geographic region from which your oil is supplied. Your socio-economic analysis must also include any issues associated with the shipping route required to move your crude oil from the source region to the plant location. This may include but is not limited to factors such as political or civil unrest, environmental, or security that might impact sustainability.

Process Safety: You must prepare a safety and environmental impact assessment of the process as well as a preliminary process specification

and management of change proposal (PC/MOC). The PC/MOC audit form is published separately. The impact assessment will include LD50/LC50 for human toxicity, UFL/LFL for flammability limits, flash point, autoignition temperature, and NFPA fire diamond entries for each feed and product stream. The assessment will also include a narrative section describing impact of the assessment on process operations. You will also create a CHEMCAD environmental report along with discussion of meaning of report contents. Complete a P&ID for the final design, along with pressure relief valve locations and sizing.

Finally, once your base design is complete, you must complete one of the two research projects described below. The results of your research will be included in your final report.

Research Topic 1: Learn as much as you can about "dieseline" and modify your design to produce 1,000 BPSD. Incorporate any design changes and changes to product flow rates into your economic analysis and submit this as a separate analysis.

Research Topic 2: Learn as much as you can about Canadian bitumen and modify your design to process 100,000 BPSD as a feed to your process. Incorporate any design changes and changes to product flow rate into your economic analysis.

Deliverables:

You are responsible for producing a design report for this project. Details are published separately in the "Deliverables" document. Electronic copy of your final files must be submitted in CANVAS, to include a pdf of your final report, and any support work documents such as Mathematica files, excel spreadsheets, and CHEMCAD files.

Grading, Grading Rubrics, and IPRs:

Grading for this project is rubric based. A grading rubric has been linked to the course web site. The rubric contains 15 grading components (15 columns). To obtain a good score, you must fully understand each column in the rubric. You are strongly encouraged to develop a detailed plan of attack for each column, to review your plan with your instructor, and to maintain frequent communication with him regarding any changes to your plan during the development of your project. This will assist you in preparing for the IPRs. For IPR grades, your instructor will assess your progress on the rubric against a reasonable level of progress (instructor expectation) at the time of the IPR, and your grade will reflect that progress.

Due Dates:

The completed project is due NLT 2359 Sunday 10 May 2026. This includes a single compiled pdf report as well as completed electronic files saved in SharePoint. In-Progress Reviews (IPRs) are by appointment with your instructor. IPR1 is due no later than 2359 on 25 March and IPR2 is due no later than 2359 on 22 April. You are encouraged to meet with your instructor outside of normal class hours for a focused appointment to ensure you are making adequate progress.

References Used in This Document

1. "Primary Energy Consumption by Source and Sector, 2024," https://www.eia.gov/energyexplained/us-energy-facts/, accessed 1 March 2026.
2. BP Statistical Review of World Energy, 2019, 68th Edition, p. 9. https://www.bp.com/content/dam/bp/business-sites/en/global/corporate/pdfs/energy-economics/statistical-review/bp-stats-review-2020-full-report.pdf, accessed 1 March 2026.
3. D.S.J. Jones and P.R. Pujado, Handbook of Petroleum Processing, Dordrecht, The Netherlands: Springer Science and Business Media, 2006, ISBN 978-1-4020-2820-5, pp. 1-6.
4. http://en.wikipedia.org/wiki/Basic_sediment_and_water, accessed 8 March 2026.
5. P.J. Daniel, S. Smuk, R. Taherian, J.J. Pop, Patent Number WO2010059601 (US 20120000279), May 27, 2010, Table 5.
6. M. Sunmoni, "Gas Flaring in Nigeria," The environmentalist, http://ecoremediation.blogspot.com/2012/06/gas-flaring-in-nigeria-what-are-harmful.html, accessed 8 March 2026.

Other Useful References

1. Glossary of Petroleum Industry Common Terms and Symbols, http://www.alken-murray.com/fuel-glossary.htm, accessed 8 March 2026.
2. Online Unit Converter, http://www.onlineconversion.com/, accessed 8 March 2026. Contains useful crude oil conversion factors.
3. Encyclopedia of Chemical Processing, USMA Library circulating books, call numbers TP9.E648 2006 and TP151.C573 1993.
4. Ullmann's Encyclopedia of Industrial Chemistry http://onlinelibrary.wiley.com/book/10.1002/14356007, accessed 8 March 2026.
5. Kirk-Othmer Encyclopedia of Chemical Technology, https://onlinelibrary.wiley.com/doi/book/10.1002/0471238961 , accessed 8 March 2026.

Checklist for Final Submission

___ Determination of the number of separation steps required

___ For each distillation column, cadets must determine
- number of trays
- tray diameter
- column shell thickness
- column height

___ For each distillation column, cadets must separately determine
- Condenser area given heat transfer coefficient
- Reboiler area given heat transfer coefficient
- Reflux drum size
- Pump capacities for any required pumps

___ Integrated process flow diagram that includes separate working units for each unit including:
- Column
- Condenser
- Reflux drum
- Reboiler
- Pumps
- Pipes

___ Include *properly formatted* CHEMCAD reports for each column:
- Each column and its supporting equipment must be in a separate appendix (one appendix per column).
- CHEMCAD spec sheets for condenser, reboiler, reflux drum, distillate pump, reflux pump, and bottom product pump
- Heat exchanger spec sheets are "tabulated data."
- Column Profile.

___ Safety and Environmental Impact Assessment in an appendix:
- CHEMCAD environmental report along with discussion of meaning of report contents
- NFPA 704 fire diamond entries for each stream
- UFL and LFL for each stream
- Completed PS/MOC Audit

___ Written design report consistent with the "Deliverables" document:
- See Chapter 11 for additional details, especially Table 11-1.
- Letter of transmittal addressed to Professor Andrew Biaglow, Department of Chemistry and Life Science, U.S. Military Academy, West Point, NY 10996