



ESPE

UNIVERSIDAD DE LAS FUERZAS ARMADAS
INNOVACIÓN PARA LA EXCELENCIA

TRANSPORTISTAS URIS

- Consultar guías por cliente

HTTP Method:	GET
URI:	http://localhost:8080/TransporteCarga/webresources/Guides/orders/clients/{IDclient}
Description:	The Uri provides the service to be able to access the guides through the customer, which in this case we use the ID as the input parameter and this will display all the guides of a client
Request Parameters:	ID client Choose method to test: <input type="text" value="GET(application/json)"/> <input type="button" value="Test"/> IDclient: <input type="text" value="0604188086"/> <input type="button" value="x"/>
JSON Response:	<pre>[{"cedulaCliente":"0604188086","cedulaTransportista":"0602175143","codigoProducto":"TOTAL","destino":"Quito","direccion":"Item 1","estadoReserva":"ANULADO","fecha":"10-6-2019","numero":1,"valorEnvio":"1.0"}, {"cedulaCliente":"0604188086","cedulaTransportista":"0650026230","codigoProducto":"TOTAL","destino":"Quito","direccion":"Item 1","estadoReserva":"ANULADO","fecha":"10-6-2019","numero":2,"valorEnvio":"3.0"}]</pre>
Status:	200 (OK)
Json file:	The response will show a json file with all the guides of a certain client

- Consultar guías por fecha

HTTP Method:	GET
URI:	http://localhost:8080/TransporteCarga/webresources/Guides/orders/dates/{date}
Description:	The Uri provides the service to be able to access the guides through the customer, which in this case we use the ID as the input parameter and this will display all the guides of a client
Request Parameters:	date Choose method to test: <input type="text" value="GET(application/json)"/> <input type="button" value="Test"/> date: <input type="text" value="10-6-2019"/>



ESPE

UNIVERSIDAD DE LAS FUERZAS ARMADAS
INNOVACIÓN PARA LA EXCELENCIA

JSON Response:	<pre>[{"cedulaCliente":"0604188086","cedulaTransportista":"0602175143","codigoProducto":"TOTAL","destino":"Quito","direccion":"Item 1","estadoReserva":"ANULADO","fecha":"10-6-2019","numero":1,"valorEnvio":"1.0"}, {"cedulaCliente":"0604188086","cedulaTransportista":"0650026230","codigoProducto":"TOTAL","destino":"Quito","direccion":"Item 1","estadoReserva":"ANULADO","fecha":"10-6-2019","numero":2,"valorEnvio":"3.0"}, {"cedulaCliente":"1718911488","cedulaTransportista":"1714786629","codigoProducto":"TOTAL","destino":"Quito","direccion":"valle","fecha":"6-2019","numero":3,"valorEnvio":"1.0"}]</pre>
Status:	200 (OK)
Json file:	The response will show a json file with all the guides of a certain date

- Consultar guías por transportistas

HTTP Method:	GET
URI:	http://localhost:8080/TransporteCarga/webresources/Guides/orders/carrier/{IDcarrier}
Description:	The Uri provides the service to be able to access the guides through the carrier, which in this case we use the ID as the input parameter and this will display all the guides of a carrier
Request Parameters:	<div>ID carrier</div> <div>Choose method to test: <input type="text" value="GET(application/json)"/> <input type="button" value="Test"/></div> <div>IDcarrier: <input type="text" value="0602175143"/></div>
JSON Response:	<pre>[{"cedulaCliente":"0604188086","cedulaTransportista":"0602175143","codigoProducto":"TOTAL","destino":"Quito","direccion":"Item 1","estadoReserva":"ANULADO","fecha":"10-6-2019","numero":1,"valorEnvio":"1.0"}]</pre>
Status:	200 (OK)
Json file:	The response will show a json file with all the guides of a certain carrier

- Listar todos los transportistas

HTTP Method:	GET
URI:	http://localhost:8080/TransporteCarga/webresources/Carriers
Description:	The Uri provides the service to be able to access all the carriers, it will show the ID, name, address, telephone, email, car plate, zone.
Request Parameters:	<div>None</div> <div>Choose method to test: <input type="text" value="GET(application/json)"/> <input type="button" value="Test"/></div>



ESPE

UNIVERSIDAD DE LAS FUERZAS ARMADAS
INNOVACIÓN PARA LA EXCELENCIA

JSON Response:	<pre>[{"correo":"mariochavezr@hotmail.com","direccion":"Quito","identificacion":"0602175143","nombre":"Nicole Chavez","placa":"qwe1234","telefono":"0998384984","zona":"valle"}, {"correo":"d@hotmail.com","direccion":"Quito","identificacion":"0650026230","nombre":"Diego","placa":"PQW1234","telefono":"0998573721","zona":"Valle de los Chillos"}, {"correo":"b@hotmail.com","direccion":"Quito","identificacion":"1714786629","nombre":"Nicolee","placa":"Valle de los Chillos","telefono":"0998573713","zona":"Quito"}]</pre>
Status:	200 (OK)
Json file:	The response will show a json file with all the carriers

- Listar todos los Zonas

HTTP Method:	GET
URI:	http://localhost:8080/TransporteCarga/webresources/Zone/zones
Description:	The Uri provides the service to be able to access all the zones, it will show the ID, name, city.
Request Parameters:	None Choose method to test: <input type="text" value="GET(application/json)"/> <input type="button" value="Test"/>
JSON Response:	<pre>[{"ciudad":"Quito","codigo":"Z282","nombre":"valle"}, {"ciudad":"Quito","codigo":"Z317","nombre":"norte"}, {"ciudad":"Quito","codigo":"Z452","nombre":"sur"}, {"ciudad":"Guayaquil","codigo":"Z782","nombre":"alboradaUno"}]</pre>
Status:	200 (OK)
Json file:	The response will show a json file with all the zones

- Crear guía

HTTP Method:	POST
URI:	http://localhost:8080/TransporteCarga/webresources/Guides/createGuide
Description:	The Uri provides the service to create a zone, in this case we use a body that will be sent next to the uri to create a zone.
Request Parameters:	Body: <pre>{"cedulaCliente":"0604188086","cedulaTransportista":"0602175143","codigoProducto":"PR761","destino":"Quito","direccion":"Item 1","estadoReserva":"ACTIVO","fecha":"10-6-2019","numero":4,"valorEnvio":"1.0"}</pre> <pre>{"cedulaCliente":"0604188086","cedulaTransportista":"0602175143","codigoProducto":"TOTAL","destino":"Quito","direccion":"Item 1","estadoReserva":"ACTIVO","fecha":"10-6-2019","numero":4,"valorEnvio":"1.0"}</pre>



ESPE

UNIVERSIDAD DE LAS FUERZAS ARMADAS
INNOVACIÓN PARA LA EXCELENCIA

JSON Response:	<div> <div>Custom Request Headers</div> <div>Status: 204 (No Content)</div> <div>Response:</div> <div> <div>Tabular View</div> <div>Raw View</div> <div>Sub-Resource</div> <div>Headers</div> <div>Http Monitor</div> </div> <div>No content in response</div> </div>
Status:	204 (No content)
Json file:	The response will show a no content in response.

- Consultar guía

HTTP Method:	GET
URI:	http://localhost:8080/TransporteCarga/webresources/Guides/guide/{number}
Description:	The Uri provides the service to access the guides through the order number, which in this case we use as an input parameter and this establishes all the guides of a number.
Request Parameters:	Number of guide Choose method to test: <input type="text" value="GET(application/json)"/> <input type="button" value="Test"/> number: <input type="text" value="4"/>
JSON Response:	Status: 200 (OK) Response: <div> <div>Tabular View</div> <div>Raw View</div> <div>Sub-Resource</div> <div>Headers</div> <div>Http Monitor</div> </div> <pre>[{"cedulaCliente":"0604188086","cedulaTransportista":"0602175143","codigoProducto":"PR761","destino":"Quito","direccion":"Item 1","estadoReserva":"ACTIVO","fecha":"10-6-2019","numero":4,"valorEnvio":"1.0"}, {"cedulaCliente":"0604188086","cedulaTransportista":"0602175143","codigoProducto":"TOTAL","destino":"Quito","direccion":"Item 1","estadoReserva":"ACTIVO","fecha":"10-6-2019","numero":4,"valorEnvio":"1.0"}]</pre>
Status:	200 (OK)
Json file:	The response will show a json file with all the guides of a number of guide.

- Eliminar guía

HTTP Method:	DELETE
URI:	http://localhost:8080/TransporteCarga/webresources/Guides/deleteGuide/{byNumber}
Description:	The Uri provides the service to remove all guides related to a guide number, in this case we use the guide number as an input parameter and this activates a search of each record that contains that number and will delete it.



ESPE

UNIVERSIDAD DE LAS FUERZAS ARMADAS
INNOVACIÓN PARA LA EXCELENCIA

Request Parameters:	<p>Number of guide</p> <p>[-] Request</p> <p>Method <input type="text" value="DELETE"/> URL <input type="text" value="http://localhost:8080/TransporteCarga/webresources/Guides/deleteGuide/4"/></p>
JSON Response:	<p>[-] Response</p> <p>Headers Response</p> <pre> Status Code : 204 No Content date : Wed, 06 Nov 2019 11:56:23 GMT server : Payara Server 4.1.2.174 #badassfish x-frame-options : SAMEORIGIN x-powered-by : Servlet/3.1 JSP/2.3 (Payara Server 4.1.2.174 #badassfish Java/Oracle Corporation/1.8) </pre>
Status:	204 (No content)
Json file:	The response will show a no content in response.

- Anular Guía

HTTP Method:	PUT
URI:	http://localhost:8080/TransporteCarga/webresources/Guides/updateGuide
Description:	The Uri provides the service for all records of a certain guide, using the number of the guide that is specified as a parameter within the body sent will activate the method that extracts the guide number and modifies the status to 'ANULADO' of each record.
Request Parameters:	<p>Body:</p> <p>Choose method to test: <input type="text" value="PUT(application/json)"/> <input type="button" value="Test"/></p> <p>Content: <pre>{"cedulaCliente":"1718911488","cedulaTransportista":"1714786629","codigoProducto":"PR761","destino":"Quito","direccion":"valle","estadoReserva":"ACTIVO","fecha":"10-6-2019","numero":3,"valorEnvio":"1.0"}</pre></p>



ESPE

UNIVERSIDAD DE LAS FUERZAS ARMADAS
INNOVACIÓN PARA LA EXCELENCIA

JSON Response:	<div>Custom Request Headers</div> <div>Status: 204 (No Content)</div> <div>Response:</div> <div>Tabular ViewRaw ViewSt</div> <div>No content in response</div>
Status:	204 (No content)
Json file:	The response will show a no content in response.

- Crear zona

HTTP Method:	POST
URI:	http://localhost:8080/TransporteCarga/webresources/Zone/createZone
Description:	The Uri provides the service to create a zone, in this case we use a body that will be sent next to the uri to create a zone.
Request Parameters:	<div>Body:</div> <div>{"ciudad":"Quito","codigo":"Z318","nombre":"villanuez"}</div> <div>Choose method to test: POST(application/json) Test</div> <div>Content: {"ciudad":"Quito","codigo":"Z318","nombre":"villanuez"}</div>
JSON Response:	<div>Status: 204 (No Content)</div> <div>Response:</div> <div>Tabular ViewRaw View</div> <div>No content in response</div>
Status:	204 (No content)
Json file:	The response will show a no content in response.

- Eliminar zona

HTTP Method:	DELETE
URI:	http://localhost:8080/TransporteCarga/webresources/Zone/deleteZone/{byCode}



ESPE

UNIVERSIDAD DE LAS FUERZAS ARMADAS
INNOVACIÓN PARA LA EXCELENCIA

Description:	The Uri provides the service to remove a zone related to its zone number, which will be sent as an input parameter and this activates a search of each record containing that number and will delete it.
Request Parameters:	<p>Code</p> <p>[-] Request</p> <p>Method <input type="text" value="DELETE"/> URL <input type="text" value="http://localhost:8080/TransporteCarga/webresources/Zone/deleteZone/Z318"/></p>
JSON Response:	<p>[-] Response</p> <p>Headers Response</p> <pre> Status Code : 204 No Content date : Wed, 06 Nov 2019 12:06:09 GMT server : Payara Server 4.1.2.174 #badassfish x-frame-options : SAMEORIGIN x-powered-by : Servlet/3.1 JSP/2.3 (Payara Server 4.1.2.174 #badassfish Java/Oracle Corporation/1.8) </pre>
Status:	204 (No content)
Json file:	The response will show a no content in response.

- Mostrar clientes

HTTP Method	GET
URI	http://localhost:8080/TransporteCarga/webresources/Clients
Description:	The Uri provides the service to access the client through the order number, which in this case we use as an input parameter and this establishes all the client of a number.
Request Parameters:	ID
JSON Response:	
Status:	200 (ok)
Json file	The response will show a json file with all the guides of a number of guide

- Eliminar cliente



ESPE

UNIVERSIDAD DE LAS FUERZAS ARMADAS
INNOVACIÓN PARA LA EXCELENCIA

HTTP Method:	DELETE
URI:	http://localhost:8080/TransporteCarga/webresources/Clients/deleteClient/{byNumber}
Description:	The Uri provides the service to remove a client related to its client number, which will be sent as an input parameter and this activates a search of each record containing that number and will delete it.
Request Parameters:	Code
JSON Response:	<div> <div>[-] Response</div> <div> <div>Headers</div> <div>Response</div> </div> <div> <div>Status Code</div> <div>date</div> <div>server</div> <div>x-frame-options</div> <div>x-powered-by</div> </div> <div> <div>: 204 No Content</div> <div>: Wed, 06 Nov 2019 12:06:09 GMT</div> <div>: Payara Server 4.1.2.174 #badassfish</div> <div>: SAMEORIGIN</div> <div>: Servlet/3.1 JSP/2.3 (Payara Server 4.1.2.174 #badassfish Java/Oracle Corporation/1.8)</div> </div> </div>
Status:	204 (No content)
Json file:	The response will show a no content in response.

)

- Crear zona

HTTP Method:	POST
URI:	http://localhost:8080/TransporteCarga/webresources/Clients/createClient
Description:	The Uri provides the service to create a client, in this case we use a body that will be sent next to the uri to create a zone.
Request Parameters:	<div> <div>Choose method to test: POST(application/json) ▼</div> <div>Test</div> </div> <div> <div>Body:</div> <div>Content: {"ciudad":"Quito","codigo":"Z318","nombre":"villanuez"}</div> </div>



ESPE

UNIVERSIDAD DE LAS FUERZAS ARMADAS
INNOVACIÓN PARA LA EXCELENCIA

JSON Response:	Status: 204 (No Content) Response: <div>Tabular View Raw View</div> <div>No content in response</div>
Status:	204 (No content)
Json file:	The response will show a no content in response.

)

Modificar cliente

HTTP Method:	PUT
URI:	http://localhost:8080/TransporteCarga/webresources/Clients/updateClient
Description:	The Uri provides the service for all records of a certain client
Request Parameters:	Body: <div>Choose method to test: PUT(application/json) Test</div> <div>Content: {"cedulaCliente":"1718911488","cedulaTransportista":"1714786629","codigoProducto":"PR761","destino":"Quito","direccion":"valle","estadoReserva":"ACTIVO","fecha":"10-6-2019","numero":3,"valorEnvio":1.0}</div>
JSON Response:	<div>Custom Request Headers</div> <div>Status: 204 (No Content) Response: <div>Tabular View Raw View St</div><div>No content in response</div></div>
Status:	204 (No content)
Json file:	The response will show a no content in response.