

# Satisfiability Modulo Theories

## Lezione 2 - An Eager Approach: Solving Bit-Vectors

(slides revision: Saturday 14<sup>th</sup> March, 2015, 11:46)

Roberto Bruttomesso

Seminario di Logica Matematica  
(Corso Prof. Silvio Ghilardi)

27 Ottobre 2011



Copyright (C) R. Bruttomesso  
Riproduzione vietata

# Recall from last lecture ...


Approaches to solve SMT formulæ are based on the observation that SMT can be **reduced** to SAT, i.e., the purely Boolean Satisfiability Problem



Copyright (C) R. Bruttomesso  
Riproduzione vietata

# Recall from last lecture ...

Approaches to solve SMT formulæ are based on the observation that SMT can be **reduced** to SAT, i.e., the purely Boolean Satisfiability Problem



Copyright (C) R. Bruttomesso  
Riproduzione vietata

## 1 Bit-Vectors

- Syntax
- Semantic
- Examples

## 2 Solving Bit-Vectors

- Bit-Blasting
- Simplifications



# Introduction

Bit-Vectors are extremely useful data structures, used to symbolically represent hardware and software constructs (see later)



Copyright (C) R. Bruttomesso  
Riproduzione vietata

# Introduction

Bit-Vectors are extremely useful data structures, used to symbolically represent hardware and software constructs (see later)

The world of Bit-Vectors is a **finite** world, i.e., with Bit-Vectors it is not possible to represent/handle arbitrarily large numbers



Copyright (C) R. Bruttomesso  
Riproduzione vietata

# Introduction

Bit-Vectors are extremely useful data structures, used to symbolically represent hardware and software constructs (see later)

The world of Bit-Vectors is a **finite** world, i.e., with Bit-Vectors it is not possible to represent/handle arbitrarily large numbers

Indeed, when speaking about Bit-Vectors we always associate a **width** (which is usually a power of 2, often 32 or 64)



Copyright (C) R. Bruttomesso  
Riproduzione vietata

# Introduction

Bit-Vectors are extremely useful data structures, used to symbolically represent hardware and software constructs (see later)

The world of Bit-Vectors is a **finite** world, i.e., with Bit-Vectors it is not possible to represent/handle arbitrarily large numbers

Indeed, when speaking about Bit-Vectors we always associate a **width** (which is usually a power of 2, often 32 or 64)

The width specifies the (maximum) **number of bits** used to represent variables and terms



Copyright (C) R. Bruttomesso  
Riproduzione vietata



# Introduction

Bit-Vectors are extremely useful data structures, used to symbolically represent hardware and software constructs (see later)

The world of Bit-Vectors is a **finite** world, i.e., with Bit-Vectors it is not possible to represent/handle arbitrarily large numbers

Indeed, when speaking about Bit-Vectors we always associate a **width** (which is usually a power of 2, often 32 or 64)

The width specifies the (maximum) **number of bits** used to represent variables and terms



Bit-Vector formulæ are mathematically characterized by the theory of Bit-Vectors  $\mathcal{BV}$



Copyright (C) R. Bruttomesso  
Riproduzione vietata


# Bit-Vectors

A bit-vector is an array of bits



# Bit-Vectors

A bit-vector is an array of bits




Selection (or Extraction):  $a_{[3]}[1 : 0]$



# Bit-Vectors

A bit-vector is an array of bits



Selection (or Extraction):  $a_{[3]}[1 : 0]$



Notice that


- $a_{[n]}[i : j]$  returns a Bit-Vector of width  $i - j + 1$  ( $0 \leq j \leq i \leq n - 1$ )



Copyright (C) R. Bruttomesso  
Riproduzione vietata

# Bit-Vectors

A bit-vector is an array of bits



Selection (or Extraction):  $a_{[3]}[1 : 0]$



Notice that


- $a_{[n]}[i : j]$  returns a Bit-Vector of width  $i - j + 1$  ( $0 \leq j \leq i \leq n - 1$ )
- $a_{[n]}[n - 1 : 0]$



Copyright (C) R. Bruttomesso  
Riproduzione vietata

# Bit-Vectors

A bit-vector is an array of bits



Selection (or Extraction):  $a_{[3]}[1 : 0]$



Notice that


- $a_{[n]}[i : j]$  returns a Bit-Vector of width  $i - j + 1$  ( $0 \leq j \leq i \leq n - 1$ )
- $a_{[n]}[n - 1 : 0] = a_{[n]}$



Copyright (C) R. Bruttomesso  
Riproduzione vietata

# Bit-Vectors

A bit-vector is an array of bits



Selection (or Extraction):  $a_{[3]}[1 : 0]$



Notice that


- $a_{[n]}[i : j]$  returns a Bit-Vector of width  $i - j + 1$  ( $0 \leq j \leq i \leq n - 1$ )
- $a_{[n]}[n - 1 : 0] = a_{[n]}$
- Selection has precedence over any other operator




Copyright (C) R. Bruttomesso  
Riproduzione vietata

# Bit-Vectors

A bit-vector is an array of bits




Concatenation  $a_{[3]} :: b_{[3]}$






# Bit-Vectors

A bit-vector is an array of bits



Concatenation  $a_{[3]} :: b_{[3]}$




Notice that

- $a_{[n]} :: b_{[m]}$  returns a Bit-Vector of width  $n + m$




# Bit-Vectors

A bit-vector is an array of bits



Concatenation  $a_{[3]} :: b_{[3]}$




Notice that

- $a_{[n]} :: b_{[m]}$  returns a Bit-Vector of width  $n + m$
- $a_{[n]}[n - 1 : i] :: a_{[n]}[i - 1 : 0]$




# Bit-Vectors

A bit-vector is an array of bits



Concatenation  $a_{[3]} :: b_{[3]}$




Notice that

- $a_{[n]} :: b_{[m]}$  returns a Bit-Vector of width  $n + m$
- $a_{[n]}[n - 1 : i] :: a_{[n]}[i - 1 : 0] = a_{[n]}[n - 1 : 0]$




# Bit-Vectors

A bit-vector is an array of bits



Concatenation  $a_{[3]} :: b_{[3]}$




Notice that

- $a_{[n]} :: b_{[m]}$  returns a Bit-Vector of width  $n + m$
- $a_{[n]}[n - 1 : i] :: a_{[n]}[i - 1 : 0] = a_{[n]}[n - 1 : 0] = a_{[n]}$




# Bit-Vectors

A bit-vector is an array of bits




Arithmetic  $a_{[3]} + b_{[3]}$




# Bit-Vectors

A bit-vector is an array of bits



Arithmetic  $a_{[3]} + b_{[3]}$



Notice that


- To be precise, we should have written  $a_{[3]} +_{[3]} b_{[3]}$  (widths must be the same)
- Semantic is that of **modular** arithmetic




Copyright (C) R. Bruttomesso  
Riproduzione vietata

# Bit-Vectors

A bit-vector is an array of bits




Bitwise  $a_{[3]}$  **AND**  $b_{[3]}$




Copyright (C) R. Bruttomesso  
Riproduzione vietata

# Bit-Vectors

A bit-vector is an array of bits



Bitwise  $a_{[3]}$  **AND**  $b_{[3]}$



Notice that

- Again, to be precise, we should have written  $a_{[3]}$  **AND**  $_{[3]}b_{[3]}$  (widths must be the same)
- Used to compute bit-mask operations





# A (non-exhaustive) list of operators and predicates

Each Bit-Vector term of width  $n$ , is associated with a sort  $BV_{[n]}$  ( $n \geq 1$ )



Copyright (C) R. Bruttomesso  
Riproduzione vietata

# A (non-exhaustive) list of operators and predicates

Each Bit-Vector term of width  $n$ , is associated with a sort  $BV[n]$  ( $n \geq 1$ )

Name	Symb	Type	Signature
Selection	$-[i : j]$	Core	$BV[n] \rightarrow BV[i-j+1]$
Concatenation	$::$		$BV[n] \times BV[m] \rightarrow BV[n+m]$
Addition	$+$	Arith.	$BV[n] \times BV[n] \rightarrow BV[n]$
Subtraction	$-$		$BV[n] \times BV[n] \rightarrow BV[n]$
Multiplication	$*$		$BV[n] \times BV[n] \rightarrow BV[n]$
Less than (signed)	$<_s$		$BV[n] \times BV[n] \rightarrow Bool$
Less than (unsigned)	$<_u$		$BV[n] \times BV[n] \rightarrow Bool$
Bitwise and	<b>AND</b>	Bitwise	$BV[n] \times BV[n] \rightarrow BV[n]$
Bitwise or	<b>OR</b>		$BV[n] \times BV[n] \rightarrow BV[n]$
Bitwise not	<b>NOT</b> _		$BV[n] \rightarrow BV[n]$



# A (non-exhaustive) list of operators and predicates

Each Bit-Vector term of width  $n$ , is associated with a sort  $BV[n]$  ( $n \geq 1$ )

Name	Symb	Type	Signature
Selection	$-[i : j]$	Core	$BV[n] \rightarrow BV[i-j+1]$
Concatenation	$::$		$BV[n] \times BV[m] \rightarrow BV[n+m]$
Addition	$+$	Arith.	$BV[n] \times BV[n] \rightarrow BV[n]$
Subtraction	$-$		$BV[n] \times BV[n] \rightarrow BV[n]$
Multiplication	$*$		$BV[n] \times BV[n] \rightarrow BV[n]$
Less than (signed)	$<_s$		$BV[n] \times BV[n] \rightarrow Bool$
Less than (unsigned)	$<_u$		$BV[n] \times BV[n] \rightarrow Bool$
Bitwise and	<b>AND</b>	Bitwise	$BV[n] \times BV[n] \rightarrow BV[n]$
Bitwise or	<b>OR</b>		$BV[n] \times BV[n] \rightarrow BV[n]$
Bitwise not	<b>NOT</b> _		$BV[n] \rightarrow BV[n]$

Moreover, we have constants, e.g.,  $101101_{[6]}$

# Bit-Vector semantic

Each sort  $\mathbf{BV}_{[n]}$  is associated with a domain  $D_n = \{0, 1, \dots, 2^n - 1\}$



Copyright (C) R. Bruttomesso  
Riproduzione vietata

# Bit-Vector semantic

Each sort  $\mathbf{BV}_{[n]}$  is associated with a domain  $D_n = \{0, 1, \dots, 2^{n-1}\}$

For example  $\mathbf{BV}_{[4]}$  is associated with  $D_4 = \{0, 1, \dots, 15\}$



Copyright (C) R. Bruttomesso  
Riproduzione vietata

# Bit-Vector semantic

Each sort  $\mathbf{BV}_{[n]}$  is associated with a domain  $D_n = \{0, 1, \dots, 2^{n-1}\}$

For example  $\mathbf{BV}_{[4]}$  is associated with  $D_4 = \{0, 1, \dots, 15\}$

As usual, the semantic for the other terms depends on a particular **assignment** to the variables



Copyright (C) R. Bruttomesso  
Riproduzione vietata

# Bit-Vector semantic

Each sort  $\mathbf{BV}_{[n]}$  is associated with a domain  $D_n = \{0, 1, \dots, 2^{n-1}\}$   
For example  $\mathbf{BV}_{[4]}$  is associated with  $D_4 = \{0, 1, \dots, 15\}$

As usual, the semantic for the other terms depends on a particular **assignment** to the variables

Each variable  $x_{[n]}$  is associated with a function  $\llbracket x_{[n]} \rrbracket$  of type  $D_n \rightarrow \{0, 1\}$




# Bit-Vector semantic

Each sort  $\mathbf{BV}_{[n]}$  is associated with a domain  $D_n = \{0, 1, \dots, 2^{n-1}\}$

For example  $\mathbf{BV}_{[4]}$  is associated with  $D_4 = \{0, 1, \dots, 15\}$

As usual, the semantic for the other terms depends on a particular **assignment** to the variables

Each variable  $x_{[n]}$  is associated with a function  $\llbracket x_{[n]} \rrbracket$  of type  $D_n \rightarrow \{0, 1\}$






# Bit-Vector semantic

Each sort  $\mathbf{BV}_{[n]}$  is associated with a domain  $D_n = \{0, 1, \dots, 2^{n-1}\}$

For example  $\mathbf{BV}_{[4]}$  is associated with  $D_4 = \{0, 1, \dots, 15\}$

As usual, the semantic for the other terms depends on a particular **assignment** to the variables

Each variable  $x_{[n]}$  is associated with a function  $\llbracket x_{[n]} \rrbracket$  of type  $D_n \rightarrow \{0, 1\}$



$nat_n(-)$  is a helper meta-function, to facilitate the presentation



$$\llbracket c_{[n]} \rrbracket := \lambda x \in [0, n-1]. \begin{cases} 0 & \text{if the } x\text{-th bit is 0} \\ 1 & \text{otherwise} \end{cases}$$

$$\llbracket t_{[l]} :: s_{[k]} \rrbracket := \lambda x \in [0, \dots, l+k-1]. \begin{cases} \llbracket s_{[n]} \rrbracket(x) & \text{if } x < l \\ \llbracket t_{[n]} \rrbracket(x-l) & \text{otherwise} \end{cases}$$

$$\llbracket t_{[n]}[i:j] \rrbracket := \lambda x \in [0, i-j+1]. \llbracket t_{[n]} \rrbracket(x+j)$$

$$\llbracket t_{[n]} + s_{[n]} \rrbracket := \text{nat}_n^{-1}(\text{nat}_n(\llbracket t_{[n]} \rrbracket) + \text{nat}_n(\llbracket s_{[n]} \rrbracket)) \% 2^n$$

$$\llbracket t_{[n]} \mathbf{AND} s_{[n]} \rrbracket := \lambda x \in [0, n-1]. \begin{cases} 0 & \text{if } \llbracket t_{[n]} \rrbracket(x) = 0 \\ 0 & \text{if } \llbracket s_{[n]} \rrbracket(x) = 0 \\ 1 & \text{otherwise} \end{cases}$$

$$\llbracket t_{[n]} <_u s_{[n]} \rrbracket := \begin{cases} \top & \text{if } \text{nat}_n(\llbracket t_{[n]} \rrbracket) <_u \text{nat}_n(\llbracket s_{[n]} \rrbracket) \\ \perp & \text{otherwise} \end{cases}$$



# Example 1: C code

Pseudo-code

```
i := 1
while ( i > 0 )
    i := i + 1
```



Copyright (C) R. Bruttomesso  
Riproduzione vietata

# Example 1: C code

Pseudo-code

```
i := 1
while ( i > 0 )
    i := i + 1
```

C equivalent

```
unsigned i = 1;
while ( i > 0 )
    i = i + 1;
```



Copyright (C) R. Bruttomesso  
Riproduzione vietata

## Example 2: C code

Evaluation of  $BV_{[32]}$  with C

```
unsigned a = 0xFFFF0000;
```

```
unsigned b = 0x0000FFFF;
```

```
printf( "a + b    : %8X\n", a + b );
```

```
printf( "a * b    : %8X\n", a * b );
```

```
printf( "a AND b  : %8X\n", a & b );
```

```
printf( "a OR b   : %8X\n", a | b );
```



Copyright (C) R. Bruttomesso  
Riproduzione vietata

# Example 3: Circuit

```
module counter(clk, count);


    input clk ;
    output [2:0] count ;
    wire cin ;
    reg [2:0] count ;

    assign cin = ~count [0] & ~count [1] & ~count [2];

    initial begin
        count = 3'b0;
    end

    always @ ( posedge clk )
    begin
        count [0] <= cin;
        count [1] <= count [0];
        count [2] <= count [1];
    end

end module
```



Copyright (C) R. Bruttomesso  
Riproduzione vietata

## 1 Bit-Vectors

- Syntax
- Semantic
- Examples

## 2 Solving Bit-Vectors

- Bit-Blasting
- Simplifications



Our goal is to devise an automatic decision procedure (SMT-solver) to check the satisfiability of a given Bit-Vector formula





# Bit-Blasting

Our goal is to devise an automatic decision procedure (SMT-solver) to check the satisfiability of a given Bit-Vector formula

State-of-the-art techniques are based on reduction to SAT. It is called **bit-blasting**



Copyright (C) R. Bruttomesso  
Riproduzione vietata

Our goal is to devise an automatic decision procedure (SMT-solver) to check the satisfiability of a given Bit-Vector formula

State-of-the-art techniques are based on reduction to SAT. It is called **bit-blasting**

- the formula is seen as a circuit, in which variables and constants are inputs, while other terms are intermediate nodes. The outermost Boolean connective or predicate represents the output



Our goal is to devise an automatic decision procedure (SMT-solver) to check the satisfiability of a given Bit-Vector formula

State-of-the-art techniques are based on reduction to SAT. It is called **bit-blasting**

- the formula is seen as a circuit, in which variables and constants are inputs, while other terms are intermediate nodes. The outermost Boolean connective or predicate represents the output
- each variable is assigned to a vector of Boolean variables ( $n$  variables for a variable of sort  $BV_{[n]}$ )




Our goal is to devise an automatic decision procedure (SMT-solver) to check the satisfiability of a given Bit-Vector formula

State-of-the-art techniques are based on reduction to SAT. It is called **bit-blasting**


- the formula is seen as a circuit, in which variables and constants are inputs, while other terms are intermediate nodes. The outermost Boolean connective or predicate represents the output
- each variable is assigned to a vector of Boolean variables ( $n$  variables for a variable of sort  $BV_{[n]}$ )
- each intermediate node is assigned to a vector of Boolean formulae ( $n$  formulae for a term of sort  $BV_{[n]}$ )




$$(a_{[2]} \mathbf{AND} b_{[4]}[1:0]) = (c_{[2]} + d_{[2]})$$




$$(a_{[2]} \mathbf{AND} b_{[4]}[1 : 0]) = (c_{[2]} + d_{[2]})$$



$$(a_{[2]} \mathbf{AND} b_{[4]}[1:0]) = (c_{[2]} + d_{[2]})$$




$$(a_{[2]} \mathbf{AND} b_{[4]}[1 : 0]) = (c_{[2]} + d_{[2]})$$







$$(a_{[2]} \mathbf{AND} b_{[4]}[1 : 0]) = (c_{[2]} + d_{[2]})$$




$$(a_{[2]} \mathbf{AND} b_{[4]}[1 : 0]) = (c_{[2]} + d_{[2]})$$




$$(a_{[2]} \mathbf{AND} b_{[4]}[1 : 0]) = (c_{[2]} + d_{[2]})$$




$$(a_{[2]} \mathbf{AND} b_{[4]}[1 : 0]) = (c_{[2]} + d_{[2]})$$



$$(a_{[2]} \mathbf{AND} b_{[4]}[1 : 0]) = (c_{[2]} + d_{[2]})$$



$$(a_{[2]} \mathbf{AND} b_{[4]}[1 : 0]) = (c_{[2]} + d_{[2]})$$



$$((b^1 \wedge a^1) \leftrightarrow (c^1 \oplus d^1 \oplus (c^0 \wedge d^0))) \wedge ((b^0 \wedge a^0) \leftrightarrow (c^0 \oplus d^0))$$



# Bit-Blasing Algorithm (1)

$BB := \{\}, C := \{\}$

**Procedure** Bit-Blast-Term(  $t : BV_{[n]}$  term )

**if** (  $t \in C$  ) **return**;       // If already in cache, skip  
**else**  $C := C \cup t$        // Put in cache



# Bit-Blasing Algorithm (1)

$BB := \{\}, C := \{\}$

**Procedure** Bit-Blast-Term(  $t : BV_{[n]}$  term )

**if** (  $t \in C$  ) **return**;       // If already in cache, skip  
**else**  $C := C \cup t$        // Put in cache

**if** (  $t$  is a  $BV_{[n]}$  variable )  
    // Let  $x$  be the name of the variable  
     $BB := BB \cup \{x \mapsto [x^{n-1}, \dots, x^0]\}$   
    // where  $x^i$  are fresh Boolean variables





# Bit-Blasing Algorithm (1)

$BB := \{\}, C := \{\}$

**Procedure** Bit-Blast-Term(  $t : BV_{[n]}$  term )

**if** (  $t \in C$  ) **return**;       // If already in cache, skip  
**else**  $C := C \cup t$        // Put in cache

**if** (  $t$  is a  $BV_{[n]}$  variable )

    // Let  $x$  be the name of the variable  
     $BB := BB \cup \{x \mapsto [x^{n-1}, \dots, x^0]\}$   
    // where  $x^i$  are fresh Boolean variables

**else if** (  $t$  is a  $BV_{[n]}$  constant )

    // Let  $c$  be the constant  
     $BB := BB \cup \{c \mapsto [c^{n-1}, \dots, c^0]\}$   
    // where  $c^i$  is  $\perp$  if the  $i$ -th bit of  $c$  is 0,  $\top$  otherwise



# Bit-Blasing Algorithm (1)

$BB := \{\}, C := \{\}$

**Procedure** Bit-Blast-Term(  $t : BV_{[n]}$  term )

**if** (  $t \in C$  ) **return**;       // If already in cache, skip  
**else**  $C := C \cup t$        // Put in cache

**if** (  $t$  is a  $BV_{[n]}$  variable )  
    // Let  $x$  be the name of the variable  
     $BB := BB \cup \{x \mapsto [x^{n-1}, \dots, x^0]\}$   
    // where  $x^i$  are fresh Boolean variables

**else if** (  $t$  is a  $BV_{[n]}$  constant )  
    // Let  $c$  be the constant  
     $BB := BB \cup \{c \mapsto [c^{n-1}, \dots, c^0]\}$   
    // where  $c^i$  is  $\perp$  if the  $i$ -th bit of  $c$  is 0,  $\top$  otherwise

**else if** (  $t$  is  $(t_1 \text{ AND } t_2)$ , and  $t_1, t_2$  are  $BV_{[n]}$  terms )  
    Bit-Blast-Term(  $t_1$  )  
    Bit-Blast-Term(  $t_2$  )  
     $BB := BB \cup \{t \mapsto [BB(t_1, n-1) \wedge BB(t_2, n-1), \dots, BB(t_1, 0) \wedge BB(t_2, 0)]\}$   
    ...

where  $BB(t, i)$  means:

- 1 retrieve the correspondence  $t \mapsto [t^{n-1}, \dots, t^0]$ , and
- 2 return  $t^i$



Copyright (C) R. Bruttomesso  
Riproduzione vietata

# Bit-Blasing Algorithm (2)

**Procedure** Bit-Blast(  $\varphi : \mathbf{BV}_{[n]}$  formula )

**if** (  $\varphi$  is  $(t_1 = t_2)$ , and  $t_1, t_2$  are  $\mathbf{BV}_{[n]}$  terms )

    Bit-Blast-Term(  $t_1$  )

    Bit-Blast-Term(  $t_2$  )

$\mathbf{BB} := \mathbf{BB} \cup \{ \varphi \mapsto ((\mathbf{BB}(t_1, n-1) \leftrightarrow \mathbf{BB}(t_2, n-1)) \wedge \dots \wedge (\mathbf{BB}(t_1, 0) \leftrightarrow \mathbf{BB}(t_2, 0))) \}$



# Bit-Blasing Algorithm (2)

**Procedure** Bit-Blast(  $\varphi : \mathbf{BV}_{[n]}$  formula )

**if** (  $\varphi$  is  $(t_1 = t_2)$ , and  $t_1, t_2$  are  $\mathbf{BV}_{[n]}$  terms )

    Bit-Blast-Term(  $t_1$  )

    Bit-Blast-Term(  $t_2$  )

$\mathbf{BB} := \mathbf{BB} \cup \{ \varphi \mapsto ((\mathbf{BB}(t_1, n-1) \leftrightarrow \mathbf{BB}(t_2, n-1)) \wedge \dots \wedge (\mathbf{BB}(t_1, 0) \leftrightarrow \mathbf{BB}(t_2, 0))) \}$

**else if** (  $\varphi$  is  $(t_1 <_u t_2)$ , and  $t_1, t_2$  are  $\mathbf{BV}_{[n]}$  terms )

    Bit-Blast-Term(  $t_1$  )

    Bit-Blast-Term(  $t_2$  )

$\mathbf{BB} := \mathbf{BB} \cup \{ \dots \}$



# Bit-Blasing Algorithm (2)

**Procedure** Bit-Blast(  $\varphi : \text{BV}_{[n]}$  formula )

**if** (  $\varphi$  is  $(t_1 = t_2)$ , and  $t_1, t_2$  are  $\text{BV}_{[n]}$  terms )

    Bit-Blast-Term(  $t_1$  )

    Bit-Blast-Term(  $t_2$  )

$\text{BB} := \text{BB} \cup \{ \varphi \mapsto ((\text{BB}(t_1, n-1) \leftrightarrow \text{BB}(t_2, n-1)) \wedge \dots \wedge (\text{BB}(t_1, 0) \leftrightarrow \text{BB}(t_2, 0))) \}$

**else if** (  $\varphi$  is  $(t_1 <_u t_2)$ , and  $t_1, t_2$  are  $\text{BV}_{[n]}$  terms )

    Bit-Blast-Term(  $t_1$  )

    Bit-Blast-Term(  $t_2$  )

$\text{BB} := \text{BB} \cup \{ \dots \}$

**else if** (  $\varphi$  is  $\varphi_1 \wedge \varphi_2$  are  $\text{BV}_{[n]}$  formula )

    Bit-Blast(  $\varphi_1$  )

    Bit-Blast(  $\varphi_2$  )

$\text{BB} := \text{BB} \cup \{ \varphi \mapsto (\text{BB}(\varphi_1) \wedge \text{BB}(\varphi_2)) \}$

...

where  $\text{BB}(\varphi)$  means:


**1** retrieve the correspondence  $\varphi \mapsto \psi$ , and

**2** return  $\psi$



Copyright (C) R. Bruttomesso  
Riproduzione vietata

# SMT via Bit-Blasing



Copyright (C) R. Bruttomesso  
Riproduzione vietata

# Bit-Blasing pros and cons

## Pros

- Very easy to write, if compared to write a native Bit-Vector solver



Copyright (C) R. Bruttomesso  
Riproduzione vietata

# Bit-Blasing pros and cons

## Pros

- Very easy to write, if compared to write a native Bit-Vector solver
- Boolean model from SAT can be mapped back to a model for each Bit-Vector variable. If  $x_{[n]}$  was bit-blasted as  $x^{n-1}, \dots, x^0$ 
  - retrieve SAT assignment for each  $x^i$  (e.g.,  $x^0 = \top$ ,  $x^1 = \perp$ )
  - construct actual value for  $x_{[n]}$  by mapping  $\top$  to 1 and  $\perp$  to 0 (e.g.,  $x_{[2]} = 01$ )



Copyright (C) R. Bruttomesso  
Riproduzione vietata



# Bit-Blasing pros and cons

## Pros

- Very easy to write, if compared to write a native Bit-Vector solver
- Boolean model from SAT can be mapped back to a model for each Bit-Vector variable. If  $x_{[n]}$  was bit-blasted as  $x^{n-1}, \dots, x^0$ 
  - retrieve SAT assignment for each  $x^i$  (e.g.,  $x^0 = \top$ ,  $x^1 = \perp$ )
  - construct actual value for  $x_{[n]}$  by mapping  $\top$  to 1 and  $\perp$  to 0 (e.g.,  $x_{[2]} = 01$ )

## Cons

- Does not scale very well. Consider the formula  $\neg(x_{[n]} = 0_{[32]}) \wedge (x_{[n]} \text{ **AND** } y_{[n]}) = (x_{[n]} + y_{[n]})$ . It is unsat for **every**  $n$ .



Copyright (C) R. Bruttomesso  
Riproduzione vietata

# Bit-Blasing pros and cons

## Pros

- Very easy to write, if compared to write a native Bit-Vector solver
- Boolean model from SAT can be mapped back to a model for each Bit-Vector variable. If  $x_{[n]}$  was bit-blasted as  $x^{n-1}, \dots, x^0$ 
  - retrieve SAT assignment for each  $x^i$  (e.g.,  $x^0 = \top$ ,  $x^1 = \perp$ )
  - construct actual value for  $x_{[n]}$  by mapping  $\top$  to 1 and  $\perp$  to 0 (e.g.,  $x_{[2]} = 01$ )

## Cons

- Does not scale very well. Consider the formula  $\neg(x_{[n]} = 0_{[32]}) \wedge (x_{[n]} \text{ AND } y_{[n]}) = (x_{[n]} + y_{[n]})$ . It is unsat for **every**  $n$ . But to prove it for  $n = 32$  requires 64 Boolean variables, to prove it with  $n = 1024$  requires 2048 Boolean variables



# Bit-Blasing pros and cons

## Pros

- Very easy to write, if compared to write a native Bit-Vector solver
- Boolean model from SAT can be mapped back to a model for each Bit-Vector variable. If  $x_{[n]}$  was bit-blasted as  $x^{n-1}, \dots, x^0$ 
  - retrieve SAT assignment for each  $x^i$  (e.g.,  $x^0 = \top$ ,  $x^1 = \perp$ )
  - construct actual value for  $x_{[n]}$  by mapping  $\top$  to 1 and  $\perp$  to 0 (e.g.,  $x_{[2]} = 01$ )

## Cons

- Does not scale very well. Consider the formula  $\neg(x_{[n]} = 0_{[32]}) \wedge (x_{[n]} \text{ **AND** } y_{[n]}) = (x_{[n]} + y_{[n]})$ . It is unsat for **every**  $n$ . But to prove it for  $n = 32$  requires 64 Boolean variables, to prove it with  $n = 1024$  requires 2048 Boolean variables
- It destroys the structure of the formula. In the encoding  $x_{[32]}$  is not seen as a “single object” but each  $x^i$  is unrelated and independent



Copyright (C) R. Bruttomesso  
Riproduzione vietata

# Simplifications


We use **simplification** rules to fight the two problems in previous slide, before bit-blasting everything



Copyright (C) R. Bruttomesso  
Riproduzione vietata

# Simplifications


We use **simplification** rules to fight the two problems in previous slide, before bit-blasting everything



Copyright (C) R. Bruttomesso  
Riproduzione vietata

# Simplifications

We use **simplification** rules to fight the two problems in previous slide, before bit-blasting everything



Simplifications exploit properties of Bit-Vectors to try to reduce the complexity of the formula. We see here some examples, but many more rules do exist. Also, it is very important the way they are combined together



# Trivial Simplifications

The following are trivial consequences of the semantic of Bit-Vectors and formulæ in general



Copyright (C) R. Bruttomesso  
Riproduzione vietata

# Trivial Simplifications

The following are trivial consequences of the semantic of Bit-Vectors and formulæ in general

Bit-Vectors trivial simplifications

- $t = t \Rightarrow \top$  for a generic term
- $c = d \Rightarrow \perp$  for two different constants  $c$  and  $d$
- $t \mathbf{AND} 0 \dots 0 \Rightarrow 0 \dots 0$  for a generic term
- ...



Copyright (C) R. Bruttomesso  
Riproduzione vietata



# Trivial Simplifications

The following are trivial consequences of the semantic of Bit-Vectors and formulæ in general

Bit-Vectors trivial simplifications

- $t = t \Rightarrow \top$  for a generic term
- $c = d \Rightarrow \perp$  for two different constants  $c$  and  $d$
- $t \mathbf{AND} 0 \dots 0 \Rightarrow 0 \dots 0$  for a generic term
- ...
  
- $\varphi \wedge \varphi \Rightarrow \varphi$  for a generic formula
- $\varphi \wedge \top \Rightarrow \varphi$  for a generic formula
- $\varphi \vee \top \Rightarrow \top$  for a generic formula
- ...



Copyright (C) R. Bruttomesso  
Riproduzione vietata

If a term is **ground**, i.e., it contains no variables, then it can be always simplified to a single constant



If a term is **ground**, i.e., it contains no variables, then it can be always simplified to a single constant

Examples:

- $0000 :: 1000 \Rightarrow 00001000$
- $0010[1 : 0] \Rightarrow 10$
- $0100 + 0101 \Rightarrow 1001$



# Variable Elimination Rule

Suppose that the input formula  $\varphi$  is of the kind

$$\varphi' \wedge (x_{[n]} = t_{[n]})$$

where  $x_{[n]}$  is a variable, and  $t_{[n]}$  is a term **not containing**  $x_{[n]}$



# Variable Elimination Rule

Suppose that the input formula  $\varphi$  is of the kind

$$\varphi' \wedge (x_{[n]} = t_{[n]})$$

where  $x_{[n]}$  is a variable, and  $t_{[n]}$  is a term **not containing**  $x_{[n]}$

then we can rewrite  $\varphi$  as

$$\varphi'[t_{[n]}/x_{[n]}]$$

i.e., we replace every occurrence of  $x_{[n]}$  by  $t_{[n]}$ .



Copyright (C) R. Bruttomesso  
Riproduzione vietata

# Variable Elimination Rule

Suppose that the input formula  $\varphi$  is of the kind

$$\varphi' \wedge (x_{[n]} = t_{[n]})$$

where  $x_{[n]}$  is a variable, and  $t_{[n]}$  is a term **not containing**  $x_{[n]}$

then we can rewrite  $\varphi$  as

$$\varphi'[t_{[n]}/x_{[n]}]$$

i.e., we replace every occurrence of  $x_{[n]}$  by  $t_{[n]}$ . We save  $n$  Boolean variables in the reduction to SAT



Copyright (C) R. Bruttomesso  
Riproduzione vietata

# Concatenation Elimination Rule

Suppose that we have the equality

$$t_{[n]} :: s_{[m]} = r_{[n]} :: u_{[m]}$$

then, because the concatenations **match**, we can rewrite it as



# Concatenation Elimination Rule

Suppose that we have the equality

$$t_{[n]} :: s_{[m]} = r_{[n]} :: u_{[m]}$$

then, because the concatenations **match**, we can rewrite it as

$$(t_{[n]} = r_{[n]}) \wedge (s_{[m]} = u_{[m]})$$

this rewriting may give more opportunity for applications of previous rules



Copyright (C) R. Bruttomesso  
Riproduzione vietata



- 1 Complete the missing cases in procedures Bit-Blast-Term and Bit-Blast
- 2 Bit-Blast the formula  $\neg(x_{[3]} = 000) \wedge (x_{[3]} \mathbf{AND} y_{[3]}) = (x_{[3]} + y_{[3]})$
- 3 Simplify the formula  $(x_{[4]} :: y_{[4]}) = (z_{[4]} :: x_{[4]}) \wedge \neg(y_{[4]} = z_{[4]})$

