

Contents	6	Math	17
1 All Macros	1	6.1 Combi	17
2 DP	1	6.2 Linear Sieve	17
2.1 1D-1D	1	6.3 Pollard Rho	17
2.2 Convex Hull Trick	2	6.4 Chinese Remainder Theorem	17
2.3 Divide and Conquer dp	2	6.5 Mobius Function	17
2.4 Dynamic CHT	2	6.6 FFT	18
2.5 FFT Online	3	6.7 NTT	18
2.6 Knuth optimization	3	6.8 WalshHadamard	19
2.7 Li Chao Tree	3	6.9 Berlekamp Massey	19
3 Data Structure	3	6.10 Lagrange	20
3.1 Segment Tree	3	6.11 Shanks’ Baby Step, Giant Step	20
3.2 Persistent Segment Tree	4	6.12 Xor Basis	20
3.3 SegTree Beats	4	7 String	20
3.4 HashTable	5	7.1 Aho Corasick	20
3.5 DSU With Rollbacks	5	7.2 Double hash	21
3.6 Binary Trie	5	7.3 Manacher’s	22
3.7 BIT-2D	6	7.4 Suffix Array	22
3.8 Divide And Conquer Query Offline	6	7.5 Z Algo	22
3.9 MO with Update	6	8 Equations and Formulas	23
3.10 SparseTable (Rectangle Query)	7	8.1 Catalan Numbers	23
4 Geometry	7	8.2 Stirling Numbers First Kind	23
4.1 Point	7	8.3 Stirling Numbers Second Kind	23
4.2 Linear	8	8.4 Other Combinatorial Identities	23
4.3 Circular	8	8.5 Different Math Formulas	23
4.4 Convex	9	8.6 GCD and LCM	23
4.5 Polygon	11		
4.6 Half Plane	12		
5 Graph	13		
5.1 Graph Template	13		
5.2 SCC	13		
5.3 Tree All	13		
5.4 Euler Tour on Edge	14		
5.5 LCA In O(1)	14		
5.6 HLD	14		
5.7 Dinic Max Flow	15		
5.8 Min Cost Max Flow	15		
5.9 Block Cut Tree	16		
5.10 Bridge Tree	16		
5.11 Tree Isomorphism	16		

Sublime Build

```
{
    "cmd" : ["g++ -std=c++14 -DSONIC $file_name -o
        $file_base_name && timeout 4s ./ $file_base_name<
        inputf.in>outputf.in"],
    "selector" : "source.cpp",
    "file_regex": "^(\\.\\.[:])*:(\\[0-9\\+\\):?(\\[0-9\\+\\)??:? (\\.*)$
        ",
    "shell": true,
    "working_dir" : "$file_path"
}
```

vimrc

```
set mouse=a
set termguicolors
filetype plugin indent on
syntax on

" Some useful settings
set smartindent expandtab ignorecase smartcase
    incsearch relativenumber nowrap autoread splitright
    splitbelow
set tabstop=4            "the width of a tab
set shiftwidth=4        "the width for indent
colorscheme torte

"auto pair curlybraces
inoremap {<ENTER> }<LEFT><CR><ESC><S-o>

" mapping jj to esc
inoremap jj <ESC>

"compile and run using file input put
autocmd filetype cpp map <F5> :wa<CR>:!clear && g++ % -
    D LOCAL -std=c++17 -Wall -Wextra -Wconversion -
    Wshadow -Wfloat-equal -o ~/Codes/prog && (timeout 5
    ~/Codes/prog < ~/Codes/in) > ~/Codes/out<CR>
"copy to input file
map <F4> :!xclip -o -sel clip > ~/Codes/in <CR><CR>
map <F6> :vsplit ~/Codes/in<CR>:split ~/Codes/out<CR><C
    -w>=20<C-w><<C-w><C-h>

" Leader key
let mapleader=',,'

" Copy template
noremap <Leader>t :!cp ~/Codes/temp.cpp %<CR><CR>
:autocmd BufNewFile *.cpp Or ~/Codes/temp.cpp
```

```
"note if vim-features +clipboard is not found, it will
not work
"for fast check :echo has('clipboard') = 0 if clipboard
features not present,
"need vim-gtk / vim-gtk3 package for this
set clipboard=unnamedplus
```

Stress-tester

```
#!/bin/bash
# Call as stresstester ITERATIONS [--count]
```

```
g++ gen.cpp -o gen
g++ sol.cpp -o sol
g++ brute.cpp -o brute
```

```
for i in $(seq 1 "$1") ; do
    echo "Attempt $i/$1"
    ./gen > in.txt
    ./sol < in.txt > out1.txt
    ./brute < in.txt > out2.txt
    diff -y out1.txt out2.txt > diff.txt
    if [ $? -ne 0 ] ; then
        echo "Differing Testcase Found:"; cat in.txt
        echo -e "\nOutputs:"; cat diff.txt
        break
    fi
done
```

1 All Macros

```
//#pragma GCC optimize("Ofast")
//#pragma GCC optimization ("O3")
//#pragma comment(linker, "/stack:200000000")
//#pragma GCC optimize("unroll-loops")
//#pragma GCC target("sse,sse2,sse3,ssse3,sse4,popcnt,abm
    ,mmx,avx,tune=native")
```

```
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;
    //find_by_order(k) --> returns iterator to the kth
    largest element counting from 0
    //order_of_key(val) --> returns the number of items
    in a set that are strictly smaller than our item
template <typename DT>
using ordered_set = tree <DT, null_type, less<DT>,
    rb_tree_tag,tree_order_statistics_node_update>;
```

```
/*--- DEBUG TEMPLATE STARTS HERE ---*/
#ifdef SFT
void show(int x) {cerr << x;}
```

```
void show(long long x) {cerr << x;}
void show(double x) {cerr << x;}
void show(char x) {cerr << '\'' << x << '\'';}
void show(const string &x) {cerr << "\"" << x << "\"";}
void show(bool x) {cerr << (x ? "true" : "false");}
```

```
template<typename T, typename V>
void show(pair<T, V> x) { cerr << '{'; show(x.first);
    cerr << ", "; show(x.second); cerr << '}'; }
template<typename T>
void show(T x) {int f = 0; cerr << "{"; for (auto &i: x)
    cerr << (f++ ? ", " : ""), show(i); cerr << "}";}
```

```
void debug_out(string s) {
    cerr << '\n';
}
```

```
template <typename T, typename... V>
void debug_out(string s, T t, V... v) {
    s.erase(remove(s.begin(), s.end(), ' '), s.end());
    cerr << "          "; // 8 spaces
    cerr << s.substr(0, s.find(','));
    s = s.substr(s.find(',') + 1);
    cerr << " = ";
    show(t);
    cerr << endl;
    if(sizeof...(v)) debug_out(s, v...);
}
```

```
#define debug(x...) cerr << "LINE: " << __LINE__ << endl;
    debug_out(#x, x); cerr << endl;
#else
#define debug(x...)
#endif
```

2 DP

2.1 1D-1D

```
/// Author: anachor
```

```
#include <bits/stdc++.h>
using namespace std;
```

```
/// Solves dp[i] = min(dp[j] + cost(j+1, i)) given that
    cost() is QF
long long solve1D(int n, long long cost(int, int)) {
    vector<long long> dp(n + 1), opt(n + 1);
    deque<pair<int, int>> dq;
    dq.push_back({0, 1});
    dp[0] = 0;

    for (int i = 1; i <= n; i++) {
```

```

opt[i] = dq.front().first;
dp[i] = dp[opt[i]] + cost(opt[i] + 1, i);
if (i == n) break;

dq[0].second++;
if (dq.size() > 1 && dq[0].second == dq[1].second) dq
    .pop_front();

int en = n;
while (dq.size()) {
    int o = dq.back().first, st = dq.back().second;
    if (dp[o] + cost(o + 1, st) >= dp[i] + cost(i + 1,
        st))
        dq.pop_back();
    else {
        int lo = st, hi = en;
        while (lo < hi) {
            int mid = (lo + hi + 1) / 2;
            if (dp[o] + cost(o + 1, mid) < dp[i] + cost(i +
                1, mid))
                lo = mid;
            else
                hi = mid - 1;
        }
        if (lo < n) dq.push_back({i, lo + 1});
        break;
    }
    en = st - 1;
}
if (dq.empty()) dq.push_back({i, i + 1});
}
return dp[n];
}

/// Solves https://open.kattis.com/problems/coveredwalkway
const int N = 1e6 + 7;
long long x[N];
int c;
long long cost(int l, int r) { return (x[r] - x[l]) * (x[
    r] - x[l]) + c; }

int main() {
    ios::sync_with_stdio(false);
    cin.tie(0);

    int n;
    cin >> n >> c;
    for (int i = 1; i <= n; i++) cin >> x[i];
    cout << solve1D(n, cost) << endl;
}

```

```

}

2.2 Convex Hull Trick

struct line {
    ll m, c;
    line() {}
    line(ll m, ll c) : m(m), c(c) {}
};

struct convex_hull_trick {
    vector<line> lines;
    int ptr = 0;
    convex_hull_trick() {}
    bool bad(line a, line b, line c) {
        return 1.0 * (c.c - a.c) * (a.m - b.m) < 1.0 * (b.c -
            a.c) * (a.m - c.m);
    }
    void add(line L) {
        int sz = lines.size();
        while (sz >= 2 && bad(lines[sz - 2], lines[sz - 1], L
            )) {
            lines.pop_back();
            sz--;
        }
        lines.pb(L);
    }
    ll get(int idx, int x) { return (1ll * lines[idx].m * x
        + lines[idx].c); }
    ll query(int x) {
        if (lines.empty()) return 0;
        if (ptr >= lines.size()) ptr = lines.size() - 1;
        while (ptr < lines.size() - 1 && get(ptr, x) > get(
            ptr + 1, x)) ptr++;
        return get(ptr, x);
    }
};

ll sum[MAX];
ll dp[MAX];
int arr[MAX];
int main() {
    fastio;
    int t;
    cin >> t;
    while (t--) {
        int n, a, b, c;
        cin >> n >> a >> b >> c;
        for (int i = 1; i <= n; i++) cin >> sum[i];
        for (int i = 1; i <= n; i++) dp[i] = 0, sum[i] += sum
            [i - 1];
        convex_hull_trick cht;
        cht.add(line(0, 0));
    }
}

```

```

for (int pos = 1; pos <= n; pos++) {
    dp[pos] = cht.query(sum[pos]) - 1ll * a * sqr(sum[
        pos]) - c;
    cht.add(line(2ll * a * sum[pos], dp[pos] - a * sqr(
        sum[pos])));
}
ll ans = (-1ll * dp[n]);
ans += (1ll * sum[n] * b);
cout << ans << "\n";
}

2.3 Divide and Conquer dp

const int K = 805, N = 4005;
LL dp[2][N], _cost[N][N];
// 1-indexed for convenience
LL cost(int l, int r) {
    return _cost[r][r] - _cost[l - 1][r] - _cost[r][l - 1]
        + _cost[l - 1][l - 1] >> 1;
}

void compute(int cnt, int l, int r, int optl, int optr) {
    if (l > r) return;
    int mid = l + r >> 1;
    LL best = INT_MAX;
    int opt = -1;
    for (int i = optl; i <= min(mid, optr); i++) {
        LL cur = dp[cnt ^ 1][i - 1] + cost(i, mid);
        if (cur < best) best = cur, opt = i;
    }
    dp[cnt][mid] = best;
    compute(cnt, l, mid - 1, optl, opt);
    compute(cnt, mid + 1, r, opt, optr);
}

LL dnc_dp(int k, int n) {
    fill(dp[0] + 1, dp[0] + n + 1, INT_MAX);
    for (int cnt = 1; cnt <= k; cnt++) {
        compute(cnt & 1, 1, n, 1, n);
    }
    return dp[k & 1][n];
}

```

2.4 Dynamic CHT

```

typedef long long LL;

const LL IS_QUERY = -(1LL << 62);

struct line {
    LL m, b;
    mutable function <const line*> succ;
}

```

```

bool operator < (const line &rhs) const {
    if (rhs.b != IS_QUERY) return m < rhs.m;
    const line *s = succ();
    if (!s) return 0;
    LL x = rhs.m;
    return b - s -> b < (s -> m - m) * x;
}

};

struct HullDynamic : public multiset <line> {
    bool bad (iterator y) {
        auto z = next(y);
        if (y == begin()) {
            if (z == end()) return 0;
            return y -> m == z -> m && y -> b <= z -> b;
        }
        auto x = prev(y);
        if (z == end()) return y -> m == x -> m && y -> b <=
            x -> b;
        return 1.0 * (x -> b - y -> b) * (z -> m - y -> m) >=
            1.0 * (y -> b - z -> b) * (y -> m - x -> m);
    }

    void insert_line (LL m, LL b) {
        auto y = insert({m, b});
        y -> succ = [=] {return next(y) == end() ? 0 : &*next
            (y);};
        if (bad(y)) {erase(y); return;}
        while (next(y) != end() && bad(next(y))) erase(next(y)
            );
        while (y != begin() && bad(prev(y))) erase(prev(y));
    }

    LL eval (LL x) {
        auto l = *lower_bound((line) {x, IS_QUERY});
        return l.m * x + l.b;
    }
}

};

```

2.5 FFT Online

```

void fftOnline(vector <LL> &a, vector <LL> b) {
    int n = a.size();
    auto call = [&](int l, int r, auto &call){
        if(l >= r) return;
        int mid = l + r >> 1;
        call(l, mid, call);

        vector <LL> _a(a.begin() + l, a.begin() + mid +
            1);

```

```

        vector <LL> _b(b.begin(), b.begin() + (r - l + 1)
            );
        auto c = fft :: anyMod(_a, _b);

        for(int i = mid + 1; i <= r; i++) {
            a[i] += c[i - l];
            a[i] -= (a[i] >= mod) * mod;
        }
        call(mid + 1, r, call);
    };
    call(0, n - 1, call);
}

```

2.6 Knuth optimization

```

const int N = 1005;
LL dp[N][N], a[N];
int opt[N][N];
LL cost(int i, int j) { return a[j + 1] - a[i]; }
LL knuth_optimization(int n) {
    for (int i = 0; i < n; i++) {
        dp[i][i] = 0;
        opt[i][i] = i;
    }
    for (int i = n - 2; i >= 0; i--) {
        for (int j = i + 1; j < n; j++) {
            LL mn = LLONG_MAX;
            LL c = cost(i, j);
            for (int k = opt[i][j - 1]; k <= min(j - 1, opt[i +
                1][j]); k++) {
                if (mn > dp[i][k] + dp[k + 1][j] + c) {
                    mn = dp[i][k] + dp[k + 1][j] + c;
                    opt[i][j] = k;
                }
            }
            dp[i][j] = mn;
        }
    }
    return dp[0][n - 1];
}

```

2.7 Li Chao Tree

```

struct line {
    LL m, c;
    line(LL m = 0, LL c = 0) : m(m), c(c) {}
};

LL calc(line L, LL x) { return 1LL * L.m * x + L.c; }
struct node {
    LL m, c;
    line L;
    node *lft, *rt;

```

```

    node(LL m = 0, LL c = 0, node *lft = NULL, node *rt =
        NULL)
        : L(line(m, c)), lft(lft), rt(rt) {}
};

struct LiChao {
    node *root;
    LiChao() { root = new node(); }
    void update(node *now, int L, int R, line newline) {
        int mid = L + (R - L) / 2;
        line lo = now->L, hi = newline;
        if (calc(lo, L) > calc(hi, L)) swap(lo, hi);
        if (calc(lo, R) <= calc(hi, R)) {
            now->L = hi;
            return;
        }
        if (calc(lo, mid) < calc(hi, mid)) {
            now->L = hi;
            if (now->rt == NULL) now->rt = new node();
            update(now->rt, mid + 1, R, lo);
        } else {
            now->L = lo;
            if (now->lft == NULL) now->lft = new node();
            update(now->lft, L, mid, hi);
        }
    }

    LL query(node *now, int L, int R, LL x) {
        if (now == NULL) return -inf;
        int mid = L + (R - L) / 2;
        if (x <= mid)
            return max(calc(now->L, x), query(now->lft, L, mid,
                x));
        else
            return max(calc(now->L, x), query(now->rt, mid + 1,
                R, x));
    }
};

```

3 Data Structure

3.1 Segment Tree

```

const int N = 1000006;

using DT = LL;
using LT = LL;
constexpr DT I = 0;
constexpr LT None = 0;
DT val[4 * N];
LT lazy[4 * N];
int L, R;

void pull(int s, int e, int node) {

```

```

    val[node] = val[node << 1] + val[node << 1 | 1];
}
void apply(const LT &U, int s, int e, int node) {
    val[node] += (e - s + 1) * U;
    lazy[node] += U;
}
void reset(int node) { lazy[node] = None; }
DT merge(const DT &a, const DT &b) { return a + b; }
DT get(int s, int e, int node) { return val[node]; }
void push(int s, int e, int node) {
    if (s == e) return;
    apply(lazy[node], s, s + e >> 1, node << 1);
    apply(lazy[node], s + e + 2 >> 1, e, node << 1 | 1);
    reset(node);
}
void build(int s, int e, vector<DT> &v, int node = 1) {
    int m = s + e >> 1;
    if (s == e) {
        val[node] = v[s];
        return;
    }
    build(s, m, v, node * 2);
    build(m + 1, e, v, node * 2 + 1);
    pull(s, e, node);
}
void update(int S, int E, LT uval, int s = L, int e = R,
            int node = 1) {
    if (S > E) return;
    if (S == s and E == e) {
        apply(uval, s, e, node);
        return;
    }
    push(s, e, node);
    int m = s + e >> 1;
    update(S, min(m, E), uval, s, m, node * 2);
    update(max(S, m + 1), E, uval, m + 1, e, node * 2 + 1);
    pull(s, e, node);
}
DT query(int S, int E, int s = L, int e = R, int node =
        1) {
    if (S > E) return I;
    if (s == S and e == E) return get(s, e, node);
    push(s, e, node);
    int m = s + e >> 1;
    DT L = query(S, min(m, E), s, m, node * 2);
    DT R = query(max(S, m + 1), E, m + 1, e, node * 2 + 1);
    return merge(L, R);
}
void init(int _L, int _R, vector<DT> &v) {
    L = _L, R = _R;

```

```

    build(L, R, v);
}

```

3.2 Persistent Segment Tree

```

struct Node {
    int l = 0, r = 0, val = 0;
} tr[20 * N];
int ptr = 0;
int build(int st, int en) {
    int u = ++ptr;
    if (st == en) return u;
    int mid = (st + en) / 2;
    auto& [l, r, val] = tr[u];
    l = build(st, mid);
    r = build(mid + 1, en);
    val = tr[l].val + tr[r].val;
    return u;
}

int update(int pre, int st, int en, int idx, int v) {
    int u = ++ptr;
    tr[u] = tr[pre];
    if (st == en) {
        tr[u].val += v;
        return u;
    }
    int mid = (st + en) / 2;
    auto& [l, r, val] = tr[u];
    if (idx <= mid) {
        r = tr[pre].r;
        l = update(tr[pre].l, st, mid, idx, v);
    } else {
        l = tr[pre].l;
        r = update(tr[pre].r, mid + 1, en, idx, v);
    }
    tr[u].val = tr[l].val + tr[r].val;
    return u;
}

// finding the kth element in a range
int query(int left, int right, int st, int en, int k) {
    if (st == en) return st;
    int cnt = tr[tr[right].l].val - tr[tr[left].l].val;
    int mid = (st + en) / 2;
    if (cnt >= k) return query(tr[left].l, tr[right].l,
        st, mid, k);
    else return query(tr[left].r, tr[right].r, mid + 1,
        en, k - cnt);
}

int V[N], root[N], a[N];
int main() {

```

```

    map<int, int> mp; int n, q;
    cin >> n >> q;
    for (int i = 1; i <= n; i++) cin >> a[i], mp[a[i]];
    int c = 0;
    for (auto x : mp) mp[x.first] = ++c, V[c] = x.first;
    root[0] = build(1, n);
    for (int i = 1; i <= n; i++) {
        root[i] = update(root[i - 1], 1, n, mp[a[i]], 1);
    }
    while (q--) {
        int l, r, k; cin >> l >> r >> k; l++, k++;
        cout << V[query(root[l - 1], root[r], 1, n, k)]
            << '\n';
    }
    return 0;
}

```

3.3 SegTree Beats

```

const int N = 2e5 + 5;
LL mx[4 * N], mn[4 * N], smx[4 * N], smn[4 * N], sum[4 *
    N], add[4 * N];
int mxcnt[4 * N], mncnt[4 * N];

int L, R;

void applyMax(int u, LL x) {
    sum[u] += mncnt[u] * (x - mn[u]);
    if (mx[u] == mn[u]) mx[u] = x;
    if (smx[u] == mn[u]) smx[u] = x;
    mn[u] = x;
}

void applyMin(int u, LL x) {
    sum[u] -= mxcnt[u] * (mx[u] - x);
    if (mn[u] == mx[u]) mn[u] = x;
    if (smn[u] == mx[u]) smn[u] = x;
    mx[u] = x;
}

void applyAdd(int u, LL x, int tl, int tr) {
    sum[u] += (tr - tl + 1) * x;
    add[u] += x;
    mx[u] += x, mn[u] += x;
    if (smx[u] != -INF) smx[u] += x;
    if (smn[u] != INF) smn[u] += x;
}

void push(int u, int tl, int tr) {
    int lft = u << 1, ryt = lft | 1, mid = tl + tr >> 1;
    if (add[u] != 0) {
        applyAdd(lft, add[u], tl, mid);
        applyAdd(ryt, add[u], mid + 1, tr);
        add[u] = 0;
    }
}

```

```

}
if (mx[u] < mx[lft]) applyMin(lft, mx[u]);
if (mx[u] < mx[ryt]) applyMin(ryt, mx[u]);

if (mn[u] > mn[lft]) applyMax(lft, mn[u]);
if (mn[u] > mn[ryt]) applyMax(ryt, mn[u]);
}

void merge(int u) {
    int lft = u << 1, ryt = lft | 1;
    sum[u] = sum[lft] + sum[ryt];

    mx[u] = max(mx[lft], mx[ryt]);
    smx[u] = max(smx[lft], smx[ryt]);
    if (mx[lft] != mx[ryt]) smx[u] = max(smx[u], min(mx[lft], mx[ryt]));
    mxcnt[u] = (mx[u] == mx[lft]) * mxcnt[lft] + (mx[u] == mx[ryt]) * mxcnt[ryt];

    mn[u] = min(mn[lft], mn[ryt]);
    smn[u] = min(smn[lft], smn[ryt]);
    if (mn[lft] != mn[ryt]) smn[u] = min(smn[u], max(mn[lft], mn[ryt]));
    mncnt[u] = (mn[u] == mn[lft]) * mncnt[lft] + (mn[u] == mn[ryt]) * mncnt[ryt];
}

void minimize(int l, int r, LL x, int tl = L, int tr = R, int u = 1) {
    if (l > tr or tl > r or mx[u] <= x) return;
    if (l <= tl and tr <= r and smx[u] < x) {
        applyMin(u, x);
        return;
    }
    push(u, tl, tr);
    int mid = tl + tr >> 1, lft = u << 1, ryt = lft | 1;
    minimize(l, r, x, tl, mid, lft);
    minimize(l, r, x, mid + 1, tr, ryt);
    merge(u);
}

void maximize(int l, int r, LL x, int tl = L, int tr = R, int u = 1) {
    if (l > tr or tl > r or mn[u] >= x) return;
    if (l <= tl and tr <= r and smn[u] > x) {
        applyMax(u, x);
        return;
    }
    push(u, tl, tr);
    int mid = tl + tr >> 1, lft = u << 1, ryt = lft | 1;
    maximize(l, r, x, tl, mid, lft);
    maximize(l, r, x, mid + 1, tr, ryt);
    merge(u);
}

```

```

}
void increase(int l, int r, LL x, int tl = L, int tr = R, int u = 1) {
    if (l > tr or tl > r) return;
    if (l <= tl and tr <= r) {
        applyAdd(u, x, tl, tr);
        return;
    }
    push(u, tl, tr);
    int mid = tl + tr >> 1, lft = u << 1, ryt = lft | 1;
    increase(l, r, x, tl, mid, lft);
    increase(l, r, x, mid + 1, tr, ryt);
    merge(u);
}

LL getSum(int l, int r, int tl = L, int tr = R, int u = 1) {
    if (l > tr or tl > r) return 0;
    if (l <= tl and tr <= r) return sum[u];
    push(u, tl, tr);
    int mid = tl + tr >> 1, lft = u << 1, ryt = lft | 1;
    return getSum(l, r, tl, mid, lft) + getSum(l, r, mid + 1, tr, ryt);
}

void build(LL a[], int tl = L, int tr = R, int u = 1) {
    if (tl == tr) {
        sum[u] = mn[u] = mx[u] = a[tl];
        mxcnt[u] = mncnt[u] = 1;
        smx[u] = -INF;
        smn[u] = INF;
        return;
    }
    int mid = tl + tr >> 1, lft = u << 1, ryt = lft | 1;
    build(a, tl, mid, lft);
    build(a, mid + 1, tr, ryt);
    merge(u);
}

void init(LL a[], int _L, int _R) {
    L = _L, R = _R;
    build(a);
}

```

3.4 HashTable

```

#include <ext/pb_ds/assoc_container.hpp>
using namespace __gnu_pbds;

const int RANDOM = chrono::high_resolution_clock::now().time_since_epoch().count();
unsigned hash_f(unsigned x) {
    x = ((x >> 16) ^ x) * 0x45d9f3b;
    x = ((x >> 16) ^ x) * 0x45d9f3b;
}

```

```

return x = (x >> 16) ^ x;
}

unsigned hash_combine(unsigned a, unsigned b) { return a * 31 + b; }
struct chash {
    int operator()(int x) const { return hash_f(x); }
};
typedef gp_hash_table<int, int, chash> gp;
gp table;

```

3.5 DSU With Rollbacks

```

struct Rollback_DSU {
    int n;
    vector<int> par, sz;
    vector<pair<int, int>> op;
    Rollback_DSU(int n) : par(n), sz(n, 1) {
        iota(par.begin(), par.end(), 0);
        op.reserve(n);
    }
    int Anc(int node) {
        for (; node != par[node]; node = par[node])
            ; // no path compression
        return node;
    }
    void Unite(int x, int y) {
        if (sz[x = Anc(x)] < sz[y = Anc(y)]) swap(x, y);
        op.emplace_back(x, y);
        par[y] = x;
        sz[x] += sz[y];
    }
    void Undo(int t) {
        for (; op.size() > t; op.pop_back()) {
            par[op.back().second] = op.back().second;
            sz[op.back().first] -= sz[op.back().second];
        }
    }
};

```

3.6 Binary Trie

```

const int N = 1e7 + 5, b = 30;
int tc = 1;
struct node {
    int vis = 0;
    int to[2] = {0, 0};
    int val[2] = {0, 0};
    void update() {
        to[0] = to[1] = 0;
        val[0] = val[1] = 0;
        vis = tc;
    }
};

```

```

    }
} T[N + 2];
node *root = T;
int ptr = 0;
node *nxt(node *cur, int x) {
    if (cur->to[x] == 0) cur->to[x] = ++ptr;
    assert(ptr < N);
    int idx = cur->to[x];
    if (T[idx].vis < tc) T[idx].update();
    return T + idx;
}
int query(int j, int aj) {
    int ans = 0, jaj = j ^ aj;
    node *cur = root;
    for (int k = b - 1; ~k; k--) {
        maximize(ans, nxt(cur, (jaj >> k & 1) ^ 1)->val[1 ^ (
            aj >> k & 1)]);
        cur = nxt(cur, (jaj >> k & 1));
    }
    return ans;
}
void insert(int j, int aj, int val) {
    int jaj = j ^ aj;
    node *cur = root;
    for (int k = b - 1; ~k; k--) {
        cur = nxt(cur, (jaj >> k & 1));
        maximize(cur->val[j >> k & 1], val);
    }
}
void clear() {
    tc++;
    ptr = 0;
    root->update();
}

```

3.7 BIT-2D

```

const int N = 1008;
int bit[N][N], n, m;
int a[N][N], q;
void update(int x, int y, int val) {
    for (; x < N; x += -x & x)
        for (int j = y; j < N; j += -j & j) bit[x][j] += val;
}
int get(int x, int y) {
    int ans = 0;
    for (; x; x -= x & -x)
        for (int j = y; j; j -= j & -j) ans += bit[x][j];
    return ans;
}
int get(int x1, int y1, int x2, int y2) {

```

```

    return get(x2, y2) - get(x1 - 1, y2) - get(x2, y1 - 1)
        + get(x1 - 1, y1 - 1);
}

```

3.8 Divide And Conquer Query Offline

```

namespace up {
int l[N], r[N], u[N], v[N], tm;
void push(int _l, int _r, int _u, int _v) {
    l[tm] = _l, r[tm] = _r, u[tm] = _u, v[tm] = _v;
    tm++;
}
} // namespace up
namespace que {
int node[N], tm;
LL ans[N];
void push(int _node) { node[++tm] = _node; }
} // namespace que
namespace edge_set {
void push(int i) { dsu ::merge(up ::u[i], up ::v[i]); }
void pop(int t) { dsu ::rollback(t); }
int time() { return dsu ::op.size(); }
LL query(int u) { return a[dsu ::root(u)]; }
} // namespace edge_set
namespace dncq {
vector<int> tree[4 * N];
void update(int idx, int l = 0, int r = que ::tm, int
    node = 1) {
    int ul = up ::l[idx], ur = up ::r[idx];
    if (r < ul or ur < l) return;
    if (ul <= l and r <= ur) {
        tree[node].push_back(idx);
        return;
    }
    int m = l + r >> 1;
    update(idx, l, m, node << 1);
    update(idx, m + 1, r, node << 1 | 1);
}
void dfs(int l = 0, int r = que ::tm, int node = 1) {
    int cur = edge_set ::time();
    for (int e : tree[node]) edge_set ::push(e);
    if (l == r) {
        que ::ans[l] = edge_set ::query(que ::node[l]);
    } else {
        int m = l + r >> 1;
        dfs(l, m, node << 1);
        dfs(m + 1, r, node << 1 | 1);
    }
    edge_set ::pop(cur);
}
} // namespace dncq

```

```

void push_updates() {
    for (int i = 0; i < up ::tm; i++) dncq ::update(i);
}

```

3.9 MO with Update

```

const int N = 1e5 + 5, sz = 2700, bs = 25;
int arr[N], freq[2 * N], cnt[2 * N], id[N], ans[N];
struct query {
    int l, r, t, L, R;
    query(int l = 1, int r = 0, int t = 1, int id = -1)
        : l(l), r(r), t(t), L(l / sz), R(r / sz) {}
    bool operator<(const query &rhs) const {
        return (L < rhs.L) or (L == rhs.L and R < rhs.R) or
            (L == rhs.L and R == rhs.R and t < rhs.t);
    }
} Q[N];
struct update {
    int idx, val, last;
} Up[N];
int qi = 0, ui = 0;
int l = 1, r = 0, t = 0;

void add(int idx) {
    --cnt[freq[arr[idx]]];
    freq[arr[idx]]++;
    cnt[freq[arr[idx]]]++;
}
void remove(int idx) {
    --cnt[freq[arr[idx]]];
    freq[arr[idx]]--;
    cnt[freq[arr[idx]]]++;
}
void apply(int t) {
    const bool f = l <= Up[t].idx and Up[t].idx <= r;
    if (f) remove(Up[t].idx);
    arr[Up[t].idx] = Up[t].val;
    if (f) add(Up[t].idx);
}
void undo(int t) {
    const bool f = l <= Up[t].idx and Up[t].idx <= r;
    if (f) remove(Up[t].idx);
    arr[Up[t].idx] = Up[t].last;
    if (f) add(Up[t].idx);
}
int mex() {
    for (int i = 1; i <= N; i++)
        if (!cnt[i]) return i;
    assert(0);
}
int main() {

```



```

sort(id + 1, id + qi + 1, [&](int x, int y) { return Q[
    x] < Q[y]; });
for (int i = 1; i <= qi; i++) {
    int x = id[i];
    while (Q[x].t > t) apply(++t);
    while (Q[x].t < t) undo(t--);
    while (Q[x].l < l) add(--l);
    while (Q[x].r > r) add(++r);
    while (Q[x].l > l) remove(l++);
    while (Q[x].r < r) remove(r--);
    ans[x] = mex();
}
}

```

3.10 SparseTable (Rectangle Query)

```

#include <bits/stdc++.h>
using namespace std;

```

```

const int MAXN = 505;
const int LOGN = 9;

```

```

// O(n^2 (logn)^2)
// Supports Rectangular Query
int A[MAXN][MAXN];
int M[MAXN][MAXN][LOGN][LOGN];

```

```

void Build2DSparse(int N) {
    for (int i = 1; i <= N; i++) {
        for (int j = 1; j <= N; j++) {
            M[i][j][0][0] = A[i][j];
        }
        for (int q = 1; (1 << q) <= N; q++) {
            int add = 1 << (q - 1);
            for (int j = 1; j + add <= N; j++) {
                M[i][j][q][q] = max(M[i][j][0][q - 1], M[i][j + add][0][q - 1]);
            }
        }
    }

    for (int p = 1; (1 << p) <= N; p++) {
        int add = 1 << (p - 1);
        for (int i = 1; i + add <= N; i++) {
            for (int q = 0; (1 << q) <= N; q++) {
                for (int j = 1; j <= N; j++) {
                    M[i][j][p][q] = max(M[i][j][p - 1][q], M[i + add][j][p - 1][q]);
                }
            }
        }
    }
}

```

```

}
// returns max of all A[i][j], where x1<=i<=x2 and y1<=j<=y2
int Query(int x1, int y1, int x2, int y2) {
    int kX = log2(x2 - x1 + 1);
    int kY = log2(y2 - y1 + 1);
    int addX = 1 << kX;
    int addY = 1 << kY;

    int ret1 = max(M[x1][y1][kX][kY], M[x1][y2 - addY + 1][kX][kY]);
    int ret2 = max(M[x2 - addX + 1][y1][kX][kY], M[x2 - addX + 1][y2 - addY + 1][kX][kY]);
    return max(ret1, ret2);
}

```

4 Geometry

4.1 Point

```

typedef double Tf;
typedef double Ti; // use long long for exactness
const Tf PI = acos(-1), EPS = 1e-9;
int dcmp(Tf x) { return abs(x) < EPS ? 0 : (x < 0 ? -1 : 1); }

struct Point {
    Ti x, y;
    Point(Ti x = 0, Ti y = 0) : x(x), y(y) {}

    Point operator+(const Point& u) const { return Point(x + u.x, y + u.y); }
    Point operator-(const Point& u) const { return Point(x - u.x, y - u.y); }
    Point operator*(const LL u) const { return Point(x * u, y * u); }
    Point operator*(const Tf u) const { return Point(x * u, y * u); }
    Point operator/(const Tf u) const { return Point(x / u, y / u); }

    bool operator==(const Point& u) const { return dcmp(x - u.x) == 0 && dcmp(y - u.y) == 0; }
    bool operator!=(const Point& u) const { return !(*this == u); }
    bool operator<(const Point& u) const { return dcmp(x - u.x) < 0 || (dcmp(x - u.x) == 0 && dcmp(y - u.y) < 0); }
}

```

```

};
Ti dot(Point a, Point b) { return a.x * b.x + a.y * b.y; }
Ti cross(Point a, Point b) { return a.x * b.y - a.y * b.x; }
Tf length(Point a) { return sqrt(dot(a, a)); }
Ti sqLength(Point a) { return dot(a, a); }
Tf distance(Point a, Point b) { return length(a - b); }
Tf angle(Point u) { return atan2(u.y, u.x); }

// returns angle between oa, ob in (-PI, PI]
Tf angleBetween(Point a, Point b) {
    Tf ans = angle(b) - angle(a);
    return ans <= -PI ? ans + 2 * PI : (ans > PI ? ans - 2 * PI : ans);
}

// Rotate a ccw by rad radians, Tf Ti same
Point rotate(Point a, Tf rad) {
    return Point(a.x * cos(rad) - a.y * sin(rad), a.x * sin(rad) + a.y * cos(rad));
}

// rotate a ccw by angle th with cos(th) = co && sin(th) = si, tf ti same
Point rotatePrecise(Point a, Tf co, Tf si) {
    return Point(a.x * co - a.y * si, a.y * co + a.x * si);
}

Point rotate90(Point a) { return Point(-a.y, a.x); }
// scales vector a by s such that length of a becomes s, Tf Ti same
Point scale(Point a, Tf s) { return a / length(a) * s; }
// returns an unit vector perpendicular to vector a, Tf Ti same
Point normal(Point a) {
    Tf l = length(a);
    return Point(-a.y / l, a.x / l);
}

// returns 1 if c is left of ab, 0 if on ab && -1 if right of ab
int orient(Point a, Point b, Point c) { return dcmp(cross(b - a, c - a)); }

/// Use as sort(v.begin(), v.end(), polarComp(0, dir))
/// Polar comparator around 0 starting at direction dir
struct polarComp {
    Point O, dir;
    polarComp(Point O = Point(0, 0), Point dir = Point(1, 0)) : O(O), dir(dir) {}
    bool half(Point p) { return dcmp(cross(dir, p)) < 0 || (dcmp(cross(dir, p)) == 0 && dcmp(dot(dir, p)) > 0); }
}

```



```

}
bool operator()(Point p, Point q) {
    return make_tuple(half(p), 0) < make_tuple(half(q),
        cross(p, q));
}
};
struct Segment {
    Point a, b;
    Segment(Point aa, Point bb) : a(aa), b(bb) {}
};
typedef Segment Line;
struct Circle {
    Point o;
    Tf r;
    Circle(Point o = Point(0, 0), Tf r = 0) : o(o), r(r) {}
    // returns true if point p is in || on the circle
    bool contains(Point p) { return dcmp(sqLength(p - o) -
        r * r) <= 0; }
    // returns a point on the circle rad radians away from
    // +X CCW
    Point point(Tf rad) {
        static_assert(is_same<Tf, Ti>::value);
        return Point(o.x + cos(rad) * r, o.y + sin(rad) * r);
    }
    // area of a circular sector with central angle rad
    Tf area(Tf rad = PI + PI) { return rad * r * r / 2; }
    // area of the circular sector cut by a chord with
    // central angle alpha
    Tf sector(Tf alpha) { return r * r * 0.5 * (alpha - sin
        (alpha)); }
};

```

4.2 Linear

```

// **** LINE LINE INTERSECTION START ****
// returns true if point p is on segment s
bool onSegment(Point p, Segment s) {
    return dcmp(cross(s.a - p, s.b - p)) == 0 && dcmp(dot(s
        .a - p, s.b - p)) <= 0;
}
// returns true if segment p && q touch or intersect
bool segmentsIntersect(Segment p, Segment q) {
    if (onSegment(p.a, q) || onSegment(p.b, q)) return true
        ;
    if (onSegment(q.a, p) || onSegment(q.b, p)) return true
        ;

    Ti c1 = cross(p.b - p.a, q.a - p.a);
    Ti c2 = cross(p.b - p.a, q.b - p.a);
    Ti c3 = cross(q.b - q.a, p.a - q.a);
    Ti c4 = cross(q.b - q.a, p.b - q.a);

```

```

    return dcmp(c1) * dcmp(c2) < 0 && dcmp(c3) * dcmp(c4) <
        0;
}
bool linesParallel(Line p, Line q) {
    return dcmp(cross(p.b - p.a, q.b - q.a)) == 0;
}
// lines are represented as a ray from a point: (point,
// vector)
// returns false if two lines (p, v) && (q, w) are
// parallel or collinear
// true otherwise, intersection point is stored at o via
// reference, Tf Ti Same
bool lineLineIntersection(Point p, Point v, Point q,
    Point w, Point& o) {
    if (dcmp(cross(v, w)) == 0) return false;
    Point u = p - q;
    o = p + v * (cross(w, u) / cross(v, w));
    return true;
}
// returns false if two lines p && q are parallel or
// collinear
// true otherwise, intersection point is stored at o via
// reference
bool lineLineIntersection(Line p, Line q, Point& o) {
    return lineLineIntersection(p.a, p.b - p.a, q.a, q.b -
        q.a, o);
}
// returns the distance from point a to line l
// **** LINE LINE INTERSECTION FINISH ****
Tf distancePointLine(Point p, Line l) {
    return abs(cross(l.b - l.a, p - l.a) / length(l.b - l.a
        ));
}
// returns the shortest distance from point a to segment
// s
Tf distancePointSegment(Point p, Segment s) {
    if (s.a == s.b) return length(p - s.a);
    Point v1 = s.b - s.a, v2 = p - s.a, v3 = p - s.b;
    if (dcmp(dot(v1, v2)) < 0)
        return length(v2);
    else if (dcmp(dot(v1, v3)) > 0)
        return length(v3);
    else
        return abs(cross(v1, v2) / length(v1));
}
// returns the shortest distance from segment p to
// segment q
Tf distanceSegmentSegment(Segment p, Segment q) {
    if (segmentsIntersect(p, q)) return 0;
    Tf ans = distancePointSegment(p.a, q);

```

```

    ans = min(ans, distancePointSegment(p.b, q));
    ans = min(ans, distancePointSegment(q.a, p));
    ans = min(ans, distancePointSegment(q.b, p));
    return ans;
}
// returns the projection of point p on line l, Tf Ti
// Same
Point projectPointLine(Point p, Line l) {
    Point v = l.b - l.a;
    return l.a + v * ((Tf)dot(v, p - l.a) / dot(v, v));
}

```

4.3 Circular

```

// Extremely inaccurate for finding near touches
// compute intersection of line l with circle c
// The intersections are given in order of the ray (l.a,
// l.b), Tf Ti same
vector<Point> circleLineIntersection(Circle c, Line l) {
    vector<Point> ret;
    Point b = l.b - l.a, a = l.a - c.o;
    Tf A = dot(b, b), B = dot(a, b);
    Tf C = dot(a, a) - c.r * c.r, D = B * B - A * C;
    if (D < -EPS) return ret;
    ret.push_back(l.a + b * (-B - sqrt(D + EPS)) / A);
    if (D > EPS) ret.push_back(l.a + b * (-B + sqrt(D)) / A
        );
    return ret;
}
// signed area of intersection of circle(c.o, c.r) &&
// triangle(c.o, s.a, s.b) [cross(a-o, b-o)/2]
Tf circleTriangleIntersectionArea(Circle c, Segment s) {
    using Linear::distancePointSegment;
    Tf OA = length(c.o - s.a);
    Tf OB = length(c.o - s.b);
    // sector
    if (dcmp(distancePointSegment(c.o, s) - c.r) >= 0)
        return angleBetween(s.a - c.o, s.b - c.o) * (c.r * c.
            r) / 2.0;
    // triangle
    if (dcmp(OA - c.r) <= 0 && dcmp(OB - c.r) <= 0)
        return cross(c.o - s.b, s.a - s.b) / 2.0;
    // three part: (A, a) (a, b) (b, B)
    vector<Point> Sect = circleLineIntersection(c, s);
    return circleTriangleIntersectionArea(c, Segment(s.a,
        Sect[0])) +
        circleTriangleIntersectionArea(c, Segment(Sect
            [0], Sect[1])) +
        circleTriangleIntersectionArea(c, Segment(Sect
            [1], s.b));
}

```

```
// area of intersecion of circle(c.o, c.r) && simple
polyson(p[]])
Tf circlePolyIntersectionArea(Circle c, Polygon p) {
    Tf res = 0;
    int n = p.size();
    for (int i = 0; i < n; ++i)
        res += circleTriangleIntersectionArea(c, Segment(p[i]
            ], p[(i + 1) % n]));
    return abs(res);
}
// locates circle c2 relative to c1
// interior          (d < R - r)      ----> -2
// interior tangents (d = R - r)      ----> -1
// concentric        (d = 0)
// secants           (R - r < d < R + r) ----> 0
// exterior tangents (d = R + r)      ----> 1
// exterior          (d > R + r)      ----> 2
int circleCirclePosition(Circle c1, Circle c2) {
    Tf d = length(c1.o - c2.o);
    int in = dcmp(d - abs(c1.r - c2.r)), ex = dcmp(d - (c1.
        r + c2.r));
    return in < 0 ? -2 : in == 0 ? -1 : ex == 0 ? 1 : ex >
        0 ? 2 : 0;
}
// compute the intersection points between two circles c1
&& c2, Tf Ti same
vector<Point> circleCircleIntersection(Circle c1, Circle
    c2) {
    vector<Point> ret;
    Tf d = length(c1.o - c2.o);
    if (dcmp(d) == 0) return ret;
    if (dcmp(c1.r + c2.r - d) < 0) return ret;
    if (dcmp(abs(c1.r - c2.r) - d) > 0) return ret;

    Point v = c2.o - c1.o;
    Tf co = (c1.r * c1.r + sqLength(v) - c2.r * c2.r) / (2
        * c1.r * length(v));
    Tf si = sqrt(abs(1.0 - co * co));
    Point p1 = scale(rotatePrecise(v, co, -si), c1.r) + c1.
        o;
    Point p2 = scale(rotatePrecise(v, co, si), c1.r) + c1.o
        ;

    ret.push_back(p1);
    if (p1 != p2) ret.push_back(p2);
    return ret;
}
// intersection area between two circles c1, c2
Tf circleCircleIntersectionArea(Circle c1, Circle c2) {
    Point AB = c2.o - c1.o;
```

```
Tf d = length(AB);
if (d >= c1.r + c2.r) return 0;
if (d + c1.r <= c2.r) return PI * c1.r * c1.r;
if (d + c2.r <= c1.r) return PI * c2.r * c2.r;

Tf alpha1 = acos((c1.r * c1.r + d * d - c2.r * c2.r) /
    (2.0 * c1.r * d));
Tf alpha2 = acos((c2.r * c2.r + d * d - c1.r * c1.r) /
    (2.0 * c2.r * d));
return c1.sector(2 * alpha1) + c2.sector(2 * alpha2);
}
// returns tangents from a point p to circle c, Tf Ti
same
vector<Point> pointCircleTangents(Point p, Circle c) {
    vector<Point> ret;
    Point u = c.o - p;
    Tf d = length(u);
    if (d < c.r)
        ;
    else if (dcmp(d - c.r) == 0) {
        ret = {rotate(u, PI / 2)};
    } else {
        Tf ang = asin(c.r / d);
        ret = {rotate(u, -ang), rotate(u, ang)};
    }
    return ret;
}
// returns the points on tangents that touches the circle
, Tf Ti Same
vector<Point> pointCircleTangencyPoints(Point p, Circle c
    ) {
    Point u = p - c.o;
    Tf d = length(u);
    if (d < c.r)
        return {};
    else if (dcmp(d - c.r) == 0)
        return {c.o + u};
    else {
        Tf ang = acos(c.r / d);
        u = u / length(u) * c.r;
        return {c.o + rotate(u, -ang), c.o + rotate(u, ang)};
    }
}
// for two circles c1 && c2, returns two list of points a
&& b
// such that a[i] is on c1 && b[i] is c2 && for every i
// Line(a[i], b[i]) is a tangent to both circles
// CAUTION: a[i] = b[i] in case they touch | -1 for c1 =
    c2
```

```
int circleCircleTangencyPoints(Circle c1, Circle c2,
    vector<Point> &a,
                                vector<Point> &b) {
    a.clear(), b.clear();
    int cnt = 0;
    if (dcmp(c1.r - c2.r) < 0) {
        swap(c1, c2);
        swap(a, b);
    }
    Tf d2 = sqLength(c1.o - c2.o);
    Tf rdif = c1.r - c2.r, rsum = c1.r + c2.r;
    if (dcmp(d2 - rdif * rdif) < 0) return 0;
    if (dcmp(d2) == 0 && dcmp(c1.r - c2.r) == 0) return -1;

    Tf base = angle(c2.o - c1.o);
    if (dcmp(d2 - rdif * rdif) == 0) {
        a.push_back(c1.point(base));
        b.push_back(c2.point(base));
        cnt++;
        return cnt;
    }

    Tf ang = acos((c1.r - c2.r) / sqrt(d2));
    a.push_back(c1.point(base + ang));
    b.push_back(c2.point(base + ang));
    cnt++;
    a.push_back(c1.point(base - ang));
    b.push_back(c2.point(base - ang));
    cnt++;

    if (dcmp(d2 - rsum * rsum) == 0) {
        a.push_back(c1.point(base));
        b.push_back(c2.point(PI + base));
        cnt++;
    } else if (dcmp(d2 - rsum * rsum) > 0) {
        Tf ang = acos((c1.r + c2.r) / sqrt(d2));
        a.push_back(c1.point(base + ang));
        b.push_back(c2.point(PI + base + ang));
        cnt++;
        a.push_back(c1.point(base - ang));
        b.push_back(c2.point(PI + base - ang));
        cnt++;
    }
    return cnt;
}
```

4.4 Convex

```
/// minkowski sum of two polygons in O(n)
Polygon minkowskiSum(Polygon A, Polygon B) {
    int n = A.size(), m = B.size();
```

```

rotate(A.begin(), min_element(A.begin(), A.end()), A.end());
rotate(B.begin(), min_element(B.begin(), B.end()), B.end());

A.push_back(A[0]);
B.push_back(B[0]);
for (int i = 0; i < n; i++) A[i] = A[i + 1] - A[i];
for (int i = 0; i < m; i++) B[i] = B[i + 1] - B[i];

Polygon C(n + m + 1);
C[0] = A.back() + B.back();
merge(A.begin(), A.end() - 1, B.begin(), B.end() - 1, C.begin() + 1,
      polarComp(Point(0, 0), Point(0, -1)));
for (int i = 1; i < C.size(); i++) C[i] = C[i] + C[i - 1];
C.pop_back();
return C;
}
// finds the rectangle with minimum area enclosing a
// convex polygon and
// the rectangle with minimum perimeter enclosing a
// convex polygon
// Tf Ti Same
pair<Tf, Tf> rotatingCalipersBoundingBox(const Polygon &p) {
    using Linear::distancePointLine;
    int n = p.size();
    int l = 1, r = 1, j = 1;
    Tf area = 1e100;
    Tf perimeter = 1e100;
    for (int i = 0; i < n; i++) {
        Point v = (p[(i + 1) % n] - p[i]) / length(p[(i + 1) % n] - p[i]);
        while (dcmp(dot(v, p[r % n] - p[i]) - dot(v, p[(r + 1) % n] - p[i])) < 0)
            r++;
        while (j < r || dcmp(cross(v, p[j % n] - p[i]) - cross(v, p[(j + 1) % n] - p[i])) < 0)
            j++;
        while (l < j || dcmp(dot(v, p[l % n] - p[i]) - dot(v, p[(l + 1) % n] - p[i])) > 0)
            l++;
        Tf w = dot(v, p[r % n] - p[i]) - dot(v, p[l % n] - p[i]);
        Tf h = distancePointLine(p[j % n], Line(p[i], p[(i + 1) % n]));
    }

```

```

        area = min(area, w * h);
        perimeter = min(perimeter, 2 * w + 2 * h);
    }
    return make_pair(area, perimeter);
}
// returns the left side of polygon u after cutting it by
// ray a->b
Polygon cutPolygon(Polygon u, Point a, Point b) {
    using Linear::lineLineIntersection;
    using Linear::onSegment;

    Polygon ret;
    int n = u.size();
    for (int i = 0; i < n; i++) {
        Point c = u[i], d = u[(i + 1) % n];
        if (dcmp(cross(b - a, c - a)) >= 0) ret.push_back(c);
        if (dcmp(cross(b - a, d - c)) != 0) {
            Point t;
            lineLineIntersection(a, b - a, c, d - c, t);
            if (onSegment(t, Segment(c, d))) ret.push_back(t);
        }
    }
    return ret;
}
// returns true if point p is in or on triangle abc
bool pointInTriangle(Point a, Point b, Point c, Point p) {
    return dcmp(cross(b - a, p - a)) >= 0 && dcmp(cross(c - b, p - b)) >= 0 &&
           dcmp(cross(a - c, p - c)) >= 0;
}
// pt must be in ccw order with no three collinear points
// returns inside = -1, on = 0, outside = 1
int pointInConvexPolygon(const Polygon &pt, Point p) {
    int n = pt.size();
    assert(n >= 3);

    int lo = 1, hi = n - 1;
    while (hi - lo > 1) {
        int mid = (lo + hi) / 2;
        if (dcmp(cross(pt[mid] - pt[0], p - pt[0])) > 0)
            lo = mid;
        else
            hi = mid;
    }

    bool in = pointInTriangle(pt[0], pt[lo], pt[hi], p);
    if (!in) return 1;
}

```

```

    if (dcmp(cross(pt[lo] - pt[lo - 1], p - pt[lo - 1])) == 0) return 0;
    if (dcmp(cross(pt[hi] - pt[lo], p - pt[lo])) == 0) return 0;
    if (dcmp(cross(pt[hi] - pt[(hi + 1) % n], p - pt[(hi + 1) % n])) == 0) return 0;
    return -1;
}
// Extreme Point for a direction is the farthest point in that direction
// u is the direction for extremeness
int extremePoint(const Polygon &poly, Point u) {
    int n = (int)poly.size();
    int a = 0, b = n;
    while (b - a > 1) {
        int c = (a + b) / 2;
        if (dcmp(dot(poly[c] - poly[(c + 1) % n], u)) >= 0 &&
            dcmp(dot(poly[c] - poly[(c - 1 + n) % n], u)) >= 0) {
            return c;
        }
    }

    bool a_up = dcmp(dot(poly[(a + 1) % n] - poly[a], u)) >= 0;
    bool c_up = dcmp(dot(poly[(c + 1) % n] - poly[c], u)) >= 0;
    bool a_above_c = dcmp(dot(poly[a] - poly[c], u)) > 0;

    if (a_up && !c_up)
        b = c;
    else if (!a_up && c_up)
        a = c;
    else if (a_up && c_up) {
        if (a_above_c)
            b = c;
        else
            a = c;
    } else {
        if (!a_above_c)
            b = c;
        else
            a = c;
    }
}

if (dcmp(dot(poly[a] - poly[(a + 1) % n], u)) > 0 &&
    dcmp(dot(poly[a] - poly[(a - 1 + n) % n], u)) > 0)
    return a;
return b % n;

```

```

}
// For a convex polygon p and a line l, returns a list of
// segments
// of p that touch or intersect line l.
// the i'th segment is considered (p[i], p[(i + 1) modulo
// |p|])
// #1 If a segment is collinear with the line, only that
// is returned
// #2 Else if l goes through i'th point, the i'th segment
// is added
// Complexity: O(lg |p|)
vector<int> lineConvexPolyIntersection(const Polygon &p,
    Line l) {
    assert((int)p.size() >= 3);
    assert(l.a != l.b);

    int n = p.size();
    vector<int> ret;

    Point v = l.b - l.a;
    int lf = extremePoint(p, rotate90(v));
    int rt = extremePoint(p, rotate90(v) * Ti(-1));
    int olf = orient(l.a, l.b, p[lf]);
    int ort = orient(l.a, l.b, p[rt]);

    if (!olf || !ort) {
        int idx = (!olf ? lf : rt);
        if (orient(l.a, l.b, p[(idx - 1 + n) % n]) == 0)
            ret.push_back((idx - 1 + n) % n);
        else
            ret.push_back(idx);
        return ret;
    }
    if (olf == ort) return ret;

    for (int i = 0; i < 2; ++i) {
        int lo = i ? rt : lf;
        int hi = i ? lf : rt;
        int olo = i ? ort : olf;

        while (true) {
            int gap = (hi - lo + n) % n;
            if (gap < 2) break;

            int mid = (lo + gap / 2) % n;
            int omid = orient(l.a, l.b, p[mid]);
            if (!omid) {
                lo = mid;
                break;
            }

```

```

        if (omid == olo)
            lo = mid;
        else
            hi = mid;
    }
    ret.push_back(lo);
}
return ret;
// Calculate [ACW, CW] tangent pair from an external
// point
constexpr int CW = -1, ACW = 1;
bool isGood(Point u, Point v, Point Q, int dir) {
    return orient(Q, u, v) != -dir;
}
Point better(Point u, Point v, Point Q, int dir) {
    return orient(Q, u, v) == dir ? u : v;
}
Point pointPolyTangent(const Polygon &pt, Point Q, int
    dir, int lo, int hi) {
    while (hi - lo > 1) {
        int mid = (lo + hi) / 2;
        bool pvs = isGood(pt[mid], pt[mid - 1], Q, dir);
        bool nxt = isGood(pt[mid], pt[mid + 1], Q, dir);

        if (pvs && nxt) return pt[mid];
        if (!pvs || !nxt) {
            Point p1 = pointPolyTangent(pt, Q, dir, mid + 1, hi
                );
            Point p2 = pointPolyTangent(pt, Q, dir, lo, mid -
                1);
            return better(p1, p2, Q, dir);
        }

        if (!pvs) {
            if (orient(Q, pt[mid], pt[lo]) == dir)
                hi = mid - 1;
            else if (better(pt[lo], pt[hi], Q, dir) == pt[lo])
                hi = mid - 1;
            else
                lo = mid + 1;
        }
        if (!nxt) {
            if (orient(Q, pt[mid], pt[lo]) == dir)
                lo = mid + 1;
            else if (better(pt[lo], pt[hi], Q, dir) == pt[lo])
                hi = mid - 1;
            else
                lo = mid + 1;
        }
    }
}

```

```

}

Point ret = pt[lo];
for (int i = lo + 1; i <= hi; i++) ret = better(ret, pt
    [i], Q, dir);
return ret;
}
// [ACW, CW] Tangent
pair<Point, Point> pointPolyTangents(const Polygon &pt,
    Point Q) {
    int n = pt.size();
    Point acw_tan = pointPolyTangent(pt, Q, ACW, 0, n - 1);
    Point cw_tan = pointPolyTangent(pt, Q, CW, 0, n - 1);
    return make_pair(acw_tan, cw_tan);
}

```

4.5 Polygon

```

typedef vector<Point> Polygon;
// removes redundant colinear points
// polygon can't be all colinear points
Polygon RemoveCollinear(const Polygon &poly) {
    Polygon ret;
    int n = poly.size();
    for (int i = 0; i < n; i++) {
        Point a = poly[i];
        Point b = poly[(i + 1) % n];
        Point c = poly[(i + 2) % n];
        if (dcmp(cross(b - a, c - b)) != 0 && (ret.empty() ||
            b != ret.back()))
            ret.push_back(b);
    }
    return ret;
}
// returns the signed area of polygon p of n vertices
Tf signedPolygonArea(const Polygon &p) {
    Tf ret = 0;
    for (int i = 0; i < (int)p.size() - 1; i++)
        ret += cross(p[i] - p[0], p[i + 1] - p[0]);
    return ret / 2;
}
// given a polygon p of n vertices, generates the convex
// hull in in CCW
// Tested on https://acm.timus.ru/problem.aspx?space=1&
// num=1185
// Caution: when all points are colinear AND
// removeRedundant == false
// output will be contain duplicate points (from upper
// hull) at back
Polygon convexHull(Polygon p, bool removeRedundant) {
    int check = removeRedundant ? 0 : -1;

```

```

sort(p.begin(), p.end());
p.erase(unique(p.begin(), p.end()), p.end());

int n = p.size();
Polygon ch(n + n);
int m = 0; // preparing lower hull
for (int i = 0; i < n; i++) {
    while (m > 1 &&
           dcmp(cross(ch[m - 1] - ch[m - 2], p[i] - ch[m - 1])) <= check)
        m--;
    ch[m++] = p[i];
}
int k = m; // preparing upper hull
for (int i = n - 2; i >= 0; i--) {
    while (m > k &&
           dcmp(cross(ch[m - 1] - ch[m - 2], p[i] - ch[m - 2])) <= check)
        m--;
    ch[m++] = p[i];
}
if (n > 1) m--;
ch.resize(m);
return ch;
}

// returns inside = -1, on = 0, outside = 1
int pointInPolygon(const Polygon &p, Point o) {
    using Linear::onSegment;
    int wn = 0, n = p.size();
    for (int i = 0; i < n; i++) {
        int j = (i + 1) % n;
        if (onSegment(o, Segment(p[i], p[j])) || o == p[i])
            return 0;
        int k = dcmp(cross(p[j] - p[i], o - p[i]));
        int d1 = dcmp(p[i].y - o.y);
        int d2 = dcmp(p[j].y - o.y);
        if (k > 0 && d1 <= 0 && d2 > 0) wn++;
        if (k < 0 && d2 <= 0 && d1 > 0) wn--;
    }
    return wn ? -1 : 1;
}

// Given a simple polygon p, and a line l, returns (x, y)
// x = longest segment of l in p, y = total length of l
// in p.
pair<Tf, Tf> linePolygonIntersection(Line l, const
    Polygon &p) {
    using Linear::lineLineIntersection;
    int n = p.size();
    vector<pair<Tf, int>> ev;
    for (int i = 0; i < n; ++i) {

```

```

        Point a = p[i], b = p[(i + 1) % n], z = p[(i - 1 + n)
            % n];
        int ora = orient(l.a, l.b, a), orb = orient(l.a, l.b,
            b),
            orz = orient(l.a, l.b, z);
        if (!ora) {
            Tf d = dot(a - l.a, l.b - l.a);
            if (orz && orb) {
                if (orz != orb) ev.emplace_back(d, 0);
                // else // Point Touch
            } else if (orz)
                ev.emplace_back(d, orz);
            else if (orb)
                ev.emplace_back(d, orb);
        } else if (ora == -orb) {
            Point ins;
            lineLineIntersection(l, Line(a, b), ins);
            ev.emplace_back(dot(ins - l.a, l.b - l.a), 0);
        }
    }
    sort(ev.begin(), ev.end());

    Tf ans = 0, len = 0, last = 0, tot = 0;
    bool active = false;
    int sign = 0;
    for (auto &qq : ev) {
        int tp = qq.second;
        Tf d = qq.first; // current Segment is (last, d)
        if (sign) { // On Border
            len += d - last;
            tot += d - last;
            ans = max(ans, len);
            if (tp != sign) active = !active;
            sign = 0;
        } else {
            if (active) { // Strictly Inside
                len += d - last;
                tot += d - last;
                ans = max(ans, len);
            }
            if (tp == 0)
                active = !active;
            else
                sign = tp;
        }
    }
    last = d;
    if (!active) len = 0;
}
ans /= length(l.b - l.a);
tot /= length(l.b - l.a);

```

```

    return {ans, tot};
}

4.6 Half Plane

using Linear::lineLineIntersection;
struct DirLine {
    Point p, v;
    Tf ang;
    DirLine() {}
    // Directed line containing point P in the direction v
    DirLine(Point p, Point v) : p(p), v(v) { ang = atan2(v.
        y, v.x); }
    bool operator<(const DirLine& u) const { return ang < u
        .ang; }
};
// returns true if point p is on the ccw-left side of ray
// l
bool onLeft(DirLine l, Point p) { return dcmp(cross(l.v,
    p - l.p)) >= 0; }

// Given a set of directed lines returns a polygon such
// that
// the polygon is the intersection by halfplanes created
// by the
// left side of the directed lines. MAY CONTAIN DUPLICATE
// POINTS
int halfPlaneIntersection(vector<DirLine>& li, Polygon&
    poly) {
    int n = li.size();
    sort(li.begin(), li.end());

    int first, last;
    Point* p = new Point[n];
    DirLine* q = new DirLine[n];
    q[first = last = 0] = li[0];

    for (int i = 1; i < n; i++) {
        while (first < last && !onLeft(li[i], p[last - 1]))
            last--;
        while (first < last && !onLeft(li[i], p[first]))
            first++;
        q[++last] = li[i];

        if (dcmp(cross(q[last].v, q[last - 1].v)) == 0) {
            last--;
            if (onLeft(q[last], li[i].p)) q[last] = li[i];
        }

        if (first < last)

```

```

    lineLineIntersection(q[last - 1].p, q[last - 1].v,
        q[last].p, q[last].v,
            p[last - 1]);
}

while (first < last && !onLeft(q[first], p[last - 1]))
    last--;
if (last - first <= 1) {
    delete[] p;
    delete[] q;
    poly.clear();
    return 0;
}
lineLineIntersection(q[last].p, q[last].v, q[first].p,
    q[first].v, p[last]);

int m = 0;
poly.resize(last - first + 1);
for (int i = first; i <= last; i++) poly[m++] = p[i];
delete[] p;
delete[] q;
return m;
}

```

5 Graph

5.1 Graph Template

```

struct edge {
    int u, v;
    edge(int u = 0, int v = 0) : u(u), v(v) {}
    int to(int node) { return u ^ v ^ node; }
};

struct graph {
    int n;
    vector<vector<int>> adj;
    vector<edge> edges;
    graph(int n = 0) : n(n), adj(n) {}
    void addEdge(int u, int v, bool dir = 1) {
        adj[u].push_back(edges.size());
        if (dir) adj[v].push_back(edges.size());
        edges.emplace_back(u, v);
    }
    int addNode() {
        adj.emplace_back();
        return n++;
    }
    edge &operator()(int idx) { return edges[idx]; }
    vector<int> &operator[](int u) { return adj[u]; }
};

```

5.2 SCC

```

typedef long long LL;
const LL N = 1e6 + 7;

bool vis[N];
vector<int> adj[N], adjr[N];
vector<int> order, component;
// tp = 0 ,finding topo order, tp = 1 , reverse edge
// traversal

void dfs(int u, int tp = 0) {
    vis[u] = true;
    if (tp) component.push_back(u);
    auto& ad = (tp ? adjr : adj);
    for (int v : ad[u])
        if (!vis[v]) dfs(v, tp);
    if (!tp) order.push_back(u);
}

int main() {
    for (int i = 1; i <= n; i++) {
        if (!vis[i]) dfs(i);
    }
    memset(vis, 0, sizeof vis);
    reverse(order.begin(), order.end());
    for (int i : order) {
        if (!vis[i]) {
            // one component is found
            dfs(i, 1), component.clear();
        }
    }
}

```

5.3 Tree All

```

using Tree = Graph;
namespace talgo {
int time;
void dfs(int u, int p, vec &par, vec &lvl, Tree &T) {
    for (int e : T[u]) {
        int v = T(e).to(u);
        if (v == p) continue;
        par[v] = u, lvl[v] = lvl[u] + 1;
        dfs(v, u, par, lvl, T);
    }
}

mat ancestorTable(vec &par) {
    int n = par.size(), sz = __lg(n) + 1;
    mat anc(sz, par);

    for (int k = 1; k < sz; k++) {

```

```

        for (int i = 0; i < n; i++) {
            anc[k][i] = anc[k - 1][anc[k - 1][i]];
        }
    }
    return anc;
}

int getAncestor(int u, int ht, mat &anc) {
    int sz = anc.size();

    for (int k = 0; k < sz; k++) {
        if (ht >> k & 1) u = anc[u][k];
    }
    return u;
}

bool isAncestor(int u, int par, vec &st, vec &en) {
    return st[par] <= st[u] and en[par] >= en[u];
}

int subtreeSize(int u, vec &st, vec &en) { return en[u] -
    st[u] + 1 >> 1; }

int lca(int u, int v, vec &lvl, mat &anc) {
    if (lvl[u] > lvl[v]) swap(u, v);

    for (int k = anc.size() - 1; ~k; k--) {
        if (lvl[u] + (1 << k) <= lvl[v]) v = anc[k][v];
    }
    if (u == v) return u;

    for (int k = anc.size() - 1; ~k; k--) {
        if (anc[k][u] != anc[k][v]) u = anc[k][u], v = anc[k][v];
    }
    return anc[0][u];
}

int dis(int u, int v, vec &lvl, mat &anc) {
    int g = lca(u, v, lvl, anc);
    return lvl[u] + lvl[v] - 2 * lvl[g];
}

namespace ct {
int getCentroid(int u, int p, int st, vec &sz, vec &blk,
    Tree &T) {
    for (int e : T[u]) {
        int v = T(e).to(u);
        if (v == p or blk[v] or sz[v] * 2 <= sz[st]) continue
        ;

```



```

    return getCentroid(v, u, st, sz, blk, T);
}
return u;
}
int compCalc(int u, int p, vec &sz, vec &blk, Tree &T) {
    sz[u] = 1;
    for (int e : T[u]) {
        int v = T(e).to(u);
        if (v == p or blk[v]) continue;
        sz[u] += compCalc(v, u, sz, blk, T);
    }
    return sz[u];
}

int decompose(int u, int p, vec &sz, vec &blk, Tree &T,
    Tree &CT) {
    compCalc(u, -1, sz, blk, T);
    u = getCentroid(u, -1, u, sz, blk, T);
    blk[u] = 1;
    for (int e : T[u]) {
        int v = T(e).to(u);
        if (blk[v]) continue;
        v = decompose(v, u, sz, blk, T, CT);
        CT.addEdge(u, v);
    }
    return u;
}

int getCentroidTree(int root, Tree &T, Tree &CT) {
    vec sz(T.n), blk(T.n);
    return decompose(root, -1, sz, blk, T, CT);
}
}

```

5.4 Euler Tour on Edge

```

// for simplicity, G[idx] contains the adjacency list of
// a node
// while G(e) is a reference to the e-th edge.
const int N = 2e5 + 5;
int in[N], out[N], fwd[N], bck[N];
int t = 0;
void dfs(graph &G, int node, int par) {
    out[node] = t;
    for (int e : G[node]) {
        int v = G(e).to(node);
        if (v == par) continue;
        fwd[e] = t++;
        dfs(G, v, node);
        bck[e] = t++;
    }
    in[node] = t - 1;
}

```

```

}
void init(graph &G, int node) {
    t = 0;
    dfs(G, node, node);
}

5.5 LCA In O(1)

/* LCA in O(1)
 * depth calculates weighted distance
 * level calculates distance by number of edges
 * Preprocessing in NlongN */
LL depth[N];
int level[N];

int st[N], en[N], LOG[N], par[N];
int a[N], id[N], table[L][N];

vector<PII> adj[N];
int n, root, Time, cur;

void init(int nodes, int root_) {
    n = nodes, root = root_, LOG[0] = LOG[1] = 0;
    for (int i = 2; i <= n; i++) LOG[i] = LOG[i >> 1] + 1;
    for (int i = 0; i <= n; i++) adj[i].clear();
}

void addEdge(int u, int v, int w) {
    adj[u].push_back(PII(v, w));
    adj[v].push_back(PII(u, w));
}

int lca(int u, int v) {
    if (en[u] > en[v]) swap(u, v);
    if (st[v] <= st[u] && en[u] <= en[v]) return v;

    int l = LOG[id[v] - id[u] + 1];
    int p1 = id[u], p2 = id[v] - (1 << l) + 1;
    int d1 = level[table[l][p1]], d2 = level[table[l][p2]];

    if (d1 < d2)
        return par[table[l][p1]];
    else
        return par[table[l][p2]];
}

LL dist(int u, int v) {
    int l = lca(u, v);
    return (depth[u] + depth[v] - (depth[l] * 2));
}

```

```

/* Euler tour */
void dfs(int u, int p) {
    st[u] = ++Time, par[u] = p;

    for (auto [v, w] : adj[u]) {
        if (v == p) continue;
        depth[v] = depth[u] + w;
        level[v] = level[u] + 1;
        dfs(v, u);
    }

    en[u] = ++Time;
    a[++cur] = u, id[u] = cur;
}

/* RMQ */
void pre() {
    cur = Time = 0, dfs(root, root);
    for (int i = 1; i <= n; i++) table[0][i] = a[i];

    for (int l = 0; l < L - 1; l++) {
        for (int i = 1; i <= n; i++) {
            table[l + 1][i] = table[l][i];

            bool C1 = (1 << l) + i <= n;
            bool C2 = level[table[l][i + (1 << l)]] < level[
                table[l][i]];

            if (C1 && C2) table[l + 1][i] = table[l][i + (1 <<
                l)];
        }
    }
}

```

5.6 HLD

```

const int N = 1e6 + 7;
template <typename DT>
struct Segtree {
    // write lazy segtree here
};
Segtree<int> tree(N);
vector<int> adj[N];
int depth[N], par[N], pos[N];
int head[N], heavy[N], cnt;

int dfs(int u, int p) {
    int SZ = 1, mxsz = 0, heavyc;
    depth[u] = depth[p] + 1;

    for (auto v : adj[u]) {

```



```

    if (v == p) continue;
    par[v] = u;
    int subsz = dfs(v, u);
    if (subsz > mxsz) heavy[u] = v, mxsz = subsz;
    SZ += subsz;
}
return SZ;
}

void decompose(int u, int h) {
    head[u] = h, pos[u] = ++cnt;
    if (heavy[u] != -1) decompose(heavy[u], h);

    for (int v : adj[u]) {
        if (v == par[u]) continue;
        if (v != heavy[u]) decompose(v, v);
    }
}

int query(int a, int b) {
    int ret = 0;
    for (; head[a] != head[b]; b = par[head[b]]) {
        if (depth[head[a]] > depth[head[b]]) swap(a, b);
        ret += tree.query(1, 0, cnt, pos[head[b]], pos[b]);
    }

    if (depth[a] > depth[b]) swap(a, b);
    ret += tree.query(1, 0, cnt, pos[a], pos[b]);
    return ret;
}

```

5.7 Dinic Max Flow

```

// flow with demand(lower bound) only for DAG
// create new src and sink
// add_edge(new src, u, sum(in_demand[u]))
// add_edge(u, new sink, sum(out_demand[u]))
// add_edge(old sink, old src, inf)
// if (sum of lower bound == flow) then demand satisfied
// flow in every edge i = demand[i] + e.flow

```

```

using Ti = long long;
const Ti INF = 1LL << 60;
struct edge {
    int v, u;
    Ti cap, flow = 0;
    edge(int v, int u, Ti cap) : v(v), u(u), cap(cap) {}
};

const int N = 1e5 + 50;
vector<edge> edges;
vector<int> adj[N];
int m = 0, n;
int level[N], ptr[N];

```

```

queue<int> q;
bool bfs(int s, int t) {
    for (q.push(s), level[s] = 0; !q.empty(); q.pop()) {
        for (int id : adj[q.front()]) {
            auto &ed = edges[id];
            if (ed.cap - ed.flow > 0 and level[ed.u] == -1)
                level[ed.u] = level[ed.v] + 1, q.push(ed.u);
        }
    }
    return level[t] != -1;
}

Ti dfs(int v, Ti pushed, int t) {
    if (pushed == 0) return 0;
    if (v == t) return pushed;
    for (int &cid = ptr[v]; cid < adj[v].size(); cid++) {
        int id = adj[v][cid];
        auto &ed = edges[id];
        if (level[v] + 1 != level[ed.u] || ed.cap - ed.flow < 1) continue;
        Ti tr = dfs(ed.u, min(pushed, ed.cap - ed.flow), t);
        if (tr == 0) continue;
        ed.flow += tr;
        edges[id ^ 1].flow -= tr;
        return tr;
    }
    return 0;
}

void init(int nodes) {
    m = 0, n = nodes;
    for (int i = 0; i < n; i++) level[i] = -1, ptr[i] = 0,
        adj[i].clear();
}

void addEdge(int v, int u, Ti cap) {
    edges.emplace_back(v, u, cap), adj[v].push_back(m++);
    edges.emplace_back(u, v, 0), adj[u].push_back(m++);
}

Ti maxFlow(int s, int t) {
    Ti f = 0;
    for (auto &ed : edges) ed.flow = 0;
    for (; bfs(s, t); memset(level, -1, n * 4)) {
        for (memset(ptr, 0, n * 4); Ti pushed = dfs(s, INF, t); f += pushed);
    }
    return f;
}

```

5.8 Min Cost Max Flow

```

mt19937 rnd(chrono::steady_clock::now().time_since_epoch
().count());

```

```

const LL inf = 1e9;
struct edge {
    int v, rev;
    LL cap, cost, flow;
    edge() {}
    edge(int v, int rev, LL cap, LL cost)
        : v(v), rev(rev), cap(cap), cost(cost), flow(0) {}
};

struct mcmf {
    int src, sink, n;
    vector<int> par, idx, Q;
    vector<bool> inq;
    vector<LL> dis;
    vector<vector<edge>> g;
    mcmf() {}
    mcmf(int src, int sink, int n)
        : src(src),
          sink(sink),
          n(n),
          par(n),
          idx(n),
          inq(n),
          dis(n),
          g(n),
          Q(10000005) {} // use Q(n) if not using random
    void add_edge(int u, int v, LL cap, LL cost, bool
        directed = true) {
        edge _u = edge(v, g[v].size(), cap, cost);
        edge _v = edge(u, g[u].size(), 0, -cost);
        g[u].pb(_u);
        g[v].pb(_v);
        if (!directed) add_edge(v, u, cap, cost, true);
    }

    bool spfa() {
        for (int i = 0; i < n; i++) {
            dis[i] = inf, inq[i] = false;
        }
        int f = 0, l = 0;
        dis[src] = 0, par[src] = -1, Q[l++] = src, inq[src] = true;
        while (f < l) {
            int u = Q[f++];
            for (int i = 0; i < g[u].size(); i++) {
                edge &e = g[u][i];
                if (e.cap <= e.flow) continue;
                if (dis[e.v] > dis[u] + e.cost) {
                    dis[e.v] = dis[u] + e.cost;
                    par[e.v] = u, idx[e.v] = i;
                    if (!inq[e.v]) inq[e.v] = true, Q[l++] = e.v;
                    // if (!inq[e.v]) {

```

```

    // inq[e.v] = true;
    // if (f && rnd() & 7) Q[--f] = e.v;
    // else Q[l++] = e.v;
    // }
}
inq[u] = false;
}
return (dis[sink] != inf);
}
pair<LL, LL> solve() {
    LL mincost = 0, maxflow = 0;
    while (spfa()) {
        LL bottleneck = inf;
        for (int u = par[sink], v = idx[sink]; u != -1; v =
            idx[u], u = par[u]) {
            edge &e = g[u][v];
            bottleneck = min(bottleneck, e.cap - e.flow);
        }
        for (int u = par[sink], v = idx[sink]; u != -1; v =
            idx[u], u = par[u]) {
            edge &e = g[u][v];
            e.flow += bottleneck;
            g[e.v][e.rev].flow -= bottleneck;
        }
        mincost += bottleneck * dis[sink], maxflow +=
            bottleneck;
    }
    return make_pair(mincost, maxflow);
}
};
// want to minimize cost and don't care about flow
// add edge from sink to dummy sink (cap = inf, cost = 0)
// add edge from source to sink (cap = inf, cost = 0)
// run mcmf, cost returned is the minimum cost

```

5.9 Block Cut Tree

```

vector<vector<int>> components;
vector<int> cutpoints, start, low;
vector<bool> is_cutpoint;
stack<int> st;
void find_cutpoints(int node, graph &G, int par = -1, int
    d = 0) {
    low[node] = start[node] = d++;
    st.push(node);
    int cnt = 0;
    for (int e : G[node])
        if (int to = G(e).to(node); to != par) {
            if (start[to] == -1) {
                find_cutpoints(to, G, node, d + 1);
            }
        }
    }
}

```

```

    cnt++;
    if (low[to] >= start[node]) {
        is_cutpoint[node] = par != -1 or cnt > 1;
        components.push_back({node}); // starting a new
            block with the point
        while (st.top() != node)
            components.back().push_back(st.top()), st.pop
                ();
    }
    }
    low[node] = min(low[node], low[to]);
}
}
graph tree;
vector<int> id;
void init(graph &G) {
    int n = G.n;
    start.assign(n, -1), low.resize(n), is_cutpoint.resize(
        n), id.assign(n, -1);
    find_cutpoints(0, G);
    for (int u = 0; u < n; ++u)
        if (is_cutpoint[u]) id[u] = tree.addNode();
    for (auto &comp : components) {
        int node = tree.addNode();
        for (int u : comp)
            if (!is_cutpoint[u])
                id[u] = node;
            else
                tree.addEdge(node, id[u]);
    }
    if (id[0] == -1) // corner - 1
        id[0] = tree.addNode();
}
}

```

5.10 Bridge Tree

```

vector<vector<int>> components;
vector<int> depth, low;
stack<int> st;
vector<int> id;
vector<edge> bridges;
graph tree;
void find_bridges(int node, graph &G, int par = -1, int d
    = 0) {
    low[node] = depth[node] = d;
    st.push(node);
    for (int id : G[node]) {
        int to = G(id).to(node);
        if (par != to) {
            if (depth[to] == -1) {
                find_bridges(to, G, node, d + 1);
            }
        }
    }
}

```

```

    if (low[to] > depth[node]) {
        bridges.emplace_back(node, to);
        components.push_back({});
        for (int x = -1; x != to; x = st.top(), st.pop()
            )
            components.back().push_back(st.top());
    }
    low[node] = min(low[node], low[to]);
}
}
if (par == -1) {
    components.push_back({});
    while (!st.empty()) components.back().push_back(st.
        top()), st.pop();
}
}
graph &create_tree() {
    for (auto &comp : components) {
        int idx = tree.addNode();
        for (auto &e : comp) id[e] = idx;
    }
    for (auto &[l, r] : bridges) tree.addEdge(id[l], id[r])
        ;
    return tree;
}
void init(graph &G) {
    int n = G.n;
    depth.assign(n, -1), id.assign(n, -1), low.resize(n);
    for (int i = 0; i < n; i++)
        if (depth[i] == -1) find_bridges(i, G);
}
}

```

5.11 Tree Isomorphism

```

mp["01"] = 1;
ind = 1;
int dfs(int u, int p) {
    int cnt = 0;
    vector<int> vs;
    for (auto v : g1[u]) {
        if (v != p) {
            int got = dfs(v, u);
            vs.pb(got);
            cnt++;
        }
    }
    if (!cnt) return 1;

    sort(vs.begin(), vs.end());
    string s = "0";
}

```

```

for (auto i : vs) s += to_string(i);
vs.clear();
s.pb('1');
if (mp.find(s) == mp.end()) mp[s] = ++ind;
int ret = mp[s];
return ret;
}

```

6 Math

6.1 Combi

```

array<int, N + 1> fact, inv, inv_fact;
void init() {
    fact[0] = inv_fact[0] = 1;
    for (int i = 1; i <= N; i++) {
        inv[i] = i == 1 ? 1 : (LL)inv[i - mod % i] * (mod / i + 1) % mod;
        fact[i] = (LL)fact[i - 1] * i % mod;
        inv_fact[i] = (LL)inv_fact[i - 1] * inv[i] % mod;
    }
}
LL C(int n, int r) {
    return (r < 0 or r > n) ? 0 : (LL)fact[n] * inv_fact[r] % mod * inv_fact[n - r] % mod;
}

```

6.2 Linear Sieve

```

const int N = 1e7;
vector<int> primes;
int spf[N + 5], phi[N + 5], NOD[N + 5], cnt[N + 5], POW[N + 5];
bool prime[N + 5];
int SOD[N + 5];
void init() {
    fill(prime + 2, prime + N + 1, 1);
    SOD[1] = NOD[1] = phi[1] = spf[1] = 1;
    for (LL i = 2; i <= N; i++) {
        if (prime[i]) {
            primes.push_back(i), spf[i] = i;
            phi[i] = i - 1;
            NOD[i] = 2, cnt[i] = 1;
            SOD[i] = i + 1, POW[i] = i;
        }
        for (auto p : primes) {
            if (p * i > N or p > spf[i]) break;
            prime[p * i] = false, spf[p * i] = p;
            if (i % p == 0) {
                phi[p * i] = p * phi[i];
                NOD[p * i] = NOD[i] / (cnt[i] + 1) * (cnt[i] + 2);
                cnt[p * i] = cnt[i] + 1;
            }
        }
    }
}

```

```

SOD[p * i] = SOD[i] / SOD[POW[i]] * (SOD[POW[i]] + p * POW[i]),
POW[p * i] = p * POW[i];
break;
} else {
    phi[p * i] = phi[p] * phi[i];
    NOD[p * i] = NOD[p] * NOD[i], cnt[p * i] = 1;
    SOD[p * i] = SOD[p] * SOD[i], POW[p * i] = p;
}
}
}
}

```

6.3 Pollard Rho

```

LL mul(LL a, LL b, LL mod) {
    return (__int128)a * b % mod;
    // LL ans = a * b - mod * (LL) (1.L / mod * a * b);
    // return ans + mod * (ans < 0) - mod * (ans >= (LL) mod);
}
LL bigmod(LL num, LL pow, LL mod) {
    LL ans = 1;
    for (; pow > 0; pow >>= 1, num = mul(num, num, mod))
        if (pow & 1) ans = mul(ans, num, mod);
    return ans;
}
bool is_prime(LL n) {
    if (n < 2 or n % 6 % 4 != 1) return (n | 1) == 3;
    LL a[] = {2, 325, 9375, 28178, 450775, 9780504, 1795265022};
    LL s = __builtin_ctzll(n - 1), d = n >> s;
    for (LL x : a) {
        LL p = bigmod(x % n, d, n), i = s;
        for (; p != 1 and p != n - 1 and x % n and i--; p = mul(p, p, n))
            ;
        if (p != n - 1 and i != s) return false;
    }
    return true;
}
LL get_factor(LL n) {
    auto f = [&](LL x) { return mul(x, x, n) + 1; };
    LL x = 0, y = 0, t = 0, prod = 2, i = 2, q;
    for (; t++ % 40 or gcd(prod, n) == 1; x = f(x), y = f(f(f(y))) {
        (x == y) ? x = i++, y = f(x) : 0;
        prod = (q = mul(prod, max(x, y) - min(x, y), n)) ? q : prod;
    }
    return gcd(prod, n);
}

```

```

}
map<LL, int> factorize(LL n) {
    map<LL, int> res;
    if (n < 2) return res;
    LL small_primes[] = {2, 3, 5, 7, 11, 13, 17, 19, 23, 29, 31, 37, 41, 43, 47, 53, 59, 61, 67, 71, 73, 79, 83, 89, 97};
    for (LL p : small_primes)
        for (; n % p == 0; n /= p, res[p]++)
            ;
    auto _factor = [&](LL n, auto &_factor) {
        if (n == 1) return;
        if (is_prime(n))
            res[n]++;
        else {
            LL x = get_factor(n);
            _factor(x, _factor);
            _factor(n / x, _factor);
        }
    };
    _factor(n, _factor);
    return res;
}

```

6.4 Chinese Remainder Theorem

```

// given a, b will find solutions for
// ax + by = 1
tuple<LL, LL, LL> EGCD(LL a, LL b) {
    if (b == 0)
        return {1, 0, a};
    else {
        auto [x, y, g] = EGCD(b, a % b);
        return {y, x - a / b * y, g};
    }
}
// given modulo equations, will apply CRT
PLL CRT(vector<PLL> &v) {
    LL V = 0, M = 1;
    for (auto &[v, m] : v) { // value % mod
        auto [x, y, g] = EGCD(M, m);
        if ((v - V) % g != 0) return {-1, 0};
        V += x * (v - V) / g % (m / g) * M, M *= m / g;
        V = (V % M + M) % M;
    }
    return make_pair(V, M);
}

```

6.5 Mobius Function

```

const int N = 1e6 + 5;
int mob[N];
void mobius() {
    memset(mob, -1, sizeof mob);
    mob[1] = 1;
    for (int i = 2; i < N; i++)
        if (mob[i]) {
            for (int j = i + i; j < N; j += i) mob[j] -= mob[i];
        }
}

```

6.6 FFT

```

using CD = complex<double>;
typedef long long LL;
const double PI = acos(-1.0L);

int N;
vector<int> perm;
vector<CD> wp[2];
void precalculate(int n) {
    assert((n & (n - 1)) == 0), N = n;
    perm = vector<int>(N, 0);
    for (int k = 1; k < N; k <= 1) {
        for (int i = 0; i < k; i++) {
            perm[i] <= 1;
            perm[i + k] = 1 + perm[i];
        }
    }
    wp[0] = wp[1] = vector<CD>(N);
    for (int i = 0; i < N; i++) {
        wp[0][i] = CD(cos(2 * PI * i / N), sin(2 * PI * i / N));
        wp[1][i] = CD(cos(2 * PI * i / N), -sin(2 * PI * i / N));
    }
}
void fft(vector<CD> &v, bool invert = false) {
    if (v.size() != perm.size()) precalculate(v.size());
    for (int i = 0; i < N; i++)
        if (i < perm[i]) swap(v[i], v[perm[i]]);
    for (int len = 2; len <= N; len *= 2) {
        for (int i = 0, d = N / len; i < N; i += len) {
            for (int j = 0, idx = 0; j < len / 2; j++, idx += d) {
                CD x = v[i + j];
                CD y = wp[invert][idx] * v[i + j + len / 2];
                v[i + j] = x + y;
                v[i + j + len / 2] = x - y;
            }
        }
    }
}

```

```

    }
}
if (invert) {
    for (int i = 0; i < N; i++) v[i] /= N;
}
}
void pairfft(vector<CD> &a, vector<CD> &b, bool invert = false) {
    int N = a.size();
    vector<CD> p(N);
    for (int i = 0; i < N; i++) p[i] = a[i] + b[i] * CD(0, 1);
    fft(p, invert);
    p.push_back(p[0]);
    for (int i = 0; i < N; i++) {
        if (invert) {
            a[i] = CD(p[i].real(), 0);
            b[i] = CD(p[i].imag(), 0);
        } else {
            a[i] = (p[i] + conj(p[N - i])) * CD(0.5, 0);
            b[i] = (p[i] - conj(p[N - i])) * CD(0, -0.5);
        }
    }
}
vector<LL> multiply(const vector<LL> &a, const vector<LL> &b) {
    int n = 1;
    while (n < a.size() + b.size()) n <= 1;
    vector<CD> fa(a.begin(), a.end()), fb(b.begin(), b.end());
    fa.resize(n);
    fb.resize(n);
    // fft(fa); fft(fb);
    pairfft(fa, fb);
    for (int i = 0; i < n; i++) fa[i] = fa[i] * fb[i];
    fft(fa, true);
    vector<LL> ans(n);
    for (int i = 0; i < n; i++) ans[i] = round(fa[i].real());
    return ans;
}
const int M = 1e9 + 7, B = sqrt(M) + 1;
vector<LL> anyMod(const vector<LL> &a, const vector<LL> &b) {
    int n = 1;
    while (n < a.size() + b.size()) n <= 1;
    vector<CD> al(n), ar(n), bl(n), br(n);
    for (int i = 0; i < a.size(); i++) al[i] = a[i] % M / B, ar[i] = a[i] % M % B;
}

```

```

for (int i = 0; i < b.size(); i++) bl[i] = b[i] % M / B, br[i] = b[i] % M % B;
pairfft(al, ar);
pairfft(bl, br);
// fft(al); fft(ar); fft(bl); fft(br);
for (int i = 0; i < n; i++) {
    CD ll = (al[i] * bl[i]), lr = (al[i] * br[i]);
    CD rl = (ar[i] * bl[i]), rr = (ar[i] * br[i]);
    al[i] = ll;
    ar[i] = lr;
    bl[i] = rl;
    br[i] = rr;
}
pairfft(al, ar, true);
pairfft(bl, br, true);
// fft(al, true); fft(ar, true); fft(bl, true);
    fft(br, true);
vector<LL> ans(n);
for (int i = 0; i < n; i++) {
    LL right = round(br[i].real()), left = round(al[i].real());
    ;
    LL mid = round(round(bl[i].real()) + round(ar[i].real()));
    ans[i] = ((left % M) * B * B + (mid % M) * B + right) % M;
}
return ans;
}

```

6.7 NTT

```

const LL N = 1 << 18;
const LL MOD = 786433;

vector<LL> P[N];
LL rev[N], w[N | 1], a[N], b[N], inv_n, g;
LL Pow(LL b, LL p) {
    LL ret = 1;
    while (p) {
        if (p & 1) ret = (ret * b) % MOD;
        b = (b * b) % MOD;
        p >>= 1;
    }
    return ret;
}
LL primitive_root(LL p) {
    vector<LL> factor;
    LL phi = p - 1, n = phi;
    for (LL i = 2; i * i <= n; i++) {
        if (n % i) continue;
    }
}

```

```

    factor.emplace_back(i);
    while (n % i == 0) n /= i;
}
if (n > 1) factor.emplace_back(n);
for (LL res = 2; res <= p; res++) {
    bool ok = true;
    for (LL i = 0; i < factor.size() && ok; i++)
        ok &= Pow(res, phi / factor[i]) != 1;
    if (ok) return res;
}
return -1;
}

void prepare(LL n) {
    LL sz = abs(31 - __builtin_clz(n));
    LL r = Pow(g, (MOD - 1) / n);
    inv_n = Pow(n, MOD - 2);
    w[0] = w[n] = 1;
    for (LL i = 1; i < n; i++) w[i] = (w[i - 1] * r) % MOD;
    for (LL i = 1; i < n; i++)
        rev[i] = (rev[i >> 1] >> 1) | ((i & 1) << (sz - 1));
}

void NTT(LL *a, LL n, LL dir = 0) {
    for (LL i = 1; i < n - 1; i++)
        if (i < rev[i]) swap(a[i], a[rev[i]]);
    for (LL m = 2; m <= n; m <= 1) {
        for (LL i = 0; i < n; i += m) {
            for (LL j = 0; j < (m >> 1); j++) {
                LL &u = a[i + j], &v = a[i + j + (m >> 1)];
                LL t = v * w[dir ? n - n / m * j : n / m * j] %
                    MOD;
                v = u - t < 0 ? u - t + MOD : u - t;
                u = u + t >= MOD ? u + t - MOD : u + t;
            }
        }
    }
    if (dir)
        for (LL i = 0; i < n; i++) a[i] = (inv_n * a[i]) %
            MOD;
}

vector<LL> mul(vector<LL> p, vector<LL> q) {
    LL n = p.size(), m = q.size();
    LL t = n + m - 1, sz = 1;
    while (sz < t) sz <= 1;
    prepare(sz);

    for (LL i = 0; i < n; i++) a[i] = p[i];
    for (LL i = 0; i < m; i++) b[i] = q[i];
    for (LL i = n; i < sz; i++) a[i] = 0;
    for (LL i = m; i < sz; i++) b[i] = 0;

```

```

    NTT(a, sz);
    NTT(b, sz);
    for (LL i = 0; i < sz; i++) a[i] = (a[i] * b[i]) % MOD;
    NTT(a, sz, 1);

    vector<LL> c(a, a + sz);
    while (c.size() && c.back() == 0) c.pop_back();
    return c;
}

```

6.8 WalshHadamard

```

#include <bits/stdc++.h>
using namespace std;
typedef long long LL;
#define bitwiseXOR 1
// #define bitwiseAND 2
// #define bitwiseOR 3
const LL MOD = 30011;

```

```

LL BigMod(LL b, LL p) {
    LL ret = 1;
    while (p > 0) {
        if (p % 2 == 1) {
            ret = (ret * b) % MOD;
        }
        p = p / 2;
        b = (b * b) % MOD;
    }
    return ret % MOD;
}

```

```

void FWHT(vector<LL>& p, bool inverse) {
    LL n = p.size();
    assert((n & (n - 1)) == 0);

```

```

    for (LL len = 1; 2 * len <= n; len <= 1) {
        for (LL i = 0; i < n; i += len + len) {
            for (LL j = 0; j < len; j++) {
                LL u = p[i + j];
                LL v = p[i + len + j];

```

```

#ifdef bitwiseXOR
        p[i + j] = (u + v) % MOD;
        p[i + len + j] = (u - v + MOD) % MOD;
#endif // bitwiseXOR

```

```

#ifdef bitwiseAND
        if (!inverse) {
            p[i + j] = v % MOD;
            p[i + len + j] = (u + v) % MOD;

```

```

        } else {
            p[i + j] = (-u + v) % MOD;
            p[i + len + j] = u % MOD;
        }
#endif // bitwiseAND

```

```

#ifdef bitwiseOR
        if (!inverse) {
            p[i + j] = u + v;
            p[i + len + j] = u;
        } else {
            p[i + j] = v;
            p[i + len + j] = u - v;
        }
#endif // bitwiseOR
    }
}

```

```

#ifdef bitwiseXOR
    if (inverse) {
        LL val = BigMod(n, MOD - 2); // Option 2: Exclude
        for (LL i = 0; i < n; i++) {
            // assert(p[i]%n==0); //Option 2: Include
            p[i] = (p[i] * val) % MOD; // Option 2: p[i]/=n;
        }
    }
#endif // bitwiseXOR
}

```

6.9 Berlekamp Massey

```

struct berlekamp_massey { // for linear recursion
    typedef long long LL;
    static const int SZ = 2e5 + 5;
    static const int MOD = 1e9 + 7; /// mod must be a prime
    LL m, a[SZ], h[SZ], t_[SZ], s[SZ], t[SZ];
    // bigmod goes here
    inline vector<LL> BM( vector<LL> &x ) {
        LL lf, ld;
        vector<LL> ls, cur;
        for (int i = 0; i < int(x.size()); ++i) {
            LL t = 0;
            for (int j = 0; j < int(cur.size()); ++j) t = (t
                + x[i - j - 1] * cur[j]) % MOD;
            if ( (t - x[i]) % MOD == 0 ) continue;
            if ( !cur.size() ) {
                cur.resize( i + 1 );
                lf = i; ld = (t - x[i]) % MOD;
                continue;
            }

```

```

    LL k = -(x[i] - t) * bigmod( ld , MOD - 2 , MOD ) %
        MOD;
    vector <LL> c(i - lf - 1);
    c.push_back( k );
    for ( int j = 0; j < int(ls.size()); ++j ) c.
        push_back(-ls[j] * k % MOD);
    if ( c.size() < cur.size() ) c.resize( cur.size() )
        ;
    for ( int j = 0; j < int(cur.size()); ++j ) c[j] =
        (c[j] + cur[j]) % MOD;
    if (i - lf + (int)ls.size() >= (int)cur.size() ) ls
        = cur, lf = i, ld = (t - x[i]) % MOD;
    cur = c;
}
for ( int i = 0; i < int(cur.size()); ++i ) cur[i] =
    (cur[i] % MOD + MOD) % MOD;
return cur;
}
inline void mull( LL *p , LL *q ) {
    for ( int i = 0; i < m + m; ++i ) t_[i] = 0;
    for ( int i = 0; i < m; ++i ) if ( p[i] )
        for ( int j = 0; j < m; ++j ) t_[i + j] = (t_[i +
            j] + p[i] * q[j]) % MOD;
    for ( int i = m + m - 1; i >= m; --i ) if ( t_[i] )
        for ( int j = m - 1; ~j; --j ) t_[i - j - 1] = (
            t_[i - j - 1] + t_[i] * h[j]) % MOD;
    for ( int i = 0; i < m; ++i ) p[i] = t_[i];
}
inline LL calc( LL K ) {
    for ( int i = m; ~i; --i ) s[i] = t[i] = 0;
    s[0] = 1; if ( m != 1 ) t[1] = 1; else t[0] = h[0];
    while ( K ) {
        if ( K & 1 ) mull( s , t );
        mull( t , t ); K >>= 1;
    }
    LL su = 0;
    for ( int i = 0; i < m; ++i ) su = (su + s[i] * a[i])
        % MOD;
    return (su % MOD + MOD) % MOD;
}
/// already calculated upto k , now calculate upto n.
inline vector <LL> process( vector <LL> &x , int n ,
    int k ) {
    auto re = BM( x );
    x.resize( n + 1 );
    for ( int i = k + 1; i <= n; ++i ) {
        for ( int j = 0; j < re.size(); j++ ) {
            x[i] += 1LL * x[i - j - 1] % MOD * re[j] % MOD; x
                [i] %= MOD;
        }
    }
}

```

```

    }
    return x;
}
inline LL work( vector <LL> &x , LL n ) {
    if ( n < int(x.size()) ) return x[n] % MOD;
    vector <LL> v = BM( x ); m = v.size(); if ( !m )
        return 0;
    for ( int i = 0; i < m; ++i ) h[i] = v[i], a[i] = x[i
        ];
    return calc( n ) % MOD;
}
} rec;
vector <LL> v;
void solve() {
    int n;
    cin >> n;
    cout << rec.work(v, n - 1) << endl;
}

```

6.10 Lagrange

```

// p is a polynomial with n points.
// p(0), p(1), p(2), ... p(n-1) are given.
// Find p(x).
LL Lagrange(vector<LL> &p, LL x) {
    LL n = p.size(), L, i, ret;
    if (x < n) return p[x];
    L = 1;
    for (i = 1; i < n; ++i) {
        L = (L * (x - i)) % MOD;
        L = (L * bigmod(MOD - i, MOD - 2)) % MOD;
    }
    ret = (L * p[0]) % MOD;
    for (i = 1; i < n; ++i) {
        L = (L * (x - i + 1)) % MOD;
        L = (L * bigmod(x - i, MOD - 2)) % MOD;
        L = (L * bigmod(i, MOD - 2)) % MOD;
        L = (L * (MOD + i - n)) % MOD;
        ret = (ret + L * p[i]) % MOD;
    }
    return ret;
}

```

6.11 Shanks' Baby Step, Giant Step

```

// Finds  $a^x = b \pmod p$ 

LL bigmod(LL b, LL p, LL m) {
    LL babyStepGiantStep(LL a, LL b, LL p) {
        LL i, j, c, sq = sqrt(p);
        map<LL, LL> babyTable;
    }
}

```

```

for (j = 0, c = 1; j <= sq; j++, c = (c * a) % p)
    babyTable[c] = j;

LL giant = bigmod(a, sq * (p - 2), p);

for (i = 0, c = 1; i <= sq; i++, c = (c * giant) % p) {
    if (babyTable.find((c * b) % p) != babyTable.end())
        return i * sq + babyTable[(c * b) % p];
}

return -1;
}

```

6.12 Xor Basis

```

struct XorBasis {
    static const int sz = 64;
    array<ULL, sz> base = {0}, back;
    array<int, sz> pos;
    void insert(ULL x, int p) {
        ULL cur = 0;
        for (int i = sz - 1; ~i; i--)
            if (x >> i & 1) {
                if (!base[i]) {
                    base[i] = x, back[i] = cur, pos[i] = p;
                    break;
                } else x ^= base[i], cur |= 1ULL << i;
            }
    }
    pair<ULL, vector<int>> construct(ULL mask) {
        ULL ok = 0, x = mask;
        for (int i = sz - 1; ~i; i--)
            if (mask >> i & 1 and base[i]) mask ^= base[i], ok
                |= 1ULL << i;
        vector<int> ans;
        for (int i = 0; i < sz; i++)
            if (ok >> i & 1) {
                ans.push_back(pos[i]);
                ok ^= back[i];
            }
        return {x ^ mask, ans};
    }
};

```

7 String

7.1 Aho Corasick

```

struct AC {
    int N, P;
    const int A = 26;
    vector<vector<int>> next;
}

```



```

vector<int> link, out_link;
vector<vector<int>> out;
AC() : N(0), P(0) { node(); }
int node() {
    next.emplace_back(A, 0);
    link.emplace_back(0);
    out_link.emplace_back(0);
    out.emplace_back(0);
    return N++;
}
inline int get(char c) { return c - 'a'; }
int add_pattern(const string T) {
    int u = 0;
    for (auto c : T) {
        if (!next[u][get(c)]) next[u][get(c)] = node();
        u = next[u][get(c)];
    }
    out[u].push_back(P);
    return P++;
}
void compute() {
    queue<int> q;
    for (q.push(0); !q.empty(); ) {
        int u = q.front(); q.pop();
        for (int c = 0; c < A; ++c) {
            int v = next[u][c];
            if (!v) next[u][c] = next[link[u]][c];
            else {
                link[v] = u ? next[link[u]][c] : 0;
                out_link[v] = out[link[v]].empty() ?
                    out_link[link[v]] : link[v];
                q.push(v);
            }
        }
    }
}
int advance(int u, char c) {
    while (u && !next[u][get(c)]) u = link[u];
    u = next[u][get(c)];
    return u;
}
void match(const string S) {
    int u = 0;
    for (auto c : S) {
        u = advance(u, c);
        for (int v = u; v; v = out_link[v]) {
            for (auto p : out[v]) cout << "match " << p <<
                endl;
        }
    }
}

```

```

}
};
int main() {
    AC aho; int n; cin >> n;
    while (n--) {
        string s; cin >> s;
        aho.add_pattern(s);
    }
    aho.compute(); string text;
    cin >> text; aho.match(text);
    return 0;
}

```

7.2 Double hash

```

// define +, -, * for (PLL, LL) and (PLL, PLL), % for (
    PLL, PLL);
PLL base(1949313259, 1997293877);
PLL mod(2091573227, 2117566807);

PLL power(PLL a, LL p) {
    PLL ans = PLL(1, 1);
    for(; p; p >>= 1, a = a * a % mod) {
        if(p & 1) ans = ans * a % mod;
    }
    return ans;
}

PLL inverse(PLL a) { return power(a, (mod.ff - 1) * (mod.
    ss - 1) - 1); }
PLL inv_base = inverse(base);
PLL val;
vector<PLL> P;

void hash_init(int n) {
    P.resize(n + 1);
    P[0] = PLL(1, 1);
    for (int i = 1; i <= n; i++) P[i] = (P[i - 1] * base) %
        mod;
}

PLL append(PLL cur, char c) { return (cur * base + c) %
    mod; }
// prepends c to string with size k
PLL prepend(PLL cur, int k, char c) { return (P[k] * c +
    cur) % mod; }
// replaces the i-th (0-indexed) character from right
    from a to b;
PLL replace(PLL cur, int i, char a, char b) {
    cur = (cur + P[i] * (b - a)) % mod;
    return (cur + mod) % mod;
}

```

```

// Erases c from the back of the string
PLL pop_back(PLL hash, char c) {
    return ((hash - c) * inv_base) % mod + mod;
}
// Erases c from front of the string with size len
PLL pop_front(PLL hash, int len, char c) {
    return ((hash - P[len - 1] * c) % mod + mod) % mod;
}
// concatenates two strings where length of the right is
    k
PLL concat(PLL left, PLL right, int k) { return (left * P
    [k] + right) % mod; }
// Calculates hash of string with size len repeated cnt
    times
// This is O(log n). For O(1), pre-calculate inverses
PLL repeat(PLL hash, int len, LL cnt) {
    PLL mul = (P[len * cnt] - 1) * inverse(P[len] - 1);
    mul = (mul % mod + mod) % mod;
    PLL ret = (hash * mul) % mod;
    if (P[len].ff == 1) ret.ff = hash.ff * cnt;
    if (P[len].ss == 1) ret.ss = hash.ss * cnt;
    return ret;
}
LL get(PLL hash) { return ((hash.ff << 32) ^ hash.ss); }
struct hashlist {
    int len;
    vector<PLL> H, R;
    hashlist() {}
    hashlist(string& s) {
        len = (int)s.size();
        hash_init(len);
        H.resize(len + 1, PLL(0, 0)), R.resize(len + 2, PLL
            (0, 0));
        for (int i = 1; i <= len; i++) H[i] = append(H[i -
            1], s[i - 1]);
        for (int i = len; i >= 1; i--) R[i] = append(R[i +
            1], s[i - 1]);
    }
    // 1-indexed
    PLL range_hash(int l, int r) {
        return ((H[r] - H[l - 1] * P[r - l + 1]) % mod + mod)
            % mod;
    }
    PLL reverse_hash(int l, int r) {
        return ((R[l] - R[r + 1] * P[r - l + 1]) % mod + mod)
            % mod;
    }
    PLL concat_range_hash(int l1, int r1, int l2, int r2) {
        return concat(range_hash(l1, r1), range_hash(l2, r2),
            r2 - l2 + 1);
    }
}

```



```

}
PLL concat_reverse_hash(int l1, int r1, int l2, int r2)
{
    return concat(reverse_hash(l2, r2), reverse_hash(l1,
        r1), r1 - l1 + 1);
}
};

```

7.3 Manacher's

```

vector<int> d1(n);
// d[i] = number of palindromes taking s[i] as center
for (int i = 0, l = 0, r = -1; i < n; i++) {
    int k = (i > r) ? 1 : min(d1[l + r - i], r - i + 1);
    while (0 <= i - k && i + k < n && s[i - k] == s[i + k])
        k++;
    d1[i] = k--;
    if (i + k > r) l = i - k, r = i + k;
}
vector<int> d2(n);
// d[i] = number of palindromes taking s[i-1] and s[i] as
// center
for (int i = 0, l = 0, r = -1; i < n; i++) {
    int k = (i > r) ? 0 : min(d2[l + r - i + 1], r - i + 1);
    while (0 <= i - k - 1 && i + k < n && s[i - k - 1] == s[i + k]) k++;
    d2[i] = k--;
    if (i + k > r) l = i - k - 1, r = i + k;
}

```

7.4 Suffix Array

```

vector<VI> c;
VI sort_cyclic_shifts(const string &s) {
    int n = s.size();
    const int alphabet = 256;
    VI p(n), cnt(alphabet, 0);

    c.clear();
    c.emplace_back();
    c[0].resize(n);

    for (int i = 0; i < n; i++) cnt[s[i]]++;
    for (int i = 1; i < alphabet; i++) cnt[i] += cnt[i - 1];
    for (int i = 0; i < n; i++) p[--cnt[s[i]]] = i;

    c[0][p[0]] = 0;
    int classes = 1;

    for (int i = 1; i < n; i++) {

```

```

        if (s[p[i]] != s[p[i - 1]]) classes++;
        c[0][p[i]] = classes - 1;
    }

    VI pn(n), cn(n);
    cnt.resize(n);
    for (int h = 0; (1 << h) < n; h++) {
        for (int i = 0; i < n; i++) {
            pn[i] = p[i] - (1 << h);
            if (pn[i] < 0) pn[i] += n;
        }
        fill(cnt.begin(), cnt.end(), 0);
        /// radix sort
        for (int i = 0; i < n; i++) cnt[c[h][pn[i]]]++;
        for (int i = 1; i < classes; i++) cnt[i] += cnt[i - 1];
        for (int i = n - 1; i >= 0; i--) p[--cnt[c[h][pn[i]]]] = pn[i];

        cn[p[0]] = 0;
        classes = 1;

        for (int i = 1; i < n; i++) {
            PII cur = {c[h][p[i]], c[h][(p[i] + (1 << h)) % n]};
            PII prev = {c[h][p[i - 1]], c[h][(p[i - 1] + (1 << h)) % n]};
            if (cur != prev) ++classes;
            cn[p[i]] = classes - 1;
        }
        c.push_back(cn);
    }
    return p;
}

VI suffix_array_construction(string s) {
    s += "!";
    VI sorted_shifts = sort_cyclic_shifts(s);
    sorted_shifts.erase(sorted_shifts.begin());
    return sorted_shifts;
}

/// LCP between the ith and jth (i != j) suffix of the
/// STRING
int suffixLCP(int i, int j) {
    assert(i != j);
    int log_n = c.size() - 1;

    int ans = 0;
    for (int k = log_n; k >= 0; k--) {
        if (c[k][i] == c[k][j]) {
            ans += 1 << k;

```

```

            i += 1 << k;
            j += 1 << k;
        }
    }
    return ans;
}

VI lcp_construction(const string &s, const VI &sa) {
    int n = s.size();
    VI rank(n, 0);
    VI lcp(n - 1, 0);

    for (int i = 0; i < n; i++) rank[sa[i]] = i;

    for (int i = 0, k = 0; i < n; i++, k -= (k != 0)) {
        if (rank[i] == n - 1) {
            k = 0;
            continue;
        }
        int j = sa[rank[i] + 1];
        while (i + k < n && j + k < n && s[i + k] == s[j + k]) k++;
        lcp[rank[i]] = k;
    }
    return lcp;
}

```

7.5 Z Algo

```

vector<int> calcz(string s) {
    int n = s.size();
    vector<int> z(n);
    int l = 0, r = 0;
    for (int i = 1; i < n; i++) {
        if (i > r) {
            l = r = i;
            while (r < n && s[r] == s[r - l]) r++;
            z[i] = r - l, r--;
        } else {
            int k = i - l;
            if (z[k] < r - i + 1) z[i] = z[k];
            else {
                l = i;
                while (r < n && s[r] == s[r - l]) r++;
                z[i] = r - l, r--;
            }
        }
    }
    return z;
}

```

8 Equations and Formulas

8.1 Catalan Numbers

$$C_n = \frac{1}{n+1} \binom{2n}{n} \quad C_0 = 1, C_1 = 1 \text{ and } C_n = \sum_{k=0}^{n-1} C_k C_{n-1-k}$$

The number of ways to completely parenthesize $n+1$ factors.

The number of triangulations of a convex polygon with $n+2$ sides (i.e. the number of partitions of polygon into disjoint triangles by using the diagonals).

The number of ways to connect the $2n$ points on a circle to form n disjoint i.e. non-intersecting chords.

The number of rooted full binary trees with $n+1$ leaves (vertices are not numbered). A rooted binary tree is full if every vertex has either two children or no children.

Number of permutations of $1, \dots, n$ that avoid the pattern 123 (or any of the other patterns of length 3); that is, the number of permutations with no three-term increasing sub-sequence. For $n = 3$, these permutations are 132, 213, 231, 312 and 321.

8.2 Stirling Numbers First Kind

The Stirling numbers of the first kind count permutations according to their number of cycles (counting fixed points as cycles of length one).

$S(n, k)$ counts the number of permutations of n elements with k disjoint cycles.

$S(n, k) = (n-1) \cdot S(n-1, k) + S(n-1, k-1)$, where, $S(0, 0) =$

$$1, S(n, 0) = S(0, n) = 0 \quad \sum_{k=0}^n S(n, k) = n!$$

The unsigned Stirling numbers may also be defined algebraically, as the coefficient of the rising factorial:

$$x^{\bar{n}} = x(x+1)\dots(x+n-1) = \sum_{k=0}^n S(n, k) x^k$$

Lets $[n, k]$ be the stirling number of the first kind, then

$$\left[n \atop k \right] = \sum_{0 \leq i_1 < i_2 < \dots < i_k < n} i_1 i_2 \dots i_k.$$

8.3 Stirling Numbers Second Kind

Stirling number of the second kind is the number of ways to partition a set of n objects into k non-empty subsets.

$S(n, k) = k \cdot S(n-1, k) + S(n-1, k-1)$, where $S(0, 0) = 1, S(n, 0) = S(0, n) = 0$ $S(n, 2) = 2^{n-1} - 1$ $S(n, k) \cdot k!$ = number of ways to color n nodes using colors from 1 to k such that each color is used at least once.

An r -associated Stirling number of the second kind is the number of ways to partition a set of n objects into k subsets, with

each subset containing at least r elements. It is denoted by $S_r(n, k)$ and obeys the recurrence relation. $S_r(n+1, k) = k S_r(n, k) + \binom{n}{r-1} S_r(n-r+1, k-1)$

Denote the n objects to partition by the integers $1, 2, \dots, n$. Define the reduced Stirling numbers of the second kind, denoted $S^d(n, k)$, to be the number of ways to partition the integers $1, 2, \dots, n$ into k nonempty subsets such that all elements in each subset have pairwise distance at least d . That is, for any integers i and j in a given subset, it is required that $|i - j| \geq d$. It has been shown that these numbers satisfy, $S^d(n, k) = S(n-d+1, k-d+1), n \geq k \geq d$

8.4 Other Combinatorial Identities

$$\binom{n}{k} = \frac{n}{k} \binom{n-1}{k-1}$$

$$\sum_{i=0}^k \binom{n+i}{i} = \sum_{i=0}^k \binom{n+i}{n} = \binom{n+k+1}{k}$$

$$n, r \in N, n > r, \sum_{i=r}^n \binom{i}{r} = \binom{n+1}{r+1}$$

If $P(n) = \sum_{k=0}^n \binom{n}{k} \cdot Q(k)$, then,

$$Q(n) = \sum_{k=0}^n (-1)^{n-k} \binom{n}{k} \cdot P(k)$$

If $P(n) = \sum_{k=0}^n (-1)^k \binom{n}{k} \cdot Q(k)$, then,

$$Q(n) = \sum_{k=0}^n (-1)^k \binom{n}{k} \cdot P(k)$$

8.5 Different Math Formulas

Picks Theorem : $A = i + b/2 - 1$

Derangements : $d(i) = (i-1) \times (d(i-1) + d(i-2))$

$$\frac{n}{ab} - \left\{ \frac{bn}{a} \right\} - \left\{ \frac{an}{b} \right\} + 1$$

8.6 GCD and LCM

if m is any integer, then $\gcd(a + m \cdot b, b) = \gcd(a, b)$

The gcd is a multiplicative function in the following sense:

if a_1 and a_2 are relatively prime, then $\gcd(a_1 \cdot a_2, b) = \gcd(a_1, b) \cdot \gcd(a_2, b)$.

$$\gcd(a, \text{lcm}(b, c)) = \text{lcm}(\gcd(a, b), \gcd(a, c)).$$

$$\text{lcm}(a, \gcd(b, c)) = \gcd(\text{lcm}(a, b), \text{lcm}(a, c)).$$

For non-negative integers a and b , where a and b are not both zero, $\gcd(n^a - 1, n^b - 1) = n^{\gcd(a, b)} - 1$

$$\gcd(a, b) = \sum_{k|a \text{ and } k|b} \phi(k)$$

$$\sum_{i=1}^n [\gcd(i, n) = k] = \phi\left(\frac{n}{k}\right)$$

$$\sum_{k=1}^n \gcd(k, n) = \sum_{d|n} d \cdot \phi\left(\frac{n}{d}\right)$$

$$\sum_{k=1}^n x^{\gcd(k, n)} = \sum_{d|n} x^d \cdot \phi\left(\frac{n}{d}\right)$$

$$\sum_{k=1}^n \frac{1}{\gcd(k, n)} = \sum_{d|n} \frac{1}{d} \cdot \phi\left(\frac{n}{d}\right) = \frac{1}{n} \sum_{d|n} d \cdot \phi(d)$$

$$\sum_{k=1}^n \frac{k}{\gcd(k, n)} = \frac{n}{2} \cdot \sum_{d|n} \frac{1}{d} \cdot \phi\left(\frac{n}{d}\right) = \frac{n}{2} \cdot \frac{1}{n} \cdot \sum_{d|n} d \cdot \phi(d)$$

$$\sum_{k=1}^n \frac{n}{\gcd(k, n)} = 2 * \sum_{k=1}^n \frac{k}{\gcd(k, n)} - 1, \text{ for } n > 1$$

$$\sum_{i=1}^n \sum_{j=1}^n [\gcd(i, j) = 1] = \sum_{d=1}^n \mu(d) \left\lfloor \frac{n}{d} \right\rfloor^2$$

$$\sum_{i=1}^n \sum_{j=1}^n \gcd(i, j) = \sum_{d=1}^n \phi(d) \left\lfloor \frac{n}{d} \right\rfloor^2$$

$$\sum_{i=1}^n \sum_{j=1}^n i \cdot j [\gcd(i, j) = 1] = \sum_{i=1}^n \phi(i) i^2$$

$$F(n) = \sum_{i=1}^n \sum_{j=1}^n \text{lcm}(i, j) = \sum_{l=1}^n \left(\frac{(1 + \lfloor \frac{n}{l} \rfloor) (\lfloor \frac{n}{l} \rfloor)}{2} \right)^2 \sum_{d|l} \mu(d) l d$$