Process & Decision Documentation

Entry Header

Name:Abiha Shah

Role(s):everything

Primary responsibility for this work:everything

Goal of Work Session

I was trying to understand how to integrate audio into the existing code while keeping the original animation structure intact and make sure it works well.

Tools, Resources, or Inputs Used

- ChatGPT 5.2

GenAI Documentation

Everyone must complete this section. If not GenAI was used, write, “No GenAI used for this task.” When GenAI is not used, process evidence should still demonstrate iteration, revision, or development over time.

Because GenAI can closely mimic human-created work, instructors or TAs may occasionally request additional process evidence to confirm non-use. This may include original working files (e.g., an illustrator file), intermediate drafts, or a brief check-in with a TA to walk through your process.

These requests are not an assumption of misconduct. They are part of ensuring academic integrity in an environment where distinguishing between human-created and AI-generated work is increasingly difficult.

If GenAI was used (keep each response as brief as possible):

Date Used: 13/3/26

Tool Disclosure: ChatGPT 5.2

Purpose of Use: To ask fro support on how to a dd sound to the code

Summary of Interaction: It helped explain how to load and play sound and also suggested where to place the sound code within the existing animation script.

Human Decision Point(s): I chose which suggestions to implement and adjusted the code so that the sound would only play when the right arrow key was pressed

Integrity & Verification Note: I tested the code in the browser to confirm that the sound worked correctly and that the fox animation still moved the way it should.

Scope of GenAI Use: GenAI only explaining how to integrate sound into the sketch.

Limitations or Misfires: Some suggestions from the tool initially did not work because the sound library was missing from the HTML file which I had to later on add msyelf.

Summary of Process (Human + Tool)

I started by changing the existing Week 6 example to include a sound file. I added the sound file, loaded the file in the preload function, and changed it when the right arrow key was pressed. When the sound did not work initially, I tested different solutions and checked both the JavaScript and HTML files to find the issue. After discovering that the p5 sound library was missing, I added it and tested the code again until the sound played correctly with the animation.

Decision Points & Trade-offs

One key decision was how to integrate the sound without changing the structure of the original example too much in this I had to make them make sound add in the sketch file and assets otherwise it wouldn't have worked.

Verification & Judgement

I verified the result by running the sketch in the browser and pressing the right arrow key to confirm that both the animation and sound worked together.

Limitations, Dead Ends, or Open Questions

Initially the sound did not work because the p5 sound library was not included in the HTML file

Appendix

Please include a full transcript of your conversation with the GenAI. GenAI transcripts are used for transparency and verification only and are not assessed for writing quality or completeness.

Papers, Please / One

Night Ultimate

Werewolf

Add sound or simple physics to your sketch

e.g., visual ehects triggered by motion,

collisions, or player actions.

Here are easy ways to add **sound or simple physics** to your sketch depending on which game you choose:

Papers, Please

You could add:

- **Stamp sound** when a passport is approved or denied
- **Paper sliding sound** when documents move across the desk
- A small **screen shake** or red flash when the player makes a wrong decision
- Simple physics like documents **falling or stacking** if dragged too quickly
- A gate/barrier animation that opens or closes based on the player's choice

One Night Ultimate Werewolf

You could add:

- A **flip sound** when role cards are turned over

A spooky **howl sound** when the werewolf role is revealed

Cards that slide, bounce, or rotate when swapped

A glowing or pulsing effect when it becomes a player's turn

A dramatic shake or flash when the final vote happens

Easy player-action effects

These usually work well in sketches:

Click → sound + scale pop

Drag → object follows mouse with slight lag

Collision → bounce or knockback

Wrong move → buzzer sound + red flash

Correct move → chime + sparkle/glow

If you want, I can also give you one super simple effect idea for each game that would be easiest to code.

Week6_Examples (1).zip

Zip Archive

base don these hwo do i do week 1 example on vscode

Thought for 17s

Yep — based on these examples, the **Week 1 example in VS Code** is usually done the **same way structurally**, just much simpler.

What to do in VS Code

1. Make a project folder

Create a folder like:

week1-example

Inside it, make these files:

```
week1-example
├── index.html
├── sketch.js
└── style.css
```

You do **not** need all the sprite/assets folders yet for Week 1 unless your assignment says so.

2. Put this in index.html
This loads p5.js and your sketch file.

```html
<!doctype html>
<html lang="en">
  <head>
    <meta charset="utf-8" />
    <title>Week 1 Example</title>
    <link rel="stylesheet" href="style.css" />
  </head>
  <body>
    <script src="https://cdn.jsdelivr.net/npm/p5@1.11.4/lib/p5.min.js"></script>
    <script src="sketch.js"></script>
```

```
  </body>
</html>
```

3. Put this in style.css

```
body
  margin: 0;
  overflow: hidden;
}
canvas
  display: block;
}
```

4. Put this in sketch.js

This is a super basic Week 1 p5 sketch:

```
function setup
  createCanvas 600  400
}

function draw
  background 220

  ellipse mouseX  mouseY  50  50
}
```

When you run it, a circle follows your mouse.

How to run it in VS Code

Option 1: Live Server

This is the easiest.

- Open the folder in **VS Code**
- Install the **Live Server** extension
- Right-click index.html
- Click Open with Live Server

It should open in your browser.

How this connects to your Week 6 examples

Your uploaded examples use the same basic setup:

- an index.html
- a sketch.js
- sometimes a style.css
- extra libraries or assets only when needed

For example, in your Week 6 file, index.html loads:

- p5
- p5play
- planck
- sketch.js

For **Week 1**, you usually only need:

- p5
- sketch.js

So Week 1 is basically a stripped-down version of that structure.

If your Week 1 task is “add sound or simple physics”

Then you can start with something like this:

```
let x = 100
let speed = 3

function setup
  createCanvas 600  400
}

function draw
  background 220

  x += speed

  if  x > width - 25 || x < 25
    speed *= -1  // simple bounce physics
  }

  ellipse x  200  50  50
}
```

That gives you a simple physics-style bounce.

If you want sound too

Then in index.html, add p5 sound:

```
<script src="https://cdnjs.cloudflare.com/ajax/libs/p5.js/1.11.4/addons/
p5.sound.min.js"></script>
```

So it becomes:

```
<body>
  <script src="https://cdn.jsdelivr.net/npm/p5@1.11.4/lib/p5.min.js"></script>
  <script src="https://cdnjs.cloudflare.com/ajax/libs/p5.js/1.11.4/addons/
p5.sound.min.js"></script>
  <script src="sketch.js"></script>
</body>
```

Then your sketch.js could be:

```
let osc

function setup
  createCanvas 600  400
  osc = new p5.Oscillator('sine');
  osc.start();
  osc.amp(0);
}

function draw
  background 220
  ellipse mouseX  mouseY  50  50
```

```
}

function mousePressed
  osc.freq(440);
  osc.amp(0.3, 0.05);
}

function mouseReleased
  osc.amp(0, 0.2);
}
```

Easiest way to think about it

For Week 1 in VS Code:

> index.html = loads everything
>
> style.css = page styling
>
> sketch.js = where your p5 code goes
>
> use Live Server to run it

If you want, I can make you a **full Week 1 starter project** for either:
Papers, Please style, or **One Night Ultimate Werewolf** style.

how do i add sound to thsi with teh sound maker already in it

If your project already has the p5 sound library ("sound maker") included, then you only need 3 small steps in sketch.js to add sound.

I'll show the **basic pattern**, and you can plug it into your sketch.

1. Make a sound variable

At the **top of** sketch.js

```
let soundEffect
```

2. Load the sound

Use preload() so the sound loads before the game starts.

```
function preload
  soundEffect = loadSound "sound.mp3"
}
```

Put your sound file (mp3 or wav) in the same folder as sketch.js.

Example folder:

```
project
 |
 ├── index.html
 ├── sketch.js
 ├── sound.mp3
```

3. Play the sound when something happens

For example when clicking, colliding, or stamping.

Example: play sound on click

```
function mousePressed
  soundEffect.
}
```

Example full sketch

```
let soundEffect

function preload
  soundEffect = loadSound "click.mp3"
}

function setup
  createCanvas 600  400
}

function draw
  background 200
  ellipse mouseX  mouseY  50  50
}

function mousePressed
  soundEffect.
}
```

Now every click plays the sound.

Example for your assignment ideas

Papers Please stamp

```
function mousePressed
  stampSound.
}
```

Collision sound

```
if(sprite1.collides(sprite2)){
  hitSound.
}
```

Key pickup

```
if(player.overlaps(key)){
  keySound.
}
```

IMPORTANT (students forget this)

Browsers block sound until **user interaction** happens.

So the sound must be triggered by something like:

```
mousePressed()
keyPressed()
```

button click

collision during gameplay

If you want, send me your sketch.js

and I can insert the exact 2–3 lines needed so the sound works in your specific project.

what do i add

Since your project already has the p5 sound library included, you only need to add three small things to your sketch.js.

1. Add a sound variable (top of file)

At the very top of sketch.js:

```
let clickSound
```

2. Load the sound

Add a preload() function:

```
function preload
  clickSound = loadSound "click.mp3"
}
```

Put the sound file (click.mp3) in the same folder as sketch.js.

Example folder:

```
project
 |
 ├── index.html
 ├── sketch.js
 ├── click.mp3
```

3. Play the sound when something happens

For example when the player clicks:

```
function mousePressed
  clickSound.
}
```

Full simple example

```
let clickSound

function preload
  clickSound = loadSound "click.mp3"
}

function setup
  createCanvas 600  400
```

```
}

function draw
  background 220
  ellipse mouseX  mouseY  50  50
}

function mousePressed
  clickSound.
}
```

Example for your assignment (maze game)

Play a sound when the player **hits a wall**:

```
if(player.collides(wall)){
  hitSound.
}
```

Play a sound when the player **gets a key**:

```
if(player.overlaps(key)){
  keySound.
}
```

✅ So the only things you add are:

let soundName;

loadSound() in preload()

soundName.play() when an action happens

If you want, send your sketch.js, and I'll show you exactly where to insert the sound in your code so it works with your maze game.

no its fro this /*

```
  Week 6 — Example 1: Sprites, Sprite Sheets, & Animation


  Course: GBDA302 | Instructors: Dr. Karen Cochrane & David Han

  Date: Feb. 26, 2026


  Controls:

    A or D (Left / Right Arrow)   Horizontal movement

    W (Up Arrow)                  Jump

    S (Down Arrow)                Idle

    Space Bar                     Attack


*/


let player;

let playerImg;


let playerAnis = {

  idle: { row: 0, frames: 4, frameDelay: 10 },
```

```
  run: { row: 1, frames: 4, frameDelay: 3 },
  jump: { row: 2, frames: 3, frameDelay: 8, frame: 0 },
  attack: { row: 3, frames: 6, frameDelay: 2 },
};

// level constants

// camera view size
const VIEWW = 320,
  VIEWH = 180;

// size of individual animation frames
const FRAME_W = 32,
  FRAME_H = 32;

// gravity
const GRAVITY = 0;

function preload() {
  // --- IMAGES ---
  playerImg = loadImage("assets/foxSpriteSheet.png");
}

function setup() {
  // pixelated rendering with autoscaling
  new Canvas(VIEWW, VIEWH, "pixelated");
```

```
  // needed to correct an visual artifacts from attempted antialiasing
  allSprites.pixelPerfect = true;

  world.gravity.y = GRAVITY;

  // --- PLAYER ---
  player = new Sprite(VIEWW/2, VIEWH/2, FRAME_W, FRAME_H); // create the player
  player.spriteSheet = playerImg; // use the sprite sheet
  player.rotationLock = true; // turn off rotations (player shouldn't rotate)

  // player animation parameters
  player.anis.w = FRAME_W;
  player.anis.h = FRAME_H;
  player.anis.offset.y = -4; // offset the collision box up
  player.addAnis(playerAnis); // add the player animations defined earlier
  player.ani = "idle"; // default to the idle animation
  player.w = 18; // set the width of the collsion box
  player.h = 20; // set the height of the collsion box
  player.removeColliders();
  player.friction = 0; // set the friciton to 0 so we don't stick to walls
  player.bounciness = 0; // set the bounciness to 0 so the player doesn't bounce
}

function draw() {
  // --- BACKGROUND ---
  background("skyblue");
```

```
  // --- PLAYER CONTROLS ---
  if (kb.presses("up")) {
    player.ani = "jump";
  } else if (kb.presses("right")){
    player.ani = "run";
    player.mirror.x = false;
  } else if (kb.presses("left")){
    player.ani = "run";
    player.mirror.x = true;
  } else if (kb.presses(" ")){
    player.ani = "attack";
  } else if (kb.presses("down")){
    // Grounded: idle or run
    player.ani = "idle";
  }
}
```

Got it — for this exact Week 6 fox animation code, add sound like this.

1. Add sound variables at the top

Put these near your other let lines:

```
let jumpSound
let attackSound
let runSound
```

2. Load the sound files in preload()

Inside your existing preload():

```
function preload
  // --- IMAGES ---
  playerImg = loadImage "assets/foxSpriteSheet.png"

  // --- SOUNDS ---
  jumpSound = loadSound "assets/jump.mp3"
  attackSound = loadSound "assets/attack.mp3"
  runSound = loadSound "assets/run.mp3"
}
```

Make sure those sound files are actually in your assets folder.

3. Play sounds inside your controls

Update your draw() controls like this:

```
function draw
  // --- BACKGROUND ---
  background "skyblue"

  // --- PLAYER CONTROLS ---
  if (kb.presses("up")) {
    player.      = "jump"
    jumpSound.
```

```
  } else if (kb.presses("right")) {
    player.      = "run"
    player.          .   = false
    runSound.
  } else if (kb.presses("left")) {
    player.      = "run"
    player.          .   = true
    runSound.
  } else if (kb.presses(" ")) {
    player.      = "attack"
    attackSound.
  } else if (kb.presses("down")) {
    player.      = "idle"
  }
}
```

4. Better version for run sound

If you use runSound.play() every key press, it may sound repetitive. A cleaner version is:

```
} else if (kb.presses("right")) {
  player.      = "run"
  player.          .   = false
  if (!runSound.isPlaying()) {
    runSound.
  }
} else if (kb.presses("left")) {
```

```
  player.      = "run"
  player.          .   = true
  if (!runSound.isPlaying()) {
    runSound.
  }
}
```

5. Full edited version

Here’s your code with sound added:

```
/*
  Week 6 — Example 1: Sprites, Sprite Sheets, & Animation
*/

let player
let playerImg

let jumpSound
let attackSound
let runSound

let playerAnis =
  idle: { row: 0, frames: 4, frameDelay: 10 },
  run: { row: 1, frames: 4, frameDelay: 3 },
  jump: { row: 2, frames: 3, frameDelay: 8, frame: 0 },
  attack: { row: 3, frames: 6, frameDelay: 2 },
```

```
};

// level constants
const VIEWW = 320
  VIEWH = 180

const FRAME_W = 32
  FRAME_H = 32

const GRAVITY = 0

function preload
  // --- IMAGES ---
  playerImg = loadImage "assets/foxSpriteSheet.png"

  // --- SOUNDS ---
  jumpSound = loadSound "assets/jump.mp3"
  attackSound = loadSound "assets/attack.mp3"
  runSound = loadSound "assets/run.mp3"
}

function setup
  new Canvas VIEWW VIEWH "pixelated"

  allSprites.pixelPerfect = true;

  world.gravity.y = GRAVITY;
```

```
  // --- PLAYER ---
  player = new Sprite VIEWW / 2  VIEWH / 2  FRAME_W  FRAME_H
  player.spriteSheet = playerImg;
  player.rotationLock = true;

  player.       .    = FRAME_W
  player.       .   = FRAME_H
  player.       .          .   = -4
  player.              playerAnis
  player.      = "idle"
  player.    = 18
  player.   = 20
  player.removeColliders();
  player.friction = 0;
  player.bounciness = 0;
}

function draw
  background "skyblue"

  if (kb.presses("up")) {
    player.      = "jump"
    jumpSound.
  } else if (kb.presses("right")) {
    player.      = "run"
    player.          .   = false
```

```
    if (!runSound.isPlaying()) {
      runSound.
    }
  } else if (kb.presses("left")) {
    player.      = "run"
    player.          .   = true
    if (!runSound.isPlaying()) {
      runSound.
    }
  } else if (kb.presses(" ")) {
    player.      = "attack"
    attackSound.
  } else if (kb.presses("down")) {
    player.      = "idle"
  }
}
```

6. Important

Your [redacted] must already include the p5 sound library. If not, add:

```
<script src="https://cdnjs.cloudflare.com/ajax/libs/p5.js/1.11.4/addons/
p5.sound.min.js"></script>
```

And put it after p5.js, before [redacted].

7. Easiest possible version

If your teacher just wants **one sound effect added**, do only this:

At top:

```
let attackSound
```

In preload():

```
attackSound = loadSound "assets/attack.mp3"
```

In the space bar section:

```
} else if (kb.presses(" ")) {
  player.      = "attack"
  attackSound.
}
```

That's the simplest correct answer.

If you paste your index.html too, I can check whether the sound library is already set up right.

i just want it to b ethere when the right arrow is clicked

Perfect — if you only want sound when the right arrow is pressed, you only need 3 small additions.

1. Add a sound variable at the top

Right under your other let variables:

```
let runSound
```

2. Load the sound in preload()

Add this inside your existing preload():

```
runSound = loadSound "assets/run.mp3"
```

So your preload becomes:

```
function preload
  // --- IMAGES ---
  playerImg = loadImage "assets/foxSpriteSheet.png"

  // --- SOUND ---
  runSound = loadSound "assets/run.mp3"
}
```

3. Play the sound when the right arrow is pressed

Modify the right arrow section in draw():

```
else if (kb.presses("right")){
  player.      = "run"
  player.          .   = false
  runSound.
}
```

That’s it.

Now every time the right arrow is pressed, the sound will play.

Just make sure the file exists:

assets/run.mp3

✅ Summary of the only lines you add

```
let runSound
```

```
runSound = loadSound "assets/run.mp3"
```

```
runSound.
```

If you want, I can also show you a cleaner version where the sound only plays once while holding the key (so it doesn’t spam) — which usually looks better in games.

wait what do i save the sound as then

You should save the sound as an `.mp3` **file** (this is the easiest and most reliable for browsers).

1. File name

Save it exactly like this:

run.mp3

2. Put it in the assets folder

Your project should look like this:

```
project-folder
 |
 ├── index.html
 ├── sketch.js
 |
 └── assets
     ├── foxSpriteSheet.png
     └── run.mp3
```

3. Your code should match the file name

In preload():

```
runSound = loadSound "assets/run.mp3"
```

If the name or location is different, the sound will not load.

4. Good places to get sounds (free)

You can download a small sound and rename it to run.mp3:

https://pixabay.com/sound-effects/

https://freesound.org/

Short sounds like:

- footsteps
- running
- whoosh
- jump

work well.

5. Quick tip

If you download a file called something like:

footsteps-running-12345.mp3

You can rename it to

run.mp3

so your code stays simple.

✅ Final checklist

- File type: **.mp3**
- File name: **run.mp3**
- Location: **assets folder**
- Code: "assets/run.mp3"

If you want, I can also show you a super small running/footstep sound that works perfectly for this fox animation.

ok s i added it to assets and now

Great — now you only need to connect it in **three places in your code**.

1. Add the sound variable (top of the file)

Put this with your other let variables:

```
let runSound
```

2. Load the sound in preload()

Add this inside your existing preload() function:

```
function preload
  // --- IMAGES ---
  playerImg = loadImage "assets/foxSpriteSheet.png"

  // --- SOUND ---
  runSound = loadSound "assets/run.mp3"
}
```

3. Play the sound when the right arrow is pressed

Find this part of your code:

```
else if (kb.presses("right")){
  player.      = "run"
  player.         .   = false
```

```
}
```

Change it to:

```
else if (kb.presses("right")){
  player.      = "run"
  player.          .   = false
  runSound.
}
```

Final result

Now when you press the right arrow, the fox will:

switch to the **run animation**

play the run sound

If the sound doesn't play

Make sure:

The file is exactly named

run.mp3

It is inside

assets/run.mp3

Your index.html includes the p5 sound library:

```
<script src="https://cdnjs.cloudflare.com/ajax/libs/p5.js/1.11.4/addons/p5.sound.min.js"></script>
```

If you want, I can also show you one small improvement teachers like: making the sound not spam repeatedly when the key is held down.

its nto working

Stopped thinking

tell em again how do i do it

No problem — let's do it **step-by-step exactly** so it works.

1️⃣ Make sure the sound library is loaded

Open [redacted] and make sure this line exists **before** [redacted]:

```
<script src="https://cdnjs.cloudflare.com/ajax/libs/p5.js/1.11.4/addons/p5.sound.min.js"></script>
```

It should look like this:

```
<script src="https://cdn.jsdelivr.net/npm/p5@1.11.4/lib/p5.min.js"></script>
```

```
<script src="https://cdnjs.cloudflare.com/ajax/libs/p5.js/1.11.4/addons/p5.sound.min.js"></script>
<script src="sketch.js"></script>
```

If this line is missing, **sound will never work**.

2️⃣ Add a variable at the top of your code

At the top of sketch.js:

```
let runSound
```

Put it with your other let variables.

3️⃣ Load the sound in preload()

Your preload() should look like this:

```
function preload
  playerImg = loadImage "assets/foxSpriteSheet.png"
  runSound = loadSound "assets/run.mp3"
}
```

Make sure the file exists here:

```
assets/run.mp3
```

4️⃣ Play the sound when pressing RIGHT

Find this part:

```
else if (kb.presses("right")){
  player.      = "run"
  player.         .   = false
}
```

Change it to:

```
else if (kb.presses("right")){
  player.      = "run"
  player.         .   = false
  runSound.
}
```

5️⃣ Click the screen once

Browsers require one mouse click before sound works.

So after the game loads:

Click anywhere in the canvas

Press the **right arrow**

✔️ Quick checklist

Make sure all these are true:

run.mp3 is inside the **assets folder**

`loadSound("assets/run.mp3")` matches the file name exactly

p5.sound.min.js is loaded in index.html

You clicked the screen once

✅ If you want, paste your `index.html` and `preload()` **function** here and I'll quickly spot the exact issue (it's usually one tiny line missing).

i downlaoded a mp3 file from pixaby

Good — downloading an MP3 from Pixabay is correct. Now make sure these exact steps are done.

1️⃣ Put the MP3 in the assets folder

Your folder should look like this:

```
project
 |
 ├── index.html
 ├── sketch.js
 |
 └── assets
     ├── foxSpriteSheet.png
     └── run.mp3
```

If Pixabay downloaded something like:

footsteps-12345.mp3

Rename it to:

run.mp3

This avoids mistakes.

2️⃣ Add the sound variable

At the top of your code:

```
let runSound
```

3️⃣ Load the sound in preload()

Your preload should look like this:

```
function preload
  playerImg = loadImage "assets/foxSpriteSheet.png"
  runSound = loadSound "assets/run.mp3"
}
```

4️⃣ Play the sound when pressing RIGHT

Find this section:

```
else if (kb.presses("right")){
  player.      = "run"
  player.          .   = false
}
```

Change it to:

```
else if (kb.presses("right")){
  player.      = "run"
  player.          .   = false
  runSound.
}
```

5️⃣ VERY IMPORTANT: click the screen first

Browsers block sound until **you click the page once**.

So:

1️⃣ Run the game

2️⃣ **Click the canvas once**

3️⃣ Press the **right arrow**

Now the sound should play.

6️⃣ If it still doesn't work

The problem is usually missing the sound library.

Open [redacted] and make sure this exists:

<script src="https://cdnjs.cloudflare.com/ajax/libs/p5.js/1.11.4/addons/p5.sound.min.js"></script>

It must be **before** sketch.js.

✅ If you want, send a **screenshot of your assets folder and preload()**, and I can tell you exactly what's wrong in about 5 seconds.

no its wrong

Use this exact version.

The main thing that was missing

when i played it the fox disappeared

when i played the fox disappeared, check my code and see what im doing wrong /*

```
  Week 6 — Example 1: Sprites, Sprite Sheets, & Animation

  Course: GBDA302 | Instructors: Dr. Karen Cochrane & David Han
  Date: Feb. 26, 2026

  Controls:
    A or D (Left / Right Arrow)   Horizontal movement
    W (Up Arrow)                  Jump
    S (Down Arrow)                Idle
    Space Bar                     Attack

*/
```

```
let runSound;
let player;
let playerImg;

let playerAnis = {
  idle: { row: 0, frames: 4, frameDelay: 10 },
  run: { row: 1, frames: 4, frameDelay: 3 },
  jump: { row: 2, frames: 3, frameDelay: 8, frame: 0 },
  attack: { row: 3, frames: 6, frameDelay: 2 },
};

// level constants

// camera view size
const VIEWW = 320,
  VIEWH = 180;

// size of individual animation frames
const FRAME_W = 32,
  FRAME_H = 32;

// gravity
const GRAVITY = 0;

function preload() {
  playerImg = loadImage("assets/foxSpriteSheet.png");
  runSound = loadSound("assets/run.mp3");
```

```
}

function setup() {
  // pixelated rendering with autoscaling
  new Canvas(VIEWW, VIEWH, "pixelated");

  // needed to correct an visual artifacts from attempted antialiasing
  allSprites.pixelPerfect = true;

  world.gravity.y = GRAVITY;

  // --- PLAYER ---
  player = new Sprite(VIEWW / 2, VIEWH / 2, FRAME_W, FRAME_H); // create the
player
  player.spriteSheet = playerImg; // use the sprite sheet
  player.rotationLock = true; // turn off rotations (player shouldn't rotate)

  // player animation parameters
  player.anis.w = FRAME_W;
  player.anis.h = FRAME_H;
  player.anis.offset.y = -4; // offset the collision box up
  player.addAnis(playerAnis); // add the player animations defined earlier
  player.ani = "idle"; // default to the idle animation
  player.w = 18; // set the width of the collsion box
  player.h = 20; // set the height of the collsion box
  player.removeColliders();
  player.friction = 0; // set the friciton to 0 so we don't stick to walls
```

```
  player.bounciness = 0; // set the bounciness to 0 so the player doesn't bounce
}

function draw() {
  // --- BACKGROUND ---
  background("skyblue");

  // --- PLAYER CONTROLS ---
  if (kb.presses("up")) {
    player.ani = "jump";
  } else if (kb.presses("right")) {
    player.ani = "run";
    player.mirror.x = false;
    runSound.play();
  } else if (kb.presses("left")) {
    player.ani = "run";
    player.mirror.x = true;
  } else if (kb.presses(" ")) {
    player.ani = "attack";
  } else if (kb.presses("down")) {
    // Grounded: idle or run
    player.ani = "idle";
  }
}
```

Your fox is probably not actually “disappearing” — the sketch is likely **crashing when you press right**.

The code itself is mostly fine. The problem is most likely this line:

```
runSound.
```

If the sound did not load properly, then pressing right causes an error, and the animation stops.

What to try first

Change this:

```
runSound.
```

to this:

```
if  runSound
  runSound.
}
```

So your right-arrow section becomes:

```
else if (kb.presses("right")) {
  player.      = "run"
  player.          .   = false
  if  runSound
    runSound.
  }
}
```

Better full version

Use this exact code:

```
let runSound
let player
let playerImg

let playerAnis =
  idle: { row: 0, frames: 4, frameDelay: 10 },
  run: { row: 1, frames: 4, frameDelay: 3 },
  jump: { row: 2, frames: 3, frameDelay: 8, frame: 0 },
  attack: { row: 3, frames: 6, frameDelay: 2 },
};

const VIEWW = 320
  VIEWH = 180

const FRAME_W = 32
  FRAME_H = 32

const GRAVITY = 0

function preload
  playerImg = loadImage "assets/foxSpriteSheet.png"
  runSound = loadSound "assets/run.mp3"
}
```

```
function setup
  new Canvas VIEWW  VIEWH  "pixelated"
  allSprites.pixelPerfect = true;
  world.gravity.y = GRAVITY;

  player = new Sprite VIEWW / 2  VIEWH / 2  FRAME_W  FRAME_H
  player.spriteSheet = playerImg;
  player.rotationLock = true;

  player.       .    = FRAME_W
  player.       .   = FRAME_H
  player.       .          .   = -4
  player.             playerAnis
  player.      = "idle"
  player.    = 18
  player.   = 20
  player.removeColliders();
  player.friction = 0;
  player.bounciness = 0;
}

function draw
  background "skyblue"

  if (kb.presses("up")) {
    player.      = "jump"
```

```
  } else if (kb.presses("right")) {
    player.      = "run"
    player.         .   = false

    if (runSound && !runSound.isPlaying()) {
      runSound.
    }
  } else if (kb.presses("left")) {
    player.      = "run"
    player.         .   = true
  } else if (kb.presses(" ")) {
    player.      = "attack"
  } else if (kb.presses("down")) {
    player.      = "idle"
  }
}
```

Why this is happening

Most likely one of these:

1. p5.sound is not loaded in index.html

You need this line before sketch.js:

```
<script src="https://cdnjs.cloudflare.com/ajax/libs/p5.js/1.11.4/addons/
p5.sound.min.js"></script>
```

So it should look like:

```
<script src="https://cdn.jsdelivr.net/npm/p5@1.11.4/lib/p5.min.js"></script>
<script src="https://cdnjs.cloudflare.com/ajax/libs/p5.js/1.11.4/addons/p5.sound.min.js"></script>
<script src="sketch.js"></script>
```

If that line is missing, loadSound() breaks things.

2. The file path is wrong

Make sure the sound file is exactly here:

```
assets/run.mp3
```

And the name must match exactly:

> run.mp3 is not the same as Run.mp3
>
> run.mp3.mp3 would also fail

3. The browser blocked sound

Usually you need to click the page once before sound can play.

Easiest way to test if sound is the problem

Temporarily remove this line:

```
runSound.
```

If the fox stops disappearing, then the sound line is definitely the issue.

One small thing

Your fox is only changing animation, not actually moving. That part is okay for the example, but if you expected movement too, you would need to add something like:

```
player.  += 2
```

inside the right-arrow block.

Paste your [redacted] next and I'll tell you the exact broken line.

with this i still dont hear the osund /*

```
  Week 6 — Example 1: Sprites, Sprite Sheets, & Animation


  Course: GBDA302 | Instructors: Dr. Karen Cochrane & David Han

  Date: Feb. 26, 2026


  Controls:

    A or D (Left / Right Arrow)   Horizontal movement

    W (Up Arrow)                  Jump

    S (Down Arrow)                Idle

    Space Bar                     Attack


*/

let runSound;

let player;

let playerImg;
```

```
let playerAnis = {
  idle: { row: 0, frames: 4, frameDelay: 10 },
  run: { row: 1, frames: 4, frameDelay: 3 },
  jump: { row: 2, frames: 3, frameDelay: 8, frame: 0 },
  attack: { row: 3, frames: 6, frameDelay: 2 },
};

// level constants

// camera view size
const VIEWW = 320,
  VIEWH = 180;

// size of individual animation frames
const FRAME_W = 32,
  FRAME_H = 32;

// gravity
const GRAVITY = 0;

function preload() {
  playerImg = loadImage("assets/foxSpriteSheet.png");
  runSound = loadSound("assets/run.mp3");
}

function setup() {
  // pixelated rendering with autoscaling
```

```
  new Canvas(VIEWW, VIEWH, "pixelated");

  // needed to correct an visual artifacts from attempted antialiasing
  allSprites.pixelPerfect = true;

  world.gravity.y = GRAVITY;

  // --- PLAYER ---
  player = new Sprite(VIEWW / 2, VIEWH / 2, FRAME_W, FRAME_H); // create the
player
  player.spriteSheet = playerImg; // use the sprite sheet
  player.rotationLock = true; // turn off rotations (player shouldn't rotate)

  // player animation parameters
  player.anis.w = FRAME_W;
  player.anis.h = FRAME_H;
  player.anis.offset.y = -4; // offset the collision box up
  player.addAnis(playerAnis); // add the player animations defined earlier
  player.ani = "idle"; // default to the idle animation
  player.w = 18; // set the width of the collsion box
  player.h = 20; // set the height of the collsion box
  player.removeColliders();
  player.friction = 0; // set the friciton to 0 so we don't stick to walls
  player.bounciness = 0; // set the bounciness to 0 so the player doesn't bounce
}

function draw() {
```

```
  // --- BACKGROUND ---
  background("skyblue");

  // --- PLAYER CONTROLS ---
  if (kb.presses("up")) {
    player.ani = "jump";
  } else if (kb.presses("right")) {
    player.ani = "run";
    player.mirror.x = false;
    if (runSound) {
      runSound.play();
    }
  } else if (kb.presses("left")) {
    player.ani = "run";
    player.mirror.x = true;
  } else if (kb.presses(" ")) {
    player.ani = "attack";
  } else if (kb.presses("down")) {
    // Grounded: idle or run
    player.ani = "idle";
  }
}
```

Your sketch.js looks basically okay now. The reason you **still don't hear sound** is most likely one of these:

- p5.sound is not loaded in index.html
- the browser audio context is still locked

the file path/name is slightly wrong

Do this exact setup.

In index.html

Make sure these script lines are there, in this order:

```
<script src="https://cdn.jsdelivr.net/npm/p5@1.11.4/lib/p5.min.js"></script>
<script src="https://cdn.jsdelivr.net/npm/p5@1/lib/addons/p5.sound.min.js"></script>
<script src="https://p5play.org/v3/planck.min.js"></script>
<script src="https://p5play.org/v3/p5play.js"></script>
<script src="sketch.js"></script>
```

If the p5.sound.min.js line is missing, the sound will not work.

In your sketch.js

Use this version:

```
let runSound
let player
let playerImg

let playerAnis =
  idle: { row: 0, frames: 4, frameDelay: 10 },
  run: { row: 1, frames: 4, frameDelay: 3 },
  jump: { row: 2, frames: 3, frameDelay: 8, frame: 0 },
  attack: { row: 3, frames: 6, frameDelay: 2 },
};
```

```
const VIEWW = 320
  VIEWH = 180

const FRAME_W = 32
  FRAME_H = 32

const GRAVITY = 0

function preload
  playerImg = loadImage "assets/foxSpriteSheet.png"
  runSound = loadSound "assets/run.mp3"
}

function setup
  new Canvas VIEWW  VIEWH  "pixelated"
  allSprites.pixelPerfect = true;
  world.gravity.y = GRAVITY;

  player = new Sprite VIEWW / 2  VIEWH / 2  FRAME_W  FRAME_H
  player.spriteSheet = playerImg;
  player.rotationLock = true;

  player.       .    = FRAME_W
  player.       .   = FRAME_H
  player.       .          .   = -4
  player.              playerAnis
```

```
  player.      = "idle"
  player.    = 18
  player.    = 20
  player.removeColliders();
  player.friction = 0;
  player.bounciness = 0;
}

function draw
  background "skyblue"

  if (kb.presses("up")) {
    player.      = "jump"
  } else if (kb.presses("right")) {
    player.      = "run"
    player.          .   = false

    if (runSound && !runSound.isPlaying()) {
      runSound.
    }
  } else if (kb.presses("left")) {
    player.      = "run"
    player.          .   = true
  } else if (kb.presses(" ")) {
    player.      = "attack"
  } else if (kb.presses("down")) {
    player.      = "idle"
```

```
  }
}

function mousePressed
  userStartAudio
}
```

Important

After the page loads:

click anywhere on the game once

then press the right arrow

That mousePressed() function helps unlock audio.

Check your file name

Inside your folder, it must be exactly:

assets/run.mp3

Not:

run.MP3

run.mp3.mp3

Run.mp3

Fast test

Change this:

```
runSound = loadSound "assets/run.mp3"
```

to this:

```
runSound = loadSound
  "assets/run.mp3"
        console.     "sound loaded"
        console.     "sound failed to load"
);
```

Then open the browser console. If you see [redacted], the file path/name is the problem.

Most likely fix

The biggest issue is usually **missing** [redacted] **in** [redacted].

Paste your [redacted] and I'll point to the exact line.

its still nto working /*

```
  Week 6 — Example 1: Sprites, Sprite Sheets, & Animation


  Course: GBDA302 | Instructors: Dr. Karen Cochrane & David Han
  Date: Feb. 26, 2026


  Controls:
    A or D (Left / Right Arrow)   Horizontal movement
    W (Up Arrow)                  Jump
    S (Down Arrow)                Idle
```

```
   Space Bar                    Attack

*/
let runSound;
let player;
let playerImg;

let playerAnis = {
  idle: { row: 0, frames: 4, frameDelay: 10 },
  run: { row: 1, frames: 4, frameDelay: 3 },
  jump: { row: 2, frames: 3, frameDelay: 8, frame: 0 },
  attack: { row: 3, frames: 6, frameDelay: 2 },
};

// level constants

// camera view size
const VIEWW = 320,
  VIEWH = 180;

// size of individual animation frames
const FRAME_W = 32,
  FRAME_H = 32;

// gravity
const GRAVITY = 0;
```

```
function preload() {
  playerImg = loadImage("assets/foxSpriteSheet.png");
  runSound = loadSound("assets/run.mp3");
}

function setup() {
  // pixelated rendering with autoscaling
  new Canvas(VIEWW, VIEWH, "pixelated");

  // needed to correct an visual artifacts from attempted antialiasing
  allSprites.pixelPerfect = true;

  world.gravity.y = GRAVITY;

  // --- PLAYER ---
  player = new Sprite(VIEWW / 2, VIEWH / 2, FRAME_W, FRAME_H); // create the
player
  player.spriteSheet = playerImg; // use the sprite sheet
  player.rotationLock = true; // turn off rotations (player shouldn't rotate)

  // player animation parameters
  player.anis.w = FRAME_W;
  player.anis.h = FRAME_H;
  player.anis.offset.y = -4; // offset the collision box up
  player.addAnis(playerAnis); // add the player animations defined earlier
  player.ani = "idle"; // default to the idle animation
  player.w = 18; // set the width of the collsion box
```

```
  player.h = 20; // set the height of the collsion box
  player.removeColliders();
  player.friction = 0; // set the friciton to 0 so we don't stick to walls
  player.bounciness = 0; // set the bounciness to 0 so the player doesn't bounce
}

function draw() {
  // --- BACKGROUND ---
  background("skyblue");

  // --- PLAYER CONTROLS ---
  if (kb.presses("up")) {
    player.ani = "jump";
  } else if (kb.presses("right")) {
    player.ani = "run";
    player.mirror.x = false;
    if (runSound) {
      runSound.play();
    }
  } else if (kb.presses("left")) {
    player.ani = "run";
    player.mirror.x = true;
  } else if (kb.presses(" ")) {
    player.ani = "attack";
  } else if (kb.presses("down")) {
    // Grounded: idle or run
    player.ani = "idle";
```

```
  }
}
```

Your sketch.js is not the main problem anymore. The most likely reason is that **sound is not enabled in** index.html.

Use these exact fixes.

1. In index.html, add the sound library

You need this line **before** sketch.js:

```
<script src="https://cdn.jsdelivr.net/npm/p5@1/lib/addons/p5.sound.min.js"></script>
```

So your scripts should look like this:

```
<script src="https://cdn.jsdelivr.net/npm/p5@1/lib/p5.min.js"></script>
<script src="https://cdn.jsdelivr.net/npm/p5@1/lib/addons/p5.sound.min.js"></script>
<script src="https://p5play.org/v3/planck.min.js"></script>
<script src="https://p5play.org/v3/p5play.js"></script>
<script src="sketch.js"></script>
```

If that line is missing, loadSound() will not work.

2. Use this exact sketch.js

Replace your current code with this version:

```
let runSound
let player
```

```
let playerImg

let playerAnis =
  idle: { row: 0, frames: 4, frameDelay: 10 },
  run: { row: 1, frames: 4, frameDelay: 3 },
  jump: { row: 2, frames: 3, frameDelay: 8, frame: 0 },
  attack: { row: 3, frames: 6, frameDelay: 2 },
};

const VIEWW = 320
  VIEWH = 180

const FRAME_W = 32
  FRAME_H = 32

const GRAVITY = 0

function preload
  playerImg = loadImage "assets/foxSpriteSheet.png"

  runSound = loadSound
    "assets/run.mp3"
          console.     "sound loaded"
          console.     "sound failed to load"
  );
}
```

```
function setup
  new Canvas VIEWW  VIEWH  "pixelated"
  allSprites.pixelPerfect = true;
  world.gravity.y = GRAVITY;

  player = new Sprite VIEWW / 2  VIEWH / 2  FRAME_W  FRAME_H
  player.spriteSheet = playerImg;
  player.rotationLock = true;

  player.       .    = FRAME_W
  player.       .   = FRAME_H
  player.       .          .   = -4
  player.              playerAnis
  player.      = "idle"
  player.    = 18
  player.   = 20
  player.removeColliders();
  player.friction = 0;
  player.bounciness = 0;
}

function draw
  background "skyblue"

  if (kb.presses("up")) {
    player.      = "jump"
  } else if (kb.presses("right")) {
```

```
    player.      = "run"
    player.          .   = false

    if (runSound && !runSound.isPlaying()) {
      runSound.
    }
  } else if (kb.presses("left")) {
    player.      = "run"
    player.          .   = true
  } else if (kb.presses(" ")) {
    player.      = "attack"
  } else if (kb.presses("down")) {
    player.      = "idle"
  }
}

function mousePressed
  userStartAudio
  console.      "audio unlocked"
}
```

3. Click once before testing

After the page opens:

click anywhere on the canvas once

then press the right arrow

Without that click, browsers often block audio.

4. Make sure the file name is exactly right

Your sound file must be:

assets/run.mp3

Not:

run.MP3

Run.mp3

run.mp3.mp3

5. The easiest way to check what's wrong

Open the browser console.

You should see one of these:

sound loaded

sound failed to load

If you see **sound failed to load**, the file name/path is wrong.

If you see **sound loaded** but still hear nothing, then the issue is usually audio lock, so click once first.

6. Most likely exact issue

It is probably one of these two:

you did **not add** [redacted] **in** [redacted]

your file is not named exactly [redacted]

Paste your [redacted] and I'll point to the exact missing line.

make it like this tho

Yes — keep it simple like your original code. Use this exact version.

Add at the top:

```
let runSound
```

In preload():

```
function preload
  playerImg = loadImage "assets/foxSpriteSheet.png"
  runSound = loadSound "assets/run.mp3"
}
```

In draw():

```
else if (kb.presses("right")) {
  player.      = "run"
  player.          .   = false
  runSound.
}
```

Also add this at the bottom:

```
function mousePressed
  userStartAudio
}
```

So your full code becomes:

```
/*
  Week 6 — Example 1: Sprites, Sprite Sheets, & Animation

  Course: GBDA302 | Instructors: Dr. Karen Cochrane & David Han
  Date: Feb. 26, 2026

  Controls:
    A or D (Left / Right Arrow)   Horizontal movement
    W (Up Arrow)                  Jump
    S (Down Arrow)                Idle
    Space Bar                     Attack
*/

let runSound
let player
let playerImg

let playerAnis =
  idle: { row: 0, frames: 4, frameDelay: 10 },
  run: { row: 1, frames: 4, frameDelay: 3 },
  jump: { row: 2, frames: 3, frameDelay: 8, frame: 0 },
  attack: { row: 3, frames: 6, frameDelay: 2 },
};
```

```
// level constants
const VIEWW = 320
  VIEWH = 180

const FRAME_W = 32
  FRAME_H = 32

const GRAVITY = 0

function preload
  playerImg = loadImage "assets/foxSpriteSheet.png"
  runSound = loadSound "assets/run.mp3"
}

function setup
  new Canvas VIEWW  VIEWH  "pixelated"
  allSprites.pixelPerfect = true;
  world.gravity.y = GRAVITY;

  player = new Sprite VIEWW / 2  VIEWH / 2  FRAME_W  FRAME_H
  player.spriteSheet = playerImg;
  player.rotationLock = true;

  player.       .    = FRAME_W
  player.       .   = FRAME_H
  player.       .          .   = -4
  player.              playerAnis
```

```
  player.      = "idle"
  player.    = 18
  player.    = 20
  player.removeColliders();
  player.friction = 0;
  player.bounciness = 0;
}

function draw
  background "skyblue"

  if (kb.presses("up")) {
    player.      = "jump"
  } else if (kb.presses("right")) {
    player.      = "run"
    player.          .   = false
    runSound.
  } else if (kb.presses("left")) {
    player.      = "run"
    player.          .   = true
  } else if (kb.presses(" ")) {
    player.      = "attack"
  } else if (kb.presses("down")) {
    player.      = "idle"
  }
}
```

```
function mousePressed
  userStartAudio
}
```

Important

Your [redacted] still needs the sound library:

```
<script src="https://cdn.jsdelivr.net/npm/p5@1/lib/addons/p5.sound.min.js"></script>
```

And when the game opens:

click once on the canvas

then press right arrow

That click is what unlocks sound. If you want, paste your [redacted] too.

wat with teh code i gav eu my insex looks liek this

```
<!doctype html>
<html lang="en">
  <head>
    <meta charset="utf-8" />
    <title>GBDA302 Week 6 - Example 1: Sprites, Sprite Sheets, & Animation</title>
    <style>
      body {
        margin: 0;
        overflow: hidden;
        background: #222;
      }
      canvas {
        display: block;
```

```
    }
  </style>
 </head>
 <body>
  <script src="https://cdn.jsdelivr.net/npm/p5@1.11.4/lib/p5.min.js"></script>
  <script src="https://p5play.org/v3/planck.min.js"></script>
  <script src="https://p5play.org/v3/p5play.min.js"></script>
  <script src="sketch.js"></script>
 </body>
</html>
```

That's the issue — your [redacted] is missing the sound library.

Add this line **between** [redacted] and [redacted]:

```
<script src="https://cdn.jsdelivr.net/npm/p5@1.11.4/lib/addons/p5.sound.min.js"></
script>
```

So your full [redacted] should be:

```
<!doctype html>
<html lang="en">
 <head>
  <meta charset="utf-8" />
  <title>GBDA302 Week 6 - Example 1: Sprites, Sprite Sheets, & Animation</title>
  <style>
   body {
    margin: 0;
```

```
      overflow: hidden;
      background: #222;
    }
    canvas {
      display: block;
    }
  </style>
</head>
<body>
  <script src="https://cdn.jsdelivr.net/npm/p5@1.11.4/lib/p5.min.js"></script>
  <script src="https://cdn.jsdelivr.net/npm/p5@1.11.4/lib/addons/p5.sound.min.js"></
script>
  <script src="https://p5play.org/v3/planck.min.js"></script>
  <script src="https://p5play.org/v3/p5play.min.js"></script>
  <script src="sketch.js"></script>
</body>
</html>
```

Then keep your sketch.js like this:

```
let runSound
let player
let playerImg

let playerAnis =
  idle: { row: 0, frames: 4, frameDelay: 10 },
  run: { row: 1, frames: 4, frameDelay: 3 },
```

```
  jump: { row: 2, frames: 3, frameDelay: 8, frame: 0 },
  attack: { row: 3, frames: 6, frameDelay: 2 },
};

const VIEWW = 320
  VIEWH = 180

const FRAME_W = 32
  FRAME_H = 32

const GRAVITY = 0

function preload
  playerImg = loadImage "assets/foxSpriteSheet.png"
  runSound = loadSound "assets/run.mp3"
}

function setup
  new Canvas VIEWW  VIEWH  "pixelated"
  allSprites.pixelPerfect = true;
  world.gravity.y = GRAVITY;

  player = new Sprite VIEWW / 2  VIEWH / 2  FRAME_W  FRAME_H
  player.spriteSheet = playerImg;
  player.rotationLock = true;

  player.       .    = FRAME_W
```

```
  player.       .   = FRAME_H
  player.       .         .   = -4
  player.             playerAnis
  player.      = "idle"
  player.    = 18
  player.   = 20
  player.removeColliders();
  player.friction = 0;
  player.bounciness = 0;
}

function draw
  background "skyblue"

  if (kb.presses("up")) {
    player.      = "jump"
  } else if (kb.presses("right")) {
    player.      = "run"
    player.         .   = false
    runSound.
  } else if (kb.presses("left")) {
    player.      = "run"
    player.         .   = true
  } else if (kb.presses(" ")) {
    player.      = "attack"
  } else if (kb.presses("down")) {
    player.      = "idle"
```

```
  }
}

function mousePressed
  userStartAudio
}
```

After that:

save both files

refresh the browser

click once anywhere on the game

press the right arrow

That should make it work.