

Administrator: Command Prompt

Microsoft Windows [Version 6.1.7601]
Copyright (c) 2009 Microsoft Corporation. All rights reserved.

C:\Users\user>ipconfig

Windows IP Configuration

Ethernet adapter Local Area Connection:

Connection-specific DNS Suffix . :
Link-local IPv6 Address : fe80::2ceb:ccb5:788:1e35%11
IPv4 Address. : 50.0.0.10
Subnet Mask : 255.0.0.0
Default Gateway :

Tunnel adapter isatap.{42A1F8B7-30A8-4EF7-81AF-C694F5F3D81B}:

Media State : Media disconnected
Connection-specific DNS Suffix . :

Tunnel adapter 6T04 Adapter:

Connection-specific DNS Suffix . :
IPv6 Address. : 2002:3200:a::3200:a
Default Gateway :

C:\Users\user>ping 50.0.0.20

Pinging 50.0.0.20 with 32 bytes of data:

Reply from 50.0.0.20: bytes=32 time=2ms TTL=128
Reply from 50.0.0.20: bytes=32 time<1ms TTL=128
Reply from 50.0.0.20: bytes=32 time=1ms TTL=128
Reply from 50.0.0.20: bytes=32 time<1ms TTL=128

Ping statistics for 50.0.0.20:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 0ms, Maximum = 2ms, Average = 0ms

C:\Users\user>

C:\ Administrator: Command Prompt

Microsoft Windows [Version 6.1.7601]
Copyright (c) 2009 Microsoft Corporation. All rights reserved.

C:\Users\user>ipconfig

Windows IP Configuration

Ethernet adapter Local Area Connection:

Connection-specific DNS Suffix . :
Link-local IPv6 Address : fe80::35fd:cc8:9b31:c87e%11
IPv4 Address. : 50.0.0.20
Subnet Mask : 255.0.0.0
Default Gateway :

Tunnel adapter isatap.{42A1F8B7-30A8-4EF7-81AF-C694F5F3D81B}:

Media State : Media disconnected
Connection-specific DNS Suffix . :

Tunnel adapter 6T04 Adapter:

Connection-specific DNS Suffix . :
IPv6 Address. : 2002:3200:14::3200:14
Default Gateway :

C:\Users\user>ping 50.0.0.10

Pinging 50.0.0.10 with 32 bytes of data:
Reply from 50.0.0.10: bytes=32 time=2ms TTL=128
Reply from 50.0.0.10: bytes=32 time=1ms TTL=128
Reply from 50.0.0.10: bytes=32 time=1ms TTL=128
Reply from 50.0.0.10: bytes=32 time=1ms TTL=128

Ping statistics for 50.0.0.10:
Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 1ms, Maximum = 2ms, Average = 1ms

C:\Users\user>

C:\ Administrator: Command Prompt

Microsoft Windows [Version 6.1.7601]
Copyright (c) 2009 Microsoft Corporation. All rights reserved.

C:\Users\user>ping sys1

Pinging sys1 [fe80::2ceb:ccb5:788:1e35%11] with 32 bytes of data:

Reply from fe80::2ceb:ccb5:788:1e35%11: time<1ms

Reply from fe80::2ceb:ccb5:788:1e35%11: time<1ms

Reply from fe80::2ceb:ccb5:788:1e35%11: time<1ms

Reply from fe80::2ceb:ccb5:788:1e35%11: time=1ms

Ping statistics for fe80::2ceb:ccb5:788:1e35%11:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

Approximate round trip times in milli-seconds:

Minimum = 0ms, Maximum = 1ms, Average = 0ms

C:\Users\user>

Administrator: Command Prompt

Microsoft Windows [Version 6.1.7601]
Copyright (c) 2009 Microsoft Corporation. All rights reserved.

C:\Users\user>ping sys2

Pinging sys2 [fe80::35fd:cc8:9b31:c87e%11] with 32 bytes of data:

Reply from fe80::35fd:cc8:9b31:c87e%11: time<1ms

Reply from fe80::35fd:cc8:9b31:c87e%11: time=1ms

Reply from fe80::35fd:cc8:9b31:c87e%11: time=1ms

Reply from fe80::35fd:cc8:9b31:c87e%11: time=1ms

Ping statistics for fe80::35fd:cc8:9b31:c87e%11:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

Approximate round trip times in milli-seconds:

Minimum = 0ms, Maximum = 1ms, Average = 0ms

C:\Users\user>_

PC1

Physical

Config

Desktop

Programming

Attributes

Command Prompt

X

```
Cisco Packet Tracer PC Command Line 1.0
C:\>ipconfig

FastEthernet0 Connection: (default port)

    Connection-specific DNS Suffix.:
    Link-local IPv6 Address.....: FE80::2D0:58FF:FEBE:BA96
    IPv6 Address.....: ::
    IPv4 Address.....: 50.0.0.20
    Subnet Mask.....: 255.0.0.0
    Default Gateway.....: ::
                        0.0.0.0

Bluetooth Connection:

    Connection-specific DNS Suffix.:
    Link-local IPv6 Address.....: ::
    IPv6 Address.....: ::
    IPv4 Address.....: 0.0.0.0
    Subnet Mask.....: 0.0.0.0
    Default Gateway.....: ::
                        0.0.0.0

C:\>ping 50.0.0.10

Pinging 50.0.0.10 with 32 bytes of data:

Reply from 50.0.0.10: bytes=32 time<1ms TTL=128
Reply from 50.0.0.10: bytes=32 time<1ms TTL=128
Reply from 50.0.0.10: bytes=32 time<1ms TTL=128
Reply from 50.0.0.10: bytes=32 time<1ms TTL=128

Ping statistics for 50.0.0.10:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\>
```



Top

PC0

Physical

Config

Desktop

Programming

Attributes

Command Prompt

X

Cisco Packet Tracer PC Command Line 1.0

C:\>ipconfig

FastEthernet0 Connection:(default port)

Connection-specific DNS Suffix.:
Link-local IPv6 Address.....: FE80::2E0:F7FF:FEED:D1E
IPv6 Address.....: ::
IPv4 Address.....: 50.0.0.10
Subnet Mask.....: 255.0.0.0
Default Gateway.....: ::
0.0.0.0

Bluetooth Connection:

Connection-specific DNS Suffix.:
Link-local IPv6 Address.....: ::
IPv6 Address.....: ::
IPv4 Address.....: 0.0.0.0
Subnet Mask.....: 0.0.0.0
Default Gateway.....: ::
0.0.0.0

C:\>ping 50.0.0.20

Pinging 50.0.0.20 with 32 bytes of data:

Reply from 50.0.0.20: bytes=32 time<1ms TTL=128
Reply from 50.0.0.20: bytes=32 time<1ms TTL=128
Reply from 50.0.0.20: bytes=32 time<1ms TTL=128
Reply from 50.0.0.20: bytes=32 time<1ms TTL=128

Ping statistics for 50.0.0.20:
Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\>

☐ Top







