



School: Campus:

Academic Year: Subject Name: Subject Code:

Semester: Program: Branch: Specialization:

Date:

Applied and Action Learning

(Learning by Doing and Discovery)

Name of the Experiment : Frontend Connect – Web3.js Integration

Coding Phase : Pseudo Code/Flow Chart/Algorithm

1. Start React project using `npx create-react-app`.
2. Install `web3` library.
3. Create `.env` file with:
4. In `app.js`:
 - Import Web3 and connect to MetaMask.
 - Load contract using ABI & address from `.env`.
 - Fetch `storedData` using `contract.methods.get().call()`.
 - Send transaction using `contract.methods.set(value).send()`.
5. Test the frontend by setting and getting values.

Apparatus/Software Used:

- Node.js & npm
- React.js
- Web3.js
- MetaMask
- **Network:** Sepolia Testnet

Testing Phase:

- Deployed `SimpleStorage` contract to Sepolia using Remix.
- Noted the contract address & ABI.
- Created `.env` file to store sensitive data.
- Connected frontend to MetaMask.
- Verified:
- Reading stored value works.
- Writing new value updates blockchain data.

Implementation Phase: Final Output (no error)

Step 1: Create a smart contract in remix IDE.

```
1 // SPDX-License-Identifier: MIT
2 pragma solidity ^0.8.0;
3 contract SimpleStorage{
4     uint public storedData;
5
6
7     constructor(uint _data) {    infinite gas 73800 gas
8         storedData = _data;
9     }
10
11     function set(uint x) public {    22514 gas
12         storedData = x;
13     }
14
15     function get() public view returns (uint) {    2453 gas
16         return storedData;
17     }
18 }
19
```

Step 2: Create a React app in VS Code.

- Open VS Code.
- Open a terminal inside of VS Code.
- Run this code (`npx create-react-app simple-storage-web3`).
- Then run `cd simple-storage-web3`.
- Then install web3 like run this code(`npm install web3`).

Step 3: Create a `.env` File.

- Write The deployed contract address from Remix or blockchain explorer.

```
1 REACT_APP_CONTRACT_ADDRESS=0x30DFDC7d8D9437A22Fe7DEa570C1477ac8aC9592
2 REACT_APP_NETWORK=sepolia
```

Step 4: Connect in `src/App.js`

- Replace `App.js` with something like:

```

import React, { useEffect, useState } from "react";
import Web3 from "web3";

// Load contract address from .env file
const CONTRACT_ADDRESS = process.env.REACT_APP_CONTRACT_ADDRESS;

// ABI for the contract
const ABI = [
  {
    inputs: [{ internalType: "uint256", name: "x", type: "uint256" }],
    name: "set",
    outputs: [],
    stateMutability: "nonpayable",
    type: "function",
  },
  {
    inputs: [
      { internalType: "uint256", name: "_data", type: "uint256" }
    ],
    stateMutability: "nonpayable",
    type: "constructor"
  },
  {
    inputs: [],
    name: "get",
    outputs: [{ internalType: "uint256", name: "", type: "uint256" }],
    stateMutability: "view",
    type: "function",
  },
  {
    inputs: [],
    name: "storedData",
    outputs: [{ internalType: "uint256", name: "", type: "uint256" }],
    stateMutability: "view",
    type: "function",
  },
];

function App() {
  const [account, setAccount] = useState("");
  const [contract, setContract] = useState(null);
  const [web3, setWeb3] = useState(null);
  const [inputValue, setInputValue] = useState("");
  const [storedValue, setStoredValue] = useState(null);

  useEffect(() => {
    const init = async () => {
      // Check for MetaMask
      if (window.ethereum) {
        try {
          const web3Instance = new Web3(window.ethereum);
          await window.ethereum.request({ method: "eth_requestAccounts" });
          const accounts = await web3Instance.eth.getAccounts();
          const contractInstance = new web3Instance.eth.Contract(ABI, CONTRACT_ADDRESS);
          setWeb3(web3Instance);
          setAccount(accounts[0]);
          setContract(contractInstance);
        } catch (error) {
          console.error("Wallet connection failed:", error);
        }
      } else {
        alert("Please install MetaMask to use this app.");
      }
    };

    init();
  }, []);

  const handleSet = async () => {
    if (contract && account) {
      try {
        await contract.methods.set(inputValue).send({ from: account });
        alert("Value set successfully!");
      } catch (err) {
        console.error("Error setting values:", err);
      }
    }
  };

  const handleGet = async () => {
    if (contract) {
      try {
        const value = await contract.methods.get().call();
        setStoredValue(value);
      } catch (err) {
        console.error("Error reading values:", err);
      }
    }
  };
}

export default App;

```

Step 5: Run the App

- In terminal: `npm start`

Step 6: After run this open React app at <http://localhost:3000>.



Simple Storage DApp (Web3.js)



Connect MetaMask

- Then connect the meta mask.
- Then Enter some value and set value .



Simple Storage DApp (Web3.js)

Connected: 0xc7e72E73c924058a28afDd1Bc27A30208379511b



Disconnect Wallet

Stored Value: 230

Update



Retrieve Latest Data

Observations

- Web3.js successfully connected frontend to blockchain.
- MetaMask allowed account access and transaction confirmation.
- Updating values from frontend reflected immediately on blockchain

ASSESSMENT

Rubrics	Full Mark	Marks Obtained	Remarks
Concept	10		
Planning and Execution/ Practical Simulation/ Programming	10		
Result and Interpretation	10		
Record of Applied and Action Learning	10		
Viva	10		
Total	50		

Signature of the Student:

Name :

Regn. No. :

Page No.....

Signature of the Faculty:

** As applicable according to the experiment.
Two sheets per experiment (10-20) to be used.*

