E+P 8

NMAP to Discover Live Host Using Nmap Scans on the try Hack Me platform

Introduction:

when tragetting a network. We need an efficient tool to handle repetitive task. the tool Should help us find out which Systems are active and what Service are running on those System.

This room is the first of four in this Nmap series. These four rooms are also Part of the Network Security module

- Nmap live Host Discovery
- Nmap basic Port Scans
- Nmap Advanced Port Scans
- Nmap Post Port Scans

ARP Scan : This Scan uses ARP request to discover live host

ICMP Scan : this can use ICMP requests to identify live host

TCP/UDP ping Scan : This scan send Packes to TCP ports and UDP ports to determine live host.

Subnetworks

A network segment is a group of computers linked through a shared medium, like an ethernet swith or wifi access point. In IP network, a Subnetwork typically consist of one or more network segment connected togethter and configured to use the same route. A network segment is physical connection, while a Subnetwork is logical connection

TCP ACK ping

To utilize ACK ping in Nmap, which
Send a packet with the ACK flag set, you
need to run Nmap as privileged user. If you
attempt this as an unprivileged user, Nmap
will perform a 3-Way handshake by default.

UDP Ping

You can also employ UDP to check if a
host is online. Unlike TCP SYN Ping, sending
UDP packet to an open port typically doesn't
elicit a response.

In Summary, while sending UDP packets
to open UDP ports may not trigger a
response. Sending them to closed UDP ports
can indirectly indicate that the target is
online as it may generate a port unreach-
able ICMP message.

b configuration of Wireless LAN using CISCO Packet Tracer

Design a topology with three PC's connected from Linksys Wireless routers

Perform following configuration

- Configure Static IP on Pc and Wireless Router
- set SSID to Mother Network
- Set IP address of router to 192.168.0.1 PC0 to 192.168.0.2 PC1 to 192.168.0.3 and PC2 to 192.168.0.4.
- Secure your network by configuring WAP key on Router
- Connect PC by using WAP key

To complete these tasks follows these Step by Step instruction.

Step 1: Click on wireless router

- select Administration tab from top Menu set username and password to admin and click on Save Setting

- Next click on Wireless tab and set Sta
SSID to Mother Network

- Now Select wireless Security and chang
Security Mode to WEP

- Set key1 to 0123456789.

- Again go in the end of Pages and click o
Save Setting

- Now we have completed all given
on Wireless router. Now configure the Stati
on all three PC's

- Double click on PC select Desktop
click on IP configuration select Static IP
set IP as given below

PC	IP	Subnetmark	Default Gatew
PC0	192.168.0.2	255.255.255.0	192.168.0.
PC1	192.168.0.3	255.255.255.0	192.168.0.
PC2	192.168.0.4	255.255.255.0	192.168.0.1

- Repeat Same process on PC1 and PC2

Result : NMAP discover live host using NMAP has been done successfully