Team ID : SWTID-2026-4363

Team Size : 4

Team Leader : B.Abirami

EMail Id : abirami182007@gmail.com

NM Id : B8052AA8DB4F42A89944E68B3580FA7E

Team members :

1. **T.Akshaya**
   Email Id : priyatamilt615@gmail.com
   NM Id : 40B59E943616E62AB0142961CFD5E6B2
2. **V. Aarthi**
   Email Id : vaarthi995@gmail.com
   NM Id : 32C5AB2613C9264BDAC4B6BEE751E092
3. **K. Abinaya**
   Email Id : abinayakumar727@gmail.com
   NM Id : AAABDBAF386D9F283544F42E2B353FE3

Team Title

Script-Controlled ACL – Restrict Record Access Based on Field Value

Description :

This lab demonstrates how to implement a **script-controlled Access Control List (ACL)** to restrict users from viewing records unless they meet specific conditions. In this scenario, only users belonging to the **EEE branch** are allowed to view records where the **Branch** field is set to **EEE**, while administrators retain full access.


Timer :

3 hrs

Milestone-1 Creation of Users and Roles

User Creation:

1. Log in to the ServiceNow instance with **admin** access.
2. **Create** a test user:
   - Navigate to User Administration → Users
   - Click **New**
   - **User ID:** EEE User
   - **First name:** EEE
   - **Last name:** User
   - **Email:** eeeuser@gmail.com
   - Save the record




GO FURTHER



Role Creation

- Navigate to **User Administration → Roles**
- Click **New**
- **Name**: Enter role name as bb1
- **Description**: Brief role purpose
- Click **Submit**
- Create other roles also like **bb2,bb3,bb4.(follow the same procedure)**
- Assign all the roles to the EEE User






Tables Creation

1. In the **Application Navigator**, search for **System Definition → Tables**.
2. Click **New** and create a custom table with the following details:
    - **Label:** Institution Details
    - **Name:** u_institution_details
    - **Extends for :** false





3. Click **Submit**.
4. Add the following fields to the **u_institution_details** table:
    - **Student Roll Number**– Auto Number
    - **Student Name** – Reference- User
    - **Faculty Name** – Reference- User
    - **Branch** – Choice (ECE, EEE, CSE)
    - **Email**– String
    - **Phone Number**– String
    - **Description**– Multi String
5. Save the Table



6. Create multiple records in the **Student Records** table with different branch values (ECE, EEE, CSE).



Creation of Access Control Lists(Read ACL)

1. In the **Application Navigator**, search for **System Security → Access Control (ACL)**.
2. Elevate "Security_admin" role
3. Click **New** to create a new ACL.
4. Enter the following details:
    - **Type:** record
    - **Operation:** read
    - **Name:** u_institution_details
    - **Active:** true


- **Advanced:** true

5. In the **Requires role** related list, add
   - bb1 (custom role)
6. Add Data condition as **Branch is EEE**
7. In the **Script** field, add the following script

```
(function () {

// Allow admin users full access
if (gs.hasRole('admin')) {
  return true;
}
// Allow only EEE branch users to see EEE records
if (gs.hasRole('bb1')){
  return true;
}
// Deny access for all others
return false;
})();
```

8. Click **Submit** to save the ACL



Elevate role

Close dialog

Elevate a role by adding privileges, which end when you log out. Learn more

AVAILABLE ROLES

- [x] security_admin


  Grant modification access to High Security Settings, allow user to modify the Access Control List

Cancel




Access Controls
Updated
Search
Actions on selected rows...
New
All
Name
Decision Type
Operation
Type
Active
Updated by
Updated
sn_try_build_agent_message
Deny Unless
read
record
true
system
19-10-2025 22:23:04
sn_try_build_agent_freemium_usage_log
sn_try_build_agent_conversation
delete
write
sn_try_build_agent_event_telemetry
report_view
sn_try_build_agent_task_telemetry
sn_try_build_agent_knowledge_source
Allow If
61 to 80 of 32,702


Access Control
u_institution_details
Update
Delete
* Type
record
* Operation
read
Decision Type
Allow If
Admin overrides
Protection policy
-- None --
Application
Global
Active
Advanced
* Name
Institution Details [u_institution_details]
Description
Applies To
Add Filter Condition
Add OR Clause
-- choose field --
-- oper --
-- value --


Data Condition
Condition
Add Filter Condition
Add OR Clause
Branch
is
EEE
AND
OR
Advanced Condition
Controlled by References
Script
Turn on ECMAScript 2021 (ES12) mode
(function() {
if (gs.hasRole('bol')) {
return true;
} else {
return false;
}
})();

9. Impersonate **EEE users** and open the Student Records list.
10. Copy the table name u_institution_details.list/LIST and paste in the All menu.
11. Impersonate **Admin** and open the Student Records list.

Verify :


- User with **bb1 role** can view **only EEE branch records**



- User without the role cannot view any records





- Admin user can view **all records regardless of branch**




Creation of Access Control Lists(Create ACL)

1. Click **New** to create a new ACL(Create)
2. Enter the following details:
    - **Type:** record
    - **Operation:** create
    - **Name:** u_institution_details
    - **Active:** true
3. In the **Requires role** related list, add:
    - bb2 (custom role)
4. No need to add any Data condition
5. Save the ACL Record









Verify :

- User with **bb1 &bb2 roles** can view **only EEE branch records b New** Button




Creation of Access Control Lists(Write ACL)


12. Click New to create a new ACL(Write)
13. Enter the following details:
    - Type: record
    - Operation: Write
    - Name: u_institution_details


- Active: true

14. In the Requires role related list, add:
    - bb3 (custom role)
15. No need to add any Data condition
16. Save the ACL Record









Verify :

- User with **bb1 &bb2 &bb3 roles** can view and edit the **EEE branch records along with New Button**






Creation of Access Control Lists(Delete ACL)

17. Click **New** to create a new ACL(Delete)
18. Enter the following details
    - **Type:** record
    - **Operation:** Delete
    - **Name:** u_institution_details
    - **Active:** true
19. In the **Requires role** related list, add
    - bb4 (custom role)
20. No need to add any Data condition
21. Save the ACL Record










Security Attribute Condition

Verify :

- Users with **bb1 &bb2 &bb3&bb4 roles** can see, create and edit along with delete the **EEE branch records.**







Outcome :

By completing this lab, learners gain a comprehensive understanding of how script-controlled READ, WRITE, CREATE, and DELETE ACLs enforce record-level security, how user roles and record field values are evaluated together to make access decisions, and how ACLs protect sensitive data from unauthorized viewing, modification, creation, and deletion across forms, lists, and Service Portal interfaces.