

Appium Mobile Testing Report

Documentation-Only Quality Assurance Package

Prepared for: Dentzy App Mobile QA

Report Date: 11 July 2026

Generated: 2026-07-11 12:12:55

Execution Status: Not Executed

Table of Contents

Placeholder for table of contents

0

Project Overview

This report is a senior-level QA documentation package prepared without executing any automation tests. It defines Appium mobile testing scope, structure, and representative coverage for the Dentzy application.

Scope

Coverage includes splash, authentication, registration, dashboard, profile, settings, search, notifications, permissions, offline mode, session management, logout, error handling, boundary, negative, and regression scenarios.

Test Environment

Platform: Android. State: Documentation-only. Framework context: Appium mobile testing coverage package.

Environment Item	Value
Platform	Android
Target Device	Emulator-based mobile test environment
Framework	Appium mobile testing with documented coverage
Execution State	Not Executed

Test Strategy

Risk-based coverage is used across critical journeys, negative paths, boundary values, offline resilience, and regression verification.

Test Execution Summary

Sample / documentation-only summary: no execution was performed for this report.

Metric	Value	Notes
Total Planned Cases	300	Documentation coverage plan
Executed Cases	0	No tests were run
Overall Status	Not Executed	Documentation only

Defect Summary

No defects are recorded because no live execution was performed.

Detailed Test Cases

Splash Screen

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity
green	App branding and launch transition	Verify Cold Start Screen supports cold start	App is installed and breaking the user ready	1. Open the splash screen path in the app. 2. Trigger the cold start launch variation for the splash screen flow. 3. Observe the on-screen response and navigation outcome.	The splash screen should render the brand,	Not Executed	Not Executed	P1	Highly to the
green	App branding and launch transition	Verify First Run Display supports first-run	App is installed and breaking the user ready	1. Open the splash screen path in the app. 2. Trigger the first-run display variation for the splash screen flow. 3. Observe the on-screen response and navigation outcome.	The splash screen should render the brand,	Not Executed	Not Executed	P1	Highly to the
green	App branding and launch transition	Verify Splash Animation supports loading a	App is installed and breaking the user ready	1. Open the splash screen path in the app. 2. Trigger the loading animation variation for the splash screen flow. 3. Observe the on-screen response and navigation outcome.	The splash screen should render the brand,	Not Executed	Not Executed	P2	Highly to the
green	App branding and launch transition	Verify Background to Foreground Resum	App is installed and breaking the user ready	1. Open the splash screen path in the app. 2. Trigger the background to foreground resume variation for the splash screen flow. 3. Observe the on-screen response and navigation outcome.	The splash screen should render the brand,	Not Executed	Not Executed	P2	Highly to the
green	App branding and launch transition	Verify Force Close And Relaunch force close	App is installed and breaking the user ready	1. Open the splash screen path in the app. 2. Trigger the force close and relaunch variation for the splash screen flow. 3. Observe the on-screen response and navigation outcome.	The splash screen should render the brand,	Not Executed	Not Executed	P1	Highly to the
green	App branding and launch transition	Verify Slow Network Response slow network	App is installed and breaking the user ready	1. Open the splash screen path in the app. 2. Trigger the slow network response variation for the splash screen flow. 3. Observe the on-screen response and navigation outcome.	The splash screen should render the brand,	Not Executed	Not Executed	P2	Highly to the
green	App branding and launch transition	Verify Offline Network Support offline network	App is installed and breaking the user ready	1. Open the splash screen path in the app. 2. Trigger the offline network condition variation for the splash screen flow. 3. Observe the on-screen response and navigation outcome.	The splash screen should render the brand,	Not Executed	Not Executed	P1	Highly to the
green	App branding and launch transition	Verify Cached Data Fallback supports cached data	App is installed and breaking the user ready	1. Open the splash screen path in the app. 2. Trigger the cached data fallback variation for the splash screen flow. 3. Observe the on-screen response and navigation outcome.	The splash screen should render the brand,	Not Executed	Not Executed	P2	Highly to the
green	App branding and launch transition	Verify Accessibility Focus Order accessibility focus	App is installed and breaking the user ready	1. Open the splash screen path in the app. 2. Trigger the accessibility focus order variation for the splash screen flow. 3. Observe the on-screen response and navigation outcome.	The splash screen should render the brand,	Not Executed	Not Executed	P2	Highly to the
green	App branding and launch transition	Verify Localization Rendering supports localization	App is installed and breaking the user ready	1. Open the splash screen path in the app. 2. Trigger the localization rendering variation for the splash screen flow. 3. Observe the on-screen response and navigation outcome.	The splash screen should render the brand,	Not Executed	Not Executed	P1	Highly to the
green	App branding and launch transition	Verify Repeated Tap Handling repeated	App is installed and breaking the user ready	1. Open the splash screen path in the app. 2. Trigger the repeated tap handling variation for the splash screen flow. 3. Observe the on-screen response and navigation outcome.	The splash screen should render the brand,	Not Executed	Not Executed	P2	Highly to the
green	App branding and launch transition	Verify Boundary Validation supports boundary	App is installed and breaking the user ready	1. Open the splash screen path in the app. 2. Trigger the boundary input validation variation for the splash screen flow. 3. Observe the on-screen response and navigation outcome.	The splash screen should render the brand,	Not Executed	Not Executed	P2	Highly to the
green	App branding and launch transition	Verify Invalid Input Rejection supports invalid	App is installed and breaking the user ready	1. Open the splash screen path in the app. 2. Trigger the invalid input rejection variation for the splash screen flow. 3. Observe the on-screen response and navigation outcome.	The splash screen should render the brand,	Not Executed	Not Executed	P1	Highly to the
green	App branding and launch transition	Verify Empty State Rendering empty state	App is installed and breaking the user ready	1. Open the splash screen path in the app. 2. Trigger the empty state rendering variation for the splash screen flow. 3. Observe the on-screen response and navigation outcome.	The splash screen should render the brand,	Not Executed	Not Executed	P2	Highly to the

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity
green	App branding and launch transition	Verify Splash Screen Handling session expiry	App is installed with the branding ready for rendering the splash screen path in the app.	1. Open the app. 2. Trigger the session expiry handling variation for the splash screen flow. 3. Observe the on-screen response and navigation outcome.	The splash screen should render the brand, render the session expiry handling variation.	Not Executed for the configuration.	Failed	P1	transition clearly to the
green	App branding and launch transition	Verify Permission Prompt Handling	App is installed with the branding ready for rendering the splash screen path in the app.	1. Open the app. 2. Trigger the permission prompt handling variation for the splash screen flow. 3. Observe the on-screen response and navigation outcome.	The splash screen should render the brand, render the permission prompt handling variation.	Not Executed for the configuration.	Failed	P2	transition clearly to the
green	App branding and launch transition	Verify Notification Entry Handling	App is installed with the branding ready for rendering the splash screen path in the app.	1. Open the app. 2. Trigger the notification entry handling variation for the splash screen flow. 3. Observe the on-screen response and navigation outcome.	The splash screen should render the brand, render the notification entry handling variation.	Not Executed for the configuration.	Failed	P2	transition clearly to the
green	App branding and launch transition	Verify Deep Link Navigation	App is installed with the branding ready for rendering the splash screen path in the app.	1. Open the app. 2. Trigger the deep link navigation variation for the splash screen flow. 3. Observe the on-screen response and navigation outcome.	The splash screen should render the brand, render the deep link navigation variation.	Not Executed for the configuration.	Failed	P1	transition clearly to the
green	App branding and launch transition	Verify Device State Change Handling	App is installed with the branding ready for rendering the splash screen path in the app.	1. Open the app. 2. Trigger the device state change handling variation for the splash screen flow. 3. Observe the on-screen response and navigation outcome.	The splash screen should render the brand, render the device state change handling variation.	Not Executed for the configuration.	Failed	P2	transition clearly to the

Login

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity
	Authentication form and credentials	Verify Login Success Cold Start	User is not logged in successfully	1. Open the app. 2. Trigger the cold start launch variation for the login flow. 3. Observe the on-screen response and navigation outcome.	The login screen should validate inputs, preserve the session state.	Not Executed for the configuration.	Failed	P1	without UI breakage.
	Authentication form and credentials	Verify Login Success First Run	User is not logged in successfully	1. Open the app. 2. Trigger the first-run display variation for the login flow. 3. Observe the on-screen response and navigation outcome.	The login screen should validate inputs, preserve the session state.	Not Executed for the configuration.	Failed	P1	without UI breakage.
	Authentication form and credentials	Verify Login Success Loading Animation	User is not logged in successfully	1. Open the app. 2. Trigger the loading animation variation for the login flow. 3. Observe the on-screen response and navigation outcome.	The login screen should validate inputs, preserve the session state.	Not Executed for the configuration.	Failed	P2	without UI breakage.
	Authentication form and credentials	Verify Login Success Background To Foreground Resume	User is not logged in successfully	1. Open the app. 2. Trigger the background to foreground resume variation for the login flow. 3. Observe the on-screen response and navigation outcome.	The login screen should validate inputs, preserve the session state.	Not Executed for the configuration.	Failed	P2	without UI breakage.
	Authentication form and credentials	Verify Login Success Force Close and Relaunch	User is not logged in successfully	1. Open the app. 2. Trigger the force close and relaunch variation for the login flow. 3. Observe the on-screen response and navigation outcome.	The login screen should validate inputs, preserve the session state.	Not Executed for the configuration.	Failed	P1	without UI breakage.
	Authentication form and credentials	Verify Login Success Slow Network Response	User is not logged in successfully	1. Open the app. 2. Trigger the slow network response variation for the login flow. 3. Observe the on-screen response and navigation outcome.	The login screen should validate inputs, preserve the session state.	Not Executed for the configuration.	Failed	P2	without UI breakage.
	Authentication form and credentials	Verify Login Success Offline Network Condition	User is not logged in successfully	1. Open the app. 2. Trigger the offline network condition variation for the login flow. 3. Observe the on-screen response and navigation outcome.	The login screen should validate inputs, preserve the session state.	Not Executed for the configuration.	Failed	P1	without UI breakage.
	Authentication form and credentials	Verify Login Success Cached Data Fallback	User is not logged in successfully	1. Open the app. 2. Trigger the cached data fallback variation for the login flow. 3. Observe the on-screen response and navigation outcome.	The login screen should validate inputs, preserve the session state.	Not Executed for the configuration.	Failed	P2	without UI breakage.
	Authentication form and credentials	Verify Login Success Accessibility Focus Order	User is not logged in successfully	1. Open the app. 2. Trigger the accessibility focus order variation for the login flow. 3. Observe the on-screen response and navigation outcome.	The login screen should validate inputs, preserve the session state.	Not Executed for the configuration.	Failed	P2	without UI breakage.

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity
	Authentication form and credentials	Web browser supports localization rendering of login screen without breaking screen with a valid account on the high path authentication flows.	1. Open the app and navigate to the login screen. 2. Trigger the localization rendering variation for the login flow. 3. Observe the on-screen response and navigation outcome.	The login screen should validate inputs, preserve security, and handle session state. P1 without UI breakage.			Not Executed	P1	High
	Authentication form and credentials	Web browser supports repeated tap handling of login screen without breaking screen with a valid account on the high path authentication flows.	1. Open the app and navigate to the login screen. 2. Trigger the repeated tap handling variation for the login flow. 3. Observe the on-screen response and navigation outcome.	The login screen should validate inputs, preserve security, and handle session state. P2 without UI breakage.			Not Executed	P2	Medium
	Authentication form and credentials	Web browser supports boundary input validation of login screen without breaking screen with a valid account on the high path authentication flows.	1. Open the app and navigate to the login screen. 2. Trigger the boundary input validation variation for the login flow. 3. Observe the on-screen response and navigation outcome.	The login screen should validate inputs, preserve security, and handle session state. P2 without UI breakage.			Not Executed	P2	Medium
	Authentication form and credentials	Web browser supports invalid input rejection of login screen without breaking screen with a valid account on the high path authentication flows.	1. Open the app and navigate to the login screen. 2. Trigger the invalid input rejection variation for the login flow. 3. Observe the on-screen response and navigation outcome.	The login screen should validate inputs, preserve security, and handle session state. P1 without UI breakage.			Not Executed	P1	High
	Authentication form and credentials	Web browser supports empty state rendering of login screen without breaking screen with a valid account on the high path authentication flows.	1. Open the app and navigate to the login screen. 2. Trigger the empty state rendering variation for the login flow. 3. Observe the on-screen response and navigation outcome.	The login screen should validate inputs, preserve security, and handle session state. P2 without UI breakage.			Not Executed	P2	Medium
	Authentication form and credentials	Web browser supports session expiry handling of login screen without breaking screen with a valid account on the high path authentication flows.	1. Open the app and navigate to the login screen. 2. Trigger the session expiry handling variation for the login flow. 3. Observe the on-screen response and navigation outcome.	The login screen should validate inputs, preserve security, and handle session state. P1 without UI breakage.			Not Executed	P1	High
	Authentication form and credentials	Web browser supports permission prompt handling of login screen without breaking screen with a valid account on the high path authentication flows.	1. Open the app and navigate to the login screen. 2. Trigger the permission prompt handling variation for the login flow. 3. Observe the on-screen response and navigation outcome.	The login screen should validate inputs, preserve security, and handle session state. P2 without UI breakage.			Not Executed	P2	Medium
	Authentication form and credentials	Web browser supports notification entry handling of login screen without breaking screen with a valid account on the high path authentication flows.	1. Open the app and navigate to the login screen. 2. Trigger the notification entry handling variation for the login flow. 3. Observe the on-screen response and navigation outcome.	The login screen should validate inputs, preserve security, and handle session state. P2 without UI breakage.			Not Executed	P2	Medium
	Authentication form and credentials	Web browser supports deep link navigation of login screen without breaking screen with a valid account on the high path authentication flows.	1. Open the app and navigate to the login screen. 2. Trigger the deep link navigation variation for the login flow. 3. Observe the on-screen response and navigation outcome.	The login screen should validate inputs, preserve security, and handle session state. P1 without UI breakage.			Not Executed	P1	High
	Authentication form and credentials	Web browser supports device state change handling of login screen without breaking screen with a valid account on the high path authentication flows.	1. Open the app and navigate to the login screen. 2. Trigger the device state change handling variation for the login flow. 3. Observe the on-screen response and navigation outcome.	The login screen should validate inputs, preserve security, and handle session state. P2 without UI breakage.			Not Executed	P2	Medium

Registration

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity
on	New account creation workflow	Verify Registration supports cold start authentication screen	1. User without registration screen	1. Open the app and navigate to the registration screen. 2. Trigger the cold start launch variation for the registration flow. 3. Observe the on-screen response and navigation outcome.	The registration flow should collect required data, validate fields, and create account. P1 when all critical are v		Not Executed	P1	Critical
on	New account creation workflow	Verify Registration supports first-run display screen	1. User without registration screen	1. Open the app and navigate to the registration screen. 2. Trigger the first-run display variation for the registration flow. 3. Observe the on-screen response and navigation outcome.	The registration flow should collect required data, validate fields, and create account. P1 when all high are v		Not Executed	P1	High
on	New account creation workflow	Verify Registration supports loading animation screen	1. User without registration screen	1. Open the app and navigate to the registration screen. 2. Trigger the loading animation variation for the registration flow. 3. Observe the on-screen response and navigation outcome.	The registration flow should collect required data, validate fields, and create account. P2 when all medium are v		Not Executed	P2	Medium
on	New account creation workflow	Verify Registration supports background to foreground resume screen	1. User without registration screen	1. Open the app and navigate to the registration screen. 2. Trigger the background to foreground resume variation for the registration flow. 3. Observe the on-screen response and navigation outcome.	The registration flow should collect required data, validate fields, and create account. P2 when all medium are v		Not Executed	P2	Medium

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity
on	New account creation workflow	Verify Account Reports force close	User is on the registration screen and the app is running in the background.	1. Tap the force close button to close the app. 2. Trigger the force close and relaunch variation for the registration flow. 3. Observe the on-screen response and navigation outcome.	The registration flow should collect required data and validate fields, and then proceed to account creation.	Not Executed	Not Executed	P1	High
on	New account creation workflow	Verify Network Response slow network	User is on the registration screen and the app is running in the background.	1. Trigger the slow network response variation for the registration flow. 2. Trigger the force close and relaunch variation for the registration flow. 3. Observe the on-screen response and navigation outcome.	The registration flow should collect required data and validate fields, and then proceed to account creation.	Not Executed	Not Executed	P2	Medium
on	New account creation workflow	Verify Offline Mode Catches offline network	User is on the registration screen and the app is running in the background.	1. Trigger the offline network condition variation for the registration flow. 2. Trigger the force close and relaunch variation for the registration flow. 3. Observe the on-screen response and navigation outcome.	The registration flow should collect required data and validate fields, and then proceed to account creation.	Not Executed	Not Executed	P1	High
on	New account creation workflow	Verify Cached Data Fallback supports cached data	User is on the registration screen and the app is running in the background.	1. Trigger the cached data fallback variation for the registration flow. 2. Trigger the force close and relaunch variation for the registration flow. 3. Observe the on-screen response and navigation outcome.	The registration flow should collect required data and validate fields, and then proceed to account creation.	Not Executed	Not Executed	P2	Medium
on	New account creation workflow	Verify Accessibility Focus Order accessibility	User is on the registration screen and the app is running in the background.	1. Trigger the accessibility focus order variation for the registration flow. 2. Trigger the force close and relaunch variation for the registration flow. 3. Observe the on-screen response and navigation outcome.	The registration flow should collect required data and validate fields, and then proceed to account creation.	Not Executed	Not Executed	P2	High
on	New account creation workflow	Verify Localization Rendering supports localization	User is on the registration screen and the app is running in the background.	1. Trigger the localization rendering variation for the registration flow. 2. Trigger the force close and relaunch variation for the registration flow. 3. Observe the on-screen response and navigation outcome.	The registration flow should collect required data and validate fields, and then proceed to account creation.	Not Executed	Not Executed	P1	Medium
on	New account creation workflow	Verify Repeated Tap Handling supports repeated tap	User is on the registration screen and the app is running in the background.	1. Trigger the repeated tap handling variation for the registration flow. 2. Trigger the force close and relaunch variation for the registration flow. 3. Observe the on-screen response and navigation outcome.	The registration flow should collect required data and validate fields, and then proceed to account creation.	Not Executed	Not Executed	P2	High
on	New account creation workflow	Verify Boundary Validation supports boundary	User is on the registration screen and the app is running in the background.	1. Trigger the boundary input validation variation for the registration flow. 2. Trigger the force close and relaunch variation for the registration flow. 3. Observe the on-screen response and navigation outcome.	The registration flow should collect required data and validate fields, and then proceed to account creation.	Not Executed	Not Executed	P2	High
on	New account creation workflow	Verify Invalid Input Rejection supports invalid input	User is on the registration screen and the app is running in the background.	1. Trigger the invalid input rejection variation for the registration flow. 2. Trigger the force close and relaunch variation for the registration flow. 3. Observe the on-screen response and navigation outcome.	The registration flow should collect required data and validate fields, and then proceed to account creation.	Not Executed	Not Executed	P1	High
on	New account creation workflow	Verify Empty State Rendering supports empty state	User is on the registration screen and the app is running in the background.	1. Trigger the empty state rendering variation for the registration flow. 2. Trigger the force close and relaunch variation for the registration flow. 3. Observe the on-screen response and navigation outcome.	The registration flow should collect required data and validate fields, and then proceed to account creation.	Not Executed	Not Executed	P2	High
on	New account creation workflow	Verify Session Expiry Handling supports session expiry	User is on the registration screen and the app is running in the background.	1. Trigger the session expiry handling variation for the registration flow. 2. Trigger the force close and relaunch variation for the registration flow. 3. Observe the on-screen response and navigation outcome.	The registration flow should collect required data and validate fields, and then proceed to account creation.	Not Executed	Not Executed	P1	Critical
on	New account creation workflow	Verify Permission Prompt Handling supports permission	User is on the registration screen and the app is running in the background.	1. Trigger the permission prompt handling variation for the registration flow. 2. Trigger the force close and relaunch variation for the registration flow. 3. Observe the on-screen response and navigation outcome.	The registration flow should collect required data and validate fields, and then proceed to account creation.	Not Executed	Not Executed	P2	High
on	New account creation workflow	Verify Notification Entry Handling supports notification	User is on the registration screen and the app is running in the background.	1. Trigger the notification entry handling variation for the registration flow. 2. Trigger the force close and relaunch variation for the registration flow. 3. Observe the on-screen response and navigation outcome.	The registration flow should collect required data and validate fields, and then proceed to account creation.	Not Executed	Not Executed	P2	Medium
on	New account creation workflow	Verify Deep Link Navigation supports deep link	User is on the registration screen and the app is running in the background.	1. Trigger the deep link navigation variation for the registration flow. 2. Trigger the force close and relaunch variation for the registration flow. 3. Observe the on-screen response and navigation outcome.	The registration flow should collect required data and validate fields, and then proceed to account creation.	Not Executed	Not Executed	P1	High
on	New account creation workflow	Verify Device State Change Handling supports device state	User is on the registration screen and the app is running in the background.	1. Trigger the device state change handling variation for the registration flow. 2. Trigger the force close and relaunch variation for the registration flow. 3. Observe the on-screen response and navigation outcome.	The registration flow should collect required data and validate fields, and then proceed to account creation.	Not Executed	Not Executed	P2	High

Dashboard

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity
d	Home landing cards and quick actions dashboard	Cold start launch supports cold start launch with authentication	User is not authenticated in the session	1. Open the dashboard in the app. 2. Trigger the cold start launch variation for the dashboard flow. 3. Observe the on-screen response and navigation outcome.	The dashboard should load core widgets, display a cold start message, and navigate to the home screen.	As expected	Not Executed	High	Critical
d	Home landing cards and quick actions dashboard	First-run display shows first-run display with a bubble	User is not authenticated in the session	1. Open the dashboard in the app. 2. Trigger the first-run display variation for the dashboard flow. 3. Observe the on-screen response and navigation outcome.	The dashboard should load core widgets, display a first-run message, and navigate to the home screen.	As expected	Not Executed	High	High
d	Home landing cards and quick actions dashboard	Loading animation displays loading animation with a bubble	User is not authenticated in the session	1. Open the dashboard in the app. 2. Trigger the loading animation variation for the dashboard flow. 3. Observe the on-screen response and navigation outcome.	The dashboard should load core widgets, display a loading animation, and navigate to the home screen.	As expected	Not Executed	High	High
d	Home landing cards and quick actions dashboard	Background to foreground resume displays background to foreground resume	User is not authenticated in the session	1. Open the dashboard in the app. 2. Trigger the background to foreground resume variation for the dashboard flow. 3. Observe the on-screen response and navigation outcome.	The dashboard should load core widgets, display a background to foreground resume message, and navigate to the home screen.	As expected	Not Executed	High	High
d	Home landing cards and quick actions dashboard	Force close and relaunch displays force close and relaunch	User is not authenticated in the session	1. Open the dashboard in the app. 2. Trigger the force close and relaunch variation for the dashboard flow. 3. Observe the on-screen response and navigation outcome.	The dashboard should load core widgets, display a force close and relaunch message, and navigate to the home screen.	As expected	Not Executed	High	High
d	Home landing cards and quick actions dashboard	Slow network response displays slow network response	User is not authenticated in the session	1. Open the dashboard in the app. 2. Trigger the slow network response variation for the dashboard flow. 3. Observe the on-screen response and navigation outcome.	The dashboard should load core widgets, display a slow network response message, and navigate to the home screen.	As expected	Not Executed	High	High
d	Home landing cards and quick actions dashboard	Offline network condition displays offline network condition	User is not authenticated in the session	1. Open the dashboard in the app. 2. Trigger the offline network condition variation for the dashboard flow. 3. Observe the on-screen response and navigation outcome.	The dashboard should load core widgets, display an offline network condition message, and navigate to the home screen.	As expected	Not Executed	High	High
d	Home landing cards and quick actions dashboard	Cached data fallback displays cached data fallback	User is not authenticated in the session	1. Open the dashboard in the app. 2. Trigger the cached data fallback variation for the dashboard flow. 3. Observe the on-screen response and navigation outcome.	The dashboard should load core widgets, display a cached data fallback message, and navigate to the home screen.	As expected	Not Executed	High	High
d	Home landing cards and quick actions dashboard	Accessibility focus order displays accessibility focus order	User is not authenticated in the session	1. Open the dashboard in the app. 2. Trigger the accessibility focus order variation for the dashboard flow. 3. Observe the on-screen response and navigation outcome.	The dashboard should load core widgets, display an accessibility focus order message, and navigate to the home screen.	As expected	Not Executed	High	High
d	Home landing cards and quick actions dashboard	Localization rendering displays localization rendering	User is not authenticated in the session	1. Open the dashboard in the app. 2. Trigger the localization rendering variation for the dashboard flow. 3. Observe the on-screen response and navigation outcome.	The dashboard should load core widgets, display a localization rendering message, and navigate to the home screen.	As expected	Not Executed	High	High
d	Home landing cards and quick actions dashboard	Repeated tap handling displays repeated tap handling	User is not authenticated in the session	1. Open the dashboard in the app. 2. Trigger the repeated tap handling variation for the dashboard flow. 3. Observe the on-screen response and navigation outcome.	The dashboard should load core widgets, display a repeated tap handling message, and navigate to the home screen.	As expected	Not Executed	High	High
d	Home landing cards and quick actions dashboard	Boundary input validation displays boundary input validation	User is not authenticated in the session	1. Open the dashboard in the app. 2. Trigger the boundary input validation variation for the dashboard flow. 3. Observe the on-screen response and navigation outcome.	The dashboard should load core widgets, display a boundary input validation message, and navigate to the home screen.	As expected	Not Executed	High	High
d	Home landing cards and quick actions dashboard	Invalid input rejection displays invalid input rejection	User is not authenticated in the session	1. Open the dashboard in the app. 2. Trigger the invalid input rejection variation for the dashboard flow. 3. Observe the on-screen response and navigation outcome.	The dashboard should load core widgets, display an invalid input rejection message, and navigate to the home screen.	As expected	Not Executed	High	High
d	Home landing cards and quick actions dashboard	Empty state rendering displays empty state rendering	User is not authenticated in the session	1. Open the dashboard in the app. 2. Trigger the empty state rendering variation for the dashboard flow. 3. Observe the on-screen response and navigation outcome.	The dashboard should load core widgets, display an empty state rendering message, and navigate to the home screen.	As expected	Not Executed	High	High
d	Home landing cards and quick actions dashboard	Session expiry handling displays session expiry handling	User is not authenticated in the session	1. Open the dashboard in the app. 2. Trigger the session expiry handling variation for the dashboard flow. 3. Observe the on-screen response and navigation outcome.	The dashboard should load core widgets, display a session expiry handling message, and navigate to the home screen.	As expected	Not Executed	High	Critical
d	Home landing cards and quick actions dashboard	Permission prompt handling displays permission prompt handling	User is not authenticated in the session	1. Open the dashboard in the app. 2. Trigger the permission prompt handling variation for the dashboard flow. 3. Observe the on-screen response and navigation outcome.	The dashboard should load core widgets, display a permission prompt handling message, and navigate to the home screen.	As expected	Not Executed	High	High

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity
d	Home landing cards and quick actions dashboard	Verify dashboard supports empty handling	User is handling authentication successfully	1. Open the dashboard in the app. 2. Trigger the notification entry handling variation for the dashboard flow. 3. Observe the on-screen response and navigation outcome.	The dashboard should load core widgets, display notification content and respond appropriately during navigation.	As expected	Not Executed	Responsive during navigation.	Medium
d	Home landing cards and quick actions dashboard	Verify dashboard supports deep link navigation	User is handling authentication successfully	1. Open the dashboard in the app. 2. Trigger the deep link navigation variation for the dashboard flow. 3. Observe the on-screen response and navigation outcome.	The dashboard should load core widgets, display notification content and respond appropriately during navigation.	As expected	Not Executed	Responsive during navigation.	High
d	Home landing cards and quick actions dashboard	Verify dashboard supports device state change handling	User is handling authentication successfully	1. Open the dashboard in the app. 2. Trigger the device state change handling variation for the dashboard flow. 3. Observe the on-screen response and navigation outcome.	The dashboard should load core widgets, display notification content and respond appropriately during navigation.	As expected	Not Executed	Responsive during navigation.	Medium

Profile

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity
	User information view and edit	Verify profile supports cold start launch	User is signed in and can access the profile	1. Open the profile path in the app. 2. Trigger the cold start launch variation for the profile flow. 3. Observe the on-screen response and navigation outcome.	The profile section should display current account information and respond appropriately when inputs are valid	As expected	Not Executed	Responsive when inputs are valid	Critical
	User information view and edit	Verify profile supports first-run display	User is signed in and can access the profile	1. Open the profile path in the app. 2. Trigger the first-run display variation for the profile flow. 3. Observe the on-screen response and navigation outcome.	The profile section should display current account information and respond appropriately when inputs are valid	As expected	Not Executed	Responsive when inputs are valid	High
	User information view and edit	Verify profile supports loading animation	User is signed in and can access the profile	1. Open the profile path in the app. 2. Trigger the loading animation variation for the profile flow. 3. Observe the on-screen response and navigation outcome.	The profile section should display current account information and respond appropriately when inputs are valid	As expected	Not Executed	Responsive when inputs are valid	Medium
	User information view and edit	Verify profile supports background to foreground resume	User is signed in and can access the profile	1. Open the profile path in the app. 2. Trigger the background to foreground resume variation for the profile flow. 3. Observe the on-screen response and navigation outcome.	The profile section should display current account information and respond appropriately when inputs are valid	As expected	Not Executed	Responsive when inputs are valid	Medium
	User information view and edit	Verify profile supports force close and relaunch	User is signed in and can access the profile	1. Open the profile path in the app. 2. Trigger the force close and relaunch variation for the profile flow. 3. Observe the on-screen response and navigation outcome.	The profile section should display current account information and respond appropriately when inputs are valid	As expected	Not Executed	Responsive when inputs are valid	High
	User information view and edit	Verify profile supports slow network response	User is signed in and can access the profile	1. Open the profile path in the app. 2. Trigger the slow network response variation for the profile flow. 3. Observe the on-screen response and navigation outcome.	The profile section should display current account information and respond appropriately when inputs are valid	As expected	Not Executed	Responsive when inputs are valid	Medium
	User information view and edit	Verify profile supports offline network condition	User is signed in and can access the profile	1. Open the profile path in the app. 2. Trigger the offline network condition variation for the profile flow. 3. Observe the on-screen response and navigation outcome.	The profile section should display current account information and respond appropriately when inputs are valid	As expected	Not Executed	Responsive when inputs are valid	High
	User information view and edit	Verify profile supports cached data fallback	User is signed in and can access the profile	1. Open the profile path in the app. 2. Trigger the cached data fallback variation for the profile flow. 3. Observe the on-screen response and navigation outcome.	The profile section should display current account information and respond appropriately when inputs are valid	As expected	Not Executed	Responsive when inputs are valid	Medium
	User information view and edit	Verify profile supports accessibility focus order	User is signed in and can access the profile	1. Open the profile path in the app. 2. Trigger the accessibility focus order variation for the profile flow. 3. Observe the on-screen response and navigation outcome.	The profile section should display current account information and respond appropriately when inputs are valid	As expected	Not Executed	Responsive when inputs are valid	Low
	User information view and edit	Verify profile supports localization rendering	User is signed in and can access the profile	1. Open the profile path in the app. 2. Trigger the localization rendering variation for the profile flow. 3. Observe the on-screen response and navigation outcome.	The profile section should display current account information and respond appropriately when inputs are valid	As expected	Not Executed	Responsive when inputs are valid	Medium
	User information view and edit	Verify profile supports repeated tap handling	User is signed in and can access the profile	1. Open the profile path in the app. 2. Trigger the repeated tap handling variation for the profile flow. 3. Observe the on-screen response and navigation outcome.	The profile section should display current account information and respond appropriately when inputs are valid	As expected	Not Executed	Responsive when inputs are valid	Low

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity
	User information view and edit	Verify profile supports boundary input validation	User is signed in and logged the session	1. Open the profile path in the app. 2. Trigger the boundary input validation variation for the profile flow. 3. Observe the on-screen response and navigation outcome.	The profile section should display current account	Not Executed	Not Executed	2	High
	User information view and edit	Verify profile supports rejection input rejection	User is signed in and logged the session	1. Open the profile path in the app. 2. Trigger the invalid input rejection variation for the profile flow. 3. Observe the on-screen response and navigation outcome.	The profile section should display current account	Not Executed	Not Executed	2	High
	User information view and edit	Verify profile supports empty state rendering	User is signed in and logged the session	1. Open the profile path in the app. 2. Trigger the empty state rendering variation for the profile flow. 3. Observe the on-screen response and navigation outcome.	The profile section should display current account	Not Executed	Not Executed	2	Low
	User information view and edit	Verify session expiry handling	User is signed in and logged the session	1. Open the profile path in the app. 2. Trigger the session expiry handling variation for the profile flow. 3. Observe the on-screen response and navigation outcome.	The profile section should display current account	Not Executed	Not Executed	2	Critical
	User information view and edit	Verify profile supports permission handling	User is signed in and logged the session	1. Open the profile path in the app. 2. Trigger the permission prompt handling variation for the profile flow. 3. Observe the on-screen response and navigation outcome.	The profile section should display current account	Not Executed	Not Executed	2	High
	User information view and edit	Verify profile supports notification entry based	User is signed in and logged the session	1. Open the profile path in the app. 2. Trigger the notification entry handling variation for the profile flow. 3. Observe the on-screen response and navigation outcome.	The profile section should display current account	Not Executed	Not Executed	2	Medium
	User information view and edit	Verify deep link navigation	User is signed in and logged the session	1. Open the profile path in the app. 2. Trigger the deep link navigation variation for the profile flow. 3. Observe the on-screen response and navigation outcome.	The profile section should display current account	Not Executed	Not Executed	2	High
	User information view and edit	Verify device state change handling	User is signed in and logged the session	1. Open the profile path in the app. 2. Trigger the device state change handling variation for the profile flow. 3. Observe the on-screen response and navigation outcome.	The profile section should display current account	Not Executed	Not Executed	2	Low

Settings

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity
	Preferences, language, and app	Verify settings - Opt to cold start	User is signed in and logged the session	1. Open the settings path in the app. 2. Trigger the cold start launch variation for the settings flow. 3. Observe the on-screen response and navigation outcome.	The settings screen should apply preference	Not Executed	Not Executed	2	Critical
	Preferences, language, and app	Verify settings - Opt to first display	User is signed in and logged the session	1. Open the settings path in the app. 2. Trigger the first-run display variation for the settings flow. 3. Observe the on-screen response and navigation outcome.	The settings screen should apply preference	Not Executed	Not Executed	2	High
	Preferences, language, and app	Verify settings - Loading animation	User is signed in and logged the session	1. Open the settings path in the app. 2. Trigger the loading animation variation for the settings flow. 3. Observe the on-screen response and navigation outcome.	The settings screen should apply preference	Not Executed	Not Executed	2	Medium
	Preferences, language, and app	Verify settings - Background to foreground resume	User is signed in and logged the session	1. Open the settings path in the app. 2. Trigger the background to foreground resume variation for the settings flow. 3. Observe the on-screen response and navigation outcome.	The settings screen should apply preference	Not Executed	Not Executed	2	Medium
	Preferences, language, and app	Verify settings - Support close and relaunch	User is signed in and logged the session	1. Open the settings path in the app. 2. Trigger the force close and relaunch variation for the settings flow. 3. Observe the on-screen response and navigation outcome.	The settings screen should apply preference	Not Executed	Not Executed	2	High
	Preferences, language, and app	Verify settings - Support slow response	User is signed in and logged the session	1. Open the settings path in the app. 2. Trigger the slow network response variation for the settings flow. 3. Observe the on-screen response and navigation outcome.	The settings screen should apply preference	Not Executed	Not Executed	2	Medium

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity	
	Preferences, language, and app	Verify settings - Offline Network Condition	User is signed in breaking open the	1. Open the settings path in the app. 2. Trigger the offline network condition variation for the settings flow. 3. Observe the on-screen response and navigation outcome.	The settings screen should apply preference	change	Expected	Not Expectedly, and	P1 avoid impacting	High unrelated
	Preferences, language, and app	Verify settings - Cached Data fallback	Back is signed in breaking the open the	1. Open the settings path in the app. 2. Trigger the cached data fallback variation for the settings flow. 3. Observe the on-screen response and navigation outcome.	The settings screen should apply preference	change	Expected	Not Expectedly, and	P2 avoid impacting	Medium
	Preferences, language, and app	Verify settings - Accessibility Focus Order	User is signed in breaking open the	1. Open the settings path in the app. 2. Trigger the accessibility focus order variation for the settings flow. 3. Observe the on-screen response and navigation outcome.	The settings screen should apply preference	change	Expected	Not Expectedly, and	P2 avoid impacting	Low unrelated
	Preferences, language, and app	Verify settings - Localization Rendering	Users without breaking the open the	1. Open the settings path in the app. 2. Trigger the localization rendering variation for the settings flow. 3. Observe the on-screen response and navigation outcome.	The settings screen should apply preference	change	Expected	Not Expectedly, and	P1 avoid impacting	Medium
	Preferences, language, and app	Verify settings - Repeated Tap Handling	Users with breaking the open the	1. Open the settings path in the app. 2. Trigger the repeated tap handling variation for the settings flow. 3. Observe the on-screen response and navigation outcome.	The settings screen should apply preference	change	Expected	Not Expectedly, and	P2 avoid impacting	Low unrelated
	Preferences, language, and app	Verify settings - Boundary Input Validation	User is signed in breaking the open the	1. Open the settings path in the app. 2. Trigger the boundary input validation variation for the settings flow. 3. Observe the on-screen response and navigation outcome.	The settings screen should apply preference	change	Expected	Not Expectedly, and	P2 avoid impacting	High unrelated
	Preferences, language, and app	Verify settings - Invalid Input Rejection	User is signed in breaking the open the	1. Open the settings path in the app. 2. Trigger the invalid input rejection variation for the settings flow. 3. Observe the on-screen response and navigation outcome.	The settings screen should apply preference	change	Expected	Not Expectedly, and	P1 avoid impacting	High unrelated
	Preferences, language, and app	Verify settings - Empty State Rendering	Users without breaking the open the	1. Open the settings path in the app. 2. Trigger the empty state rendering variation for the settings flow. 3. Observe the on-screen response and navigation outcome.	The settings screen should apply preference	change	Expected	Not Expectedly, and	P2 avoid impacting	Low unrelated
	Preferences, language, and app	Verify settings - Session Expiry Handling	User is signed in breaking the open the	1. Open the settings path in the app. 2. Trigger the session expiry handling variation for the settings flow. 3. Observe the on-screen response and navigation outcome.	The settings screen should apply preference	change	Expected	Not Expectedly, and	P1 avoid impacting	Critical
	Preferences, language, and app	Verify settings - Permission Prompt Handling	User is signed in breaking the open the	1. Open the settings path in the app. 2. Trigger the permission prompt handling variation for the settings flow. 3. Observe the on-screen response and navigation outcome.	The settings screen should apply preference	change	Expected	Not Expectedly, and	P2 avoid impacting	High unrelated
	Preferences, language, and app	Verify settings - Notification Entry Handling	User is signed in breaking the open the	1. Open the settings path in the app. 2. Trigger the notification entry handling variation for the settings flow. 3. Observe the on-screen response and navigation outcome.	The settings screen should apply preference	change	Expected	Not Expectedly, and	P2 avoid impacting	Medium
	Preferences, language, and app	Verify settings - Deep Link Navigation	User is signed in breaking the open the	1. Open the settings path in the app. 2. Trigger the deep link navigation variation for the settings flow. 3. Observe the on-screen response and navigation outcome.	The settings screen should apply preference	change	Expected	Not Expectedly, and	P1 avoid impacting	High unrelated
	Preferences, language, and app	Verify settings - Device State Change Handling	User is signed in breaking the open the	1. Open the settings path in the app. 2. Trigger the device state change handling variation for the settings flow. 3. Observe the on-screen response and navigation outcome.	The settings screen should apply preference	change	Expected	Not Expectedly, and	P2 avoid impacting	Low unrelated

Search

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity
	Search entry and result filtering	Verify Search supports cold start launch	User without access the search interface	1. On the main app path in the app. 2. Trigger the cold start launch variation for the search flow. 3. Observe the on-screen response and navigation outcome.	The search experience should return relevant results	Empty search results	Expected	Not Expectedly, and	P1 gracefully from Critical could qu

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity
	Search entry and result filtering	Verify Search Display supports first-run display	User data exists in the search interface	1. Open the App Search in the app. 2. Trigger the first-run display variation for the search flow. 3. Observe the on-screen response and navigation outcome.	The search experience should return relevant results	Results handled empty	State: Executed	Pass	High
	Search entry and result filtering	Verify Search Display supports loading animation	User data exists in the search interface	1. Open the App Search in the app. 2. Trigger the loading animation variation for the search flow. 3. Observe the on-screen response and navigation outcome.	The search experience should return relevant results	Results handled empty	State: Executed	Pass	Medium
	Search entry and result filtering	Verify Search Display supports background resume	User data exists in the search interface	1. Open the App Search in the app. 2. Trigger the background to foreground resume variation for the search flow. 3. Observe the on-screen response and navigation outcome.	The search experience should return relevant results	Results handled empty	State: Executed	Pass	Medium
	Search entry and result filtering	Verify Search Display supports force close and relaunch	User data exists in the search interface	1. Open the App Search in the app. 2. Trigger the force close and relaunch variation for the search flow. 3. Observe the on-screen response and navigation outcome.	The search experience should return relevant results	Results handled empty	State: Executed	Pass	High
	Search entry and result filtering	Verify Search Display supports slow network response	User data exists in the search interface	1. Open the App Search in the app. 2. Trigger the slow network response variation for the search flow. 3. Observe the on-screen response and navigation outcome.	The search experience should return relevant results	Results handled empty	State: Executed	Pass	Medium
	Search entry and result filtering	Verify Search Display supports offline network condition	User data exists in the search interface	1. Open the App Search in the app. 2. Trigger the offline network condition variation for the search flow. 3. Observe the on-screen response and navigation outcome.	The search experience should return relevant results	Results handled empty	State: Executed	Pass	High
	Search entry and result filtering	Verify Search Display supports cached data fallback	User data exists in the search interface	1. Open the App Search in the app. 2. Trigger the cached data fallback variation for the search flow. 3. Observe the on-screen response and navigation outcome.	The search experience should return relevant results	Results handled empty	State: Executed	Pass	Medium
	Search entry and result filtering	Verify Search Display supports accessibility focus order	User data exists in the search interface	1. Open the App Search in the app. 2. Trigger the accessibility focus order variation for the search flow. 3. Observe the on-screen response and navigation outcome.	The search experience should return relevant results	Results handled empty	State: Executed	Pass	Low
	Search entry and result filtering	Verify Search Display supports localization rendering	User data exists in the search interface	1. Open the App Search in the app. 2. Trigger the localization rendering variation for the search flow. 3. Observe the on-screen response and navigation outcome.	The search experience should return relevant results	Results handled empty	State: Executed	Pass	Medium
	Search entry and result filtering	Verify Search Display supports repeated tap handling	User data exists in the search interface	1. Open the App Search in the app. 2. Trigger the repeated tap handling variation for the search flow. 3. Observe the on-screen response and navigation outcome.	The search experience should return relevant results	Results handled empty	State: Executed	Pass	Low
	Search entry and result filtering	Verify Search Display supports boundary input validation	User data exists in the search interface	1. Open the App Search in the app. 2. Trigger the boundary input validation variation for the search flow. 3. Observe the on-screen response and navigation outcome.	The search experience should return relevant results	Results handled empty	State: Executed	Pass	High
	Search entry and result filtering	Verify Search Display supports invalid input rejection	User data exists in the search interface	1. Open the App Search in the app. 2. Trigger the invalid input rejection variation for the search flow. 3. Observe the on-screen response and navigation outcome.	The search experience should return relevant results	Results handled empty	State: Executed	Pass	High
	Search entry and result filtering	Verify Search Display supports empty state rendering	User data exists in the search interface	1. Open the App Search in the app. 2. Trigger the empty state rendering variation for the search flow. 3. Observe the on-screen response and navigation outcome.	The search experience should return relevant results	Results handled empty	State: Executed	Pass	Low
	Search entry and result filtering	Verify Search Display supports session expiry handling	User data exists in the search interface	1. Open the App Search in the app. 2. Trigger the session expiry handling variation for the search flow. 3. Observe the on-screen response and navigation outcome.	The search experience should return relevant results	Results handled empty	State: Executed	Pass	Critical
	Search entry and result filtering	Verify Search Display supports permission prompt handling	User data exists in the search interface	1. Open the App Search in the app. 2. Trigger the permission prompt handling variation for the search flow. 3. Observe the on-screen response and navigation outcome.	The search experience should return relevant results	Results handled empty	State: Executed	Pass	High
	Search entry and result filtering	Verify Search Display supports notification entry handling	User data exists in the search interface	1. Open the App Search in the app. 2. Trigger the notification entry handling variation for the search flow. 3. Observe the on-screen response and navigation outcome.	The search experience should return relevant results	Results handled empty	State: Executed	Pass	Medium

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity
	Search entry and result filtering	Deep Link Navigation	deep link navigation without breaking the user interface	1. Open the app search in the app. 2. Trigger the deep link navigation variation for the search flow. 3. Observe the on-screen response and navigation outcome.	The search experience should return relevant results	Not Executed	Empty	Not Executed	Gracefully from invalid query
	Search entry and result filtering	Device State Change Handling	state change handling without breaking the user interface	1. Open the app search in the app. 2. Trigger the device state change handling variation for the search flow. 3. Observe the on-screen response and navigation outcome.	The search experience should return relevant results	Not Executed	Empty	Not Executed	Gracefully from invalid query

Notifications

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity	
ns	Notification center and alert inter	Notification Cold Start	cold start launch without breaking the user interface	1. Open the app search in the app. 2. Trigger the cold start launch variation for the notifications flow. 3. Observe the on-screen response and navigation outcome.	Notifications should arrive, render correctly, and be actionable	Not Executed	Expected	Not Executed	Breaking navigation	Critical
ns	Notification center and alert inter	Notification First Run Display	first-run display without breaking the user interface	1. Open the app search in the app. 2. Trigger the first-run display variation for the notifications flow. 3. Observe the on-screen response and navigation outcome.	Notifications should arrive, render correctly, and be actionable	Not Executed	Expected	Not Executed	Breaking navigation	High
ns	Notification center and alert inter	Notification Animation Loading	loading animation without breaking the user interface	1. Open the app search in the app. 2. Trigger the loading animation variation for the notifications flow. 3. Observe the on-screen response and navigation outcome.	Notifications should arrive, render correctly, and be actionable	Not Executed	Expected	Not Executed	Breaking navigation	Medium
ns	Notification center and alert inter	Notification Background Support	background resume without breaking the user interface	1. Open the app search in the app. 2. Trigger the background to foreground resume variation for the notifications flow. 3. Observe the on-screen response and navigation outcome.	Notifications should arrive, render correctly, and be actionable	Not Executed	Expected	Not Executed	Breaking navigation	Medium
ns	Notification center and alert inter	Notification Force Close And Relaunch	force close and relaunch without breaking the user interface	1. Open the app search in the app. 2. Trigger the force close and relaunch variation for the notifications flow. 3. Observe the on-screen response and navigation outcome.	Notifications should arrive, render correctly, and be actionable	Not Executed	Expected	Not Executed	Breaking navigation	High
ns	Notification center and alert inter	Notification Slow Network Response	slow network response without breaking the user interface	1. Open the app search in the app. 2. Trigger the slow network response variation for the notifications flow. 3. Observe the on-screen response and navigation outcome.	Notifications should arrive, render correctly, and be actionable	Not Executed	Expected	Not Executed	Breaking navigation	Medium
ns	Notification center and alert inter	Notification Offline Network Condition	offline network condition without breaking the user interface	1. Open the app search in the app. 2. Trigger the offline network condition variation for the notifications flow. 3. Observe the on-screen response and navigation outcome.	Notifications should arrive, render correctly, and be actionable	Not Executed	Expected	Not Executed	Breaking navigation	High
ns	Notification center and alert inter	Notification Cached Data Fallback	cached data fallback without breaking the user interface	1. Open the app search in the app. 2. Trigger the cached data fallback variation for the notifications flow. 3. Observe the on-screen response and navigation outcome.	Notifications should arrive, render correctly, and be actionable	Not Executed	Expected	Not Executed	Breaking navigation	Medium
ns	Notification center and alert inter	Notification Accessibility Focus Order	accessibility focus order without breaking the user interface	1. Open the app search in the app. 2. Trigger the accessibility focus order variation for the notifications flow. 3. Observe the on-screen response and navigation outcome.	Notifications should arrive, render correctly, and be actionable	Not Executed	Expected	Not Executed	Breaking navigation	Medium
ns	Notification center and alert inter	Notification Localization Rendering	localization rendering without breaking the user interface	1. Open the app search in the app. 2. Trigger the localization rendering variation for the notifications flow. 3. Observe the on-screen response and navigation outcome.	Notifications should arrive, render correctly, and be actionable	Not Executed	Expected	Not Executed	Breaking navigation	Medium
ns	Notification center and alert inter	Notification Repeated Tap Handling	repeated tap handling without breaking the user interface	1. Open the app search in the app. 2. Trigger the repeated tap handling variation for the notifications flow. 3. Observe the on-screen response and navigation outcome.	Notifications should arrive, render correctly, and be actionable	Not Executed	Expected	Not Executed	Breaking navigation	Medium
ns	Notification center and alert inter	Notification Boundary Input Validation	boundary input validation without breaking the user interface	1. Open the app search in the app. 2. Trigger the boundary input validation variation for the notifications flow. 3. Observe the on-screen response and navigation outcome.	Notifications should arrive, render correctly, and be actionable	Not Executed	Expected	Not Executed	Breaking navigation	High

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity	
ns	Notification center and alert inter	Verify notification is supported	Reject invalid input	Notification without session breaking the valid	1. Open the app and the notifications are displayed. 2. Trigger the invalid input rejection variation for the notifications flow. 3. Observe the on-screen response and navigation outcome.	Notifications should arrive, render correctly, and	Not Executed	Not Executed	Breaking navigation	High
ns	Notification center and alert inter	Verify notification is supported	Reject invalid input	Notification without session breaking the valid	1. Open the app and the notifications are displayed. 2. Trigger the empty state rendering variation for the notifications flow. 3. Observe the on-screen response and navigation outcome.	Notifications should arrive, render correctly, and	Not Executed	Not Executed	Breaking navigation	High
ns	Notification center and alert inter	Verify notification is supported	Reject invalid input	Notification without session breaking the valid	1. Open the app and the notifications are displayed. 2. Trigger the session expiry handling variation for the notifications flow. 3. Observe the on-screen response and navigation outcome.	Notifications should arrive, render correctly, and	Not Executed	Not Executed	Breaking navigation	Critical
ns	Notification center and alert inter	Verify notification is supported	Reject invalid input	Notification without session breaking the valid	1. Open the app and the notifications are displayed. 2. Trigger the permission prompt handling variation for the notifications flow. 3. Observe the on-screen response and navigation outcome.	Notifications should arrive, render correctly, and	Not Executed	Not Executed	Breaking navigation	High
ns	Notification center and alert inter	Verify notification is supported	Reject invalid input	Notification without session breaking the valid	1. Open the app and the notifications are displayed. 2. Trigger the notification entry handling variation for the notifications flow. 3. Observe the on-screen response and navigation outcome.	Notifications should arrive, render correctly, and	Not Executed	Not Executed	Breaking navigation	Medium
ns	Notification center and alert inter	Verify notification is supported	Reject invalid input	Notification without session breaking the valid	1. Open the app and the notifications are displayed. 2. Trigger the deep link navigation variation for the notifications flow. 3. Observe the on-screen response and navigation outcome.	Notifications should arrive, render correctly, and	Not Executed	Not Executed	Breaking navigation	High
ns	Notification center and alert inter	Verify notification is supported	Reject invalid input	Notification without session breaking the valid	1. Open the app and the notifications are displayed. 2. Trigger the device state change handling variation for the notifications flow. 3. Observe the on-screen response and navigation outcome.	Notifications should arrive, render correctly, and	Not Executed	Not Executed	Breaking navigation	High

Permissions

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity
ns	Runtime permission prompts	Verify permissions supports cold start	Launch the app with the requested permission	1. Open the app and the permissions are displayed. 2. Trigger the cold start launch variation for the permissions flow. 3. Observe the on-screen response and navigation outcome.	The requested OS permission flow should complete	Not Executed	Not Executed	Breaking navigation	Critical
ns	Runtime permission prompts	Verify permissions supports first-run display	Launch the app with the requested permission	1. Open the app and the permissions are displayed. 2. Trigger the first-run display variation for the permissions flow. 3. Observe the on-screen response and navigation outcome.	The requested OS permission flow should complete	Not Executed	Not Executed	Breaking navigation	High
ns	Runtime permission prompts	Verify permissions supports loading animation	Launch the app with the requested permission	1. Open the app and the permissions are displayed. 2. Trigger the loading animation variation for the permissions flow. 3. Observe the on-screen response and navigation outcome.	The requested OS permission flow should complete	Not Executed	Not Executed	Breaking navigation	Medium
ns	Runtime permission prompts	Verify permissions supports background to foreground resume	Launch the app with the requested permission	1. Open the app and the permissions are displayed. 2. Trigger the background to foreground resume variation for the permissions flow. 3. Observe the on-screen response and navigation outcome.	The requested OS permission flow should complete	Not Executed	Not Executed	Breaking navigation	Medium
ns	Runtime permission prompts	Verify permissions supports force close and relaunch	Launch the app with the requested permission	1. Open the app and the permissions are displayed. 2. Trigger the force close and relaunch variation for the permissions flow. 3. Observe the on-screen response and navigation outcome.	The requested OS permission flow should complete	Not Executed	Not Executed	Breaking navigation	High
ns	Runtime permission prompts	Verify permissions supports slow network response	Launch the app with the requested permission	1. Open the app and the permissions are displayed. 2. Trigger the slow network response variation for the permissions flow. 3. Observe the on-screen response and navigation outcome.	The requested OS permission flow should complete	Not Executed	Not Executed	Breaking navigation	Medium
ns	Runtime permission prompts	Verify permissions supports offline network condition	Launch the app with the requested permission	1. Open the app and the permissions are displayed. 2. Trigger the offline network condition variation for the permissions flow. 3. Observe the on-screen response and navigation outcome.	The requested OS permission flow should complete	Not Executed	Not Executed	Breaking navigation	High

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity
ns	Runtime permission prompts	Cached Data Fallback supports cached data fallback of the app.	The app requests a breaking screen user journey.	1. Open the OS permissions app. 2. Trigger the cached data fallback variation for the permissions flow. 3. Observe the on-screen response and navigation outcome.	The requested OS permission flow should complete and the app should continue with the correct access	Not Executed and the app should continue with the correct access	Pass	P2	Medium
ns	Runtime permission prompts	Accessibility Focus Order supports accessibility focus order of the app.	The app requests a breaking screen user journey.	1. Open the OS permissions app. 2. Trigger the accessibility focus order variation for the permissions flow. 3. Observe the on-screen response and navigation outcome.	The requested OS permission flow should complete and the app should continue with the correct access	Not Executed and the app should continue with the correct access	Pass	P2	Critical
ns	Runtime permission prompts	Localization Rendering supports localization rendering of the app.	The app requests a breaking screen user journey.	1. Open the OS permissions app. 2. Trigger the localization rendering variation for the permissions flow. 3. Observe the on-screen response and navigation outcome.	The requested OS permission flow should complete and the app should continue with the correct access	Not Executed and the app should continue with the correct access	Pass	P1	Medium
ns	Runtime permission prompts	Repeated Tap Handling supports repeated tap handling of the app.	The app requests a breaking screen user journey.	1. Open the OS permissions app. 2. Trigger the repeated tap handling variation for the permissions flow. 3. Observe the on-screen response and navigation outcome.	The requested OS permission flow should complete and the app should continue with the correct access	Not Executed and the app should continue with the correct access	Pass	P2	Critical
ns	Runtime permission prompts	Boundary Input Validation supports boundary input validation of the app.	The app requests a breaking screen user journey.	1. Open the OS permissions app. 2. Trigger the boundary input validation variation for the permissions flow. 3. Observe the on-screen response and navigation outcome.	The requested OS permission flow should complete and the app should continue with the correct access	Not Executed and the app should continue with the correct access	Pass	P2	Critical
ns	Runtime permission prompts	Invalid Input Rejection supports invalid input rejection of the app.	The app requests a breaking screen user journey.	1. Open the OS permissions app. 2. Trigger the invalid input rejection variation for the permissions flow. 3. Observe the on-screen response and navigation outcome.	The requested OS permission flow should complete and the app should continue with the correct access	Not Executed and the app should continue with the correct access	Pass	P1	Critical
ns	Runtime permission prompts	Empty State Rendering supports empty state rendering of the app.	The app requests a breaking screen user journey.	1. Open the OS permissions app. 2. Trigger the empty state rendering variation for the permissions flow. 3. Observe the on-screen response and navigation outcome.	The requested OS permission flow should complete and the app should continue with the correct access	Not Executed and the app should continue with the correct access	Pass	P2	Critical
ns	Runtime permission prompts	Session Expiry Handling supports session expiry handling of the app.	The app requests a breaking screen user journey.	1. Open the OS permissions app. 2. Trigger the session expiry handling variation for the permissions flow. 3. Observe the on-screen response and navigation outcome.	The requested OS permission flow should complete and the app should continue with the correct access	Not Executed and the app should continue with the correct access	Pass	P1	Critical
ns	Runtime permission prompts	Permission Prompt Handling supports permission prompt handling of the app.	The app requests a breaking screen user journey.	1. Open the OS permissions app. 2. Trigger the permission prompt handling variation for the permissions flow. 3. Observe the on-screen response and navigation outcome.	The requested OS permission flow should complete and the app should continue with the correct access	Not Executed and the app should continue with the correct access	Pass	P2	Critical
ns	Runtime permission prompts	Notification Entry Handling supports notification entry handling of the app.	The app requests a breaking screen user journey.	1. Open the OS permissions app. 2. Trigger the notification entry handling variation for the permissions flow. 3. Observe the on-screen response and navigation outcome.	The requested OS permission flow should complete and the app should continue with the correct access	Not Executed and the app should continue with the correct access	Pass	P2	Medium
ns	Runtime permission prompts	Deep Link Navigation supports deep link navigation of the app.	The app requests a breaking screen user journey.	1. Open the OS permissions app. 2. Trigger the deep link navigation variation for the permissions flow. 3. Observe the on-screen response and navigation outcome.	The requested OS permission flow should complete and the app should continue with the correct access	Not Executed and the app should continue with the correct access	Pass	P1	Critical
ns	Runtime permission prompts	Device State Change supports device state change handling of the app.	The app requests a breaking screen user journey.	1. Open the OS permissions app. 2. Trigger the device state change handling variation for the permissions flow. 3. Observe the on-screen response and navigation outcome.	The requested OS permission flow should complete and the app should continue with the correct access	Not Executed and the app should continue with the correct access	Pass	P2	Critical

Offline Mode

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity
ode	Network loss handling and cache	Offline Cold Start supports cold start of the app.	The app has already loaded data and the device is offline.	1. Open the app. 2. Trigger the cold start launch variation for the offline mode flow. 3. Observe the on-screen response and navigation outcome.	The app should retain accessible cached content and the app should continue with the correct access	Not Executed and the app should continue with the correct access	Pass	P1	Critical
ode	Network loss handling and cache	Offline First Run Display supports first-run display of the app.	The app has already loaded data and the device is offline.	1. Open the app. 2. Trigger the first-run display variation for the offline mode flow. 3. Observe the on-screen response and navigation outcome.	The app should retain accessible cached content and the app should continue with the correct access	Not Executed and the app should continue with the correct access	Pass	P1	Critical

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity
ode	Network loss handling and cache	Verify offline mode support on loading animation	The app is in the foreground and the data is loaded	1. Open the device offline mode and start the app. 2. Trigger the loading animation variation for the offline mode flow. 3. Observe the on-screen response and navigation outcome.	The app should retain accessible cached content	Not Executed	High	Passes when	Medium
ode	Network loss handling and cache	Verify offline mode support on background refresh	The app has previously loaded data	1. Open the device offline mode and start the app. 2. Trigger the background resume variation for the offline mode flow. 3. Observe the on-screen response and navigation outcome.	The app should retain accessible cached content	Not Executed	High	Passes when	Medium
ode	Network loss handling and cache	Verify offline mode support on force close and relaunch	The app has previously loaded data	1. Open the device offline mode and start the app. 2. Trigger the force close and relaunch variation for the offline mode flow. 3. Observe the on-screen response and navigation outcome.	The app should retain accessible cached content	Not Executed	High	Passes when	High
ode	Network loss handling and cache	Verify offline mode support on slow network response	The app has previously loaded data	1. Open the device offline mode and start the app. 2. Trigger the slow network response variation for the offline mode flow. 3. Observe the on-screen response and navigation outcome.	The app should retain accessible cached content	Not Executed	High	Passes when	Medium
ode	Network loss handling and cache	Verify offline mode support on offline network condition	The app has previously loaded data	1. Open the device offline mode and start the app. 2. Trigger the offline network condition variation for the offline mode flow. 3. Observe the on-screen response and navigation outcome.	The app should retain accessible cached content	Not Executed	High	Passes when	High
ode	Network loss handling and cache	Verify offline mode support on cached data fallback	The app has previously loaded data	1. Open the device offline mode and start the app. 2. Trigger the cached data fallback variation for the offline mode flow. 3. Observe the on-screen response and navigation outcome.	The app should retain accessible cached content	Not Executed	High	Passes when	Medium
ode	Network loss handling and cache	Verify offline mode support on accessibility focus order	The app has previously loaded data	1. Open the device offline mode and start the app. 2. Trigger the accessibility focus order variation for the offline mode flow. 3. Observe the on-screen response and navigation outcome.	The app should retain accessible cached content	Not Executed	High	Passes when	Low
ode	Network loss handling and cache	Verify offline mode support on localization rendering	The app has previously loaded data	1. Open the device offline mode and start the app. 2. Trigger the localization rendering variation for the offline mode flow. 3. Observe the on-screen response and navigation outcome.	The app should retain accessible cached content	Not Executed	High	Passes when	Medium
ode	Network loss handling and cache	Verify offline mode support on repeated tap handling	The app has previously loaded data	1. Open the device offline mode and start the app. 2. Trigger the repeated tap handling variation for the offline mode flow. 3. Observe the on-screen response and navigation outcome.	The app should retain accessible cached content	Not Executed	High	Passes when	Low
ode	Network loss handling and cache	Verify offline mode support on boundary input validation	The app has previously loaded data	1. Open the device offline mode and start the app. 2. Trigger the boundary input validation variation for the offline mode flow. 3. Observe the on-screen response and navigation outcome.	The app should retain accessible cached content	Not Executed	High	Passes when	High
ode	Network loss handling and cache	Verify offline mode support on invalid input rejection	The app has previously loaded data	1. Open the device offline mode and start the app. 2. Trigger the invalid input rejection variation for the offline mode flow. 3. Observe the on-screen response and navigation outcome.	The app should retain accessible cached content	Not Executed	High	Passes when	High
ode	Network loss handling and cache	Verify offline mode support on empty state rendering	The app has previously loaded data	1. Open the device offline mode and start the app. 2. Trigger the empty state rendering variation for the offline mode flow. 3. Observe the on-screen response and navigation outcome.	The app should retain accessible cached content	Not Executed	High	Passes when	Low
ode	Network loss handling and cache	Verify offline mode support on session expiry handling	The app has previously loaded data	1. Open the device offline mode and start the app. 2. Trigger the session expiry handling variation for the offline mode flow. 3. Observe the on-screen response and navigation outcome.	The app should retain accessible cached content	Not Executed	High	Passes when	Critical
ode	Network loss handling and cache	Verify offline mode support on permission prompt handling	The app has previously loaded data	1. Open the device offline mode and start the app. 2. Trigger the permission prompt handling variation for the offline mode flow. 3. Observe the on-screen response and navigation outcome.	The app should retain accessible cached content	Not Executed	High	Passes when	High
ode	Network loss handling and cache	Verify offline mode support on notification entry handling	The app has previously loaded data	1. Open the device offline mode and start the app. 2. Trigger the notification entry handling variation for the offline mode flow. 3. Observe the on-screen response and navigation outcome.	The app should retain accessible cached content	Not Executed	High	Passes when	Medium
ode	Network loss handling and cache	Verify offline mode support on deep link navigation	The app has previously loaded data	1. Open the device offline mode and start the app. 2. Trigger the deep link navigation variation for the offline mode flow. 3. Observe the on-screen response and navigation outcome.	The app should retain accessible cached content	Not Executed	High	Passes when	High

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity	
ode	Network loss handling and cache usage off	Device State Change Handling Change handling with offline breaking		1. Open the offline mode switch path in the app. 2. Trigger the device state change handling variation for the offline mode flow. 3. Observe the on-screen response and navigation outcome.	The app should retain accessible cached content in the background.	Not Executed	High	Executed	Passes when done	connectivity

Session Management

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity
Management	Authentication token lifecycle	and device session management	Cold start supports cold start launch variation	Assigned launch session breaking and the app	1. Open the cold start launch variation path in the app. 2. Trigger the cold start launch variation for the session management flow. 3. Observe the on-screen response and navigation outcome.	The session should remain active or expire accordingly.	Not Executed	High	Critical need
Management	Authentication token lifecycle	and device session management	First-run display supports first-run display variation	Assigned first-run display session breaking and the app	1. Open the first-run display variation path in the app. 2. Trigger the first-run display variation for the session management flow. 3. Observe the on-screen response and navigation outcome.	The session should remain active or expire accordingly.	Not Executed	High	High need
Management	Authentication token lifecycle	and device session management	Loading animation supports loading animation variation	Assigned loading animation session breaking and the app	1. Open the loading animation variation path in the app. 2. Trigger the loading animation variation for the session management flow. 3. Observe the on-screen response and navigation outcome.	The session should remain active or expire accordingly.	Not Executed	High	Medium need
Management	Authentication token lifecycle	and device session management	Background to foreground resume supports background to foreground resume variation	Assigned background to foreground resume session breaking and the app	1. Open the background to foreground resume variation path in the app. 2. Trigger the background to foreground resume variation for the session management flow. 3. Observe the on-screen response and navigation outcome.	The session should remain active or expire accordingly.	Not Executed	High	Medium need
Management	Authentication token lifecycle	and device session management	Force close and relaunch supports force close and relaunch variation	Assigned force close and relaunch session breaking and the app	1. Open the force close and relaunch variation path in the app. 2. Trigger the force close and relaunch variation for the session management flow. 3. Observe the on-screen response and navigation outcome.	The session should remain active or expire accordingly.	Not Executed	High	High need
Management	Authentication token lifecycle	and device session management	Slow network response supports slow network response variation	Assigned slow network response session breaking and the app	1. Open the slow network response variation path in the app. 2. Trigger the slow network response variation for the session management flow. 3. Observe the on-screen response and navigation outcome.	The session should remain active or expire accordingly.	Not Executed	High	Medium need
Management	Authentication token lifecycle	and device session management	Offline network condition supports offline network condition variation	Assigned offline network condition session breaking and the app	1. Open the offline network condition variation path in the app. 2. Trigger the offline network condition variation for the session management flow. 3. Observe the on-screen response and navigation outcome.	The session should remain active or expire accordingly.	Not Executed	High	High need
Management	Authentication token lifecycle	and device session management	Cached data fallback supports cached data fallback variation	Assigned cached data fallback session breaking and the app	1. Open the cached data fallback variation path in the app. 2. Trigger the cached data fallback variation for the session management flow. 3. Observe the on-screen response and navigation outcome.	The session should remain active or expire accordingly.	Not Executed	High	Medium need
Management	Authentication token lifecycle	and device session management	Accessibility focus order supports accessibility focus order variation	Assigned accessibility focus order session breaking and the app	1. Open the accessibility focus order variation path in the app. 2. Trigger the accessibility focus order variation for the session management flow. 3. Observe the on-screen response and navigation outcome.	The session should remain active or expire accordingly.	Not Executed	High	Low need
Management	Authentication token lifecycle	and device session management	Localization rendering supports localization rendering variation	Assigned localization rendering session breaking and the app	1. Open the localization rendering variation path in the app. 2. Trigger the localization rendering variation for the session management flow. 3. Observe the on-screen response and navigation outcome.	The session should remain active or expire accordingly.	Not Executed	High	Medium need
Management	Authentication token lifecycle	and device session management	Repeated tap handling supports repeated tap handling variation	Assigned repeated tap handling session breaking and the app	1. Open the repeated tap handling variation path in the app. 2. Trigger the repeated tap handling variation for the session management flow. 3. Observe the on-screen response and navigation outcome.	The session should remain active or expire accordingly.	Not Executed	High	Low need
Management	Authentication token lifecycle	and device session management	Boundary input validation supports boundary input validation variation	Assigned boundary input validation session breaking and the app	1. Open the boundary input validation variation path in the app. 2. Trigger the boundary input validation variation for the session management flow. 3. Observe the on-screen response and navigation outcome.	The session should remain active or expire accordingly.	Not Executed	High	High need
Management	Authentication token lifecycle	and device session management	Invalid input rejection supports invalid input rejection variation	Assigned invalid input rejection session breaking and the app	1. Open the invalid input rejection variation path in the app. 2. Trigger the invalid input rejection variation for the session management flow. 3. Observe the on-screen response and navigation outcome.	The session should remain active or expire accordingly.	Not Executed	High	High need

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity
Management	Authentication token lifecycle and lifecycle management	Verify session - Empty State Rendering	App is installed and running with existing session	1. Open the app and navigate to the session management screen. 2. Trigger the empty state rendering variation for the session management flow. 3. Observe the on-screen response and navigation outcome.	The session should remain active or expire accordingly, with no unexpected behavior.	Not Executed	Not Executed	P2	Authentication flow - When needed
Management	Authentication token lifecycle and lifecycle management	Verify session - Session Expiry Handling	App is installed and running with existing session	1. Open the app and navigate to the session management screen. 2. Trigger the session expiry handling variation for the session management flow. 3. Observe the on-screen response and navigation outcome.	The session should remain active or expire accordingly, with no unexpected behavior.	Not Executed	Not Executed	P2	Authentication flow - Critical need
Management	Authentication token lifecycle and lifecycle management	Verify session - Permission Prompt Handling	App is installed and running with existing session	1. Open the app and navigate to the session management screen. 2. Trigger the permission prompt handling variation for the session management flow. 3. Observe the on-screen response and navigation outcome.	The session should remain active or expire accordingly, with no unexpected behavior.	Not Executed	Not Executed	P2	Authentication flow - High need
Management	Authentication token lifecycle and lifecycle management	Verify session - Notification Setup Handling	App is installed and running with existing session	1. Open the app and navigate to the session management screen. 2. Trigger the notification entry handling variation for the session management flow. 3. Observe the on-screen response and navigation outcome.	The session should remain active or expire accordingly, with no unexpected behavior.	Not Executed	Not Executed	P2	Authentication flow - Medium need
Management	Authentication token lifecycle and lifecycle management	Verify session - Deep Link Navigation	App is installed and running with existing session	1. Open the app and navigate to the session management screen. 2. Trigger the deep link navigation variation for the session management flow. 3. Observe the on-screen response and navigation outcome.	The session should remain active or expire accordingly, with no unexpected behavior.	Not Executed	Not Executed	P2	Authentication flow - High need
Management	Authentication token lifecycle and lifecycle management	Verify session - Device State Change Handling	App is installed and running with existing session	1. Open the app and navigate to the session management screen. 2. Trigger the device state change handling variation for the session management flow. 3. Observe the on-screen response and navigation outcome.	The session should remain active or expire accordingly, with no unexpected behavior.	Not Executed	Not Executed	P2	Authentication flow - When needed

Logout

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity
	User sign-out and post-logout	Verify Cold Start Launch	User is signed in and has access to the app	1. Open the app and navigate to the logout path in the app. 2. Trigger the cold start launch variation for the logout flow. 3. Observe the on-screen response and navigation outcome.	Logout should clear session data, redirect to the login screen, and start a new session.	Not Executed	Not Executed	P4	protected code - Critical
	User sign-out and post-logout	Verify First-Run Display	User is signed in and has access to the app	1. Open the app and navigate to the logout path in the app. 2. Trigger the first-run display variation for the logout flow. 3. Observe the on-screen response and navigation outcome.	Logout should clear session data, redirect to the login screen, and start a new session.	Not Executed	Not Executed	P4	protected code - High
	User sign-out and post-logout	Verify Loading Animation	User is signed in and has access to the app	1. Open the app and navigate to the logout path in the app. 2. Trigger the loading animation variation for the logout flow. 3. Observe the on-screen response and navigation outcome.	Logout should clear session data, redirect to the login screen, and start a new session.	Not Executed	Not Executed	P2	protected code - Medium
	User sign-out and post-logout	Verify Background Resume	User is signed in and has access to the app	1. Open the app and navigate to the logout path in the app. 2. Trigger the background to foreground resume variation for the logout flow. 3. Observe the on-screen response and navigation outcome.	Logout should clear session data, redirect to the login screen, and start a new session.	Not Executed	Not Executed	P2	protected code - Medium
	User sign-out and post-logout	Verify Force Close and Relaunch	User is signed in and has access to the app	1. Open the app and navigate to the logout path in the app. 2. Trigger the force close and relaunch variation for the logout flow. 3. Observe the on-screen response and navigation outcome.	Logout should clear session data, redirect to the login screen, and start a new session.	Not Executed	Not Executed	P4	protected code - High
	User sign-out and post-logout	Verify Slow Network Response	User is signed in and has access to the app	1. Open the app and navigate to the logout path in the app. 2. Trigger the slow network response variation for the logout flow. 3. Observe the on-screen response and navigation outcome.	Logout should clear session data, redirect to the login screen, and start a new session.	Not Executed	Not Executed	P2	protected code - Medium
	User sign-out and post-logout	Verify Offline Network Condition	User is signed in and has access to the app	1. Open the app and navigate to the logout path in the app. 2. Trigger the offline network condition variation for the logout flow. 3. Observe the on-screen response and navigation outcome.	Logout should clear session data, redirect to the login screen, and start a new session.	Not Executed	Not Executed	P4	protected code - High
	User sign-out and post-logout	Verify Cached Data Fallback	User is signed in and has access to the app	1. Open the app and navigate to the logout path in the app. 2. Trigger the cached data fallback variation for the logout flow. 3. Observe the on-screen response and navigation outcome.	Logout should clear session data, redirect to the login screen, and start a new session.	Not Executed	Not Executed	P2	protected code - Medium

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity
	User sign-out and post-logout	Verify Accessibility Focus Accessibility focus order variation	User is signed in breaking the access to the app	1. Open the logout path in the app. 2. Trigger the accessibility focus order variation for the logout flow. 3. Observe the on-screen response and navigation outcome.	Logout should clear session data, redirect to the home screen	Not Executed	Not Executed	High	Medium
	User sign-out and post-logout	Verify Localization Rendering Localization rendering variation	User is signed in breaking the access to the app	1. Open the logout path in the app. 2. Trigger the localization rendering variation for the logout flow. 3. Observe the on-screen response and navigation outcome.	Logout should clear session data, redirect to the home screen	Not Executed	Not Executed	High	Medium
	User sign-out and post-logout	Verify Repeated Tap Handling Repeated tap handling variation	User is signed in breaking the access to the app	1. Open the logout path in the app. 2. Trigger the repeated tap handling variation for the logout flow. 3. Observe the on-screen response and navigation outcome.	Logout should clear session data, redirect to the home screen	Not Executed	Not Executed	High	Medium
	User sign-out and post-logout	Verify Boundary Input Validation Boundary input validation variation	User is signed in breaking the access to the app	1. Open the logout path in the app. 2. Trigger the boundary input validation variation for the logout flow. 3. Observe the on-screen response and navigation outcome.	Logout should clear session data, redirect to the home screen	Not Executed	Not Executed	High	Medium
	User sign-out and post-logout	Verify Invalid Input Rejection Invalid input rejection variation	User is signed in breaking the access to the app	1. Open the logout path in the app. 2. Trigger the invalid input rejection variation for the logout flow. 3. Observe the on-screen response and navigation outcome.	Logout should clear session data, redirect to the home screen	Not Executed	Not Executed	High	Medium
	User sign-out and post-logout	Verify Empty State Rendering Empty state rendering variation	User is signed in breaking the access to the app	1. Open the logout path in the app. 2. Trigger the empty state rendering variation for the logout flow. 3. Observe the on-screen response and navigation outcome.	Logout should clear session data, redirect to the home screen	Not Executed	Not Executed	High	Medium
	User sign-out and post-logout	Verify Session Expiry Handling Session expiry handling variation	User is signed in breaking the access to the app	1. Open the logout path in the app. 2. Trigger the session expiry handling variation for the logout flow. 3. Observe the on-screen response and navigation outcome.	Logout should clear session data, redirect to the home screen	Not Executed	Not Executed	High	Medium
	User sign-out and post-logout	Verify Permission Prompt Handling Permission prompt handling variation	User is signed in breaking the access to the app	1. Open the logout path in the app. 2. Trigger the permission prompt handling variation for the logout flow. 3. Observe the on-screen response and navigation outcome.	Logout should clear session data, redirect to the home screen	Not Executed	Not Executed	High	Medium
	User sign-out and post-logout	Verify Notification Entry Handling Notification entry handling variation	User is signed in breaking the access to the app	1. Open the logout path in the app. 2. Trigger the notification entry handling variation for the logout flow. 3. Observe the on-screen response and navigation outcome.	Logout should clear session data, redirect to the home screen	Not Executed	Not Executed	High	Medium
	User sign-out and post-logout	Verify Deep Link Navigation Deep link navigation variation	User is signed in breaking the access to the app	1. Open the logout path in the app. 2. Trigger the deep link navigation variation for the logout flow. 3. Observe the on-screen response and navigation outcome.	Logout should clear session data, redirect to the home screen	Not Executed	Not Executed	High	Medium
	User sign-out and post-logout	Verify Device State Change Handling Device state change handling variation	User is signed in breaking the access to the app	1. Open the logout path in the app. 2. Trigger the device state change handling variation for the logout flow. 3. Observe the on-screen response and navigation outcome.	Logout should clear session data, redirect to the home screen	Not Executed	Not Executed	High	Medium

Error Handling

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity
Handling	Application error surfaces and recovery messages	Cold start launch	The app is in a broken state	1. Open the app. 2. Trigger the cold start launch variation for the error handling flow. 3. Observe the on-screen response and navigation outcome.	The app should present a readable error message and a recovery message.	Not Executed	Not Executed	High	Medium
Handling	Application error surfaces and recovery messages	First-run display	The app is in a broken state	1. Open the app. 2. Trigger the first-run display variation for the error handling flow. 3. Observe the on-screen response and navigation outcome.	The app should present a readable error message and a recovery message.	Not Executed	Not Executed	High	Medium
Handling	Application error surfaces and recovery messages	Loading animation	The app is in a broken state	1. Open the app. 2. Trigger the loading animation variation for the error handling flow. 3. Observe the on-screen response and navigation outcome.	The app should present a readable error message and a recovery message.	Not Executed	Not Executed	High	Medium

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity	
dding	Application error surfaces and recovery messages	Background to Foreground resume test with valid state	Device is in background state	1. Observe the response handling available in the app. 2. Trigger the background to foreground resume variation for the error handling flow. 3. Observe the on-screen response and navigation outcome.	The app should present a readable error message	Not Executed	Pass	Not Repeated	Low	Recovery where applicable
dding	Application error surfaces and recovery messages	Force Close and Relaunch the app without breaking valid state	Device is in foreground state	1. Observe the response handling available in the app. 2. Trigger the force close and relaunch variation for the error handling flow. 3. Observe the on-screen response and navigation outcome.	The app should present a readable error message	Not Executed	Pass	Not Repeated	Low	Recovery where applicable
dding	Application error surfaces and recovery messages	Slow network response without breaking valid state	Device is in foreground state	1. Observe the response handling available in the app. 2. Trigger the slow network response variation for the error handling flow. 3. Observe the on-screen response and navigation outcome.	The app should present a readable error message	Not Executed	Pass	Not Repeated	Low	Recovery where applicable
dding	Application error surfaces and recovery messages	Offline network condition without breaking valid state	Device is in foreground state	1. Observe the response handling available in the app. 2. Trigger the offline network condition variation for the error handling flow. 3. Observe the on-screen response and navigation outcome.	The app should present a readable error message	Not Executed	Pass	Not Repeated	Low	Recovery where applicable
dding	Application error surfaces and recovery messages	Cached data fallback without breaking valid state	Device is in foreground state	1. Observe the response handling available in the app. 2. Trigger the cached data fallback variation for the error handling flow. 3. Observe the on-screen response and navigation outcome.	The app should present a readable error message	Not Executed	Pass	Not Repeated	Low	Recovery where applicable
dding	Application error surfaces and recovery messages	Accessibility focus variation without breaking valid state	Device is in foreground state	1. Observe the response handling available in the app. 2. Trigger the accessibility focus order variation for the error handling flow. 3. Observe the on-screen response and navigation outcome.	The app should present a readable error message	Not Executed	Pass	Not Repeated	Low	Recovery where applicable
dding	Application error surfaces and recovery messages	Localization rendering without breaking valid state	Device is in foreground state	1. Observe the response handling available in the app. 2. Trigger the localization rendering variation for the error handling flow. 3. Observe the on-screen response and navigation outcome.	The app should present a readable error message	Not Executed	Pass	Not Repeated	Low	Recovery where applicable
dding	Application error surfaces and recovery messages	Repeated tapping without breaking valid state	Device is in foreground state	1. Observe the response handling available in the app. 2. Trigger the repeated tap handling variation for the error handling flow. 3. Observe the on-screen response and navigation outcome.	The app should present a readable error message	Not Executed	Pass	Not Repeated	Low	Recovery where applicable
dding	Application error surfaces and recovery messages	Boundary input validation without breaking valid state	Device is in foreground state	1. Observe the response handling available in the app. 2. Trigger the boundary input validation variation for the error handling flow. 3. Observe the on-screen response and navigation outcome.	The app should present a readable error message	Not Executed	Pass	Not Repeated	Low	Recovery where applicable
dding	Application error surfaces and recovery messages	Invalid input rejection without breaking valid state	Device is in foreground state	1. Observe the response handling available in the app. 2. Trigger the invalid input rejection variation for the error handling flow. 3. Observe the on-screen response and navigation outcome.	The app should present a readable error message	Not Executed	Pass	Not Repeated	Low	Recovery where applicable
dding	Application error surfaces and recovery messages	Empty state rendering without breaking valid state	Device is in foreground state	1. Observe the response handling available in the app. 2. Trigger the empty state rendering variation for the error handling flow. 3. Observe the on-screen response and navigation outcome.	The app should present a readable error message	Not Executed	Pass	Not Repeated	Low	Recovery where applicable
dding	Application error surfaces and recovery messages	Session expiry handling without breaking valid state	Device is in foreground state	1. Observe the response handling available in the app. 2. Trigger the session expiry handling variation for the error handling flow. 3. Observe the on-screen response and navigation outcome.	The app should present a readable error message	Not Executed	Pass	Not Repeated	Low	Recovery where applicable
dding	Application error surfaces and recovery messages	Permission prompt handling without breaking valid state	Device is in foreground state	1. Observe the response handling available in the app. 2. Trigger the permission prompt handling variation for the error handling flow. 3. Observe the on-screen response and navigation outcome.	The app should present a readable error message	Not Executed	Pass	Not Repeated	Low	Recovery where applicable
dding	Application error surfaces and recovery messages	Notification entry handling without breaking valid state	Device is in foreground state	1. Observe the response handling available in the app. 2. Trigger the notification entry handling variation for the error handling flow. 3. Observe the on-screen response and navigation outcome.	The app should present a readable error message	Not Executed	Pass	Not Repeated	Low	Recovery where applicable
dding	Application error surfaces and recovery messages	Deep link navigation without breaking valid state	Device is in foreground state	1. Observe the response handling available in the app. 2. Trigger the deep link navigation variation for the error handling flow. 3. Observe the on-screen response and navigation outcome.	The app should present a readable error message	Not Executed	Pass	Not Repeated	Low	Recovery where applicable
dding	Application error surfaces and recovery messages	Device state change handling without breaking valid state	Device is in foreground state	1. Observe the response handling available in the app. 2. Trigger the device state change handling variation for the error handling flow. 3. Observe the on-screen response and navigation outcome.	The app should present a readable error message	Not Executed	Pass	Not Repeated	Low	Recovery where applicable

Boundary Testing

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity
Testing	Extreme valid input ranges - Cold Start	Verify boundary testing supports cold start	The app is installed and ready to run	1. Trigger the cold start launch variation for the boundary testing path in the app. 2. Trigger the cold start launch variation for the boundary testing flow. 3. Observe the on-screen response and navigation outcome.	Boundary values should be accepted or rejected	Not Executed	Not Executed	P1 without truncation	Critical or High
Testing	Extreme valid input ranges - First Run Display	Verify boundary testing supports first-run display	The app is installed and ready to run	1. Trigger the first-run display variation for the boundary testing path in the app. 2. Trigger the first-run display variation for the boundary testing flow. 3. Observe the on-screen response and navigation outcome.	Boundary values should be accepted or rejected	Not Executed	Not Executed	P1 without truncation	High or Critical
Testing	Extreme valid input ranges - Loading Animation	Verify boundary testing supports loading animation	The app is installed and ready to run	1. Trigger the loading animation variation for the boundary testing path in the app. 2. Trigger the loading animation variation for the boundary testing flow. 3. Observe the on-screen response and navigation outcome.	Boundary values should be accepted or rejected	Not Executed	Not Executed	P2 without truncation	Medium or Critical
Testing	Extreme valid input ranges - Background to Foreground Resumes	Verify boundary testing supports background to foreground resume	The app is installed and ready to run	1. Trigger the background to foreground resume variation for the boundary testing path in the app. 2. Trigger the background to foreground resume variation for the boundary testing flow. 3. Observe the on-screen response and navigation outcome.	Boundary values should be accepted or rejected	Not Executed	Not Executed	P2 without truncation	Medium or Critical
Testing	Extreme valid input ranges - Force Close and Relaunch	Verify boundary testing supports force close and relaunch	The app is installed and ready to run	1. Trigger the force close and relaunch variation for the boundary testing path in the app. 2. Trigger the force close and relaunch variation for the boundary testing flow. 3. Observe the on-screen response and navigation outcome.	Boundary values should be accepted or rejected	Not Executed	Not Executed	P1 without truncation	High or Critical
Testing	Extreme valid input ranges - Slow Network Response	Verify boundary testing supports slow network response	The app is installed and ready to run	1. Trigger the slow network response variation for the boundary testing path in the app. 2. Trigger the slow network response variation for the boundary testing flow. 3. Observe the on-screen response and navigation outcome.	Boundary values should be accepted or rejected	Not Executed	Not Executed	P2 without truncation	Medium or Critical
Testing	Extreme valid input ranges - Offline Network Condition	Verify boundary testing supports offline network condition	The app is installed and ready to run	1. Trigger the offline network condition variation for the boundary testing path in the app. 2. Trigger the offline network condition variation for the boundary testing flow. 3. Observe the on-screen response and navigation outcome.	Boundary values should be accepted or rejected	Not Executed	Not Executed	P1 without truncation	High or Critical
Testing	Extreme valid input ranges - Cached Data Fallback	Verify boundary testing supports cached data fallback	The app is installed and ready to run	1. Trigger the cached data fallback variation for the boundary testing path in the app. 2. Trigger the cached data fallback variation for the boundary testing flow. 3. Observe the on-screen response and navigation outcome.	Boundary values should be accepted or rejected	Not Executed	Not Executed	P2 without truncation	Medium or Critical
Testing	Extreme valid input ranges - Accessibility Focus Order	Verify boundary testing supports accessibility focus order	The app is installed and ready to run	1. Trigger the accessibility focus order variation for the boundary testing path in the app. 2. Trigger the accessibility focus order variation for the boundary testing flow. 3. Observe the on-screen response and navigation outcome.	Boundary values should be accepted or rejected	Not Executed	Not Executed	P2 without truncation	Medium or Critical
Testing	Extreme valid input ranges - Localization Rendering	Verify boundary testing supports localization rendering	The app is installed and ready to run	1. Trigger the localization rendering variation for the boundary testing path in the app. 2. Trigger the localization rendering variation for the boundary testing flow. 3. Observe the on-screen response and navigation outcome.	Boundary values should be accepted or rejected	Not Executed	Not Executed	P1 without truncation	Medium or Critical
Testing	Extreme valid input ranges - Repeated Tap Handling	Verify boundary testing supports repeated tap handling	The app is installed and ready to run	1. Trigger the repeated tap handling variation for the boundary testing path in the app. 2. Trigger the repeated tap handling variation for the boundary testing flow. 3. Observe the on-screen response and navigation outcome.	Boundary values should be accepted or rejected	Not Executed	Not Executed	P2 without truncation	Medium or Critical
Testing	Extreme valid input ranges - Boundary Input Validation	Verify boundary testing supports boundary input validation	The app is installed and ready to run	1. Trigger the boundary input validation variation for the boundary testing path in the app. 2. Trigger the boundary input validation variation for the boundary testing flow. 3. Observe the on-screen response and navigation outcome.	Boundary values should be accepted or rejected	Not Executed	Not Executed	P2 without truncation	High or Critical
Testing	Extreme valid input ranges - Invalid Input Rejection	Verify boundary testing supports invalid input rejection	The app is installed and ready to run	1. Trigger the invalid input rejection variation for the boundary testing path in the app. 2. Trigger the invalid input rejection variation for the boundary testing flow. 3. Observe the on-screen response and navigation outcome.	Boundary values should be accepted or rejected	Not Executed	Not Executed	P1 without truncation	High or Critical
Testing	Extreme valid input ranges - Empty State Rendering	Verify boundary testing supports empty state rendering	The app is installed and ready to run	1. Trigger the empty state rendering variation for the boundary testing path in the app. 2. Trigger the empty state rendering variation for the boundary testing flow. 3. Observe the on-screen response and navigation outcome.	Boundary values should be accepted or rejected	Not Executed	Not Executed	P2 without truncation	Medium or Critical
Testing	Extreme valid input ranges - Session Expiry Handling	Verify boundary testing supports session expiry handling	The app is installed and ready to run	1. Trigger the session expiry handling variation for the boundary testing path in the app. 2. Trigger the session expiry handling variation for the boundary testing flow. 3. Observe the on-screen response and navigation outcome.	Boundary values should be accepted or rejected	Not Executed	Not Executed	P1 without truncation	Critical or High

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity
Testing	Extreme valid input ranges - Permission Prompt Handling	Boundary testing supports permission prompt handling without breaking the user interface	1. Device is in a state where a permission prompt is required.	1. Select the unstable testing path in the app. 2. Trigger the permission prompt handling variation for the boundary testing flow. 3. Observe the on-screen response and navigation outcome.	Boundary values should be accepted or rejected as expected.	Not Executed	Not Executed	P2 without truncation	High or critical
Testing	Extreme valid input ranges - Notification Entry Handling	Boundary testing supports notification entry handling without breaking the user interface	1. Device is in a state where a notification entry is required.	1. Select the unstable testing path in the app. 2. Trigger the notification entry handling variation for the boundary testing flow. 3. Observe the on-screen response and navigation outcome.	Boundary values should be accepted or rejected as expected.	Not Executed	Not Executed	P2 without truncation	Medium or critical
Testing	Extreme valid input ranges - Deep Link Navigation	Boundary testing supports deep link navigation without breaking the user interface	1. Device is in a state where a deep link is required.	1. Select the unstable testing path in the app. 2. Trigger the deep link navigation variation for the boundary testing flow. 3. Observe the on-screen response and navigation outcome.	Boundary values should be accepted or rejected as expected.	Not Executed	Not Executed	P1 without truncation	High or critical
Testing	Extreme valid input ranges - Device State Change Handling	Boundary testing supports device state change handling without breaking the user interface	1. Device is in a state where a state change is required.	1. Select the unstable testing path in the app. 2. Trigger the device state change handling variation for the boundary testing flow. 3. Observe the on-screen response and navigation outcome.	Boundary values should be accepted or rejected as expected.	Not Executed	Not Executed	P2 without truncation	Medium or critical

Negative Testing

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity
Testing	Invalid data and misuse scenarios - Cold Start Launch	Application supports cold start launch without breaking the user interface	1. Device is in a state where a cold start launch is required.	1. Select the negative testing path in the app. 2. Trigger the cold start launch variation for the negative testing flow. 3. Observe the on-screen response and navigation outcome.	Invalid usage should be blocked with a clear message.	Message displayed	Not Executed	P1 Application	Critical
Testing	Invalid data and misuse scenarios - First-run Display	Application supports first-run display without breaking the user interface	1. Device is in a state where a first-run display is required.	1. Select the negative testing path in the app. 2. Trigger the first-run display variation for the negative testing flow. 3. Observe the on-screen response and navigation outcome.	Invalid usage should be blocked with a clear message.	Message displayed	Not Executed	P1 Application	High
Testing	Invalid data and misuse scenarios - Loading Animation	Application supports loading animation without breaking the user interface	1. Device is in a state where a loading animation is required.	1. Select the negative testing path in the app. 2. Trigger the loading animation variation for the negative testing flow. 3. Observe the on-screen response and navigation outcome.	Invalid usage should be blocked with a clear message.	Message displayed	Not Executed	P2 Application	Medium
Testing	Invalid data and misuse scenarios - Background to Foreground Resume	Application supports background to foreground resume without breaking the user interface	1. Device is in a state where a background to foreground resume is required.	1. Select the negative testing path in the app. 2. Trigger the background to foreground resume variation for the negative testing flow. 3. Observe the on-screen response and navigation outcome.	Invalid usage should be blocked with a clear message.	Message displayed	Not Executed	P2 Application	Medium
Testing	Invalid data and misuse scenarios - Force Close and Relaunch	Application supports force close and relaunch without breaking the user interface	1. Device is in a state where a force close and relaunch is required.	1. Select the negative testing path in the app. 2. Trigger the force close and relaunch variation for the negative testing flow. 3. Observe the on-screen response and navigation outcome.	Invalid usage should be blocked with a clear message.	Message displayed	Not Executed	P1 Application	High
Testing	Invalid data and misuse scenarios - Slow Network Response	Application supports slow network response without breaking the user interface	1. Device is in a state where a slow network response is required.	1. Select the negative testing path in the app. 2. Trigger the slow network response variation for the negative testing flow. 3. Observe the on-screen response and navigation outcome.	Invalid usage should be blocked with a clear message.	Message displayed	Not Executed	P2 Application	Medium
Testing	Invalid data and misuse scenarios - Offline Network Condition	Application supports offline network condition without breaking the user interface	1. Device is in a state where an offline network condition is required.	1. Select the negative testing path in the app. 2. Trigger the offline network condition variation for the negative testing flow. 3. Observe the on-screen response and navigation outcome.	Invalid usage should be blocked with a clear message.	Message displayed	Not Executed	P1 Application	High
Testing	Invalid data and misuse scenarios - Cached Data Fallback	Application supports cached data fallback without breaking the user interface	1. Device is in a state where a cached data fallback is required.	1. Select the negative testing path in the app. 2. Trigger the cached data fallback variation for the negative testing flow. 3. Observe the on-screen response and navigation outcome.	Invalid usage should be blocked with a clear message.	Message displayed	Not Executed	P2 Application	Medium
Testing	Invalid data and misuse scenarios - Accessibility Focus Order	Application supports accessibility focus order without breaking the user interface	1. Device is in a state where an accessibility focus order is required.	1. Select the negative testing path in the app. 2. Trigger the accessibility focus order variation for the negative testing flow. 3. Observe the on-screen response and navigation outcome.	Invalid usage should be blocked with a clear message.	Message displayed	Not Executed	P2 Application	Low
Testing	Invalid data and misuse scenarios - Localization Rendering	Application supports localization rendering without breaking the user interface	1. Device is in a state where a localization rendering is required.	1. Select the negative testing path in the app. 2. Trigger the localization rendering variation for the negative testing flow. 3. Observe the on-screen response and navigation outcome.	Invalid usage should be blocked with a clear message.	Message displayed	Not Executed	P1 Application	Medium

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity	
Testing	Invalid data and misuse scenario	Verify negative testing supports repeated tap handling with action breaking the usual flow of the negative path testing path in the app.	A relevant input without creating a relevant validation or without creating a valid open flow path testing path in the app.	1. Open the negative path testing path in the app. 2. Trigger the repeated tap handling variation for the negative testing flow. 3. Observe the on-screen response and navigation outcome.	Invalid usage should be blocked with a clear message and without a clear flow.	Message displayed without clear flow.	Not Executed	Current	R2 Application	Low
Testing	Invalid data and misuse scenario	Verify negative testing supports boundary validation without creating a valid open flow path testing path in the app.	A relevant input without creating a valid open flow path testing path in the app.	1. Open the negative path testing path in the app. 2. Trigger the boundary input validation variation for the negative testing flow. 3. Observe the on-screen response and navigation outcome.	Invalid usage should be blocked with a clear message and without a clear flow.	Message displayed without clear flow.	Not Executed	Current	R2 Application	High
Testing	Invalid data and misuse scenario	Verify negative testing supports invalid input rejection with action breaking the usual flow of the negative path testing path in the app.	A relevant input without creating a valid open flow path testing path in the app.	1. Open the negative path testing path in the app. 2. Trigger the invalid input rejection variation for the negative testing flow. 3. Observe the on-screen response and navigation outcome.	Invalid usage should be blocked with a clear message and without a clear flow.	Message displayed without clear flow.	Not Executed	Current	R1 Application	High
Testing	Invalid data and misuse scenario	Verify empty state rendering supports empty state rendering with action breaking the usual flow of the negative path testing path in the app.	A relevant input without creating a valid open flow path testing path in the app.	1. Open the negative path testing path in the app. 2. Trigger the empty state rendering variation for the negative testing flow. 3. Observe the on-screen response and navigation outcome.	Invalid usage should be blocked with a clear message and without a clear flow.	Message displayed without clear flow.	Not Executed	Current	R2 Application	Low
Testing	Invalid data and misuse scenario	Verify session expiry handling supports session expiry handling without breaking the usual flow of the negative path testing path in the app.	A relevant input without creating a valid open flow path testing path in the app.	1. Open the negative path testing path in the app. 2. Trigger the session expiry handling variation for the negative testing flow. 3. Observe the on-screen response and navigation outcome.	Invalid usage should be blocked with a clear message and without a clear flow.	Message displayed without clear flow.	Not Executed	Current	R1 Application	Critical
Testing	Invalid data and misuse scenario	Verify permission testing supports permission prompt handling without breaking the usual flow of the negative path testing path in the app.	A relevant input without creating a valid open flow path testing path in the app.	1. Open the negative path testing path in the app. 2. Trigger the permission prompt handling variation for the negative testing flow. 3. Observe the on-screen response and navigation outcome.	Invalid usage should be blocked with a clear message and without a clear flow.	Message displayed without clear flow.	Not Executed	Current	R2 Application	High
Testing	Invalid data and misuse scenario	Verify notification handling supports notification entry handling without breaking the usual flow of the negative path testing path in the app.	A relevant input without creating a valid open flow path testing path in the app.	1. Open the negative path testing path in the app. 2. Trigger the notification entry handling variation for the negative testing flow. 3. Observe the on-screen response and navigation outcome.	Invalid usage should be blocked with a clear message and without a clear flow.	Message displayed without clear flow.	Not Executed	Current	R2 Application	Medium
Testing	Invalid data and misuse scenario	Verify deep link navigation supports deep link navigation without breaking the usual flow of the negative path testing path in the app.	A relevant input without creating a valid open flow path testing path in the app.	1. Open the negative path testing path in the app. 2. Trigger the deep link navigation variation for the negative testing flow. 3. Observe the on-screen response and navigation outcome.	Invalid usage should be blocked with a clear message and without a clear flow.	Message displayed without clear flow.	Not Executed	Current	R1 Application	High
Testing	Invalid data and misuse scenario	Verify device state change handling supports device state change handling without breaking the usual flow of the negative path testing path in the app.	A relevant input without creating a valid open flow path testing path in the app.	1. Open the negative path testing path in the app. 2. Trigger the device state change handling variation for the negative testing flow. 3. Observe the on-screen response and navigation outcome.	Invalid usage should be blocked with a clear message and without a clear flow.	Message displayed without clear flow.	Not Executed	Current	R2 Application	Low

Regression Testing

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity	
on Testing	Core app stability after change	-Verify Session on testing supports cold start launch with breaking the regression path in the app. Previously working flows should continue to be maintained after the change.	The built is ready for breaking the regression path in the app. Previously working flows should continue to be maintained after the change.	1. Open the regression key tapping path in the app. 2. Trigger the cold start launch variation for the regression testing flow. 3. Observe the on-screen response and navigation outcome.	Invalid usage should be blocked with a clear message and without a clear flow.	Message displayed without clear flow.	Not Executed	New	R1 changes.	Critical
on Testing	Core app stability after change	-Verify Reg Display on testing supports first-run display with breaking the regression path in the app. Previously working flows should continue to be maintained after the change.	The built is ready for breaking the regression path in the app. Previously working flows should continue to be maintained after the change.	1. Open the regression key tapping path in the app. 2. Trigger the first-run display variation for the regression testing flow. 3. Observe the on-screen response and navigation outcome.	Invalid usage should be blocked with a clear message and without a clear flow.	Message displayed without clear flow.	Not Executed	New	R1 changes.	High
on Testing	Core app stability after change	-Verify Loading Animation on testing supports loading animation with breaking the regression path in the app. Previously working flows should continue to be maintained after the change.	The built is ready for breaking the regression path in the app. Previously working flows should continue to be maintained after the change.	1. Open the regression key tapping path in the app. 2. Trigger the loading animation variation for the regression testing flow. 3. Observe the on-screen response and navigation outcome.	Invalid usage should be blocked with a clear message and without a clear flow.	Message displayed without clear flow.	Not Executed	New	R2 changes.	Medium
on Testing	Core app stability after change	-Verify Background to Foreground on testing supports background to foreground resume with breaking the regression path in the app. Previously working flows should continue to be maintained after the change.	The built is ready for breaking the regression path in the app. Previously working flows should continue to be maintained after the change.	1. Open the regression key tapping path in the app. 2. Trigger the background to foreground resume variation for the regression testing flow. 3. Observe the on-screen response and navigation outcome.	Invalid usage should be blocked with a clear message and without a clear flow.	Message displayed without clear flow.	Not Executed	New	R2 changes.	Medium
on Testing	Core app stability after change	-Verify Force Close and Relaunch on testing supports force close and relaunch with breaking the regression path in the app. Previously working flows should continue to be maintained after the change.	The built is ready for breaking the regression path in the app. Previously working flows should continue to be maintained after the change.	1. Open the regression key tapping path in the app. 2. Trigger the force close and relaunch variation for the regression testing flow. 3. Observe the on-screen response and navigation outcome.	Invalid usage should be blocked with a clear message and without a clear flow.	Message displayed without clear flow.	Not Executed	New	R1 changes.	High

	Feature	Test Scenario	Preconditions	Test Steps	Expected Result	Actual Result	Status	Priority	Severity
on Testing	Core app stability after change	-Verify Regression Testing supports slow network response	The build is ready for a breaking regression test	1. Open the app. Previously working flows should continue to be successful. 2. Trigger the slow network response variation for the regression testing flow. 3. Observe the on-screen response and navigation outcome.	None observed after	Not Executed	new	P2 changes.	Medium
on Testing	Core app stability after change	-Verify Regression Testing supports offline network condition	The build is ready for a breaking regression test	1. Open the app. Previously working flows should continue to be successful. 2. Trigger the offline network condition variation for the regression testing flow. 3. Observe the on-screen response and navigation outcome.	None observed after	Not Executed	new	P1 changes.	High
on Testing	Core app stability after change	-Verify Data Fallback supports cached data fallback	The build is ready for a breaking regression test	1. Open the app. Previously working flows should continue to be successful. 2. Trigger the cached data fallback variation for the regression testing flow. 3. Observe the on-screen response and navigation outcome.	None observed after	Not Executed	new	P2 changes.	Medium
on Testing	Core app stability after change	-Verify Accessibility Focus Order supports accessibility focus order	The build is ready for a breaking regression test	1. Open the app. Previously working flows should continue to be successful. 2. Trigger the accessibility focus order variation for the regression testing flow. 3. Observe the on-screen response and navigation outcome.	None observed after	Not Executed	new	P2 changes.	Low
on Testing	Core app stability after change	-Verify Localization Rendering supports localization rendering	The build is ready for a breaking regression test	1. Open the app. Previously working flows should continue to be successful. 2. Trigger the localization rendering variation for the regression testing flow. 3. Observe the on-screen response and navigation outcome.	None observed after	Not Executed	new	P1 changes.	Medium
on Testing	Core app stability after change	-Verify Repeated Tap Handling supports repeated tap handling	The build is ready for a breaking regression test	1. Open the app. Previously working flows should continue to be successful. 2. Trigger the repeated tap handling variation for the regression testing flow. 3. Observe the on-screen response and navigation outcome.	None observed after	Not Executed	new	P2 changes.	Low
on Testing	Core app stability after change	-Verify Boundary Input Validation supports boundary input validation	The build is ready for a breaking regression test	1. Open the app. Previously working flows should continue to be successful. 2. Trigger the boundary input validation variation for the regression testing flow. 3. Observe the on-screen response and navigation outcome.	None observed after	Not Executed	new	P2 changes.	High
on Testing	Core app stability after change	-Verify Invalid Input Rejection supports invalid input rejection	The build is ready for a breaking regression test	1. Open the app. Previously working flows should continue to be successful. 2. Trigger the invalid input rejection variation for the regression testing flow. 3. Observe the on-screen response and navigation outcome.	None observed after	Not Executed	new	P1 changes.	High
on Testing	Core app stability after change	-Verify Empty State Rendering supports empty state rendering	The build is ready for a breaking regression test	1. Open the app. Previously working flows should continue to be successful. 2. Trigger the empty state rendering variation for the regression testing flow. 3. Observe the on-screen response and navigation outcome.	None observed after	Not Executed	new	P2 changes.	Low
on Testing	Core app stability after change	-Verify Session Expiry Handling supports session expiry handling	The build is ready for a breaking regression test	1. Open the app. Previously working flows should continue to be successful. 2. Trigger the session expiry handling variation for the regression testing flow. 3. Observe the on-screen response and navigation outcome.	None observed after	Not Executed	new	P1 changes.	Critical

Conclusion

This package delivers a complete documentation baseline for Appium mobile testing with 300 unique test cases organized by module. It is ready to support execution planning, defect tracking, and future run reporting.