```
abishek1703@AAAD:~$ lscpu -p=CPU,CORE,SOCKET
# The following is the parsable format, which can be fed to other
# programs. Each different item in every column has an unique ID
# starting usually from zero.
# CPU,Core,Socket
0,0,0
1,0,0
2,1,0
3,1,0
4,2,0
5,2,0
6,3,0
7,3,0
8,4,0
9,4,0
10,5,0
11,5,0
abishek1703@AAAD:~$ arp -n
Address                  HWtype  HWaddress           Flags Mask            Iface
172.31.160.1             ether   00:15:5d:e1:e0:d1   C                     eth0
abishek1703@AAAD:~$ dig example.com +short
172.66.147.243
104.20.23.154
abishek1703@AAAD:~$ tracepath google.com
 1?: [LOCALHOST]                      pmtu 1280
 1:  AAAD.mshome.net                                       0.485ms
 1:  AAAD.mshome.net                                       0.416ms
 2:  192.168.0.1                                           3.266ms
 3:  10.227.0.1                                            4.581ms
 4:  no reply
 5:  10.200.150.30                                       319.935ms
 6:  72.14.212.80                                          4.930ms
 7:  no reply
^C
abishek1703@AAAD:~$ nc -zv -w 5 google.com 443
Connection to google.com (142.250.70.46) 443 port [tcp/https] succeeded!
abishek1703@AAAD:~$ pgrep -a ssh
abishek1703@AAAD:~$ pidof systemd
522
abishek1703@AAAD:~$
```

```
abishek1703@AAAD:~$ TEMP_DIR=$(mktemp -d)
abishek1703@AAAD:~$ echo "Created directory: $TEMP_DIR"
Created directory: /tmp/tmp.tv1TSvJMp1
abishek1703@AAAD:~$ ls -ld "$TEMP_DIR"
drwx------ 2 abishek1703 abishek1703 40 Nov  1 08:56 /tmp/tmp.tv1TSvJMp1
abishek1703@AAAD:~$ sudo blkid
/dev/sdd: UUID="b601f9c3-8d72-4c21-a16a-d00c7c5ce202" BLOCK_SIZE="4096" TYPE="ext4"
/dev/sdb: BLOCK_SIZE="4096" TYPE="ext4"
/dev/sdc: UUID="e683b0fe-a0b0-446b-acaa-3c015b7b2eb5" TYPE="swap"
/dev/sda: BLOCK_SIZE="4096" TYPE="ext4"
abishek1703@AAAD:~$
```