SUPPLEMENTARY INFORMATION

Reduced-Order Dynamic Model Formulations, Parameter Values, and Wave-Tank Trajectories

To be published in: Ecological Engineering (Elsevier)
Article Reference: ECOENG 108207 | Manuscript: ECOLENG-D-26-01558R1

Robust Modular Floating Wetland: Design & Wave-Tank Evaluation

Abishek Kafle[a], Samson P. Stern[b], Damar D. Wilson[b], Raman Silwal[a], Nirmal Kumar[b], Ram L. Ray[c], Venkatesh Balan[b],*, Weihang Zhu[b],*

[a] *Department of Mechanical and Aerospace Engineering, University of Houston, Houston, TX 77004, USA*
[b] *Department of Engineering Technology, University of Houston, Sugar Land, TX 77479, USA*
[c] *College of Agriculture and Human Sciences, Prairie View A&M University, Prairie View, TX 77446, USA*
** Corresponding Authors: Venkatesh Balan (vbalan@uh.edu), Weihang Zhu (wzhu21@central.uh.edu)*

Supplementary Information Contents:

• Section S1: Reduced-Order Surge–Sway–Yaw Dynamic Model (Governing Equations and Parameters Cited in Section 2.4)
• Section S2: Experimental Kinematic Motion Analysis and Moving Block Bootstrap (MBB) Formulations
• Section S3: Supplementary Wave-Tank Centroid Trajectories and Spatial Sample Density (Figure S1)
• Section S4: Public Code and Dataset Availability Summary

Section S1. Reduced-Order Dynamic Model (Surge–Sway–Yaw)

As stated in Section 2.4 of the primary manuscript, a three-degree-of-freedom (3-DOF) reduced-order horizontal dynamic model (surge, sway, and yaw) was formulated to aid the physical interpretation of the wave-tank measurements. The model's purpose is limited to verifying that experimentally observed drift (0.60–1.34 cm), heading deviations (< 1°), and line tensions (~2.0 N) fall within orders of magnitude expected from classical tethered-floater mechanics (Faltinsen, 1990; Newman, 1977). This section details the governing equations, hydrodynamic matrices, and parameter values cited in Section 2.4.

S1.1 Planar 3-DOF Equations of Motion

The laboratory floating treatment wetland (FTW) test specimen was a standardized hexagonal buoyant mat (longest side length s = 0.29 m, circumscribed diameter D = 0.58 m, width across flats W = 0.502 m, thickness t = 0.013 m). The horizontal displacement vector in body-fixed centroidal coordinates is defined as:

$$\mathbf{x}(t) = \begin{bmatrix} x(t) \\ y(t) \\ \psi(t) \end{bmatrix} \tag{S1}$$

where x(t) is surge (displacement parallel to wave propagation along the tank length, m), y(t) is sway (transverse displacement across the tank width, m), and ψ(t) is yaw (rotation about the vertical z-axis through the centroid, rad). The coupled equations of motion in the horizontal plane are governed by:

$$(M + A)\ddot{\mathbf{x}}(t) + (B_{\text{rad}} + B_{\text{visc}})\dot{\mathbf{x}}(t) + K\mathbf{x}(t) = \mathbf{F}_{\text{exc}}(t) + \mathbf{F}_{\text{drift}} \quad \text{(S2)}$$

where:

- $\boldsymbol{M}$: Structural mass and inertia matrix,
- $\boldsymbol{A}$: Hydrodynamic added-mass matrix from entrained fluid inertia,
- $\boldsymbol{B}_{\text{rad}}$: Linear wave radiation damping matrix,
- $\boldsymbol{B}_{\text{visc}}$: Equivalent linearized viscous hydrodynamic drag damping matrix,
- $\boldsymbol{K}$: Mooring restoring stiffness matrix synthesized from anchor line geometry,
- $\boldsymbol{F}_{\text{exc}}(t)$: First-order oscillatory wave excitation force vector, and
- $\boldsymbol{F}_{\text{drift}}$: Second-order steady horizontal wave drift force.

S1.2 Structural Mass and Hydrodynamic Added Mass

The structural mass matrix $\boldsymbol{M}$ for the planar regular hexagonal mat (side length s = 0.29 m, operating mass $m \approx 1.25$ kg including containers and ballast) is:

$$M = \begin{bmatrix} m & 0 & 0 \\ 0 & m & 0 \\ 0 & 0 & I_{zz} \end{bmatrix}, I_{zz} = \frac{5}{12} m s^2 \quad \text{(S3)}$$

For a shallow-draft floating plate (waterplane area $A_{\text{wp}} = (3\sqrt{3}/2)\ s^2 = 0.219\ m^2$, draft $d \approx 0.0057$ m), the hydrodynamic added-mass matrix $\boldsymbol{A} = \text{diag}(A_{11}, A_{22}, A_{66})$ is evaluated from potential flow approximations for shallow-water floating plates:

$$A_{11} \approx C_{a,\text{surge}} \rho_w A_{\text{wp}} d, A_{22} = A_{11}, A_{66} \approx C_{a,\text{yaw}} \rho_w A_{\text{wp}} d R_g^2 \quad \text{(S4)}$$

where ρ_w is freshwater density (1000 kg/m³), $R_g = \sqrt{(5/12)}$ s ≈ 0.187 m is the mass radius of gyration, and $C_{a,\text{surge}} \approx 0.28$ and $C_{a,\text{yaw}} \approx 0.25$ are dimensionless added-mass coefficients for shallow thin plates, yielding $A_{11} \approx 0.35$ kg and $A_{66} \approx 0.012$ kg·m² with consistent dimensional SI units.

S1.3 Mooring Restoring Stiffness Formulation

Anchor lines are represented as spring–dashpot tethers operating under nominal in-line operating tension $T_0 \approx 2.00$ N (matching in-line load-cell measurements). For tether line stiffness k_i, line length L_i, inclination angle θ_i, and horizontal azimuth angle α_i, horizontal restoring stiffness coefficients are synthesized as:

$$K_{xx} = \sum_{i=1}^{N_L} \left[k_i \cos^2\theta_i \cos^2\alpha_i + \frac{T_0}{L_i} \sin^2\alpha_i \right] \quad \text{(S5)}$$

$$K_{\psi\psi} = \sum_{i=1}^{N_L} k_i (-x_i \sin\alpha_i + y_i \cos\alpha_i)^2 \cos^2\theta_i \quad \text{(S6)}$$

• Tension-Guide: Restraint along the spanning guide line yields an effective longitudinal surge stiffness $K_{xx} \approx 18$ N/m and lower rotational restraint ($K_{\psi\psi} \approx 0.65$ N·m/rad).
• Distributed-Modular: Independent bottom tethers engage symmetrically around the perimeter, yielding higher horizontal stiffness ($K_{xx} \approx 48$ N/m, $K_{yy} \approx 48$ N/m) and substantially increased rotational stiffness ($K_{\psi\psi} \approx 2.10$ N·m/rad) due to expanded tether moment arms.

S1.4 Wave Excitation and 2D Radial Drift Mechanics

Under monochromatic wave forcing (frequency f = 1.0 Hz, wave amplitude a = H/2 = 0.02 m), platform motion consists of first-order oscillatory response (X_0 cos ωt, Y_0 sin ωt) superimposed on a steady second-order mean wave drift offset $x_0 = F_{drift} / K_{xx}$. The second-order horizontal wave drift force (Maruo, 1960) is:

$$\bar{F}_{drift} = \frac{1}{2}\rho_w g R^2 a^2 W_{eff} \quad \text{(S7)}$$

where $R \approx 0.18$ is the wave reflection coefficient and $W_{eff} \approx 0.502$ m is the effective frontal width, yielding $F_{drift} \approx 0.032$ N. Because the camera tracking system computes the instantaneous Euclidean distance from the origin $r(t) = \sqrt{(x(t)^2 + y(t)^2)}$, the true time-averaged mean radial drift reported in the manuscript is evaluated by exact time integration over wave period $T = 1/f$:

$$\bar{r} = \frac{1}{T}\int_0^T \sqrt{x(t)^2 + y(t)^2}\,dt \quad \text{(S8)}$$

For harmonic motion, the root-mean-square (RMS) radial excursion provides an analytical upper-bound proxy: $r_{rms} = \sqrt{(x_0^2 + 0.5(X_0^2 + Y_0^2))}$. Both the exact integral (Eq. S8) and the RMS proxy confirm that 2D radial drift is systematically larger than the 1D steady offset x_0 due to the contribution of wave-induced orbital excursions.

S1.5 Numerical Parameter Values (Table S1)

Table S1 reports the numerical parameters, physical constants, and mooring stiffness properties implemented in the reduced-order dynamic model. Parameters are derived from first principles, the measured 2.0 N line pretension, and potential flow hydrodynamics for the 29 cm laboratory specimen.

Parameter	Symbol	Value	Unit / Derivation Basis
Water density	ρ_w	1000	kg/m³ (freshwater)
Gravitational acceleration	g	9.81	m/s²
Tank water depth	h	0.45	m (measured tank level)
Hexagonal side length	s	0.29 (29.0 cm)	m (laboratory specimen)
Circumscribed diameter	D	0.58 (58.0 cm)	m (2·s, lab specimen)
Width across flats	W	0.502 (50.2 cm)	m (√3·s, lab specimen)
Mat planform area	A_{wp}	0.219	m² ((3√3/2)·s²)
Total operating mass	m	1.25	kg (foam mat + cups + ballast)
Equilibrium static draft	d	0.0057 (5.7 mm)	m (m / (ρw·Awp))
Yaw moment of inertia	I_{zz}	0.0438	kg·m² ((5/12)·m·s²)

Surge / sway added mass	A_{11}, A_{22}	0.35	kg (potential flow strip calc.)
Yaw added inertia	A_{66}	0.012	kg·m² (rotational fluid boundary)
Surge / sway damping	B_{xx}, B_{yy}	5.80	N·s/m (linearized drag + radiation)
Yaw damping	$B_{\psi\psi}$	0.18	N·m·s/rad (rotational damping)
Wave frequency	$f(\omega)$	1.0 (6.28)	Hz (rad/s) (paddle drive frequency)
Wave height / amplitude	$H(a)$	0.04 (0.02)	m (tested wave regime)
Wave reflection coeff.	R	0.18	dimensionless (perforated mat edge)
Nominal line pretension	T_0	2.00	N (load-cell operating point)
Tension-guide surge stiffness	$K_{xx,guide}$	18.0	N/m (spanning line compliance)
Tension-guide yaw stiffness	$K_{\psi\psi,guide}$	0.65	N·m/rad (edge restraint)
Distributed-modular surge stiffness	$K_{xx,mod}$	48.0	N/m (symmetric multi-anchor)
Distributed-modular yaw stiffness	$K_{\psi\psi,mod}$	2.10	N·m/rad (midline & corner anchors)

S1.6 Physical Order-of-Magnitude Verification

Table S2 demonstrates that the classical tethered-floater mechanics formulations predict the physical orders of magnitude observed during the wave-tank trials. As discussed in Sections 3.1 and 4 of the main manuscript, the reduced-order model provides a baseline rigid-body scaling reference; additional physical phenomena documented in the tank—specifically plate-bending curling and rope pretension settling in the tension-guide case—account for higher experimental excursions beyond idealized rigid-body response.

Performance Metric	Classical Model Scale	Experimental Value	Statistical 95% MBB CI
Tension-Guide: Mean drift (cm)	~ 0.5 – 1.5	1.34	[1.31, 1.38]
Tension-Guide: 95th-pct drift (cm)	~ 1.0 – 2.0	1.93	[1.82, 2.06]
Tension-Guide: RMS heading (deg)	< 1.0°	0.63°	[0.59°, 0.66°]
Distributed-Mod.: Mean drift (cm)	~ 0.4 – 0.8	0.60	[0.59, 0.60]
Distributed-Mod.: 95th-pct drift (cm)	~ 0.8 – 1.2	1.02	[0.99, 1.05]
Distributed-Mod.: RMS heading (deg)	< 0.5°	0.37°	[0.34°, 0.37°]

Section S2. Experimental Kinematic Motion Analysis and Resampling Formulations

Platform kinematics were tracked using an overhead CMOS video camera (1920 × 1080 pixels at 30 fps) calibrated against an orthogonal metric reference grid. At each discrete sample interval k = 1, 2, ..., N (where N = 360 at Δt = 5.0 s intervals over 30 min), instantaneous centroid coordinates (xk, yk) and heading angle ψk were extracted.

Translational excursion from the reference position (x0, y0) is evaluated as the 2D Euclidean radial drift (Eq. S9), and rotational stability is quantified by RMS heading deviation (Eq. S10):

$$r_k = \sqrt{(x_k - x_0)^2 + (y_k - y_0)^2}, \bar{r} = \frac{1}{N}\sum_{k=1}^{N} r_k \tag{S9}$$

$$\psi_{\text{rms}} = \sqrt{\frac{1}{N}\sum_{k=1}^{N}(\psi_k - \psi_0)^2} \tag{S10}$$

To evaluate within-run sampling uncertainty while accounting for serial autocorrelation in the wave-tank series, the Moving Block Bootstrap (MBB) (Künsch, 1989; Liu and Singh, 1992) was applied. The sample autocorrelation function at lag τ is defined as:

$$\hat{\rho}(\tau) = \frac{\sum_{k=1}^{N-\tau}(r_k - \bar{r})(r_{k+\tau} - \bar{r})}{\sum_{k=1}^{N}(r_k - \bar{r})^2} \tag{S11}$$

To avoid premature truncation from zero-crossings in oscillatory records, the block length L^* was determined from the magnitude envelope criterion as implemented in supplementary_calculations.py:

$$L^* = \min\left\{\tau \geq 1 : |\hat{\rho}(\tau)| < 0.05\right\} \cdot \Delta t \tag{S12}$$

For the tension-guide series, autocorrelation decayed inside 0.05 at lag 33 (L* = 165 s). For the distributed-modular series, low-amplitude periodic oscillations in drift remained above 0.05 across the 200-sample window; following supplementary_calculations.py, the search ceiling of 200 samples (L* ≥ 1000 s) was adopted as a conservative lower-bound block length. Resampling B = 5,000 bootstrap replicates characterized within-run sampling uncertainty under the stationarity assumption of the 30-min trial.

Section S3. Supplementary Wave-Tank Centroid Trajectories and Spatial Density

Figure S1 illustrates the two-dimensional spatial trajectory and hexbin sample density distributions of the floating mat centroid recorded over the complete 30-minute instrumented wave-tank runs (360 samples at 0.2 Hz). The plots are generated directly from the experimental datasets (TensionGuide.csv and DistributedModular.csv). The distributed-modular configuration exhibits tight spatial clustering centered within approximately ±1.0 cm of the reference position. In contrast, the tension-guide configuration exhibits wider excursions spanning up to ±2.3 cm in both longitudinal and lateral coordinates.




Figure S1. Two-dimensional horizontal centroid trajectories and spatial sample density distributions recorded during the 30-minute instrumented wave-tank trials under matched wave forcing (H = 4 cm, f = 1.0 Hz) for: (left) Tension-guide anchoring configuration; (right) Distributed-modular anchoring configuration. Color intensity represents the number of recorded position samples per spatial bin (0.2 Hz downsampled series). Axes share identical, symmetric scales (–2.5 cm to +2.5 cm) across both panels to permit direct visual comparison of lateral and longitudinal excursions.

Section S4. Public Code and Dataset Availability Summary

All software tools, data processing routines, raw time-series datasets, and dynamic screening models associated with this study are permanently hosted in a public GitHub repository to support reproducibility:

• Repository URL: https://github.com/abishekkafle/Floating-mat-tracking-

• Open-Source Software Components:

1. ftw_reduced_order_model.py: Standalone Python script solving the 3-DOF surge–sway–yaw equations of motion and computing radial drift integrals.
2. blue_hex_mat_tracker.py: OpenCV-based overhead video tracking pipeline for 2D centroid (x, y) and heading (ψ) extraction.
3. supplementary_calculations.py: Automated analysis pipeline computing radial drift, RMS heading, Moving Block Bootstrap (MBB) 95% confidence intervals, and convergence diagnostics.
4. plot.py: Production plotting script generating publication-quality figures (Figure 3, Figure 4, and Figure S1) using Wong (2011) colorblind-safe palettes.
5. FTW_Parametric_Design_Tool/: Lightweight Python screening tool estimating draft, freeboard, metacentric height, wind drag, and tether loading.

• Data Records Provided:

1. TensionGuide.csv: Complete 30-min time series of centroid coordinates (x, y, r), heading (ψ), and line tensions at 0.2 Hz (360 samples).
2. DistributedModular.csv: Complete 30-min time series for the distributed-modular configuration (360 samples).

3. results.json: Summary point estimates, autocorrelation block lengths, and bootstrap confidence intervals.

Supplementary References

[S1] O. M. Faltinsen, Sea Loads on Ships and Offshore Structures, Cambridge University Press, Cambridge, UK, 1990.

[S2] J. N. Newman, Marine Hydrodynamics, MIT Press, Cambridge, MA, 1977.

[S3] H. Maruo, The drift of a body floating in waves, J. Ship Res. 4 (1960) 1–10.

[S4] H. R. Künsch, The jackknife and the bootstrap for general stationary observations, Ann. Statist. 17 (1989) 1217–1241.

[S5] R. Y. Liu, K. Singh, Moving blocks jackknife and bootstrap capture weak dependence, in: R. LePage, L. Billard (Eds.), Exploring the Limits of Bootstrap, John Wiley & Sons, New York, 1992, pp. 225–248.

[S6] B. Wong, Points of view: Color blindness, Nat. Methods 8 (2011) 441. doi:10.1038/nmeth.1618.