

# SOC Use Case Investigation Report

## UC-001: Brute Force Detection (SOC L1 Workflow)

**Author: Abishek V**

**Date: 22 January 2026**

**Series: SOC Use Case Playbook Series (50 Use Cases)**

### Purpose

This report documents a complete SOC L1 approach for handling a brute force alert: how it is detected, triaged, investigated, classified (TP/BTP/FP), and documented using a structured playbook.

<b>Environment Type</b>	Home SOC Lab (VirtualBox VMs)
<b>Log Sources</b>	Windows Security Logs + Sysmon (optional)
<b>SIEM View</b>	SIEM-style triage + evidence checklist
<b>Target OS</b>	Windows 10 (victim endpoint)
<b>Attacker OS</b>	Kali Linux

*This document is written in SOC operational style for portfolio and investigation practice.*

## 1 Use Case Summary

**Use Case ID:** UC-001  
**Use Case Name:** Detecting Brute Force Attacks  
**Category:** Authentication / Account Attack  
**SOC Tier:** L1 (Alert triage + investigation + escalation)  
**Severity Guideline:** Medium → High (based on account type and success login)

**Short description:** A brute force alert triggers when a single account (or multiple accounts) receives repeated failed login attempts within a short time window. The L1 objective is to quickly determine if this is user error/noise or a real attack attempt, and most importantly confirm whether the attacker succeeded.

## 2 Scenario (Lab Story)

To keep this investigation realistic, the following lab scenario was used:

- **Victim endpoint:** Windows 10 VM
- **Endpoint user:** clair
- **Attacker machine:** Kali Linux VM
- **Attacker username:** kali

### Lab IP Addressing (Trusted internal range)

- Windows 10 endpoint: 192.168.56.110
- Kali attacker: 192.168.56.120
- SIEM/Log collector: 192.168.56.100 (optional)

**SOC note:** Even though this is a lab, the same checklist applies in production. Brute force alerts are high-volume alerts in SOC, so the investigation must be fast, evidence-driven, and documented clearly.

## 3 Telemetry and Evidence Requirements

### 3.1 Primary telemetry

- **Windows Security Event Logs**

### 3.2 Key Windows Event IDs

**4625** Failed logon attempt  
**4624** Successful logon  
**4740** Account locked out (if policy exists)

### 3.3 Evidence expected during brute force

Typical evidence seen during brute force investigation:

- A burst of **4625** events within a few minutes
- Common source IP repeatedly attempting authentication

- Same username targeted OR multiple usernames targeted (spray)
- Potential lockouts if account policy is configured

## 4 Detection Logic (How the Alert is Triggered)

### 4.1 Detection objective

Generate an alert when failed logins exceed a threshold within a short time window.

### 4.2 Simple SOC threshold baseline

- **10 failed logins within 5 minutes** for a normal user
- **5 failed logins within 5 minutes** for privileged/admin accounts

### 4.3 What the SOC alert should include

- Target username: `clair`
- Source IP: `192.168.56.120`
- Target host: `192.168.56.110`
- Failure count + time range
- Logon type + failure reason/status (if available)

## 5 SOC L1 Playbook (Step-by-step Analyst Workflow)

This section documents the exact L1 flow used to handle the alert.

### 5.1 Phase A: Triage (2–5 minutes)

1. Open the brute force alert and confirm:
  - alert timestamp
  - number of failed attempts
  - user/host/IP included in the alert
2. Check for duplication:
  - verify if there is already an open ticket for the same user/IP/time window
3. Quick risk judgement:
  - Is the target an admin/service account?
  - Is the target a server/DC?
  - Is the source internal or external?

### 5.2 Phase B: Investigation (10–20 minutes)

#### Step 1: Attack pattern identification

- If a single user is targeted: brute force attempt
- If many users are targeted: password spraying (higher risk)

#### Step 2: Success check (mandatory)

This is the most important step.

- Search for **4624 (successful logon)** after the burst of 4625 failures.

- If a 4624 exists after failures, treat this alert as **potential compromise** and escalate.

### Step 3: Source validation

- Validate the source IP: 192.168.56.120
- Confirm whether source is:
  - known internal system / scanner (benign)
  - unknown internal workstation (suspicious)
  - external address (suspicious)

### Step 4: Impact confirmation

- Confirm if the account was locked (4740)
- Confirm whether attempts stopped naturally or continued
- Check whether other accounts were attacked from same IP

## 6 Quick Evidence Timeline (Example)

Time (IST)	Event ID	Entity	Observation
09:42:10	4625	clair 192.168.56.120	/ Failed logon attempt begins
09:42:10– 09:44:55	4625 (x28)	clair 192.168.56.120	/ Burst of failed logons (high frequency)
09:45:01	4740	clair	Account lockout (policy enabled)
09:45:20	–	–	Attempts stopped after lockout

**Outcome (This run):** No successful login (4624) was observed after the failed attempts. Based on the evidence, the activity was classified as **True Positive (Brute Force attempt)** but **no confirmed compromise**.

## 7 False Positive / Benign Checklist

Before closing, L1 must validate common benign reasons:

- user typing wrong password repeatedly
- password manager using an old password
- cached credentials repeatedly failing (email/mobile client)
- internal scanner activity

## 8 Verdict Criteria

### 8.1 True Positive (TP)

- High-volume 4625 failures in short window
- Repeat attempts from same source
- No legitimate reason identified

## 8.2 Benign True Positive (BTP)

- confirmed scanner/test activity OR confirmed user behaviour with supporting evidence

## 8.3 Critical escalation condition

If a **4624 success** appears after the failed attempts, L1 should escalate immediately as suspected account compromise.

## 9 SOC Response Actions (Recommended)

In a real SOC environment, the recommended actions include:

- block the attacking source IP at firewall/VPN (if external and confirmed malicious)
- reset password for the impacted user (**clair**)
- enforce MFA on the account
- review exposure: RDP/VPN portals, lockout policy, password policy

## 10 Ticket Documentation (SOC Notes Template)

**Ticket Title:** UC-001 Brute Force Attempts – user **clair** – src 192.168.56.120

**Severity:** Medium (elevate to High if admin/service account targeted)

**Verdict:** True Positive (attempted brute force)

**Compromise status:** Not confirmed (no 4624 success observed)

### Example analyst notes (human SOC style)

- Observed 28 failed logon attempts (Event ID 4625) targeting user **clair** from source IP 192.168.56.120 within approximately 3 minutes.
- Reviewed for successful logons (Event ID 4624) after the failure burst; none identified.
- Account lockout observed (Event ID 4740). Attempts stopped after lockout.
- Classified as brute force attempt. Recommended password reset and MFA enforcement.

*End of Report — UC-001*