

```

-----
ok    connected

PS C:\Users\ADMIN\Downloads\KITCHEN---APP-main\KITCHEN---APP-main\kitchen-app> kubectl scale deployment api-deployment -n kitchen-app --replicas=3
deployment.apps/api-deployment scaled
deployment.apps/web-ui-deployment scaled
PS C:\Users\ADMIN\Downloads\KITCHEN---APP-main\KITCHEN---APP-main\kitchen-app> kubectl get pods -n kitchen-app
NAME                                READY   STATUS    RESTARTS   AGE
api-deployment-64f4fb86db-fwbq4     1/1     Running   0           90m
api-deployment-64f4fb86db-q54ql     1/1     Running   0           90m
api-deployment-64f4fb86db-r6brq     1/1     Running   0           6m55s
api-deployment-88b576666-mv7js      0/1     ImagePullBackOff  0           43m
mongodb-0                            1/1     Running   0           166m
web-ui-deployment-54b84559d9-4x5vt  1/1     Running   0           18m
web-ui-deployment-54b84559d9-fwz54  1/1     Running   0           9m32s
web-ui-deployment-54b84559d9-lvsnq  1/1     Running   0           19m
PS C:\Users\ADMIN\Downloads\KITCHEN---APP-main\KITCHEN---APP-main\kitchen-app> kubectl get pods -n kitchen-app
NAME                                READY   STATUS    RESTARTS   AGE
api-deployment-64f4fb86db-fwbq4     1/1     Running   0           90m
api-deployment-64f4fb86db-q54ql     1/1     Running   0           90m
api-deployment-64f4fb86db-r6brq     1/1     Running   0           7m16s
api-deployment-88b576666-mv7js      0/1     ImagePullBackOff  0           44m
mongodb-0                            1/1     Running   0           166m
web-ui-deployment-54b84559d9-4x5vt  1/1     Running   0           19m
web-ui-deployment-54b84559d9-fwz54  1/1     Running   0           9m53s
web-ui-deployment-54b84559d9-lvsnq  1/1     Running   0           19m
PS C:\Users\ADMIN\Downloads\KITCHEN---APP-main\KITCHEN---APP-main\kitchen-app>

```

The screenshot shows the Visual Studio Code interface with the following details:

- Explorer:** Displays the project structure for 'kitchen-app'. Key files include `deployment.yaml`, `web-ui.yaml`, `Dockerfile`, `nginx.conf`, and `index.html`.
- Output:** Shows the Docker build logs for the image `kitchen-web-ui-v3`. The logs indicate the build is successful, with the image exported and ready for deployment.
- Terminal:** Contains the command `docker build -t kitchen-web-ui-v3 .` and its output, showing the build progress and the final image ID.
- Status Bar:** Indicates the build is complete and the image is ready to be pushed.

```
apiVersion v1 • web-ui.yaml | api-deployment.yaml | deployment.yar x +
File Edit View
matchLabels:
  app: kitchen-web-ui
template:
  metadata:
    labels:
      app: kitchen-web-ui
  spec:
    containers:
      - name: kitchen-web-ui
        image: kitchen-web-ui:v3 # <-- your custom image for rolling update
        ports:
          - containerPort: 80
        volumeMounts:
          - name: web-ui-config
            mountPath: /etc/nginx/conf.d/default.conf
            subPath: nginx.conf
          - name: web-ui-config
            mountPath: /usr/share/nginx/html/index.html
            subPath: index.html
    livenessProbe:
      httpGet:
        path: /health
        port: 80
      initialDelaySeconds: 10
    readinessProbe:
      httpGet:
        path: /health
        port: 80
Ln 180, Col 22 | 6,116 characters | Plain text | 100% | Unix (LF) | UTF-8
```

The screenshot shows the Visual Studio Code interface with a Kubernetes deployment manifest open in the editor. The manifest is a Deployment named 'kitchen-web-ui' in the 'kitchen-app' namespace. It specifies a rolling update strategy and includes liveness and readiness probes. The terminal window shows the command 'kubectl get deployment -n kitchen-app' and the output of the deployment status. The status indicates that the deployment is 'Terminated' with an 'Error' reason. The 'kubectl get deployment' command output is as follows:

```
k8s > web-ui > ! deployment.yaml > {} spec > {} ports > {} > # nodePort
175 apiVersion: v1
PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS GITLINS
Last State: Terminated
Reason: Error
Exit Code: 255
Started: Sat, 28 Mar 2026 13:29:31 +0530
Finished: Sat, 28 Mar 2026 15:37:17 +0530
Ready: True
Restart Count: 1
Limits:
  cpu: 500m
  memory: 256Mi
Requests:
  cpu: 100m
  memory: 128Mi
Liveness: http-get http://:3000/health delay=20s timeout=3s period=15s #success=1 #failure=5
Readiness: http-get http://:3000/ready delay=0s timeout=3s period=10s #success=1 #failure=6
Environment:
  PORT: <set to the key 'PORT' of config map 'api-config'> Optional: false
  MONGO_URI: <set to the key 'mongo-uri' in secret 'mongodb-secret'> Optional: false
Mounts:
  /app/server.js from api-server-override (no, path="server.js")
  /var/run/secrets/kubernetes.io/serviceaccount from kube-api-access-rvt89 (ro)
Conditions:
  Type Status
  PodReadyToStartContainers True
  Initialized True
  Ready True
  ContainersReady True
  PodScheduled True
Volumes:
  api-server-override:
    Type: ConfigMap (a volume populated by a ConfigMap)
    Name: api-server-override
    Optional: false
  kube-api-access-rvt89:
```

