

CodeCheck Report: trainingTKUK4Q-VB5

Test Name:

[Check out Codility training tasks](#)

Summary Timeline

Tasks summary

Task	Time spent	Score
SparseBinaryDecomposition Python	28 min	100%

Total score



Tasks Details

Hard	1.	Task Score	Correctness	Performance	
	SparseBinaryDecomposition Decompose int into sum of ints having no consecutive 1s in binary form.				
			100%	100%	100%

Task description

A non-negative integer N is called *sparse* if its binary representation does not contain two consecutive bits set to 1. For example, 41 is sparse, because its binary representation is "101001" and it does not contain two consecutive 1s. On the other hand, 26 is not sparse, because its binary representation is "11010" and it contains two consecutive 1s.

Two non-negative integers P and Q are called a *sparse decomposition* of integer N if P and Q are sparse and $N = P + Q$.

For example:



- 8 and 18 are a sparse decomposition of 26 (binary representation of 8 is "1000", binary representation of 18 is "10010");
- 9 and 17 are a sparse decomposition of 26 (binary representation of 9 is "1001", binary representation of 17 is "10001");
- 2 and 24 are not a sparse decomposition of 26; though $2 + 24 = 26$, the binary representation of 24 is "11000", which is not sparse.

Write a function:


```
def solution(N)
```

that, given a non-negative integer N , returns any integer that is one

Solution

Programming language used:	Python	
Total time used:	28 minutes	
Effective time used:	28 minutes	
Notes:	<i>not defined yet</i>	

Task timeline



Code: 12:04:39 UTC, py, final, [show code in pop-up](#)
score: 100

```
1 # you can write to stdout for debugging purposes
2 # print("this is a debug message")
3
4 def solution(N):
5     # Implement your solution here
```

part of a sparse decomposition of N. The function should return -1 if there is no sparse decomposition of N.

For example, given N = 26 the function may return 8, 9, 17 or 18, as explained in the example above. All other possible results for N = 26 are 5, 10, 16 and 21.

Write an **efficient** algorithm for the following assumptions:

- N is an integer within the range [0..1,000,000,000].

Copyright 2009–2023 by Codility Limited. All Rights Reserved. Unauthorized copying, publication or disclosure prohibited.

```
6      pass
7      a = N & 0x55555555
8      b = N & 0xAAAAAAAA
9
10     if (a + b == N):
11         return a
12
13     return -1
```

Analysis summary

The solution obtained perfect score.

Analysis

Detected time complexity:

O(log(N)) or
O(1)

expand all	Example tests
▶ example1 example test n=26	✓ OK
expand all	Correctness tests
▶ simple1 n=1166	✓ OK
▶ simple2 n=561892	✓ OK
▶ simple3 n=1031	✓ OK
▶ small_power_of_two_minus_on e n=1023	✓ OK
▶ extreme n <= 5	✓ OK
expand all	Performance tests
▶ medium1 n=74901729	✓ OK
▶ medium2 n=216188401	✓ OK
▶ power_of_two_minus_one n=536870911	✓ OK
▶ big_random n=~1000000000	✓ OK
▶ maximal n=1000000000	✓ OK