

This report may contain inaccuracies. Please verify the information independently.

Adversarial Attacks Against Discrete-Time Tracking Neural Networks with Known Affine Input Transformations: Methods, Vulnerabilities, and Defenses

Quick Reference

Key Findings Table

Theme/Methodology	Key Insights	Supporting Citations
Gradient-based attacks (affine/frequency-aware)	Affine-invariant estimators, EOT, and frequency-domain perturbations improve transferability and robustness	1 2 3 4
Black-box/transfer-based attacks	More practical for real-time, but less effective than white-box; transferability is a major challenge	5 6 7 8
Affine transformations as defense	Can restore adversarial examples, but adaptive attacks (EOT, ensemble) can circumvent; trade-off with accuracy	9 10 11
Temporal consistency in attacks/defenses	Temporal-consistent perturbations improve stealth and effectiveness; temporal defenses can restore performance	12 13 14 15
Hybrid/iterative/genetic attack strategies	Combining iterative, genetic, and temporal methods yields robust, transferable attacks under affine transforms	1 16 17
Frequency-domain analysis	Frequency-aware attacks/defenses target specific bands; low-frequency perturbations are stealthier	3 18 19
Architectural factors (robustness/vulnerability)	Dense connectivity, attention, and noise sources enhance robustness; temporal mechanisms have dual roles	12 15 20 21

Direct Answer

The most effective adversarial attack methods against discrete-time tracking neural networks with known affine input transformations combine affine-invariant gradient-based techniques (such as affine-invariant gradient estimators and Expectation Over Transformation), frequency-domain perturbations, and temporal consistency strategies. Hybrid

approaches that merge iterative gradient methods with genetic algorithms and temporal perturbation techniques are particularly promising, as they balance attack effectiveness with the real-time constraints of tracking models and maintain robustness under affine transformations applied to the input space. Black-box attacks, while more practical for real-time applications, require sophisticated transferability enhancements to approach the effectiveness of white-box attacks in this context [1](#) [2](#) [3](#) [5](#) [16](#).

Study Scope

- **Time Period:** Focus on research from the past 5–7 years, with emphasis on recent advances (2020–2024).
- **Disciplines:** Machine learning, computer vision, adversarial machine learning, neural network security, signal processing.
- **Methods:** Meta-analysis of empirical studies, theoretical reviews, and synthesis of attack/defense strategies for discrete-time tracking neural networks under affine input transformations.

Assumptions & Limitations

- Most findings are empirical; rigorous theoretical frameworks for adversarial robustness under affine and temporal transformations are limited.
- Real-time constraints and black-box settings are underexplored compared to white-box, static-image scenarios.
- The interplay between spatial (affine) and temporal consistency is complex and not fully characterized in current literature.
- Defense strategies often trade off clean accuracy for robustness, and adaptive attacks can circumvent many transformation-based defenses.

Suggested Further Research

- Develop unified frameworks integrating spatial affine invariance and temporal consistency for both attacks and defenses.
- Explore scalable, adaptive attack strategies effective in black-box, real-time tracking scenarios.
- Advance theoretical analysis of adversarial robustness in dynamic, temporally correlated input spaces.
- Investigate hybrid defense mechanisms combining affine transformations, adversarial training, and temporal regularization.

1. Introduction

Adversarial attacks pose a significant threat to the reliability of neural networks, especially in safety-critical applications such as autonomous vehicles, surveillance, and robotics. Discrete-time tracking neural networks, which process sequential data to track objects or signals over time, are particularly vulnerable due to their reliance on both spatial and temporal information. The use of affine transformations (e.g., translation, rotation, scaling) in input preprocessing or as part of the data pipeline introduces additional complexity, as these transformations can both obscure and reveal vulnerabilities to adversarial manipulation.

Understanding how adversarial attacks exploit or circumvent known affine input transformations in discrete-time tracking neural networks is crucial for developing robust models and effective defenses. This report systematically

reviews state-of-the-art attack methods, analyzes the impact of affine transformations, and synthesizes insights on architectural and temporal factors influencing robustness and vulnerability [9](#) [22](#) [23](#).

Scope and Motivation

This review focuses on adversarial attacks targeting discrete-time tracking neural networks where affine transformations of the input are known or controlled. The motivation is to bridge the gap between theoretical understanding and practical attack/defense strategies, especially in real-time and dynamic environments where both spatial and temporal consistency are critical [9](#) [22](#) [23](#).

2. Background and Core Concepts

Adversarial Attacks: Mechanisms and Taxonomy

Adversarial attacks on neural networks can be broadly categorized as follows:

- **Gradient-based attacks:** Use model gradients to craft perturbations (e.g., FGSM, PGD, iterative methods).
- **Optimization-based attacks:** Formulate adversarial example generation as an optimization problem.
- **Transfer-based attacks:** Craft adversarial examples on surrogate models for black-box transfer.
- **GAN-based and decision boundary attacks:** Use generative models or boundary exploration.
- **Physical-world attacks:** Design perturbations robust to real-world transformations.
- **Black-box attacks:** Rely on input-output queries or surrogate models, without access to gradients.
- **Poisoning attacks:** Manipulate training data to degrade model performance.

Effectiveness is typically measured by attack success rate, perturbation imperceptibility, and transferability. Limitations include dependency on model access (white-box vs. black-box), computational cost, and challenges in physical realization [22](#) [24](#) [25](#) [26](#) [27](#) [28](#) [29](#).

Affine Transformations in Neural Network Inputs

Affine transformations encompass translation, rotation, scaling, and shearing. Mathematically, they are linear mappings followed by translation, preserving points, straight lines, and planes. In neural networks, affine transformations are used for data augmentation, input normalization, and as defense mechanisms against adversarial attacks.

- **Impact:** Affine transformations can disrupt the effectiveness of adversarial perturbations, but adaptive attacks (e.g., affine-invariant estimators, EOT) can maintain attack success by explicitly modeling these transformations [1](#) [9](#) [30](#) [31](#).

Discrete-Time Tracking Neural Networks: Architectures and Applications

Discrete-time tracking neural networks process sequential data (e.g., video frames, time series) to estimate the state or position of objects over time. Key architectures include:

- **CNN-based trackers:** Use convolutional layers for spatial feature extraction.
- **Recurrent neural networks (RNNs):** Model temporal dependencies (e.g., LSTM, NARX).
- **Hybrid models:** Combine CNNs with attention mechanisms or temporal modules.

Applications span visual object tracking, robotics, and time series forecasting. Unique characteristics include sensitivity to temporal consistency, motion signals, and the need for real-time processing [20](#) [23](#) [32](#) [33](#).

3. State-of-the-Art Adversarial Attack Methods for Discrete-Time Tracking Networks

Gradient-Based and Frequency-Domain Attacks

Recent advances in gradient-based attacks for tracking networks include:

- **Affine-invariant gradient estimators:** Disentangle affine transformations and convolve gradients with derived kernels, improving robustness and transferability under affine transformations [1](#) [2](#).
- **Expectation Over Transformation (EOT):** Averages gradients over distributions of transformations, maintaining attack effectiveness against randomized defenses [10](#).
- **Frequency-domain attacks:** Target specific frequency bands (often mid-to-high) to degrade tracking performance, leveraging the fact that low-frequency components are more robust and critical for tracking [3](#) [4](#).
- **Hybrid methods:** Combine iterative gradient updates with frequency or spatial domain manipulations for improved transferability [17](#).

Effectiveness: These methods achieve high attack success rates, especially in white-box settings, and can be adapted for physical-world scenarios by ensuring perturbations are robust to affine transformations.

Limitations: Computational cost and reduced effectiveness in black-box or real-time settings remain challenges.

Black-Box and Transfer-Based Attacks in Real-Time Scenarios

- **Black-box attacks:** Use surrogate models or gradient estimation, offering greater practicality for real-time applications but generally lower success rates than white-box attacks [5](#) [6](#) [7](#) [8](#).
- **Transferability:** Crafting perturbations on surrogate models and transferring them to target models is crucial, but transferability is limited, especially against defended models.
- **Efficiency:** Black-box attacks are more computationally efficient and suitable for continuous tracking tasks, but require sophisticated strategies to approach white-box effectiveness.

Temporal and Frequency Perturbations in Tracking

- **Temporal perturbations:** Exploit motion signals and temporal consistency, which are absent in static image models, making attacks more effective and transferable in tracking scenarios [15](#).
- **Frequency analysis:** Adversarial perturbations in tracking models often concentrate in mid-to-high frequency bands, while low-frequency components are more robust and essential for performance [3](#) [4](#).
- **Detection:** Frequency decomposition and comparison of tracking performance across bands can be used to detect adversarial attacks in video sequences.

Synthesis: The integration of affine-invariant, frequency-aware, and temporally consistent attack strategies is key to effective adversarial attacks on discrete-time tracking neural networks with known affine input transformations.

4. Affine Transformations: Impact on Vulnerability and Defense

Affine Transformations as Defense Mechanisms

- **Restoration:** Affine transformations can restore adversarial examples closer to the clean data distribution, leveraging the vulnerability of adversarial examples near decision boundaries [9].
- **Randomization:** Ensembles of strong input transformations (including affine) can provide computationally efficient and resilient defenses [34].
- **Limitations:** Adaptive attacks (e.g., EOT, ensemble methods) can circumvent these defenses, especially when transformation parameters are known or can be estimated [10] [35].

Adaptive Attacks Against Affine-Based Defenses

- **Ensemble and multi-form transformations:** Adaptive attacks apply multiple random transformations to inputs, bypassing defenses relying on single or deterministic transformations [36] [37].
- **EOT:** Optimizes perturbations over distributions of transformations, effectively circumventing randomized affine input defenses [10].
- **Differentiable transformation networks:** Remain vulnerable to white-box adaptive attacks, as attackers can exploit differentiability to optimize perturbations [38].

Optimizing Affine Transformation-Based Defenses

- **Parameter tuning:** Adaptive parameter selection (e.g., Bayesian optimization) can balance robustness and accuracy [11].
- **Hybrid approaches:** Combining affine transformations with adversarial training, especially in the frequency domain, enhances robustness while minimizing accuracy loss [39].
- **Affine-invariant training:** Incorporating affine invariance in training improves defense effectiveness and transferability [1] [2].

Synthesis: While affine transformations can enhance robustness, their effectiveness is limited by adaptive attacks. Optimizing transformation parameters and integrating with other defense strategies is essential for maintaining both robustness and accuracy.

5. Architectural and Temporal Factors Influencing Robustness

Architectural Features and Adversarial Robustness

- **Dense connectivity and convolutional operations:** Improve resistance to adversarial attacks; architectures like RobNets achieve superior robustness with fewer parameters [20].
- **Attention mechanisms (Transformers):** Enhance robustness by focusing on low-frequency features, though adding high-frequency feature learning can reduce robustness [21] [40].
- **Stochastic noise sources:** In analog implementations, contribute to robustness by introducing variability that disrupts adversarial perturbations [41].
- **Model complexity:** Depth and architectural design (not just parameter count) are critical for robustness [42].

Frequency Domain Vulnerabilities and Defenses

- **High-frequency perturbations:** Are most effective but more perceptible; low-frequency perturbations are stealthier but may require more sophisticated design [18](#) [43](#).
- **Frequency-aware defenses:** Filtering or suppressing high-frequency components (e.g., bilateral filtering) can reduce vulnerability, but must preserve essential information [43](#) [44](#).
- **Frequency domain analysis:** Enables detection and purification of adversarial perturbations by preserving original spectral characteristics [45](#).

Temporal Consistency and Its Dual Role

- **Enhancing robustness:** Temporal consistency mechanisms (e.g., input-dependent randomized smoothing) can certify robustness against adversarial perturbations [12](#).
- **Introducing vulnerabilities:** Temporal dependencies can be exploited by attacks, especially gradient-based ones, necessitating careful design [46](#) [47](#).
- **Restoration:** Temporal consistency in defense mechanisms can restore and even improve tracking performance after attack [15](#).
- **Neuromorphic approaches:** Temporal encoding and early exit decoding in spiking neural networks enhance robustness [48](#).

Synthesis: Architectural choices and temporal mechanisms play a dual role, enhancing robustness but also introducing new attack surfaces. Frequency and temporal awareness are critical for both attack and defense design.

6. Novel Attack Strategies and Open Vulnerabilities

Affine-Invariant and Evolutionary Attack Methods

- **Affine Transformation Attack (ATA) and Affine Genetic Attack (AGA):** Use random affine transformations and genetic algorithms to improve attack success and robustness, especially in black-box settings [16](#).
- **Affine-invariant gradient estimators:** Disentangle geometric transformations and construct affine-invariant gradients, enhancing robustness and transferability [1](#).
- **Hybrid iterative/genetic approaches:** Combine the strengths of both methods for robust, transferable attacks under affine transformations [17](#).

Temporal Consistency in Adversarial Attacks

- **Cycle-consistent attacks:** Maximize discrepancies between forward and backward tracking, enhancing effectiveness without labeled data [14](#).
- **Uniform temporal sparsity:** Perturb key frames at consistent intervals to disrupt temporal correlations while maintaining stealth [49](#).
- **Temporal consistency losses:** Enforce smooth dynamics and reduce incoherence in adversarial examples [50](#) [51](#).

Exploiting Motion Signals and Temporal Perturbations

- **Motion signal manipulation:** Frame rate scaling, truncation, and dropping introduce temporal asynchrony, challenging tracking robustness under affine transformations [52].
- **Temporal propagation strategies:** Retain cues from initial and latest frames to improve robustness against appearance changes [53].
- **Temporal misalignment as affine transformation:** Align video sequences based on object motion, exploiting temporal affine transformations for attack [54] [55].

Synthesis: Novel attack strategies that integrate affine invariance, evolutionary optimization, and temporal consistency are highly effective against discrete-time tracking neural networks with known affine input transformations. These methods exploit both spatial and temporal vulnerabilities, challenging current defense mechanisms.

7. Discussion and Future Directions

Current Gaps and Limitations

- **Theoretical analysis:** Most studies are empirical; rigorous frameworks for adversarial robustness under affine and temporal transformations are lacking [56] [57].
- **Scalability:** Existing defenses struggle with adaptive attacks and scalability, especially in dynamic, real-time settings [58].
- **Transferability:** Black-box attacks require improved transferability to be practical in real-world applications.

Opportunities for Robustness and Attack Innovation

- **Unified frameworks:** Integrate spatial affine invariance and temporal consistency for both attacks and defenses.
- **Hybrid approaches:** Combine adversarial training, input transformations, and temporal regularization for robust defenses.
- **Frequency and temporal awareness:** Design attacks and defenses that explicitly target or protect critical frequency and temporal components.
- **Adaptive mechanisms:** Develop scalable, adaptive attack strategies effective in black-box, real-time tracking scenarios [1] [48] [58] [59].

Synthesis and Conclusion

The interplay between affine transformations and temporal consistency is central to both adversarial vulnerability and robustness in discrete-time tracking neural networks. State-of-the-art attack methods leverage affine-invariant, frequency-aware, and temporally consistent strategies, while defenses increasingly rely on optimized transformation ensembles and hybrid training. However, adaptive attacks continue to challenge the effectiveness of transformation-based defenses, and the need for scalable, theoretically grounded solutions remains pressing.

Future research should prioritize unified, adaptive frameworks that dynamically integrate spatial and temporal considerations, advancing both the science of adversarial attacks and the engineering of robust, real-time tracking systems.

References

- 1. Improving the robustness of adversarial attacks using an affine-invariant gradient estimator**
Xiang, W., Su, H., Liu, C., (...), Zheng, S.. Computer Vision and Image Understanding, 2023.
<https://doi.org/10.1016/j.cviu.2023.103647>
- 2. Black-box attacks on face recognition via affine-invariant training**
Sun, B., Su, H., Zheng, S.. Neural Computing and Applications, 2024.
<https://doi.org/10.1007/s00521-024-09543-y>
- 3. An Adversarial Detection Method Based on Tracking Performance Difference of Frequency Bands**
Zhou, Z., Sun, Y., Sun, Q., (...), Zheng, Y.. Jisuanji Yanjiu yu Fazhan/Computer Research and Development, 2025.
<https://doi.org/10.7544/issn1000-1239.202440428>
- 4. Detecting Adversarial Attacks Based on Tracking Differences in Frequency Bands**
Li, C., Li, H., Zhang, G.. IEEE Transactions on Multimedia, 2025.
<https://doi.org/10.1109/TMM.2025.3535376>
- 5. FTUAttack: Feature truncation unrestricted attack based on stable diffusion model**
Han, S., Zhai, G., Chen, K., Zhang, S.. Expert Systems with Applications, 2026.
<https://doi.org/10.1016/j.eswa.2025.129604>
- 6. Towards effective and efficient adversarial defense with diffusion models for robust visual tracking**
Xu, L., Gao, P., Tang, W.-J., (...), Yuan, R.-Y.. Information Fusion, 2025.
<https://doi.org/10.1016/j.inffus.2025.103384>
- 7. Black-box targeted adversarial attacks for deep neural networks**
Zhang, X., Geng, P., Hong, W., (...), Gu, C.. Neurocomputing, 2025.
<https://doi.org/10.1016/j.neucom.2025.131017>
- 8. Adversarial attacks on industrial soft sensors: Multi-target attacks based on diffusion models**
Jiang, Q., Fan, S., Zhu, Z., (...), Zhang, X.. Information Sciences, 2026.
<https://doi.org/10.1016/j.ins.2025.122732>
- 9. Learning defense transformations for counterattacking adversarial examples**
Li, J., Zhang, S., Cao, J., Tan, M.. Neural Networks, 2023.
<https://doi.org/10.1016/j.neunet.2023.03.008>
- 10. AdvGrid: A multi-view black-box attack on infrared pedestrian detectors in the physical world**
Tiliwalidi, K., Hu, C., Lu, G., (...), Shi, W.. Applied Soft Computing, 2025.
<https://doi.org/10.1016/j.asoc.2025.112981>
- 11. Demystifying the Adversarial Robustness of Random Transformation Defenses**
Sitawarin, C., Golan-Strieb, Z., Wagner, D.. Proceedings of Machine Learning Research, 2022.
<https://www.scopus.com/pages/publications/85138550636>
- 12. IDRS: An Input-Dependent Randomized Smoothing Method Certifying the Robustness of Temporal Link Prediction Models**
Wang, Y., Liu, Q., Wu, X., Zhang, W.. Communications in Computer and Information Science, 2025.
https://doi.org/10.1007/978-981-96-9911-7_3
- 13. A motional but temporally consistent physical video examples**
Du, Z., Wei, X., Zhang, W., (...), Liu, J.. Journal of Information Security and Applications, 2022.
<https://doi.org/10.1016/j.jisa.2022.103278>
- 14. Unsupervised cycle-consistent adversarial attacks for visual object tracking**

Yao, R., Zhu, X., Zhou, Y., (...), Zhang, Y.. Displays, 2023.

<https://doi.org/10.1016/j.displa.2023.102532>

15. Robust Deep Object Tracking against Adversarial Attacks

Jia, S., Ma, C., Song, Y., (...), Yang, M.-H.. International Journal of Computer Vision, 2025.

<https://doi.org/10.1007/s11263-024-02226-0>

16. IGAff: Benchmarking Adversarial Iterative and Genetic Affine Algorithms on Deep Neural Networks

Echim, S.-V., Preda, A.-A., Cercel, D.-C., Pop, F.. Frontiers in Artificial Intelligence and Applications, 2025.

<https://doi.org/10.3233/FAIA251199>

17. SAMI-FGSM: Towards Transferable Attacks with Stochastic Gradient Accumulation

Feng, H., Chen, Y., Huang, Y., (...), Sang, H.. Computers, Materials and Continua, 2025.

<https://doi.org/10.32604/cmc.2025.064896>

18. MWDP: Multi-view wavelet-guided diffusion purifier for robust pattern recognition

Zeng, Junpeng, Qiu, Yichun, Zhou, Guoxu. Neurocomputing, 2026.

<https://doi.org/10.1016/j.neucom.2026.133041>

19. DAD++: Improved data-free test time adversarial defense

Nayak, G.K., Khatri, I., Randive, S., (...), Chakraborty, A.. Neurocomputing, 2025.

<https://doi.org/10.1016/j.neucom.2025.129453>

20. When NAS Meets Robustness: In Search of Robust Architectures against Adversarial Attacks

Guo, M., Yang, Y., Xu, R., (...), Lin, D.. Proceedings of the IEEE Computer Society Conference on Computer Vision and Pattern Recognition, 2020.

<https://doi.org/10.1109/CVPR42600.2020.00071>

21. Certified Accuracy and Robustness: How different architectures stand up to adversarial attacks

Sarih, A.E., Aneja, N., Hong, O.W.. Intelligent Systems with Applications, 2025.

<https://doi.org/10.1016/j.iswa.2025.200555>

22. Adversarial Attacks and Defenses in Machine Learning-Empowered Communication Systems and Networks: A Contemporary Survey

Wang, Y., Sun, T., Li, S., (...), Vincent Poor, H.. IEEE Communications Surveys and Tutorials, 2023.

<https://doi.org/10.1109/COMST.2023.3319492>

23. Robust Tracking Against Adversarial Attacks

Jia, S., Ma, C., Song, Y., Yang, X.. Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics), 2020.

https://doi.org/10.1007/978-3-030-58529-7_5

24. Adversarial Attacks on Neural Networks

Pranjal, Vaishnavi, Divyansh, (...), Agarwal, A.K.. Lecture Notes in Networks and Systems, 2024.

https://doi.org/10.1007/978-981-97-3594-5_34

25. Towards Adversarial Learning: From Evasion Attacks to Poisoning Attacks

Wang, W., Xu, H., Wan, Y., (...), Tang, J.. Proceedings of the ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, 2022.

<https://doi.org/10.1145/3534678.3542608>

26. Survey of Adversarial Attacks and Defense Methods for Deep Neural Networks

Zhao, H., Chang, Y.-K., Wang, W.-J.. Computer Science, 2022.

<https://doi.org/10.11896/jsjx.210900163>

27. Adversarial Attacks and Defenses: Frontiers, Advances and Practice

Xu, H., Li, Y., Jin, W., Tang, J.. Proceedings of the ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, 2020.

<https://doi.org/10.1145/3394486.3406467>

28. A Comprehensive Review of Adversarial Attacks and Defense Strategies in Deep Neural Networks

Abomakhelb, A., Abd Jalil, K.A., Buja, A.G., (...), Alenezi, A.M.. Technologies, 2025.

<https://doi.org/10.3390/technologies13050202>

29. Adversarial Deep Learning: A Survey on Adversarial Attacks and Defense Mechanisms on Image Classification

Khamaiseh, S.Y., Bagagem, D., Al-Alaj, A., (...), Alomari, H.W.. IEEE Access, 2022.

<https://doi.org/10.1109/ACCESS.2022.3208131>

30. On the Robustness of Convolutional Neural Networks Regarding Transformed Input Images

Timme, F., Kerdels, J., Peters, G.. International Joint Conference on Computational Intelligence, 2020.

<https://doi.org/10.5220/0010107203960403>

31. On the robustness of convolutional neural networks regarding transformed input images

Timme, F., Kerdels, J., Peters, G.. IJCCI 2020 - Proceedings of the 12th International Joint Conference on Computational Intelligence, 2020.

<https://www.scopus.com/pages/publications/85107271882>

32. On generation of adversarial sequences for recurrent neural networks in classification and forecasting

, Chaber, B.. 2025 26th International Conference on Computational Problems of Electrical Engineering, CPEE 2025, 2025.

<https://doi.org/10.1109/CPEE67905.2025.11236758>

33. On the Resiliency of an Analog Memristive Architecture against Adversarial Attacks

Paudel, B.R., Pentsos, V., Tragoudas, S.. Proceedings - International Symposium on Quality Electronic Design, ISQED, 2022.

<https://doi.org/10.1109/ISQED54688.2022.9806277>

34. Evaluating Input Transformation Ensembles Against Adversarial Attacks

Liu, C., DiValentin, L., Ding, A., Salem, M.B.. Communications in Computer and Information Science, 2026.

https://doi.org/10.1007/978-3-031-89518-0_5

35. Random heterogeneous spiking neural network for adversarial defense

Wang, J., Zhao, D., Du, C., (...), Zeng, Y.. iScience, 2025.

<https://doi.org/10.1016/j.isci.2025.112660>

36. Efficient physical image attacks using adversarial fast autoaugmentation methods

Du, X., Pun, C.-M., Zhou, J.. Knowledge-Based Systems, 2024.

<https://doi.org/10.1016/j.knosys.2024.112576>

37. Exploring transferable and robust adversarial perturbation generation across network hierarchy

Wang, R., Guo, Y., Yang, R., Wang, Y.. Neurocomputing, 2024.

<https://doi.org/10.1016/j.neucom.2024.128620>

38. Diversity-enhanced reconstruction as plug-in defenders against adversarial perturbations

Pang, Zeshan, Yan, Xuehu, Guo, Shasha, Lu, Yuliang. Frontiers in Artificial Intelligence, 2025.

<https://doi.org/10.3389/frai.2025.1665106>

39. FreqAT: An Adversarial Training Based on Adaptive Frequency-Domain Transform

Zhang, D., Liang, Y., Huang, Q., (...), Zeng, L.. Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics), 2025.

https://doi.org/10.1007/978-981-96-0850-8_19

40. On the Adversarial Robustness of Vision Transformers

Shao, R., Shi, Z., Yi, J., (...), Hsieh, C.-J.. Transactions on Machine Learning Research, 2022.

<https://www.scopus.com/pages/publications/105000077186>

41. The inherent adversarial robustness of analog in-memory computing

Lammie, C., Büchel, J., Vasilopoulos, A., (...), Sebastian, A.. Nature Communications, 2025.

<https://doi.org/10.1038/s41467-025-56595-2>

42. Unmasking the Vulnerabilities of Deep Learning Models: A Multi-Dimensional Analysis of Adversarial Attacks and Defenses

Juraev, F., Abuhamad, M., Chan-Tin, E., (...), AbuHmed, T.. 2024 Silicon Valley Cybersecurity Conference, SVCC 2024, 2024.

<https://doi.org/10.1109/SVCC61185.2024.10637364>

43. Explainable AI-guided test-time adversarial defense for resilient YOLO detectors in Industrial Internet of Things

Ma, R., Ying, Z., Li, W., (...), Liu, H.. Future Generation Computer Systems, 2026.

<https://doi.org/10.1016/j.future.2025.108356>

44. LPF-Defense: 3D adversarial defense based on frequency analysis

Naderi, Hanieh, Noorbakhsh, Kimia, Etemadi, Arian, Kasaei, Shohreh. PLoS ONE, 2023.

<https://doi.org/10.1371/journal.pone.0271388>

45. APDMs: Adversarial purification diffusion models for automatic modulation classification

Zhang, H., Ding, W., Zhang, D., (...), Chen, B.. Signal Processing, 2026.

<https://doi.org/10.1016/j.sigpro.2025.110249>

46. Leveraging Vulnerabilities in Temporal Graph Neural Networks via Strategic High-Impact Assaults

Jeon, D.H., Zhu, L., Li, H., (...), Niu, S.. CIKM 2025 - Proceedings of the 34th ACM International Conference on Information and Knowledge Management, 2025.

<https://doi.org/10.1145/3746252.3761282>

47. Spatio-temporal data fusion for adversarially resilient graph neural networks in construction progress management

Mostofi, F., Toğan, V., Tokdemir, O.B.. Advanced Engineering Informatics, 2026.

<https://doi.org/10.1016/j.aei.2025.104019>

48. Neuromorphic computing paradigms enhance robustness through spiking neural networks

Ding, J., Yu, Z., Liu, J.K., Huang, T.. Nature Communications, 2025.

<https://doi.org/10.1038/s41467-025-65197-x>

49. DSAA: Cross-modal transferable double sparse adversarial attacks from images to videos

Han, X., Zhang, S., Wang, H., Tian, Q.. Neurocomputing, 2025.

<https://doi.org/10.1016/j.neucom.2025.130212>

50. CSNF-TimeGAN: Class-prior spatiotemporal nonlinear feature-based time series generative adversarial network for blast furnace fault diagnosis

Yang, Y., Yang, C., Lou, S., (...), Wang, W.. Advanced Engineering Informatics, 2026.

<https://doi.org/10.1016/j.aei.2025.104213>

51. Visual tracking by matching points using diffusion model

Alansari, Mohamad, Ganapathi, Iyyakutti Iyappan, Alansari, Sara, (...), Javed, Sajid. Alexandria Engineering Journal, 2025.

<https://doi.org/10.1016/j.aej.2025.06.042>

52. A histogram transformer approach using attention-based 3D residual network for human action recognition

Sun, Maojin, Sun, Luyi. PLoS ONE, 2025.

<https://doi.org/10.1371/journal.pone.0333893>

53. Joint target and background temporal propagation for aerial tracking

Lei, X., Cheng, W., Xu, C., Yang, W.. ISPRS Journal of Photogrammetry and Remote Sensing, 2024.

<https://doi.org/10.1016/j.isprsjprs.2024.03.022>

54. Statistical Methods on Special Manifolds for Image and Video Understanding

Turaga, Pavan, Chellappa, Rama, Srivastava, Anuj. Handbook of Statistics, 2013.

<https://doi.org/10.1016/B978-0-444-53859-8.00007-2>

55. Temporal synchronization of non-overlapping videos using known object motion

Brito, D.N., Pádua, F.L.C., Pereira, G.A.S., Carceroni, R.L.. Pattern Recognition Letters, 2011.

<https://doi.org/10.1016/j.patrec.2010.02.011>

56. Feedback-Control Based Adversarial Attacks on Recurrent Neural Networks

Deka, S.A., Stipanović, D.M., Tomlin, C.J.. Proceedings of the IEEE Conference on Decision and Control, 2020.

<https://doi.org/10.1109/CDC42340.2020.9303949>

57. Dynamically Computing Adversarial Perturbations for Recurrent Neural Networks

Deka, S.A., Stipanović, D.M., Tomlin, C.J.. IEEE Transactions on Control Systems Technology, 2022.

<https://doi.org/10.1109/TCST.2022.3165980>

58. Disruptive attacks on artificial neural networks: A systematic review of attack techniques, detection methods, and protection strategies

Alobaid, A., Bonny, T., Alrahhal, M.. Intelligent Systems with Applications, 2025.

<https://doi.org/10.1016/j.iswa.2025.200529>

59. Deep Learning Model Defense Against Manipulative Adversarial Attacks: An Investigation on Adversarial Robustness Techniques

Nirmaladevi, K., Karkuzhali, S., Hency Juliet, A.H., (...), Syambabu, V.. 2025 Global Conference in Emerging Technology, GINOTECH 2025, 2025.

<https://doi.org/10.1109/GINOTECH63460.2025.11076809>