

UML Diagrams Training

Creating Professional System Designs

Learn to create Use Case, Sequence, and Class Diagrams through practical banking system examples



Use Case Diagram

Shows system functionality from user perspective



Sequence Diagram

Illustrates object interactions over time



Class Diagram

Defines system structure and relationships

Learning Objectives

By the end of this session, you will be able to:

- ☒ Create comprehensive Use Case diagrams showing actors and system boundaries
- ☒ Design Sequence diagrams that capture object interactions and message flows
- ☒ Develop Class diagrams with proper relationships and attributes
- ☒ Apply UML best practices for clear and professional diagrams
- ☒ Analyze requirements and translate them into visual system designs

Today's Approach

Step 1: Learn with guided example (Account Management)


Step 2: Practice independently (Transactions)

Step 3: Review and discuss solutions

Use Case Diagram - Account Management

Requirements Analysis:


- 1.1 View account balances
- 1.2 Check transaction history
- 1.3 Update personal information
- 1.4 Manage account settings



Use Case Diagram

Please use 'option handwritten true' to enable handwritten

Account Management Use Cases



Key Components:

Actor: Customer (external entity)

Use Cases: System functionalities

System Boundary: Defines scope of the banking system



Classroom Assignment

Quick Exercise (5 minutes)

Individual Task:

On paper, identify and list:

- 1 additional actor for this system
- 2 extend/include relationships you can add
- 1 system boundary issue you notice

Pair Discussion:

Compare with your neighbor:

- Which actors did you identify?
- What relationships make sense?
- Any missing use cases?

I AM A WORK IN PROGRESS





Use Case Exercise - Solutions

Additional Actors Identified:

- **Bank Administrator** - Manages system settings
- **Audit System** - Logs all transactions
- **Notification Service** - Sends alerts

System Boundary Issues:

Issue: AccountSettings appears disconnected

Solution: Should be associated with Account class or integrated within "Manage Account Settings" use case

Extend/Include Relationships:

View Account Balance

├─ «include» → Authenticate User
└─ «extend» → Show Account Details

Update Personal Information

├─ «include» → Authenticate User
├─ «include» → Validate Data
└─ «extend» → Send Confirmation Email


Manage Account Settings

├─ «include» → Authenticate User
└─ «extend» → Update Security Questions

💡 **Key Insight:** «include» = mandatory steps, «extend» = optional features

Sequence Diagram - View Account Balance

Scenario: Customer views their account balance



Sequence Diagram Elements:

Actors/Objects: Customer, Web Interface, Account Controller, Database

Messages: Arrows showing communication flow

Lifelines: Vertical dashed lines showing object existence

Time Flow: Top to bottom chronological order



Classroom Assignment



Hands-on Exercise (8 minutes)

Step 1 (3 min): Trace the Flow

Follow the sequence and write down:

- What happens if authentication fails?
- What if database is unavailable?
- Where would you add error handling?

Step 2 (5 min): Extend the Diagram

Sketch on paper - add to this sequence:

- Session timeout check
- Account locked scenario
- Audit logging step



Think Like a Developer: Consider edge cases and error paths - these are often missing in initial designs!

I AM A WORK IN PROGRESS





Sequence Exercise - Solutions

Error Scenarios & Solutions:

Authentication Failure:

```
Customer → Web Interface : Login Request
Web Interface → Controller : Authenticate
Controller → Database : Validate User
Database → Controller : User Invalid ✗
Controller → Web Interface : Login Failed
Web Interface → Customer : Show Error Message
Web Interface → Customer : Redirect to Login
```

Database Unavailable:

```
Controller → Database : Query Balance
Database -X Controller : Connection Timeout ✗
Controller → Web Interface : Service Unavailable
Web Interface → Customer : "Try Again Later"
Controller → Logging : Log Error Event
```



Sequence Exercise - Solutions

Extended Sequence with Enhancements:


```
Customer → Web Interface : Login Request
Web Interface → SessionManager : Check Session Timeout ✨
SessionManager → Web Interface : Session Valid
Web Interface → Controller : Authenticate
Controller → Database : Validate User
alt [Account Locked] ✨
Database → Controller : Account Locked Status
Controller → Web Interface : Account Locked Error
Web Interface → Customer : Contact Support Message
else [Account Active]
Database → Controller : User Valid
Controller → AuditLogger : Log Login Success ✨
Controller → Web Interface : Login Success
end
Web Interface → Customer : Show Dashboard
```




Best Practice: Always plan for failure scenarios - they're 50% of real-world system behavior!



Sequence Exercise - Solutions



Class Diagram - Account Management System



Class Diagram - Account Management System

Class Diagram Relationships:

Composition (◆): Customer owns Accounts (strong relationship)

Association (→): Customer has Transactions

Multiplicity: 1..* (one to many relationships)

Design Challenge (10 minutes)

Individual Task (5 min):

Design on paper:

- Add inheritance to Account class (Savings, Checking)
- Create a SecurityQuestion class
- Define relationships between all classes

Code Thinking (5 min):

Based on your diagram, write:


- Class declaration for SavingsAccount
- Constructor with proper inheritance
- One unique method for each account type



Programming Connection: Notice how UML directly translates to code structure in C++, Python, C#, or Java!

✓ Class Exercise - Solutions

Enhanced Class Diagram with Inheritance:





Class Exercise - Solutions

Code Implementation Examples:

Java/C# Style:

```
public class SavingsAccount extends Account {
    private double interestRate;

    public SavingsAccount(String accountId,
        double initialBalance,
        double rate) {
        super(accountId, initialBalance);
        this.interestRate = rate;
    }

    public double calculateInterest() {
        return getBalance() * interestRate;
    }
}
```

Python Style:

```
class CheckingAccount(Account):
    def __init__(self, account_id, initial_balance,
        overdraft_limit):
        super().__init__(account_id, initial_balance)
        self.overdraft_limit = overdraft_limit

    def check_overdraft(self, amount):
        available = self.balance + self.overdraft_limit
        return amount <= available

    def withdraw(self, amount):
        if self.check_overdraft(amount):
            super().withdraw(amount)
        else:
            raise InsufficientFundsError()
```

 **Architecture Insight:** Notice how inheritance in UML directly maps to object-oriented programming concepts across all languages!

UML Best Practices & Guidelines

✓ Do's

- Use clear, descriptive names
- Keep diagrams simple and focused
- Show only relevant details
- Use consistent notation
- Include multiplicity in relationships
- Validate with stakeholders

✗ Don'ts

- Don't overcomplicate diagrams
- Avoid crossing lines when possible
- Don't mix abstraction levels
- Don't ignore naming conventions
- Don't create diagrams without purpose
- Don't skip documentation

Diagram Selection Guide:

Use Case Diagrams: For requirements gathering and system scope definition

Sequence Diagrams: For detailed interaction flows and API design

Class Diagrams: For system architecture and database design



Classroom Assignment

Peer Review Exercise (7 minutes)

Step 1 (3 min): Review Partner's Work

- Check their previous exercises
- Identify 2 strengths in their diagrams
- Spot 1 improvement opportunity

Step 2 (4 min): Apply Best Practices

- Discuss naming conventions used
- Check relationship clarity
- Evaluate diagram completeness

 **Focus Areas:** Look for missing actors, unclear relationships, or overly complex structures

Pro Tip:

Start with Use Case diagrams to understand requirements, then create Class diagrams for structure, and finally Sequence diagrams for complex interactions.



Peer Review Exercise - Solutions

Common Issues Found & Solutions:

✗ Common Problems:

- **Missing Actors:** Forgot Admin, External APIs
- **Vague Use Cases:** "Process Request" instead of "Transfer Money"
- **Wrong Relationships:** Used association instead of composition
- **Inconsistent Naming:** Mixed camelCase and snake_case
- **Over-complexity:** Too many details in one diagram

✓ Ideal Solutions:

- **Complete Actors:** Customer, Admin, Payment Gateway, Notification Service
- **Specific Use Cases:** Action-oriented verb phrases
- **Correct Relationships:** Composition for ownership, inheritance for "is-a"
- **Consistent Style:** Choose one naming convention and stick to it
- **Right Level:** Focus on one aspect per diagram

Best Practice Checklist Applied:

Criteria	Poor Example	Good Example
Use Case Naming	✗ "Handle Money"	✓ "Transfer Money Between Accounts"
Class Attributes	✗ "data: Object"	✓ "balance: Double"
Sequence Messages	✗ "doSomething()"	✓ "validateUser(credentials)"

🎯 Key Insight from Peer Review:

The best diagrams tell a clear story that any team member can understand. If you need to explain your diagram extensively, it probably needs simplification!



Classroom Exercise

Your Turn: Create UML Diagrams for Transactions

Requirements - Transactions Module:

- 2.1 Transfer money between accounts
- 2.2 Pay bills online
- 2.3 Send money to other users
- 2.4 Schedule recurring payments

Assignment Tasks:

1. Use Case Diagram

- Identify actors (Customer, Bank System, External Payment Gateway)
- Define use cases from the requirements
- Show system boundaries

2. Sequence Diagram

- Choose: "Transfer money between accounts"
- Show: Customer, UI, TransferController, Account, Database
- Include: Validation, balance checks, transaction processing

3. Class Diagram

- Design: Transaction, Transfer, BillPayment, RecurringPayment classes
- Show: Attributes, methods, relationships
- Consider: Inheritance and composition

 Time Allocation: 45 minutes total (15 minutes per diagram)

Apply all the techniques and best practices from the previous exercises!

Summary & Next Steps

What We've Learned:

-  Created Use Case diagrams to capture functional requirements
-  Designed Sequence diagrams to show interaction flows
-  Built Class diagrams to define system structure
-  Applied UML best practices for professional diagrams



Key Takeaways

- UML diagrams are communication tools
- Start simple, add complexity gradually
- Different diagrams serve different purposes
- Consistency is crucial for team collaboration



Next Steps

- Practice with real project requirements
- Explore UML tools (Lucidchart, Draw.io)
- Study advanced UML diagram types
- Join architecture design reviews

Questions & Discussion

Ready to discuss your Transaction module designs?

Share your diagrams and let's review the solutions together!

ER Diagrams Training

ER Diagrams Training

Database Design & Data Modelling

Master Entity-Relationship diagrams for robust database design
through practical banking system examples



Real-world objects that store data



Connections between entities



Properties that describe entities

Learning Objectives

By the end of this session, you will be able to:

-  Identify entities, attributes, and relationships from business requirements
-  Create comprehensive ER diagrams with proper cardinality notation
-  Design normalized database schemas from ER diagrams
-  Apply ER modeling best practices for scalable database design
-  Transform requirements into logical and physical data models

Today's Database Design Journey

Step 1: Learn ER fundamentals with Account Management example

Step 2: Practice with guided exercises and solutions

Step 3: Design complete data model for Transactions module

Step 4: Convert ER diagrams to actual database tables

Why ER Diagrams Matter:

Good database design is the foundation of every successful application. ER diagrams help you visualize data relationships before writing a single line of SQL!

ER Diagram Fundamentals

Entities

Customer

Account

Transaction

Nouns that represent real-world objects or concepts

Relationships

owns

performs

belongs_to

Verbs that describe associations between entities

Attributes

customer_id

first_name

balance

Properties that describe entities

Cardinality Notation:

One-to-One (1:1)

Customer ——— Profile

Each customer has exactly one profile

One-to-Many (1:M)

Customer ———< Account

One customer can have multiple accounts

Many-to-Many (M:N)

Account >——< Service

Accounts can use multiple services

ER Diagram - Account Management System

Requirements Analysis:


- 1.1 View account balances
- 1.2 Check transaction history
- 1.3 Update personal information
- 1.4 Manage account settings

Entity-Relationship Diagram



ER Diagram - Account Management System

Entity-Relationship Diagram



ER Diagram Key Elements:

PK: Primary Key (unique identifier)

FK: Foreign Key (references another table)

Cardinality: 1:M relationships between Customer-Account, Account-Transaction

Normalization: Profile and Settings separated to avoid data redundancy



Classroom Exercise

Database Analysis Exercise (8 minutes)

Step 1 (4 min): Entity Analysis

For each entity, identify:

- Which attributes could be NULL?
- What data types would you choose?
- Any composite attributes to break down?

Step 2 (4 min): Relationship Validation

Check the design:

- Are all foreign keys properly placed?
- Any missing relationships?
- Could any M:N relationships exist?

 **Think SQL:** Consider how this ER diagram would translate to CREATE TABLE statements in your database!

I AM A WORK IN PROGRESS





Database Analysis Exercise - Solutions

Entity Analysis - Data Types & Constraints:

CUSTOMER Table Design:

```
CREATE TABLE Customer (  
  customer_id INT PRIMARY KEY AUTO_INCREMENT,  
  first_name VARCHAR(50) NOT NULL,  
  last_name VARCHAR(50) NOT NULL,  
  email VARCHAR(100) UNIQUE NOT NULL,  
  phone_number VARCHAR(20),  
  address TEXT,  
  date_joined TIMESTAMP DEFAULT CURRENT_TIMESTAMP  
);
```

Nullable: phone_number, address (optional info)

Constraints: email UNIQUE, names NOT NULL

ACCOUNT Table Design:

```
CREATE TABLE Account (  
  account_id INT PRIMARY KEY AUTO_INCREMENT,  
  customer_id INT NOT NULL,  
  account_type ENUM('SAVINGS', 'CHECKING', 'CREDIT') NOT  
  NULL,  
  balance DECIMAL(15,2) DEFAULT 0.00,  
  date_created TIMESTAMP DEFAULT CURRENT_TIMESTAMP,  
  is_active BOOLEAN DEFAULT TRUE,  
  FOREIGN KEY (customer_id) REFERENCES  
  Customer(customer_id)  
);
```

DECIMAL(15,2): Handles large amounts with 2 decimal precision

ENUM: Restricts account types to valid values



Database Analysis Exercise - Solutions

Relationship Validation - Issues & Fixes:

Potential Issue	Analysis	Solution
Composite Address	Should address be broken down?	Yes - street, city, state, zip for better queries
Transaction Categories	Missing transaction categorization	Add category_id FK to Transaction table
Account Joint Ownership	Current design: 1 customer per account	Create AccountHolder junction table for M:N

Enhanced ER Model:

Additional Entities Identified:

TransactionCategory - For expense tracking and reporting

AccountHolder - Junction table for joint accounts

Address - Normalized address components

Database Insight: Real banking systems often have 50+ tables - start simple and normalize as requirements grow!

Database Normalisation & ER Best Practices

✓ Normalization Benefits

- Eliminates data redundancy
- Reduces storage space
- Prevents update anomalies
- Ensures data consistency
- Improves data integrity
- Facilitates maintenance

✗ Design Pitfalls

- Over-normalization (too many joins)
- Under-normalization (data duplication)
- Missing foreign key constraints
- Inappropriate data types
- Ignoring performance implications
- No indexing strategy

✗ Unnormalized (0NF)

```
CUSTOMER_ACCOUNT
├ customer_id
├ customer_name
├ customer_email
├ account_numbers (1001,1002)
├ account_types (Savings,Checking)
├ balances (5000.00,1500.00)
└ transaction_history (long text)
```

Issues: Repeating groups, composite values

⚠ Second Normal Form (2NF)

```
CUSTOMER_ACCOUNT
├ customer_id (PK) └ account_id (PK)
├ customer_name └ customer_id (FK)
├ customer_email └ account_type
├ phone └ balance
└ date_created

TRANSACTION
├ transaction_id (PK)
├ account_id (FK)
├ amount
└ date
```

Better: Separated entities, atomic values

✓ Third Normal Form (3NF)

```
CUSTOMER_ACCOUNT
├ customer_id (PK) └ account_id (PK)
├ first_name └ customer_id (FK)
├ last_name └ account_type_id (FK)
├ email └ balance
└ phone └ date_created

ACCOUNT_TYPE TRANSACTION
├ type_id (PK) └ transaction_id (PK)
├ type_name └ account_id (FK)
├ description └ transaction_type_id (FK)
├ min_balance └ amount
└ transaction_date

TRANSACTION_TYPE
├ type_id (PK)
├ type_name
└ description
```

Ideal: No transitive dependencies

Advanced ER Modeling Concepts

Recursive Relationships

Entity relates to itself

```
EMPLOYEE
├ employee_id (PK)
├ manager_id (FK → employee_id)
├ name
└ position
```

Associative Entities

M:N relationships with attributes


```
ACCOUNT ↔ ACCOUNT_SERVICE ↔ SERVICE
├ start_date
├ end_date
└ service_fee
```

Weak Entities

Depends on strong entity for existence

```
ACCOUNT === ACCOUNT_STATEMENT
(strong) (weak - double border)
├ account_id └ account_id (FK)
├ balance └ statement_month
└ statement_year
```

Inheritance in ER Diagrams (ISA Hierarchy):





Classroom Exercise

🎯 Advanced Modeling Exercise (12 minutes)

Step 1 (6 min): Design Challenge

Model a university system with:

- Students taking multiple courses
- Professors teaching courses
- Course prerequisites
- Student grades per course

Step 2 (6 min): Implementation

Include in your design:

- 1 recursive relationship
- 1 associative entity
- 1 weak entity
- Proper normalization (3NF)

💡 **Think Complex:** Real systems have multiple relationship types - practice identifying them all!

I AM A WORK IN PROGRESS




✓ Advanced Modeling Exercise - Solutions

University System - Complete ER Model:




Advanced Concepts Applied:

- **Recursive Relationship:** PREREQUISITE table (course requires other courses)
- **Associative Entity:** ENROLLMENT (M:N with additional attributes)
- **Weak Entity:** COURSE_SCHEDULE (depends on COURSE for existence)
- **3NF Compliance:** No transitive dependencies



✓ Advanced Modeling Exercise - Solutions

SQL Implementation:



```
-- Recursive relationship
CREATE TABLE Prerequisite (
  course_id INT,
  prerequisite_id INT,
  required_grade CHAR(2),
  PRIMARY KEY (course_id, prerequisite_id),
  FOREIGN KEY (course_id) REFERENCES Course(course_id),
  FOREIGN KEY (prerequisite_id) REFERENCES Course(course_id)
);

-- Weak entity with composite key
CREATE TABLE Course_Schedule (
  course_id INT,
  schedule_id INT,
  semester VARCHAR(10),
  year INT,
  time_slot VARCHAR(20),
  room_number VARCHAR(10),
  PRIMARY KEY (course_id, schedule_id),
  FOREIGN KEY (course_id) REFERENCES Course(course_id)
);
```

Architecture Insight: Notice how complex business rules are elegantly captured through relationship design and constraints!

Summary & Next Steps

What We've Mastered:

-  Entity identification and attribute design
-  Relationship modeling with proper cardinalities
-  Database normalization to 3NF
-  Advanced concepts: weak entities, inheritance, recursive relationships
-  SQL implementation from ER designs

Key Takeaways

- ER diagrams bridge business requirements and database implementation
- Good normalization prevents future headaches
- Cardinality modeling is critical for data integrity
- Performance considerations guide design decisions

Next Steps

- Practice with real project requirements
- Explore ER tools (ERDPlus, Lucidchart, Draw.io)
- Study database optimization techniques
- Learn NoSQL data modeling patterns

From ER to Code:

Your ER diagrams directly inform ORM configurations in frameworks like Hibernate (Java), Entity Framework (C#), SQLAlchemy (Python), and Sequelize (JavaScript). Master ER modeling, and database programming becomes much more intuitive!

API Specs Planning with Swagger

Concept vs. Contract

REST API vs. OpenAPI Specification



REST API

An **architectural style** that defines principles for designing web services that are scalable, stateless, and uniform.

- ✓ Architectural principles & constraints
- ✓ Stateless communication
- ✓ Resource-based URLs
- ✓ HTTP methods (GET, POST, PUT, DELETE)
- ✓ Cacheable responses



OpenAPI Specification

A **documentation standard** that provides a machine-readable contract describing how your API works in detail.

- ✓ API documentation format
- ✓ Endpoint definitions
- ✓ Request/response schemas
- ✓ Authentication methods
- ✓ Code generation capabilities

💛 They Work Together, Not Against Each Other

REST provides the *design philosophy* and architectural principles, while OpenAPI provides the *detailed specification* that documents and describes your REST API implementation.



REST = Architecture Style

Like architectural principles for building design (e.g., "modern minimalist")



OpenAPI = Blueprint


Like detailed construction blueprints showing exact specifications and measurements

Key Takeaway: You can have a REST API without OpenAPI documentation, but OpenAPI helps make your REST API more discoverable, testable, and maintainable.

API Specs Planning with Swagger

From Use Cases to Production-Ready API Documentation

Using OpenAPI Specification & Swagger Toolchain



Training Objective

Learn to convert business use cases into well-structured API specifications systematically

OpenAPI Specification (OAS) format and **Swagger tools** for documentation, testing, and code generation, following industry best practices for REST API design.

Note: OpenAPI = Specification format | Swagger = Toolchain (Swagger UI, Swagger Editor, Swagger Codegen)

Step 1: Use Case Analysis

Given Use Case: Account Management

- **1.1 View account balances** - Read operation
- **1.2 Check transaction history** - Read with filtering
- **1.3 Update personal information** - Update operation
- **1.4 Manage account settings** - CRUD operations

Analysis Framework

For each use case, identify:

-  **Data entities** involved
-  **CRUD operations** needed
-  **Security requirements**
-  **Input/output parameters**
-  **Error scenarios**

Resource Identification

Account Balances

Transaction History

Personal Info

Account Settings

Step 2: REST Endpoint Design

GET /api/v1/accounts/{accountId}/balance

Purpose: View account balances (Use case 1.1)

GET /api/v1/accounts/{accountId}/transactions

Purpose: Check transaction history (Use case 1.2)

Query params: startDate, endDate, limit, offset

PUT /api/v1/users/{userId}/profile

Purpose: Update personal information (Use case 1.3)

GET /api/v1/accounts/{accountId}/settings

Purpose: Manage account settings (Use case 1.4 - Read)

PUT /api/v1/accounts/{accountId}/settings

Purpose: Manage account settings (Use case 1.4 - Update)

Step 3: Data Models & Schemas

Account Balance Model

```
{
  "AccountBalance": {
    "type": "object",
    "properties": {
      "accountId": {
        "type": "string",
        "example": "acc_123456789"
      },
      "accountType": {
      },
      "balance": {
      },
      "currency": {
      },
      "lastUpdated": {
      },
      "required": [
        "accountId",
        "balance",
        "currency"
      ]
    }
  }
}
```

Transaction Model

```
{
  "Transaction": {
    "type": "object",
    "properties": {
      "transactionId": {
      },
      "amount": {
      },
      "description": {
        "type": "string",
        "example": "ATM Withdrawal"
      },
      "date": {
      },
      "category": {
      },
      "balance": {
      }
    }
  }
}
```

Best Practices for Schema Design

- Use descriptive property names
- Include examples for better documentation
- Specify required fields explicitly
- Use appropriate data types and formats
- Consider validation constraints

Step 4: Complete OpenAPI Specification (for Swagger)

This YAML/JSON spec will be consumed by Swagger tools

```
{
  "openapi": "3.0.3",
  "info": {
    "servers": [
      {
        "url": "https://api.bank.com/v1",
        "description": "Production server"
      }
    ],
    "security": [
      "paths": {
        "components": {
          "schemas": {
            "AccountBalance": {
              "type": "object",
              "properties": {
                "required": [
              }
            },
          },
          "securitySchemes": {
        }
      }
    ]
  }
}
```



Complete_OpenAI_Spec.json

Step 5: Swagger Tools for Testing & Validation

Swagger UI - Interactive Documentation

Swagger UI automatically generates:

-  Interactive API documentation
-  Built-in testing interface
-  Live request/response examples
-  Schema validation
-  Try-it-out functionality

Swagger Codegen

Generate code in multiple languages:

-  **Python:** Flask, FastAPI, Django
-  **Java:** Spring Boot, JAX-RS
-  **C#:** ASP.NET Core
-  **C++:** REST SDK, Qt5 Client
-  Client SDKs for all platforms

Swagger Editor

-  Real-time spec editing
-  Syntax validation
-  Error highlighting
-  Live preview

Validation Checklist

-  Swagger Editor validates syntax
-  All use cases mapped to endpoints
-  HTTP methods align with operations
-  Request/response schemas defined
-  Error responses documented
-  Security requirements specified

Swagger-Powered Development Workflow

Write OpenAPI Spec



Swagger Editor



Swagger UI



Swagger Codegen



Implementation

Tools URLs: editor.swagger.io | swagger.io/tools/swagger-ui | swagger.io/tools/swagger-codegen



Classroom Exercise

Your Task: Design API Specs for Transactions Use Case

Use Case 2: Transactions

- **2.1 Transfer money between accounts** - Internal transfer
- **2.2 Pay bills online** - External payment
- **2.3 Send money to other users** - P2P transfer
- **2.4 Schedule recurring payments** - Automated payments

Requirements:

- Design REST endpoints for each sub-use case
- Define appropriate data models/schemas in OpenAPI format
- Include request/response examples
- Consider error scenarios
- Add security considerations
- **Bonus:** Test your spec in Swagger Editor (editor.swagger.io)

Time: 25 minutes

Deliverable: OpenAPI YAML specification ready for Swagger tools

Tip: Use Swagger Editor for real-time validation while writing your spec

Show Solution



Exercise Solution

Endpoint Design

POST /api/v1/transfers/internal

Transfer money between accounts (2.1)

POST /api/v1/payments/bills

Pay bills online (2.2)

POST /api/v1/transfers/p2p

Send money to other users (2.3)

POST /api/v1/payments/recurring

Schedule recurring payments (2.4) - Create

GET /api/v1/payments/recurring

Get scheduled payments (2.4) - List



Exercise Solution

Sample Complete Spec for Swagger Tools

```
[
  "openapi": "3.0.3",
  "info": {
    "title": "Banking API - Transactions",
    "description": "Transaction management endpoints for Swagger tools",
    "version": "1.0.0"
  },
  "servers": [
  ],
  "paths": {
  },
  "components": {
  },
  "security": [
    {
      "bearerAuth": []
    }
  ]
]
```

 **Pro Tip:** Copy this spec to editor.swagger.io to see live documentation, test endpoints, and generate client code in C++, Python, Java, or C#!

Appendix

System Design Training

System Design Training

Hands-on Deliverables

-  Draw High-Level Architecture
-  Design DB Schema for Key Entities
-  Draft REST Endpoints

Training Objective

Learn to design complete system architectures through practical examples, starting with Account Management and practicing with Transactions use case.

Example Use Case: Account Management


1. Account Management

- **1.1 View account balances** - Display current balances across all accounts
- **1.2 Check transaction history** - Show chronological list of past transactions
- **1.3 Update personal information** - Modify user profile and contact details
- **1.4 Manage account settings** - Configure preferences and security settings

We'll design:


- ✓ High-level architecture for this banking system
- ✓ Database schema for accounts, users, and transactions
- ✓ REST API endpoints for all account management operations

High-Level Architecture



Key Components:

- **API Gateway:** Routes requests, handles authentication
- **Account Service:** Core business logic for account operations
- **Database:** Stores user accounts, transactions, settings
- **Monitoring:** Tracks system health and user activity



Database Schema Design

users

user_id (PK) - UUID
email - VARCHAR(255)
first_name - VARCHAR(100)
last_name - VARCHAR(100)
phone - VARCHAR(20)
date_of_birth - DATE
created_at - TIMESTAMP
updated_at - TIMESTAMP

accounts

account_id (PK) - UUID
user_id (FK) - UUID
account_number - VARCHAR(20)
account_type - ENUM
balance - DECIMAL(15,2)
status - ENUM
created_at - TIMESTAMP
updated_at - TIMESTAMP

transactions

transaction_id (PK) - UUID
account_id (FK) - UUID
amount - DECIMAL(15,2)
transaction_type - ENUM
description - VARCHAR(255)
status - ENUM
created_at - TIMESTAMP

user_settings

setting_id (PK) - UUID
user_id (FK) - UUID
setting_key - VARCHAR(100)
setting_value - TEXT
updated_at - TIMESTAMP

REST API Endpoints

Account Balance Operations

GET /api/v1/accounts/{accountId}/balance
Get current account balance

GET /api/v1/users/{userId}/accounts/balances
Get balances for all user accounts

Personal Information

GET /api/v1/users/{userId}/profile
Get user profile information

PUT /api/v1/users/{userId}/profile
Update user profile information

Transaction History

GET /api/v1/accounts/{accountId}/transactions?page=1&limit=20
Get paginated transaction history

GET /api/v1/transactions/{transactionId}
Get specific transaction details

Account Settings

GET /api/v1/users/{userId}/settings
Get all user settings

PUT /api/v1/users/{userId}/settings/{settingKey}
Update specific setting

REST API Endpoints

Account Balance Operations

GET /api/v1/accounts/{accountId}/balance
Get current account balance

GET /api/v1/users/{userId}/accounts/balances
Get balances for all user accounts

Personal Information

GET /api/v1/users/{userId}/profile
Get user profile information

PUT /api/v1/users/{userId}/profile
Update user profile information

Transaction History

GET /api/v1/accounts/{accountId}/transactions?page=1&limit=20
Get paginated transaction history

GET /api/v1/transactions/{transactionId}
Get specific transaction details

Account Settings

GET /api/v1/users/{userId}/settings
Get all user settings

PUT /api/v1/users/{userId}/settings/{settingKey}
Update specific setting



Classroom Exercise

Your Turn: Design the Transactions Use Case

2. Transactions

- **2.1 Transfer money between accounts** - Internal account transfers
- **2.2 Pay bills online** - Payments to external billers
- **2.3 Send money to other users** - P2P money transfers
- **2.4 Schedule recurring payments** - Automated future payments



Your Deliverables:

1. **Draw High-Level Architecture** - How will you handle different transaction types?
2. **Design DB Schema** - What new tables/fields are needed?
3. **Draft REST Endpoints** - API design for all transaction operations

💡 Think About:

- How to handle different transaction types
- Recurring payment scheduling
- External biller management
- Transaction validation and security


Solution: Transaction Architecture



Key Additions:

- **Transaction Service:** Handles transfers, bill payments, P2P
- **Scheduler Service:** Manages recurring payments
- **Transaction Queue:** Ensures reliable processing
- **External APIs:** Integration with banks and billers

Solution: Transaction Architecture



Solution: Schema & APIs

Additional Database Tables

billers

`billers_id (PK)`
`billers_name`
`billers_code`
`api_endpoint`

recurring_payments

`payment_id (PK)`
`user_id (FK)`
`amount`
`frequency`
`next_payment_date`
`status`

p2p_transfers

`transfer_id (PK)`
`sender_id (FK)`
`recipient_id (FK)`
`amount`
`status`

Key API Endpoints

POST `/api/v1/transfers/internal`
Transfer between user's own accounts

POST `/api/v1/payments/bills`
Pay bills to external billers

POST `/api/v1/transfers/p2p`
Send money to other users

POST `/api/v1/payments/recurring`
Setup recurring payment

GET `/api/v1/billers/search?query=electric`
Search available billers

Logical vs Physical Data Models

Understanding the Blueprint and Construction Plans of Database Design

A **logical data model** is a high-level, abstract representation of an organization's data, focusing on business requirements and rules. A **physical data model** is the detailed, implementation-specific representation of how that data will be physically stored in a database.

The logical model is the **what**, and the physical model is the **how**.

Key Differences

Aspect	Logical Data Model	Physical Data Model
Purpose	To define the business rules and data structures	To design the actual database schema
Audience	Business analysts, project managers, and developers	Database administrators (DBAs) and developers
Abstraction	High-level and abstract. Independent of any specific database technology	Detailed and specific. Tied to a particular DBMS like SQL Server, Oracle, or MySQL
Components	Entities, attributes, primary keys, and relationships (many-to-many, one-to-many, etc.)	Tables, columns with specific data types (VARCHAR(50), INT), foreign keys, indexes, constraints, and partitions
Flexibility	Easier to change as it's not tied to a specific implementation	More rigid and complex to change due to its direct link to the physical database structure

Logical vs Physical Data Models

Understanding the Blueprint and Construction Plans of Database Design

An Analogy: Building a House 🏠

📐 Logical Model = Architect's Blueprint

Shows the rooms (entities), what's in them like windows and doors (attributes), and how the rooms are connected (relationships). Gives a clear picture of the house's layout and function from the homeowner's perspective, without specifying the exact type of bricks or pipes to be used.

🔧 Physical Model = Contractor's Construction Plan

Details the specific materials to be used (e.g., PEX piping, 2x4 lumber), the exact measurements for each column (data types and lengths), and how everything will be physically joined together (indexes, constraints). A detailed guide for the construction crew to actually build the house.

Summary: *You start with the logical model to understand the business needs and then translate it into a physical model to create the actual database.*

Classroom Exercise

Quick Exercise (5 minutes)

Individual Task:

From "online shopping" domain, identify:

- 3 entities
- 2 relationships
- 5 attributes (include 1 primary key)

Pair Discussion:

Compare and decide:

- Which entity is central?
- What are the cardinalities?
- Any weak entities identified?

I AM A WORK IN PROGRESS



✓ ER Fundamentals Exercise - Solutions

Online Shopping Domain - Ideal Solutions:

Entities Identified:

Customer

Product

Order

Additional entities students might identify:

- Category, Cart, Payment, Shipping

Relationships & Cardinality:

places

contains

- **Customer places Order:** 1:M
- **Order contains Product:** M:N
- **Product belongs_to Category:** M:1

Attributes with Data Types:

Customer Entity:

customer_id (INT)

first_name (VARCHAR)

email (VARCHAR)

phone (VARCHAR)

date_joined (DATE)

Order Entity:

order_id (INT)

order_date (DATETIME)

total_amount (DECIMAL)

status (ENUM)

Product Entity:

product_id (INT)

product_name (VARCHAR)

price (DECIMAL)

stock_quantity (INT)

🔑 **Key Insight:** Notice how Order becomes a central entity connecting Customer and Product - this is common in transactional systems!



Classroom Exercise

Normalization Exercise (10 minutes)

Individual Task (5 min):

Given this unnormalized table, design 3NF:

```
CUSTOMER_LOAN_INFO
├ customer_id, customer_name
├ loan_id, loan_type, loan_amount
├ officer_id, officer_name, officer_phone
├ branch_id, branch_name, branch_address
└ payment_schedule
```

Group Discussion (5 min):

Identify and resolve:

- Functional dependencies
- Transitive dependencies
- Required separate entities




Programming Connection: Well-normalized databases lead to cleaner ORM mappings in your applications!

I AM A WORK IN PROGRESS



✓ Normalization Exercise - Solutions

3NF Solution for Customer Loan System:





Normalization Exercise - Solutions

Functional Dependencies Resolved:

- **customer_id → customer_name:** Separated into CUSTOMER table
- **officer_id → officer_name, officer_phone:** Separated into OFFICER table
- **branch_id → branch_name, branch_address:** Separated into BRANCH table
- **loan_id → payment_schedule:** Separated into PAYMENT_SCHEDULE table

SQL Implementation Tips:

```
-- Index for common queries
CREATE INDEX idx_customer_email ON Customer(email);
CREATE INDEX idx_loan_customer ON Loan(customer_id);
CREATE INDEX idx_payment_loan ON Payment_Schedule(loan_id);

-- Constraints for business rules
ALTER TABLE Loan ADD CONSTRAINT chk_positive_amount
CHECK (loan_amount > 0);
ALTER TABLE Payment_Schedule ADD CONSTRAINT chk_payment_date
CHECK (payment_date >= CURRENT_DATE);
```

 **Performance Note:** 3NF ensures data integrity, but consider controlled denormalization for high-traffic read operations!

Understanding the Relationships

Association, Aggregation, and Composition are three fundamental types of relationships between classes in object-oriented design. They define how objects interact with each other and the degree of their interdependence.



Association

This represents a "uses-a" relationship, where objects of one class are linked to objects of another class. The objects have their own independent lifecycles.

Analogy: A doctor and a patient. A doctor can have many patients, and a patient can see multiple doctors. They exist independently.

UML Notation: A solid line connecting the classes: —



Aggregation

This is a specialized form of association, representing a "has-a" relationship. It describes a whole-part relationship where the part can exist independently of the whole.

Analogy: A team and its players. A team has players, but a player can exist without being on that specific team.

UML Notation: A solid line with an unfilled diamond: —◇



Composition

This is a strong form of aggregation, also a "has-a" relationship. Here, the part cannot exist without the whole. The lifecycle of the part is tied to the lifecycle of the whole.

Analogy: A house and its rooms. The rooms cannot exist without the house. If the house is demolished, the rooms are also destroyed.

UML Notation: A solid line with a filled diamond: —◆

A Comparative Overview

Relationship	Analogy	Ownership	Lifecycle	UML Symbol
Association	Doctor and Patient	No ownership	Independent	—
Aggregation	Team and Players	Weak "has-a"	Independent	—◇
Composition	House and Rooms	Strong "part-of"	Dependent	—◆

Key Takeaways

- ▶ The primary distinction between these relationships lies in the **strength of the connection** and the **lifecycles of the objects**.
- ▶ **Association** is the most general relationship.
- ▶ **Aggregation** implies a whole-part relationship, but the parts can exist on their own.
- ▶ **Composition** signifies a strong whole-part relationship where the parts are dependent on the whole.
- ▶ Choosing the correct relationship is crucial for designing robust and maintainable object-oriented systems.