ABNER MARTINEZ | PORTFOLIO

Firewall scan validation: Nessus with the firewall off and on


Threat Protection and Testing | Full Sail University | March 2026

Academic coursework. All scanning was performed against isolated lab virtual machines.


Redacted for publication: IP addresses, lab hostnames and URLs, lab usernames, instructor name. Black boxes mark removed content.

Abner D. Martinez-Albizu
March 30th, 2026
CYB4381-L / Prof. Joseph [redacted]
4.4 Lab Assignment: TPT Online

Scan of Firewall Off & the vulnerabilities found (Screenshot)




Scan of Firewall On & the vulnerabilities found (Screenshot)



Any difference with the scan?


Yes, as we can see the Nessus Scan Identified only 4 Info “Vulnerabilities” when the firewall and its rules where set and turned on. Additionally, as we can see in the second screenshot when the firewall was turnoff –the Nessus Scan found: 2 Critical, 5 High, 10 Medium, 2 low and 46 Info ranging from a CVSS Score of 0.0 to 10.0.

Descriptive name for my custom rule.



Are the SMB vulnerabilities still present after the scan?

No these are not present.



What other ports cloud you block to remediate the vulnerability findings from the Nessus scan?

a. **Hint: Look at the critical vulnerabilities to identify the port Nessus scanned to find the vulnerability.**
b. **If you identified a port, repeat steps 12-18 to create a firewall rule on the Windows 7 VM and re-run a scan to validate the additional vulnerabilities found on that identified port are no longer present.**

I could block port 138 and 137 too. This is because port 137 is used for name resolution, which can allow attacks to map your network and identify specific targets by their computer names. Additionally, port 138 handles traffic browser, meaning that broadcast this machine and the OS details. Will make it easier for malware to discover and profile this vulnerable system.