



INSTITUTE
FOR
COMPUTATIONAL
ENGINEERING &
SCIENCES

aUTonomous
SYSTEMS GROUP



The University of Texas at Austin
**Electrical and Computer
Engineering**
Cockrell School of Engineering

Online Learning with Implicit Exploration in Episodic Markov Decision Processes

Mahsa Ghasemi, Abolfazl Hashemi, Haris Vikalo, Ufuk Topcu

American Control Conference (ACC)

May 26th, 2021


Sequential Decision Making



**Sequential Interaction with
the environment**




**Learning from a fixed
reward**



**Offline: access to
a lot of data**



Sequential Decision Making with Varying Tasks




**Evolving environment
and task**

**Safety-critical
operation**

**Limited feedback from
the environment**

How can we design **online algorithms** with **high probability** guarantees for **varying tasks**?


Online Learning with Implicit Exploration for Varying Tasks




Contributions:

- A novel **optimistically-biased** reward estimator for **implicit exploration**
- Policy search using **online mirror descent (OMD)**
- **Minimax optimal** regret bound with **high probability**

Adversarial Markov Decision Process (A-MDP)




Bandit feedback




Loop-free episodic A-MDP:


- States are **partitioned** into layers
- Transition only exists from **one layer to the next**




Neu et al., 2020

aaaaaa







Agent's Policy Representation via Occupancy Measure

Looking for a **time-varying stochastic** policy $\pi_t : \mathcal{S} \times \mathcal{A} \rightarrow [0, 1]$

Occupancy measure: the probability induced over state-action pairs by executing a policy


$$\rho^\pi(s, a) = \Pr(\mathbf{s}_{k(s)} = s, \mathbf{a}_{k(s)} = a | \pi)$$

Stochastic stationary policy given an occupancy measure

$$\pi^\rho(a|s) = \frac{\rho(s, a)}{\sum_{a' \in \mathcal{A}} \rho(s, a')} , \quad \forall (s, a) \in \mathcal{S} \times \mathcal{A}$$

Regret Minimization

episode t



(state, action)

task t

Unknown and time-varying loss function (A-MDP)

$$\mathcal{M} = (\mathcal{S}, \mathcal{A}, \mathcal{P}, \ell_t)$$

(loss)

Bandit feedback

$$\ell_t(s_t(k), a_t(k))$$

Learn a policy with sublinear regret:

$$\mathcal{R}_T := \max_{\pi} \mathcal{L}_T - \mathcal{L}_T(\pi)$$

best fixed policy
in hindsight

Question: Can we obtain low regret with **high probability**?

Optimistic Loss Estimator

Bandit feedback \longrightarrow Estimating the loss of all state-action pairs

Goal: Obtain a **low-variance** loss estimator

A novel **optimistically biased estimator** for the loss function:

$$\hat{\ell}_t(s, a) = \frac{\ell_t(s, a)}{\rho_t(s, a) + \gamma} \mathbb{I}\{(s, a) \in \mathbf{h}(t)\}$$

\nwarrow history at current episode
 \nwarrow exploration parameter

Optimistically biased

$$\mathbb{E} \left[\hat{\ell}_t(s, a) | \mathbf{h}(t-1) \right] \leq \ell_t(s, a)$$

\longrightarrow Implicit exploration

Policy Optimization via Online Mirror Descent

Goal: Compute a **new policy** from the estimated loss function

An **OMD algorithm** utilizing the proposed loss estimator:

$$\boldsymbol{\rho}_{t+1} = \arg \min_{\rho \in \Delta(\mathcal{M})} \left\{ \underbrace{\eta \langle \rho, \hat{\ell}_t \rangle}_{\text{loss}} + \underbrace{D(\rho \| \boldsymbol{\rho}_t)}_{\text{policy change}} \right\}$$

learning rate unnormalized KL divergence

Constrained optimization \rightarrow Two-step procedure

$$\begin{aligned} \tilde{\boldsymbol{\rho}}_{t+1} &= \arg \min_{\rho} \left\{ \eta \langle \rho, \hat{\ell}_t \rangle + D(\rho \| \boldsymbol{\rho}_t) \right\} \\ \boldsymbol{\rho}_{t+1} &= \arg \min_{\rho \in \Delta(\mathcal{M})} \left\{ D(\rho \| \tilde{\boldsymbol{\rho}}_{t+1}) \right\} \end{aligned}$$

No-Regret Learning with High-Probability

Result: Establishing sublinear regret bounds both **on expectation** and **with high-probability**

Theorem: (high-probability regret bound)

Let $\delta \in (0, 1)$. If

$$\eta = \gamma = \sqrt{L \frac{\log(|\mathcal{S}||\mathcal{A}|/L)}{2T|\mathcal{S}||\mathcal{A}|}},$$

with probability at least $1 - \delta$,

$$\text{regret} \leq \mathcal{O}(\sqrt{LT|\mathcal{A}||\mathcal{S}| \log(|\mathcal{S}||\mathcal{A}|/L)} \log \frac{1}{\delta}).$$

episode length number of episodes number of states number of actions


Minimax optimal regret (up to logarithmic terms)

Conclusion and Future Work

- Proposed an **optimistic loss estimator** for learning in episodic A-MDP under bandit feedback
- Developed an **OMD policy optimization** utilizing the proposed loss estimator
- Established a **minimax optimal** regret bound with **high probability**

Future Directions

- Parameter-free and anytime algorithms
- Unknown, time-varying dynamics and large-scale state spaces



Online Learning with Implicit Exploration in Episodic Markov Decision Processes

Mahsa Ghasemi, Abolfazl Hashemi, Haris Vikalo, Ufuk Topcu

supported in part by NSF ECCS grant 1809327, DARPA grant D19AP00004, and AFRL grant FA9550-19-1-0169