

On the Performance-Complexity Tradeoff in Stochastic Greedy Weak Submodular Optimization


Abolfazl Hashemi, Haris Vikalo, Gustavo de Veciana

International Conference on Acoustics, Speech and Signal Processing (ICASSP)

6-11 June, 2021

Supported in part by NSF ECCS grant 1809327

Subset Selection and Information Gathering




Krause et al.,
2013



Subset Selection and Information Gathering




Large amount of high-dimensional data



Subset Selection and Information Gathering



Large amount of high-dimensional data




Resource-constrained decision making



Subset Selection and Information Gathering



Large amount of high-dimensional data




Resource-constrained decision making




NP-hard, combinatorial optimization tasks




Subset Selection for Sensing Networks



Subset Selection for Sensing Networks



Subset Selection for Sensing Networks



Question

- How can we perform the selection **efficiently** and with **guaranteed performance**?

Observation Selection Criteria

Scalar functions of the predicted error **covariance matrix** $f(P_t(S))$

Observation Selection Criteria

Scalar functions of the predicted error **covariance matrix** $f(P_t(S))$

Constrained combinatorial optimization

$$\hat{S} = \arg \max_{|S| \leq k} f(S)$$

NP-hard

Krause, 2011

Observation Selection Criteria

Scalar functions of the predicted error **covariance matrix** $f(P_t(S))$

Constrained combinatorial optimization

$$\hat{S} = \arg \max_{|S| \leq k} f(S)$$


NP-hard

Krause, 2011

$f(S)$ has nice properties:

- **Monotonicity**
- **Weak-submodularity**

Hashemi et al., 2018



$$f(A \cup \{d\}) - f(A) \geq f(B \cup \{d\}) - f(B)$$

Observation Selection Criteria

Scalar functions of the predicted error **covariance matrix** $f(P_t(S))$

Constrained combinatorial optimization

$$\hat{S} = \arg \max_{|S| \leq k} f(S)$$

NP-hard

Krause, 2011

$f(S)$ has nice properties:

- **Monotonicity**
- **Weak-submodularity**

Hashemi et al., 2018


Weak-submodularity
constant $0 < \alpha \leq 1$

$$f(\hat{S}) \geq (1 - e^{-\alpha}) f(S^*)$$

Optimal approximation guarantee


Krause, 2011

Approximate
greedy solution



$$f(A \cup \{d\}) - f(A) \geq f(B \cup \{d\}) - f(B)$$


Subset Selection in Large-Scale Settings



Subset Selection in Large-Scale Settings



Reduce the space of greedy by **random sampling** Mirzasoleyman et al. 2015,
Hashemi et al. 2018




Subset Selection in Large-Scale Settings



Reduce the space of greedy by **random sampling**

Mirzasoleyman et al. 2015,
Hashemi et al. 2018



How to construct R_i




Subset Selection in Large-Scale Settings



Reduce the space of greedy by **random sampling**

Mirzasoleyman et al. 2015,
Hashemi et al. 2018



How to construct R_i



The dilemma of greedy selection with restricted search space

Greedy with a restricted search space should succeed in each iteration

A fixed schedule: chance of sampling from optimal decreases given success in prior iterations

How to Select the Schedule?

Theorem 1

Let $\mathcal{P}(m, k)$ denote a series of subset selection problems where $m, k \rightarrow \infty$, $m > k$. Let ALG denote a variant of Greedy with a restricted uniform search space $\mathcal{R}_i \subset [m]$ having cardinality r . Then:

1. Vanishing regime: $\beta \in (0, 1)$ such that $\frac{r}{m} \leq k^{\beta-1}$, then

$$\limsup_{m,k \rightarrow \infty} \Pr(\mathcal{S}_{alg}^k = \mathcal{S}^*) = 0.$$

2. Relative regime: $\beta_1 \in (0, 1)$ such that $\frac{r}{m} \leq \beta_1$, then

$$0 < \delta_1 < \limsup_{m,k \rightarrow \infty} \Pr(\mathcal{S}_{alg}^k = \mathcal{S}^*) < \delta_2 < 0.63.$$

How to Select the Schedule?

Theorem 1

Let $\mathcal{P}(m, k)$ denote a series of subset selection problems where $m, k \rightarrow \infty$, $m > k$. Let ALG denote a variant of Greedy with a restricted uniform search space $\mathcal{R}_i \subset [m]$ having cardinality r . Then:

1. Vanishing regime: $\beta \in (0, 1)$ such that $\frac{r}{m} \leq k^{\beta-1}$, then


$$\limsup_{m,k \rightarrow \infty} \Pr(\mathcal{S}_{alg}^k = \mathcal{S}^*) = 0.$$

2. Relative regime: $\beta_1 \in (0, 1)$ such that $\frac{r}{m} \leq \beta_1$, then

$$0 < \delta_1 < \limsup_{m,k \rightarrow \infty} \Pr(\mathcal{S}_{alg}^k = \mathcal{S}^*) < \delta_2 < 0.63.$$


Fixed schedules fail!

Empirical Evaluation: Sparse Linear Regression




$$r = m/\sqrt{k}$$

Empirical Evaluation: Sparse Linear Regression




$$r = m/\sqrt{k}$$

Empirical Evaluation: Sparse Linear Regression




$$r = m/\sqrt{k}$$




$$r = m/2$$

Empirical Evaluation: Sparse Linear Regression




$$r = m/\sqrt{k}$$




$$r = m/2$$

Empirical Evaluation: Sparse Linear Regression




$$r = m/\sqrt{k}$$




$$r = m/2$$

We need **increasing** $\{r_i\}$ that **ultimately grows to** $r_{i_m} = m$

Empirical Evaluation: Sparse Linear Regression




$$r = m/\sqrt{k}$$



$$r = m/2$$

We need **increasing** $\{r_i\}$ that **ultimately grows to** $r_{i_m} = m$

Progressive Stochastic Greedy



Theorem 2

Let \mathcal{S}_{psg} denote the random subset selected by PSG. Then,




$$\mathbb{E}[f(\mathcal{S}_{psg})] \geq (1 - e^{-\alpha} - \alpha\epsilon^\eta) f(\mathcal{S}^*),$$

where $\eta = 1 + \mathcal{O}(1/k)$.

Applications in Clustering



Almost zero
performance
gap




Order of
magnitude
faster

Conclusion and Future Work

- **Asymptotic conditions** for identification of the optimal subset in stochastic greedy weak submodular maximization
- A **fixed** schedule **fails**, an **increasing** schedule **for high success probability**
- **PSG**: a new scheme with **near-optimal expected approximation factor**

Future Directions

- High probability guarantees vs expected guarantees
- Extensions to continuous weak submodular functions



On the Performance-Complexity Tradeoff in Stochastic Greedy Weak Submodular Optimization

Abolfazl Hashemi, Haris Vikalo, Gustavo de Veciana

Supported in part by NSF ECCS grant 1809327