

Airbus A320neo

Guide - Checklist & Procedures for Microsoft Flight Simulator 2024

by ChatGPT v1.0

Weight

Max Ramp Weight	79,400 kg (175,047 lb)
Max Takeoff Weight	79,000 kg (174,165 lb)
Max Landing Weight	67,400 kg (148,591 lb)
Max Zero Fuel Weight	64,300 kg (141,757 lb)
Typical Fuel Capacity	~6,300 US gal / 23,860 L

Dimensions

Wingspan	35.80 m (117.45 ft)
Length	37.57 m (123.27 ft)
Height	11.76 m (38.58 ft)
Typical Seats	150-180
Maximum Seating	194

Performance

Range	3,400 NM / 6,300 km
Maximum Operating Speed	M 0.82
Typical Cruise	M 0.78
Service Ceiling	39,800 ft
Engines	CFM LEAP-1A / PW1100G

Speeds / Limitations

VFE CONF 1	230 KIAS	VFE CONF 1+F	215 KIAS
VFE CONF 2	200 KIAS	VFE CONF 3	185 KIAS
VFE FULL	177 KIAS	VLE	280 KIAS / M0.67
VLO Extension	250 KIAS	VLO Retraction	220 KIAS
VMO/MMO	350 KIAS / M0.82	Green Dot	FMS calculated
S/F Speeds	FMS calculated	VAPP	FMS PERF APPR

NORMAL PROCEDURES

PREFLIGHT

PREFLIGHT INSPECTION	COMPLETED
PARKING BRAKE	SET
BAT 1 / BAT 2	ON
EXT PWR / APU	AS REQUIRED
ADIRS	NAV
FUEL QUANTITY	CHECK
OXYGEN	TEST
SIGNS	ON/AUTO
MCDU / INIT	COMPLETE
FLIGHT PLAN	ENTERED
PERF DATA	SET
BARO REF	SET
WINDOWS / DOORS	CLOSED

BEFORE START

COCKPIT PREP	COMPLETED
ACARS INIT	COMPLETED
GEAR PINS & COVERS	REMOVED
BEACON	ON
THRUST LEVERS	IDLE
PARKING BRAKE	AS REQUIRED
TRANSPONDER	AS REQUIRED
APU BLEED	ON
FUEL PUMPS	ON
ANTI-COLLISION LIGHT	ON

ENGINE START

ENGINE MODE SELECTOR	IGN/START
ENGINE 2 MASTER	ON
N2 RISE	MONITOR
ENG 2 AVAIL	CHECK
ENGINE 1 MASTER	ON
N2 RISE	MONITOR
ENG 1 AVAIL	CHECK
ENGINE MODE SELECTOR	NORM
APU BLEED	OFF
APU MASTER	OFF
ANTI-ICE	AS REQUIRED
ECAM STATUS	CHECK

BEFORE TAXI

PITCH TRIM	SET
RUDDER TRIM	ZERO
FLAPS	TAKEOFF CONFIG
SPOILERS	ARM
AUTO BRAKE	MAX
T.O. CONFIG	TEST / NORM
GROUND EQUIPMENT	CLEAR
TAXI LIGHT	ON
PARKING BRAKE	RELEASED
BRAKES	CHECK
FLIGHT CONTROLS	CHECKED

Airbus A320neo

Guide - Checklist & Procedures for Microsoft Flight Simulator 2024

by ChatGPT v1.0

BEFORE TAKEOFF

FLIGHT CONTROLS	CHECKED
FLIGHT INSTRUMENTS	CHECKED
BRIEFING	CONFIRMED
FLAP SETTING	CONFIRM
V1 / VR / V2 / FLEX TEMP	ANNOUNCE
ATC / TRANSPONDER	SET
ECAM MEMO	TO NO BLUE
CABIN CREW	ADVISED
TAKEOFF RUNWAY	CONFIRMED

NORMAL TAKEOFF

CHRONO	START
THRUST LEVERS	FLEX/MCT or TOGA
ENGINE INSTRUMENTS	CHECK
FMA	CHECK
V1	MONITOR
VR	ROTATE
PITCH ATTITUDE	15 deg target
POSITIVE RATE	GEAR UP
AP ABOVE 100 ft AGL	AS REQUIRED

CLIMB

THRUST REDUCTION ALT	CLB DETENT
ACCELERATION ALT	PITCH / SPEED
FLAPS	RETRACT ON S/F
LANDING GEAR	UP
PACKS	ON
BARO REF above TRANS ALT	STD
ECAM	MONITOR
SEAT BELTS	AS REQUIRED

CRUISE

FMA / NAV	MONITOR
ECAM MEMO	MONITOR
FUEL	MONITOR
PROGRESS PAGE	CHECK
RADAR / ANTI-ICE	AS REQUIRED

DESCENT

APPROACH BRIEFING	COMPLETE
FMGS ARRIVAL / APPR	SET
RAD NAV / LS	AS REQUIRED
QNH DESTINATION	SET
MINIMUMS	SET
SEAT BELTS	ON
BARO REF below TRANS LVL	LOCAL
ANTI-ICE	AS REQUIRED

SECURING AIRCRAFT

ADIRS	OFF
OXYGEN	OFF
APU BLEED	OFF
EMER EXIT LIGHTS	OFF
SIGNS	AS REQUIRED
APU MASTER	OFF
BAT 1 / BAT 2	OFF

APPROACH

APPROACH PHASE	ACTIVATE
LS / APPR MODE	AS REQUIRED
SPEED	MANAGED
FLAPS 1	BELOW VFE
FLAPS 2	BELOW VFE
LANDING GEAR	DOWN
SPOILERS	ARM
AUTO BRAKE	AS REQUIRED
FLAPS 3 / FULL	SET
ECAM MEMO	LDG NO BLUE

LANDING

CABIN CREW	ADVISED
AUTO THRUST	SPEED/OFF
LANDING GEAR	DOWN
SIGNS	ON
SPOILERS	ARM
FLAPS	SET
APPROACH SPEED	VAPP
LANDING LIGHTS	ON
AT 20 FT	RETARD
REVERSERS	AS REQUIRED

GO AROUND

THRUST LEVERS	TOGA
PITCH	15 deg
FLAPS	ONE STEP UP
POSITIVE CLIMB	GEAR UP
SRS / GA TRK	CHECK
ACCEL ALT	RETRACT FLAPS
THRUST LEVERS	CLB
NAV / AP	AS REQUIRED

AFTER LANDING

SPOILERS	DISARM
FLAPS	RETRACTED
APU	START
RADAR	OFF
PWS	OFF
EXTERIOR LIGHTS	AS REQUIRED
TCAS	STBY
BRAKES TEMP	CHECK

PARKING

PARKING BRAKE	SET
APU BLEED	ON
ENG MASTERS	OFF
SEAT BELTS	OFF
FUEL PUMPS	OFF
BEACON	OFF
EXTERIOR LIGHTS	AS REQUIRED
TRANSPONDER	STBY