

Cessna 404 Titan

Guide - Checklist & Procedures for (Microsoft Flight Simulator 2024)

by ChatGPT v0.1

Weight

Maximum Takeoff Weight	8,400 lbs (3,810 kg)
Maximum Landing Weight	8,100 lbs (3,674 kg)
Typical Empty Weight	4,834-4,965 lbs
Fuel Capacity	348 gal / 344 usable
Payload w/ Full Fuel	approx. 701 lbs

Dimensions

Wingspan	46 ft 4 in (14.12 m)
Length	39 ft 6 in (12.04 m)
Height	13 ft 3 in (4.04 m)
Cabin Volume	152 cu ft
Crew / Passengers	1 / up to 7

Performance

Takeoff Ground Roll	1,788 ft
Takeoff Over 50 ft	2,367 ft
Rate of Climb	1,575 ft/min
Service Ceiling	26,000 ft
Max Cruise Speed	232 KTS
Normal Cruise	217 KTS
Landing Over 50 ft	2,130 ft

Speeds

VNE	241 KIAS	VNO 212 KIAS
VA	160 KIAS	VFE 182 KIAS
VLE / VLO		182 KIAS
VMCA	78 KIAS	VS 83 KIAS
VSO	70 KIAS	VR 91-102
VX / VY		96 / 109 KIAS
VSSE / VYSE		102 / 109 KIAS
VAPP Flaps DN		91 KIAS + Wind
Max Crosswind		20 KTS

NORMAL PROCEDURES

PREFLIGHT

PREFLIGHT INSPECTION	COMPLETED
PITOT / STATIC COVERS	REMOVED
CHOCKS / TIE-DOWNS	REMOVED
AIR INTAKES	CLEAR
DOORS / BAGGAGE	SECURED
PARKING BRAKE	SET
FUEL QUANTITY	CHECK
FUEL SELECTORS L/R	MAIN TANKS
CIRCUIT BREAKERS	IN

BEFORE ENGINE START

BATTERY / AVIONICS	ON / AS REQ
BEACON LIGHT	ON
MIXTURES	FULL RICH
PROPELLERS	FULL FORWARD
THROTTLES	OPEN 1/4 IN
FUEL PUMPS	ON
MAGNETOS	ON
ANTI-COLLISION	ON

ENGINE START

AREA	CLEAR
STARTER	ENGAGE
THROTTLE	ADJUST IDLE
OIL PRESSURE	CHECK
STARTER	DISENGAGE
ALTERNATOR	ON
REPEAT	OPPOSITE ENGINE
FUEL PUMPS	OFF / AS REQ
AVIONICS	ON
ENGINE INSTRUMENTS	CHECK
VACUUM / AMPS	CHECK
ANNUNCIATORS	CHECK

BEFORE TAXI

COM / NAV / GPS	SET
ATIS	OBTAIN
CLEARANCE	OBTAIN
ALTIMETER	SET
TRANSPONDER	SET
AUTOPILOT	CHECK / OFF
FLIGHT CONTROLS	FREE & CORRECT
TRIM	SET
FLAPS	UP
PARKING BRAKE	RELEASE
BRAKES	CHECK

RUN-UP

PARKING BRAKE	SET
THROTTLES	1700 RPM
MAGNETOS	CHECK
PROPELLERS	CYCLE
ENGINE GAUGES	CHECK
FUEL PUMPS	ON
MIXTURES	RICH / SET
THROTTLES	IDLE CHECK

BEFORE TAKEOFF

DEPARTURE BRIEFING	COMPLETE
DOORS / WINDOWS	LOCKED
FUEL SELECTORS	MAIN TANKS
FUEL PUMPS	ON
MIXTURES	FULL RICH
PROPELLERS	FULL FORWARD
TRIMS	SET
FLAPS	T/O & APPR AS REQ
LANDING / STROBE	ON
TRANSPONDER	ALT

Cessna 404 Titan

Guide - Checklist & Procedures for (Microsoft Flight Simulator 2024)

by ChatGPT v0.1

NORMAL TAKEOFF	
BRAKES	HOLD
THROTTLES	ADVANCE SMOOTHLY
MANIFOLD PRESSURE	40 IN HG MAX
ENGINE INSTRUMENTS	CHECK
BRAKES	RELEASE
DIRECTIONAL CONTROL	MAINTAIN
ROTATE	91-102 KIAS
PITCH	POSITIVE CLIMB
LANDING GEAR	UP
FLAPS	UP when clear

CLIMB	
AIRSPEED	115-140 KIAS
BEST RATE	109 KIAS
POWER	33.5 IN / 1900 RPM
MIXTURES	CLIMB RANGE
FUEL PUMPS	ON initially
ENGINE PARAMETERS	MONITOR
COWL FLAPS	AS REQUIRED
ALTIMETER	STD above transition

CRUISE	
POWER	SET
MIXTURES	LEAN AS REQ
FUEL PUMPS	OFF / AS REQ
FUEL BALANCE	MONITOR
COWL FLAPS	AS REQUIRED
ENGINE / FUEL	MONITOR

DESCENT	
ATIS / WEATHER	OBTAIN
ALTIMETER	SET LOCAL
POWER REDUCTION	GRADUAL
MIXTURES	ENRICHEN
COWL FLAPS	AS REQUIRED
LANDING LIGHTS	ON below 10,000

APPROACH	
APPROACH BRIEFING	COMPLETE
NAV / GPS / CDI	SET
FUEL SELECTORS	MAIN TANKS
FUEL PUMPS	ON
MIXTURES	FULL RICH
PROPELLERS	FULL FORWARD
AIRSPEED	BELOW 182 KIAS
FLAPS	T/O & APPR

BEFORE LANDING	
LANDING GEAR	DOWN
GEAR LIGHTS	3 GREEN
FLAPS	LANDING AS REQ
AIRSPEED	91 KIAS + WIND
PROPELLERS	FULL FORWARD
MIXTURES	FULL RICH
LANDING LIGHTS	VERIFY ON
AUTOPILOT	OFF

LANDING	
AIRSPEED	VAPP / VREF
GEAR	DOWN - 3 GREEN
FLARE	AS REQUIRED
THROTTLES	IDLE
BRAKES	AS REQUIRED

GO AROUND	
THROTTLES	FULL FORWARD
PROPELLERS	FULL FORWARD
MIXTURES	FULL RICH
FLAPS	T/O & APPR
PITCH	CLIMB ATTITUDE
LANDING GEAR	UP positive rate
AIRSPEED	VX/VY AS REQ
FLAPS	UP when clear

AFTER LANDING	
FLAPS	UP
COWL FLAPS	OPEN
FUEL PUMPS	OFF
LANDING LIGHTS	OFF
STROBE LIGHTS	OFF
TRANSPONDER	STBY
TRIM	RESET

SHUTDOWN	
PARKING BRAKE	SET
AVIONICS	OFF
THROTTLES	IDLE
MIXTURES	IDLE CUT-OFF
MAGNETOS	OFF
FUEL SELECTORS	OFF
ALTERNATORS	OFF
BATTERY	OFF
CONTROL LOCK / CHOCKS	AS REQUIRED