# Boolean Algebre

Lecture 2

Prepared by: Eng.Amani Safwat

#### Introduction

- Boolean Algebra is a branch of mathematics for digital logic
- Founded by George Boole
- Used in computers and digital systems

#### **Basic Symbols**

- Variables (A, B, C....)  $\rightarrow$  Its value is 0 or 1
- AND (·)
- OR (+)
- NOT (')

#### **Basic Laws**

- Identity Law: A+0=A, A·1=A
- Null Law: A+1=1, A·0=0
- Idempotent Law: A+A=A, A·A=A
- Complement Law: A+A'=1, A·A'=0
- Commutative Law : A+B=B+A , A.B = B.A
- Associative Law: A+B+C=(A+B)+C, A.B.C=(A.B).C
- Distributive Law: A.(B+C)=A.B+A.C, A+(B.C)=(A+B).(A+C)
- De Morgan's Theorem: (A+B)`=A`.B`, (A.B)`=A+B`

EX 1:

$$F = A + AB$$

We take out a common factor

$$A(1+B) => 1+B=1$$

So 
$$F = A$$

EX 2:

$$F = AB + AB$$

$$A(B + B') => B + B' = 1$$

```
EX 3:
```

$$F = A (A`+B)$$

$$AA$$
 + $AB => A.A$  =0

EX 4:

$$F = AB + BC(B + C)$$

AB+BBC+BCC

$$B(A+C)$$

So 
$$f = B(A+C)$$

EX 5:

F = AA + AC + AB + BC

A+AC+AB+BC

A(1+C+B)+BC

So F= A+BC

EX 6:

AB+A(A+C)+B(A+C)

AB +AA+AC+AB+C

AB+A+AC+C

A(B+1+C)+C

So F = A + C

```
EX 7:
F = (((CD)' + A')' + ((C'D + A'))'
= C'+D'+A.(C+D').A
=(C'+D'+A).(AC+AD')
=ACC'+ACD' + AAC +AD'C'+A D'D'+ AAD'
=ACD' + AC + AD'C' + AD'
=AC(D+1)(ADC+AD)
=AC+AD(C+1)
=AC+AD`
=A(C+D)
```

# Thank you