## Portal/Hail API

## Changes

#### Version 1.0 (2018-05-23)

Backward incompatible changes:

- Move altFreq and related variant annotations out of masks and into singleVariantResults in the results endpoint.
- Rename results to groupResults in results endpoint.
- Change grouping and type of groups to be groupType universally.
- Remove redundant type from results in results endpoint.

New additions:

- singleVariantResults section of results JSON to allow for also returning single variant statistics in one call.
- Include single variant p-values in scorecov section of the scores/covariances endpoint.

### Version 0.1 (2018-04-27)

Initial document.

# API specification

## Retrieve available datasets/masks

A dataset is a set of variant genotypes and samples (e.g. a VCF.)

A mask is defined by:

- 1. Variant filtering criteria
- 2. Variant grouping criteria

Variant filtering:

- Allele frequency
- Annotation about a variant (protein-truncating, loss-of-function, etc.)

## Grouping:

- Gene
- Chromatin state regions (enhancer, silencer, promoter, insulator, etc.)
- KEGG pathways (variants within genes that belong to the pathway)
- Gene ontology terms (similar to KEGG)

Masks would be available per dataset.

For now, a description of the variant filtering and grouping criteria will probably just have to be plain text without some type of formal grammar.

#### Request

GET /api/aggregation/metadata

#### Response

```
{
  "data": [
    {
      "dataset": 42,
      "analysis": "52K Exomes",
      "masks": [
          "id": "PTV",
          "description": "Protein truncating variants",
          "groupType": "gene",
          "identifier": "ENSEMBL"
        },
          "id": "PTV & LoF & AF<0.05",
          "description": "Protein truncating variants with AF < 0.05",
          "groupType": "gene",
          "identifier": "ENSEMBL"
        },
          "id": "PTV & LoF & AF<0.05",
          "description": "Protein truncating and loss-of-function variants with AF < 0.05",
          "groupType": "gene",
          "identifier": "ENSEMBL"
        }
     ]
    }
 ]
}
```

#### Retrieve covariance in region given dataset/mask(s)

#### Request

Only requesting scores and covariance for the "PTV" mask just to save some space.

#### POST /api/aggregation/covariance

```
{
  "chrom": "6",
  "start": 1,
  "end": 100000,
  "dataset": 42,
  "masks": [
      "PTV"
  ]
}
```

#### Response

We want to be able to retrieve as much of the masks/covariance data all at once to minimize round trips to the server. This structure would allow retrieving covariance for multiple masks all at once.

Note that all scores and covariances are assumed to be counting towards the alternate allele. It is also critical that alternate allele frequencies are included so as to be able to orient scores/covariances towards the

minor allele when performing the aggregation tests.

This response is slightly condensed to save space.

```
{
  "data": {
    "masks": [
      {
        "id": "PTV",
        "label": "Includes only protein truncating variants",
        "groupType": "gene",
        "groups": {
          "ENSG000001": {
            "variants": [
              "2:21228642_G/A",
              "2:21230094_AT/A",
              "2:21230336_AT/A"
            ]
          },
          "ENSG000002": {
            "variants": [
              "19:11216264_G/T",
              "19:11218173_AACCCATC/A"
            ]
        }
      }
    ],
    "scorecov": [
      {
        "mask": "PTV",
        "group": "ENSG000001",
        "scores": [
          0.1,
          0.3,
          0.5
        ],
        "covariance": [
          0.3,
          0.4,
          0.65,
          0.1,
          0.83,
          0.99
        ],
        "altFreq": [
          0.033,
          0.001,
          0.00045
        ],
        "pvalue": [
          0.000431,
          0.05,
          1.23e-06
        ],
```

```
"sigmaSquared": 0.08,
        "nsamples": 3550
      },
      {
        "mask": "PTV",
        "group": "ENSG000002",
        "scores": [
          0.443,
          0.911
        ],
        "covariance": [
          0.291,
          0.384,
          0.14
        ],
        "altFreq": [
          0.0025,
          0.03
        ],
        "pvalue": [
          0.043,
          0.0002
        ],
        "sigmaSquared": 0.08,
        "nsamples": 3550
    ]
 }
}
```

#### Retrieving pre-computed aggregation test results

In the case where aggregation tests have already been pre-computed for some of the datasets server-side, we could use this API to retrieve those results and display them in LZ.

Note that rare metal.js, after running aggregation tests, will return results for matted in the exact same format as the response below.

## Request

Looks identical to the same request used to retrieve covariance.

## POST /api/aggregation/results

```
{
  "chrom": "6",
  "start": 1,
  "end": 100000,
  "dataset": 42,
  "masks": [
      "PTV"
  ]
}
```

#### Response

If results were already available server-side, say if they were pre-computed, we could accept a response of this format and be able to show the results within LZ without performing any aggregation test computations.

Note: the results are not ordered; the order in which groups appear in groupResults does not necessarily match the order in which groups appear in data.masks. Similarly with singleVariantResults.

```
{
  "id": 42,
  "description": "52K Exomes",
  "data": {
    "masks": [
      {
        "id": "PTV",
        "label": "Includes only protein truncating variants",
        "groupType": "gene",
        "groups": {
          "ENSG000001": {
            "variants": [
              "2:21228642_G/A",
              "2:21230094 AT/A",
              "2:21230336_AT/A"
            ]
          },
          "ENSG000002": {
            "variants": [
              "19:11216264_G/T",
              "19:11218173_AACCCATC/A"
          }
        }
      }
    ],
    "singleVariantResults": [
        "variant": "2:21228642 G/A",
        "altFreq": 0.033,
        "pvalue": 0.01141
      },
        "variant": "2:21230094 AT/A",
        "altFreq": 0.001,
        "pvalue": 1e-4
      },
      {
      }
    ],
    "groupResults": [
        "group": "ENSG000001",
        "mask": "PTV",
        "test": "SKAT-0",
        "pvalue": 1.8e-09
```

```
},
     {
        "group": "ENSG000002",
        "mask": "PTV",
        "test": "SKAT-0",
        "pvalue": 1.7883e-09
     }
      }
}
```