

UM11434

IW416 Labtool User Guide

Rev. 2 — 2 February 2021

User manual

Document information

Information	Content
Keywords	Labtool test setup, Device under test (DUT) setup, driver, firmware, Labtool application installation and usage, calibration data, Wi-Fi and Bluetooth Labtool commands, Bluetooth RF test sequences, Wi-Fi RF test sequences
Abstract	Explains how to set up the Labtool test environment, how to install the driver and firmware, and how to use the Labtool software application.



Revision history

Rev	Date	Description
v.1	20190917	Initial version
v.2	20210202	Modifications <ul style="list-style-type: none"> • Applied NXP branding and version numbering • Section 1.1 "Purpose and scope": updated • Section 2 "Labtool test setup": updated • Section 3.1 "Linux Ubuntu installation": updated • Section 3.3 "Software download": updated • Section 3.4 "Building IW416 drivers": renamed (no change in the content) • Section 3.5 "Building MFG bridge application and copying MFG firmware": renamed and updated • Section 3.6 "Loading IW416 driver and executing the firmware and bridge": renamed and updated • Section 4.1 "Labtool setup on Windows PC": renamed and updated • Section 4.2 "Calibration data": updated • Section 6.1 "Command 9: Get Tx/Rx antenna configuration (valid when Antenna diversity is supported)": added • Section 6.2 "Command 10: Set Tx/Rx antenna configuration (valid when Antenna diversity is supported)": added • Section 6.3 "Command 11: Get RF channel configuration": updated • Section 6.5 "Command 13: Get RF data rate": added • Section 6.14 "Command 34: Enable/disable BSSID filter": added • Section 6.29 "Command 146: Get the number of calibrations done on OTP": added • Section 6.33 "Command 198: Start RSSI data collection": added • Section 6.34 "Command 199: Stop RSSI data collection and report result": added • Section 6.35 "Wi-Fi RF test examples": added test examples for RSSI measurement • Section 7.26 "Bluetooth RF test examples": updated

1 Introduction

This document provides guidance for the installation and usage of IW416 Labtool application. The Labtool is a software test tool used to control and run various RF and regulatory compliance tests.

1.1 Purpose and scope

This document explains how to set up the IW416 Labtool test environment including the installation of IW416 driver, loading manufacturing firmware, and using Labtool software application. The Wi-Fi and Bluetooth radio Labtool commands are detailed along with some RF test examples.

1.2 References

[Table 1](#) lists the references.

Table 1. References

Reference type	Reference title
Datasheet	DS - IW416 - Dual-band 1x1 Wi-Fi 4 and Bluetooth 5.1 Combo SoC
Design package	RD-IW416-QFN-WIB3-1A-V2: design package for IW416 reference design with QFN package and one antenna
Design package	RD-IW416-QFN-WIB3-2A-V2: design package for IW416 reference design with QFN package and two antennas
Design package	RD-IW416-CSP-WIB3-1A-V1: design package for IW416 reference design with CSP package and one antenna
Design package	RD-W8978-CSP-WIB3-2A-V1: design package for IW416 reference design with CSP package and two antennas
User manual	UM11350 - IW416 Reference Design Kit User Guide
Application note	AN12794 - IW416 Calibration Structure

2 Labtool test setup

The Labtool is a test tool that enables RF testing for IW416 device. The Labtool is used for the following:

- Measurement of RF parameters such as transmit power, EVM, and receiver sensitivity
- Regulatory compliance testing (EMC/EMI)

The Labtool is part of the Manufacturing Software (MFG SW) package which includes the following components:

- Labtool application: this tool runs on a Windows PC
- IW416 device driver for Ubuntu Linux
- IW416 manufacturing (MFG) firmware: specialized firmware build that enables the manufacturing test mode on IW416 device.
- Manufacturing bridge application: this application runs on the device under test (DUT). The bridge application enables Labtool application running on the Windows PC to communicate with the DUT over an ethernet interface.

[Figure 1](#) shows a block diagram of a test setup running the Labtool. The test setup includes:

1. Device Under Test (DUT): The DUT is a system that includes IW416 device. The DUT needs the following software components:
 - IW416 device driver and manufacturing firmware
 - Manufacturing bridge applicationIf you are testing IW416 evaluation board using SDIO/UART interface or an IW416-based wireless module, then connect the board or module to a PC/platform running Linux.
2. Windows PC: The Labtool application runs on a Windows PC
3. The RF tester, that is the test instrument
4. Ethernet switch




Figure 1. Labtool Test Setup

3 Device under test setup

The host system provides the means for the Labtool to communicate with the DUT that runs on Linux Ubuntu.

This section details the installation of Linux Ubuntu on the (Linux) Bridge computer and the configuration setup prior to the download and build of the driver and firmware.

3.1 Linux Ubuntu installation

Install the Linux Ubuntu 16.04 along with the required tools and applications packages on the (Linux) Bridge computer. Perform this initial setup once. Subsequent releases will only require to copy IW416 firmware and driver files to their respective locations on the Bridge computer.

The procedure to set up a Bridge computer is as follows:

Step 1: Install Linux Ubuntu 16.04 system. The following command installs the 64-bit Linux Ubuntu system and is given as an example. You can also install the 32-bit Linux Ubuntu.:

```
$ Ubuntu-16.04.-desktop-amd64.iso
```

Step 2: Set up the environment.

Create a super-user or root administrator with the following command:

```
$ sudo bash # <user password>
```

Update the kernel and install the related patch with the following commands:

Ask your local NXP FAE for the kernel update package (*Ubuntu_16.tgz*) or download the 4.8.0 kernel from the internet.

Note: In case of a new requirement for the kernel or patch with the new release driver package, check the driver release notes included in the driver release package available on [IW416 Tools and Software tab](#) on NXP website.

```
$ tar -zxvf Ubuntu_16.tar
$ cd Ubuntu_16
$ bash install.sh
$ reboot
```

Step 3 - Check the kernel version and install the Ubuntu packages:

```
$ uname -r
$ apt-get install vim
$ apt-get install gawk
$ apt-get install openssh-server
$ apt-get install libnl-3-dev
$ apt-get install libnl-genl-3-dev
$ apt-get install libreadline6-dev
$ apt-get install libssl-dev
$ apt-get install libbluetooth-dev
$ apt-get install libncurses5-dev
$ apt-get install libpcsc-lite-dev
$ apt-get install libc6-dev-i386
```

3.2 Linux bridge computer configuration

Step 1 - Disable the Linux firewall temporarily with the following command:

```
$ service iptables stop
```

Step 2 – Disable the open-source driver (*mwifiex*) to avoid a mutual conflict with NXP driver.

Execute the following commands to disable the open-source driver:

```
$ cd /lib/modules/`uname -r`/kernel/drivers/net/wireless/marvell/  
mwifiex  
$ for f in `find -name '*mwifi*';do mv "$f" `echo "$f" | sed s/.ko/  
_none/`;done  
$ cd /lib/modules/`uname -r`/kernel/drivers/BT  
$ for f in `find -name '*mrvl*';do mv "$f" `echo "$f" | sed s/.ko/  
_none/`;done
```

3.3 Software download

The software packages are available for download on [IW416 Tools and Software tab](#) on NXP website.

Make sure to download the two software packages:

- IW416 production software release package
- IW416 MFG software release package

Note: Ask your local NXP FAE for specific software packages.

3.3.1 Production software release package

The production software release package includes the Wi-Fi and Bluetooth driver source code. Both the Wi-Fi and Bluetooth drivers are needed for Labtool testing.

IW416 production software is available for download on [IW416 Tools and Software tab](#) on NXP website.

Note: Ask your local NXP FAE for specific software packages.

3.3.2 MFG software release package

The MFG software release package includes the MFG firmware, the Labtool executable (.exe file), and the MFG bridge application. All three software items are needed for Labtool testing.

The MFG software release is published on [IW416 Tools and Software Tab](#) on NXP website.

3.4 Building IW416 drivers

This section explains how to build both the Wi-Fi and Bluetooth drivers once you have downloaded the production software package published on [IW416 Tools and Software tab](#)).

Note: *IW416 device was formerly named 88W8978. The firmware and driver still refer to 8978 or 88W8978.*

Step 1 – Open a terminal window on the (Linux) Host PC and use the `cd` command to the folder where the software is downloaded.

Step 2: Unzip the driver release package and all other files in it with the following commands:

```
$ tar -xvf SD-WLAN-SD-BT-8978-U16-MMC...pxx-GPL.tar
$ tar -xzvf SD-BT-8978-U16-MMC-...-GPL-src.tgz
$ tar -xzvf SD-BT-CHAR-8978-U16-MMC-...-GPL-src.tgz
$ tar -xzvf SD-UAPSTA-8978-U16-MMC-...-mlan-src.tgz
$ tar -xzvf SD-UAPSTA-8978-U16-MMC-...-app-src.tgz
$ tar -xzvf SD-UAPSTA-8978-U16-MMC-...-GPL-src.tgz
```

The folder named `SD-UAPSTA-UART-BT-8978-U16-MMC-...-GPL` includes the WiFi and Bluetooth driver source code.

Step 3: Navigate to `wlan_src` directory and run the following commands to compile the driver for Wi-Fi:

```
$ cd wlan_src
$ make clean
$ make build
```

After the compilation, the folder `bin_sd8978` is created. It includes the Wi-Fi driver files `mlan.ko` and `sd8xxx.ko`.

Step 4: Navigate to `mbt_src` directory and run the following commands to compile the Bluetooth driver:

```
$ mbt_src
$ make clean
$ make build
```

After the compilation, the folder `bin_sd8978_bt` is created and includes the Bluetooth driver file `bt8xxx.ko`.

3.5 Building MFG bridge application and copying MFG firmware

This section provides the steps for the installation of the MFG firmware and the build of the Bridge application.

Step 1: Navigate to the directory where the MFG software release package was downloaded and use the following command to extract the file:

```
$ cd <path-to-folder-with-mfg-software-release-package>
$ unzip MFG-W8978-MF-WiFi-BT-BRG-FC-...-bin.zip
```

The extracted release package includes the following:

- The *FwImage* directory which includes the MFG Firmware
- The *Bridge* directory with the source code for the bridge application
- The *release* directory containing the Labtool executable for the Windows computer

[Figure 2](#) shows the content of *FwImage* directory.








 <code>sdio8978_sdio_combo.bin</code>	12/1/2020 5:22 AM	BIN File	415 KB
 <code>sdio8978_uart_combo.bin</code>	12/1/2020 5:34 AM	BIN File	415 KB
 <code>usb8978_usb_combo.bin</code>	12/1/2020 6:01 AM	BIN File	442 KB
 <code>w8978d_SDIO_SDIO_SDIO.bin</code>	12/1/2020 5:22 AM	BIN File	86 KB
 <code>w8978d_SDIO_UART_UART.bin</code>	12/1/2020 5:34 AM	BIN File	86 KB
 <code>w8978o_SDIO_SDIO_SDIO.bin</code>	12/1/2020 5:18 AM	BIN File	330 KB
 <code>w8978o_SDIO_UART_UART.bin</code>	12/1/2020 5:30 AM	BIN File	330 KB

Figure 2. FwImage directory content

Step 2: Navigate to the *FwImage* directory and select the MFG firmware bin file that matches the host interface type and copy it to the Linux firmware path `/lib/firmware/nxp/`.

For example, the firmware binary file `sdio8978_sdio_combo.bin` supports both Wi-Fi and Bluetooth over an SDIO interface. Run the commands to copy the bin file:

```
$ cd MFG_W8978...pxx/bin/FwImage
$ cp sdio8978_sdio_combo.bin /lib/firmware/nxp/
```

If there is no folder with the name *nxp* under `/lib/firmware/` path, run the commands to create the folder:

```
$ cd /lib/firmware/
$ mkdir nxp
```

Step 3: Go to the *Bridge* folder and compile the bridge application:

```
$ cd MFG_W8xxx...pxx/Bridge
$ tar -xzf bridge_linux_xx.xx.xx.xx-src.tgz
$ cd bridge_linux_xx.xx.xx.xx.xx/bridge
$ make build
```

The `mfgbridge` application executable is created in the `bin_mfgbridge` directory.

3.6 Loading IW416 driver and executing the firmware and bridge

The procedure to load the Wi-Fi and Bluetooth drivers and to run the Bridge application is as follows:

Step 1: Install Wi-Fi and Bluetooth drivers.

Go to the folder which includes the Wi-Fi driver files (*mlan.ko* and *sd8xxx.ko*), and run the following commands:

```
$ insmod mlan.ko
$ insmod sd8978.ko mfg_mode=1 drv_mode=1 fw_name=nxp/
sdio8978_sdio_combo.bin cal_data_cfg=none
$ dmesg
$ iwconfig
```

Use the `dmesg` command to check the driver and firmware load status. If the status is correct the command output is as shown below. No message returns if either the firmware or driver did not load correctly.

```
WLAN FW is active
wlan: Driver loaded successfully
```

Use the `iwconfig` command to confirm that the Wi-Fi device is defined as the `mlan0` interface with the following messages:

```
mlan0 IEEE 802.11-DS ESSID:""
Mode:Auto channel=0 Access Point:Not-Associated
Bit Rate:0 kb/s Tx Power=off
Retry limit:0 RTS thr=0 Fragment thr:off
Power Management:off
Link Quality=0/5 Signal level=0 dBm Noise level=0 dBm
Rx invalid nwid:0 Rx invalid crypt:0 Rx invalid frag:0
Tx excessive retries:0 Invalid misc:0 Missed beacon:0
```

Similarly, navigate to the folder which includes the Bluetooth driver file (*bt8xxx.ko*) and execute the following commands:

```
$ insmod bt8xxx.ko
$ dmesg
$ hciconfig
```

If the status is correct the command output is as shown below. No message returns if either the firmware or driver did not load correctly.

```
BT FW is active (0)
BT: Driver loaded successfully
```

Use the `hciconfig` command to confirm that the Bluetooth device is defined as the `hci0` interface with the following messages:

```
hci0 Type: BR/EDR Bus:SDIO
BD Address: C0:95:DA:00:43:61 ACL MTU: 1021:7 SCO MTU: 120:6
UP RUNNING PSCAN
RX bytes:824 acl:0 sco:0 events:41 errors:0
TX bytes:1168 acl:0 sco:0 events:41 errors:0
```

If the Bluetooth is down, try to reset the Bluetooth interface to `hci0` or disconnect IW416 board. Unload the drivers with the following commands:

```
$ rmmod sd8xxx.ko
$ rmmod mlam.ko
$ rmmod bt8xxx.ko
```

Step 2: Configure the DUT IP address.

We use the following IP addresses as examples in the commands shown for this step:

- (Linux) Bridge computer IP address: 192.168.0.10
- (Windows) Host computer IP address: 192.168.0.58

In the Linux system, configure the Ethernet IP address with the following command:

```
>ifconfig -a
```

Check the Ethernet name. The following command assumes the Ethernet name is `ethx`:

```
>ifconfig ethx 192.168.0.10
```

Check the Ethernet connection state between the (Windows) Host computer and the (Linux) Bridge computer using the `ping` command.

In the Windows Terminal window, execute the following command:

```
>ping 192.168.0.10
```

In the Linux platform terminal execute the following command:

```
>ping 192.168.0.58
```

Ensure that both the (Windows) Host computer and (Linux) Bridge computer IP addresses are under the same subnet.

Step 3: Run the bridge application.

Go to the bridge folder under the MFG release package where the bridge application was compiled previously, and run the bridge application with the following command:

```
$/mfgbridge
```

To terminate the bridge application, type CTRL+C in the bridge window.

To restart the bridge application, execute the `$/mfgbridge` command again.

4 Windows PC setup

4.1 Labtool setup on Windows PC

The Host computer runs on Windows operating system (64 bit and 32 bit). The procedure to set up the environment is as follows:

Step 1: Download the MFG software release package *MFG-W8xxx...pax.bin* published on [IW416 Tools and Software tab](#) on NXP website. The MFG software release package includes the MFG firmware, the Labtool executable (.exe file), and the MFG bridge application. All three software items are needed for Labtool testing.

Step 2: Unzip the MFG firmware software release.

Step 3 - Copy the *...bin/release/labtool* folder to the Host computer and make sure the path length has less than 255 characters. [Figure 3](#) shows the *labtool* repository content:





















	AddCal.dll	12/1/2020 6:13 AM	Application extens...	1,131 KB
	AddCalDLL.dll	12/1/2020 6:13 AM	Application extens...	1,131 KB
	AddCalDLL.lib	12/1/2020 6:13 AM	LIB File	2 KB
	DutApi89XXDII.h	12/1/2020 6:13 AM	H File	19 KB
	DutApiMimoBtDII.dll	12/1/2020 6:13 AM	Application extens...	442 KB
	DutApiMimoBtDII.lib	12/1/2020 6:13 AM	LIB File	108 KB
	DutApiMimoBtDIIDualIf.dll	12/1/2020 6:14 AM	Application extens...	463 KB
	DutApiMimoBtDIIDualIf.lib	12/1/2020 6:14 AM	LIB File	110 KB
	DutApiMimoBtDIIUart.dll	12/1/2020 6:14 AM	Application extens...	605 KB
	DutApiMimoBtDIIUart.lib	12/1/2020 6:14 AM	LIB File	110 KB
	DutApiSisoBt	12/1/2020 6:14 AM	Application	376 KB
	DutBtApi.hc	12/1/2020 6:13 AM	HC File	7 KB
	DutBtApi89XXDII.h	12/1/2020 6:13 AM	H File	21 KB
	DutWlanApi.hc	12/1/2020 6:13 AM	HC File	19 KB
	DutWlanApi89XXDII.h	12/1/2020 6:13 AM	H File	33 KB
	Flash_SPI_header.bin	12/1/2020 6:13 AM	BIN File	4 KB
	Flash_SPI_header.sbin	12/1/2020 6:13 AM	SBIN File	4 KB
	GenHeader.bin	12/1/2020 6:13 AM	BIN File	1 KB
	SetUp	12/1/2020 6:13 AM	Configuration setti...	3 KB
	UsbHeader.bin	12/1/2020 6:13 AM	BIN File	1 KB

Figure 3. Labtool Repository Content

Step 4: Disable the Windows firewall.

Step 5: Open the Network and Sharing Center on the Windows PC. Change the network address of the Ethernet port to the same subnet as the (Linux) Bridge computer. The following IP addresses are used in this document:

- (Windows) Host computer: 192.168.0.58
- (Linux) Bridge computer: 192.168.0.10

Step 6: Open the *SetUp.ini* file using a text editor. The value of the parameter `DutIpAddress` is the IP address of the DUT. The parameter `HostIpAddress` is the IP address of the Windows PC. Edit the file as follows:

```
[DutIp]
DutIpAddress = 192.168.0.10
HostIpAddress = 192.168.0.58
Protocol = TCP
```

Step 7: In the *SetUp.ini* file, the parameter `NO_EEPROM` is used to specify the calibration data storage option. The default value is 1 (Use calibration data from the external configuration file).

For general RF evaluation and test, set the file option to 1 to use the calibration data from an external file. If the calibration data is already stored in the OTP memory of IW416 device, set the value to 2.

```
[DutInitSet]
0 = EEPROM support
1 = No EEPROM support
2 = OTP support
NO_EEPROM = 1
NoEepromBtFlexFileName = WlanCalData_ext.conf
NoEepromWlanFlexFileName = WlanCalData_ext.conf
```

Note: *No_EEPROM support refers to the calibration data from the external configuration file.*

Step 8: Save the “*SetUp.ini*” file after making the changes.

4.2 Calibration data

The DUT requires calibration data for optimal performance. The calibration data is included in the *.conf* file or programmed into the on-chip OTP memory of IW416 device. The *.conf* file is included in the reference design package for the WLCSP and QFN packages available on [IW416 Tools and Software tab](#). See [Figure 4](#).

Before launching the Labtool, copy the *.conf* file into the Labtool working directory and rename the file as *WlanCalData_ext.conf* (see [Figure 5](#)).

<input type="checkbox"/> Name	Date modified	Type	Size
<input type="checkbox"/> WlanCalData_ext_RD_W8978_QFN_WIB3_1A_V1.conf	2019/8/16 13:32	CONF File	1 KB
<input type="checkbox"/> WlanCalData_ext_RD_W8978_QFN_WIB3_2A_V1.conf	2019/8/16 13:33	CONF File	1 KB

Figure 4. Calibration data file (*.conf*)

<input type="checkbox"/> Name	Date modified	Type	Size
<input type="checkbox"/> AddCal.dll	2019/8/13 7:02	Application extension	1,131 KB
<input type="checkbox"/> AddCalDLL.dll	2019/8/13 7:02	Application extension	1,131 KB
<input type="checkbox"/> AddCalDLL.lib	2019/8/13 7:02	OrCADSpiceADModel...	2 KB
<input type="checkbox"/> DPD_PM_PM.Conf	2019/8/13 7:02	CONF File	4 KB
<input checked="" type="checkbox"/> DPD_Tool.exe	2019/8/13 7:02	Application	97 KB
<input type="checkbox"/> DutApi89XXDII.h	2019/8/13 7:02	H File	17 KB
<input type="checkbox"/> DutApiMimoBtDII.dll	2019/8/13 7:03	Application extension	438 KB
<input type="checkbox"/> DutApiMimoBtDII.lib	2019/8/13 7:03	OrCADSpiceADModel...	106 KB
<input type="checkbox"/> DutApiMimoBtDIIDualIf.dll	2019/8/13 7:05	Application extension	459 KB
<input type="checkbox"/> DutApiMimoBtDIIDualIf.lib	2019/8/13 7:05	OrCADSpiceADModel...	109 KB
<input type="checkbox"/> DutApiMimoBtDIIUart.dll	2019/8/13 7:04	Application extension	601 KB
<input type="checkbox"/> DutApiMimoBtDIIUart.lib	2019/8/13 7:04	OrCADSpiceADModel...	108 KB
<input checked="" type="checkbox"/> DutApiSisoBt.exe	2019/8/13 7:06	Application	374 KB
<input type="checkbox"/> DutBtApi.hc	2019/8/13 7:02	HC File	7 KB
<input type="checkbox"/> DutBtApi89XXDII.h	2019/8/13 7:02	H File	21 KB
<input type="checkbox"/> DutWlanApi.hc	2019/8/13 7:02	HC File	19 KB
<input type="checkbox"/> DutWlanApi89XXDII.h	2019/8/13 7:02	H File	32 KB
<input type="checkbox"/> Flash_SPI_header.bin	2019/8/13 7:02	BIN File	4 KB
<input type="checkbox"/> Flash_SPI_header.sbin	2019/8/13 7:02	SBIN File	4 KB
<input type="checkbox"/> GenHeader.bin	2019/8/13 7:02	BIN File	1 KB
<input type="checkbox"/> SetUp.ini	2019/8/13 7:02	Configuration settings	3 KB
<input type="checkbox"/> UsbHeader.bin	2019/8/13 7:02	BIN File	1 KB
<input checked="" type="checkbox"/> WlanCalData_ext.conf	2019/8/16 13:32	CONF File	1 KB

Figure 5. *WlanCalData_Ext.conf* in Labtool directory

5 Labtool usage

5.1 Starting Labtool

Ensure the bridge application is running prior to starting the Labtool application. The procedure to start the Labtool application is as follows:

Step 1: Double-click on *DutApiSisoBt.exe*. [Figure 6](#) shows the Labtool start window:

```
Name:          Dut labtool
Version:       1.0.0.10
Date:         Dec  1 2020 (06:14:31)

Note:

1. =====WiFi tool=====
2. =====BT   tool=====

Enter CMD 99 to Exit
```

Figure 6. Labtool start window

Step 2: At the command prompt, enter “1” to start the Wi-Fi radio operation or “2” to start the Bluetooth radio operation.

Step 3: To confirm whether the bridge and host setups are working properly, issue the command 88 to check the firmware and Labtool version number.

- If the correct version numbers are returned, start the RF test procedure.
- If the version numbers are incorrect, check the host, DUT, and bridge connections. Confirm the Wi-Fi and Bluetooth drivers are installed correctly.

[Figure 7](#) shows the correct state of command 88 execution.

```
Name:          Dut labtool
Version:       1.0.0.10
Date:         Dec 1 2020 (06:14:31)

Note:

1. =====WiFi tool=====
2. =====BT  tool=====

Enter CMD 99 to Exit

Enter option: 1

Name:          DutApiClass
Interface:     EtherNet
Version:       1.0.0.10
Date:         Dec 1 2020 (06:13:26)

Note:

D:\MFG-W8978-MF-WIFI-BT-BRG-FC-VS2013-1.0.0.10-16.80.10.p127\bin\release\labtool\setup.ini
Dut's IP 192.168.0.10:9930
Host's IP 192.168.0.58:9931
DutIf_UdpIp::delay 0
DutIf_UdpIp::vg_IfSpy 0
TCP connecting...
DutIf_InitConnection: 0x00000000
-----
                        W89xx (802.11a/g/b/n/ac) TEST MENU
-----

Enter option: 88

DLL Version : 1.0.0.10
LabTool Version: 1.0.0.10|
FW Version: 16.80.10.127      Mfg Version: 3.0.0.4
SOC OR Version: 2.3      Customer ID: 0
RF OR Version: 1.1      Customer ID: 0
Enter option: 22?
```

Figure 7. Command 88 execution

5.2 Running commands

Each time a Labtool command is executed, the console returns a status byte. A successful command execution is indicated by a status byte with all 0s ([Figure 8](#)).

```
Enter option: 11
DutIf_GetRfChannel: 0x00000000
RF Channel: 6 <2437.0 MHz>
Enter option: 111
DutIf_GetChannelBw: 0x00000000
Channel Bw: 0
Enter option: _
```

Figure 8. Status – Successful command execution

A failed command returns invalid data and is indicated by a non-0 status byte (0x00000001 to 0xFFFFFFFF). This could indicate a problem with the communication to the DUT, incorrect firmware, no firmware download, wrong version of Labtool/firmware, and so on.

```
Enter option: 11
DutIf_GetRfChannel: 0xFFFFFFFF9
RF Channel: 0 (0.0 MHz)
Enter option: 111
DutIf_GetChannelBw: 0xFFFFFFFF9
Channel Bw: 0
```

Figure 9. Status – Failed command execution

When using the transmit commands (25, 33, 35), note that all the Very High Throughput (VHT) rates are not available for all bandwidth and antenna path combinations. An error code in the returned status byte of 0xE indicates that the rate is not supported by the DUT. Enter a “?” at the Labtool prompt to list all the available commands.

5.3 Closing Labtool

To **close** Labtool, issue Command 99 once.

To **quit** Labtool, issue command 99 twice.

5.4 Getting help

The Labtool application realizes its functions (such as enable Tx/Rx tests) through the related Labtool commands. Labtool commands are listed in the Command Line Interface (CLI) menu.

Enter ? at the command prompt in the main window to get the CLI menu.

Enter <command number>? for the detailed usage and help menu for the respective command.

For example, enter 10?.to get the detailed Command 10 usage (including the command options) and related help file are shown in the main window.

6 Wi-Fi Labtool commands

Table 2. Wi-Fi Labtool command summary

Command
Command 9: Get Tx/Rx antenna configuration (valid when Antenna diversity is supported)
Command 10: Set Tx/Rx antenna configuration (valid when Antenna diversity is supported)
Command 11: Get RF channel configuration
Command 12: Set RF channel configuration
Command 13: Get RF data rate
Command 18: Set transmitter in CW mode
Command 22: Set power at antenna using calibration data
Command 25: Transmit with duty cycle Tx mode
Command 29: Get RF band configuration
Command 30: Set RF band configuration
Command 31: Clear Rx packet count
Command 32: Get and clear Rx packet count
Command 33: Transmit multicast packets
Command 34: Enable/disable BSSID filter
Command 35: Transmit with SIFS gap
Command 38: Transmit unicast packet
Command 44: Storage type get/set function
Command 45: Read MAC address from OTP
Command 46: Write MAC address to OTP
Command 53: Set calibration data to storage from text file
Command 54: Get calibration data from storage into file
Command 88: Get firmware/hardware version
Command 95: Get XTAL calibration offset
Command 96: Set XTAL calibration offset
Command 99: Exit Labtool application
Command 111: Get channel bandwidth
Command 112: Set channel bandwidth
Command 144: Read OTP raw data
Command 146: Get the number of calibrations done on OTP
Command 147: Get free lines in OTP
Command 148: Write patch block to OTP
Command 149: Write user data to OTP
Command 198: Start RSSI data collection
Command 199: Stop RSSI data collection and report result

6.1 Command 9: Get Tx/Rx antenna configuration (valid when Antenna diversity is supported)

This command is used to check which antenna is connected to the Wi-Fi radio when more than one antenna is used for Antenna diversity application.

Syntax: 9

Return data: GetTxAntenna: Antenna X (where X = 1 or 2)

6.2 Command 10: Set Tx/Rx antenna configuration (valid when Antenna diversity is supported)

This command is used to set the desired antenna to the Wi-Fi radio when more than one antenna is used for Antenna diversity application

Syntax: 10 <antenna number>

Where:

Command parameter	Description
antenna number	Number used to qualify the Tx/Rx antenna 1 = Main 2 = Aux

Example

10 1 // Sets the main antenna

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

6.3 Command 11: Get RF channel configuration

This command returns the values of the current RF channel, such as channel and offset.

Syntax: 11

Return data

Channel: Current channel number (see [Section 8.1 "RF channels"](#))

Offset: Boundary (applicable to non-20 MHz bandwidth channel)

- 0x1 = lower boundary of channel
- 0x3 = upper boundary of channel

Offset = 1 indicates that the channel number displayed (or set, in the case of Command 12) is the lower boundary of the channel.

If the channel bandwidth is 40 MHz (2.4 GHz band) and the channel center is 8, the Labtool reports Ch 6 with offset 1 or Ch 10 with offset 3.

6.4 Command 12: Set RF channel configuration

This command sets the RF channel. Specify the RF channel in the appropriate band (2.4 GHz or 5 GHz) or an error will occur.

Syntax: #23 <channel>

Where:

Command parameter	Description
Channel	Channel number When 40 MHz bandwidth is enabled, then the channel specified is the left most/lower channel.

Examples

12 6 // Sets Ch 6 in 20 MHz bandwidth mode

```
112 1 // Sets to 40 MHz bandwidth
12 36 // Sets Ch 36 with offset 1 (Ch 36 + Ch 40 bonded pair)
```

12 6 // Sets Ch 6 in 20 MHz bandwidth mode

```
112 1 // Sets to 40 MHz bandwidth
12 40 // Sets Ch 40 with offset 3 (Ch 36 + Ch 40 bonded pair)
```

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

6.5 Command 13: Get RF data rate

This command is used to check the current data rate set for the Wi-Fi radio.

Syntax: 13

Example(s)

13 // reads back current data rate for Wi-Fi radio

Return data: DataRate: X // Where X is the number associated with the data rate. See [Table 3](#)

Table 3. RF data rates

DataRate (X)	RF data rate
1	1M
2	2M
3	5.5M
4	11M
5	22M
6	6M
7	9M
8	12M
9	18M
10	24M
11	36M
12	48M
13	54M
14	72M
15	MCS0
16	MCS1
17	MCS2
18	MCS3
19	MCS4
20	MCS5
21	MCS6
22	MCS7
47	MCS32

6.6 Command 18: Set transmitter in CW mode

This command transmits an un-modulated carrier as a Continuous Wave (CW) tone.

Syntax: 18 <Enable>

Where:

Command parameter	Description
Enable	Mode enable 0 = disable (default) 1 = enable

Examples

```
18 1 // Turns on transmission
```

```
18 0 // Turns off transmission
```

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

6.7 Command 22: Set power at antenna using calibration data

This command sets the Tx power at the antenna using stored calibration data.

Syntax: 22 <channel> <power level> <modulation> <forceCalData>

Where:

Command parameter	Description
channel	Tx Channel See Section 8.1 . Default = Ch 6.
power level	Tx Power Level (dBm)
modulation	Modulation 00 = 802.11b CCK (default) 01 = 802.11g/a/p OFDM 10 = 802.11n MCS
forceCalData	Force calibration data Valid only for NO_EEPROM mode 0 = download calibration data only if not downloaded yet (default) 1 = force configuration file to be downloaded

Example

```
22 6 13 1 1 // Sets power for Ch 6, 13 dBm transmit power with OFDM modulation rates, and forces the configuration file download
```

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

6.8 Command 25: Transmit with duty cycle Tx mode

This command enables the device in modulated, packet-based, fixed duty cycle transmit mode after the power is manually set.

Syntax: 25 <enable> <data rate> <PayLoadWeight> <ShortGI>
<AdvCoding> <TxBfOn> <GFMode> <STBC> <PowerID> <SignalBw>

Where:

Command parameter	Description
enable	Mode enable 0 = disable (default) 1 = enable
data rate	Data Rate See Section 8.2 "Data rates" for mapping. Default = 4
PayLoadWeight	Represents a payload duty percentage (default = 50) Pattern = 0xB496DEB6 Short Preamble = 0 1 (default = 0)
ShortGI	Short guard interval 0 = long guard interval (default) 1 = short guard interval
AdvCoding	Advanced Coding 0 = BCC (default) 1 = LDPC
TxBfOn	Tx Beamform On 0 = disable (default) 1 = enable
GFMode	Greenfield mode 0 = disable (default) 1 = enable
PowerID	Power ID Set to -1 See Section 6.7 "Command 22: Set power at antenna using calibration data" for Power ID mapping.
SignalBW	Signal bandwidth 0 = 20 MHz 1 = 40 MHz -1 = follow deviceBW as in Section 6.3 "Command 11: Get RF channel configuration" and Section 6.4 "Command 12: Set RF channel configuration" (default)

Examples

25 1 4 // Turns on transmitter and specifies data rate (11 Mbit/s)

25 0 // Turns off transmitter

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

6.9 Command 29: Get RF band configuration

This command gets the RF band configuration.

Syntax: 29

Return data: Current RF band

- 0 = 2.4 GHz
- 1 = 5 GHz

6.10 Command 30: Set RF band configuration

This command sets the RF band configuration.

Syntax: 30 <band>

Where:

Command parameter	Description
band	RF band 0 = 2.4 GHz (default) 1 = 5 GHz

Examples

```
30 0 // Sets 2.4 GHz band
```

```
30 1 // Sets 5 GHz band
```

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

6.11 Command 31: Clear Rx packet count

This command clears the packet count register (start Rx Frame Error Rate (FER) test). The receiver continuously counts the received multi-cast packets.

Syntax: 31

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

6.12 Command 32: Get and clear Rx packet count

This command gets the counts for Rx, multi-cast and error packets, and clears the Rx packet counter (stop Rx FER test).

Syntax: 32

Return data: Displays the received multi-cast packet count

6.13 Command 33: Transmit multicast packets

This command transmits a specific number of multicast packets. It is used for measuring Rx sensitivity if connected to another radio module, such as a receiver

Syntax: 33 <Len> <Count> <Rate> <Pattern> <ShortPreamble>
<ActSubCh> <ShortGI> <AdvCoding> <TxBfOn> <GFMode> <STBC>
<PowerID> <SignalBw> <BSSID>

Where:

Command parameter	Description
Len	Packet byte length Default is 0x400
Count	Packet count Default is 0x64
Rate	Data rate See Section 8.2 "Data rates" . Default is 4.
Pattern	Packet data pattern Default is 0xB496DEB6
ShortPreamble	Short preamble 0 = long preamble 1 = short preamble (default)
ActSubCh	Active sub channel 00 = low 01 = upper 10 = both 11 = both (default)
ShortGI	Guard interval (GI) length 0 = long GI (default) 1 = short GI
AdvCoding	Advanced coding 0 = BCC (default) 1 = LDPC
TxBfOn	Tx Beamform On 0 = disable (default) 1 = enable
GFMode	Greenfield mode 0 = disable (default) 1 = enable
STBC	Space-time block code 0 = disable (default) 1 = enable
PowerID	Power ID Set to -1. See Section 6.7 "Command 22: Set power at antenna using calibration data" for Power ID mapping

Command parameter	Description
SignalBW	Signal Bandwidth -1 = follows deviceBW as in Section 6.26 "Command 111: Get channel bandwidth" and Section 6.27 "Command 112: Set channel bandwidth" (default) 0x0 = 20 MHz 0x1 = 40 MHz
BSSID	Basic Service Set ID The format is xx.xx.xx.xx.xx.xx. If is not set, all 0xFs will be used.

Example

33 400 64 4 // Transmits 100 multicast packets with 1024-byte payload at data rate of 11 Mbit/s

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

6.14 Command 34: Enable/disable BSSID filter

This command is used to enable/disable BSSID filter for the Wi-Fi receiver test.

Syntax: 34 <mode> <BSSID>

Where:

Command parameter	Description
mode	Number associated with the mode 0 = set the receiver in promiscuous mode 1 = enable BSSID filter 2 = read BSSID register settings (default) 3 = disable promiscuous mode 4 = disable BSSID filter
BSSID	Hex number representing the basic service set ID: xx.xx.xx.xx.xx.xx (x must be a Hex Number)

Example(s)

34 1 66.77.88.99.AA.BB // enables BSSID filter for BSSID = 66.77.88.99.AA.BB

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

6.15 Command 35: Transmit with SIFS gap

This command continuously transmits standard 802.11 packets with an adjustable time gap specified by a configurable Short Interframe Space (SIFS) interval of 0 to 250 μ s.

Syntax: 35 <Enable> <Rate> <AdjustTxBurstGap> <BurstSifsInUs>
<Packet Length> <Pattern> <ShortPreamble> <ActSubCh> <ShortGI>
<AdvCoding> <TxBfOn> <GFMode> <STBC> <DPD> <PowerID> <SignalBw>
<BSSID>

Where:

Command parameter	Description
Enable	Mode enable 0 = disable (default) 1 = enable
Rate	Data Rate See Section 8.2 "Data rates" for mapping. Some data rates are only available in some channel bandwidth modes. Default is 4.
AdjustTxBurstGap	Adjust Tx burst gap 0 = disable (default) 1 = enable
BurstSifsInUs	Burst SIFS (μ s) Minimum is 16 μ s. Maximum is 10 ms.
Packet Length	Packet byte length (in hexadecimal) Maximum length is 15 KB (Kilobytes), or 0x3A98 in hexadecimal.
Pattern	Packet data pattern Default is 0xB496DEB6
ShortPreamble	Short preamble 0 = long preamble 1 = short preamble (default)
ActSubCh	Active sub channel 00 = low 01 = upper 10 = both 11 = both (default)
ShortGI	Short guard interval (GI) 0 = long GI (default) 1 = short GI
AdvCoding	Advanced coding 0 = BCC (default) 1 = LDPC
TxBfOn	Tx Beamform On 0 = disable (default) 1 = enable

Command parameter	Description
GFMode	Greenfield Mode 0 = disable (default) 1 = enable
STBC	Space-time block code 0 = disable (default) 1 = enable
DPD	Deep power down (DPD) 0 = disable (default) 1 = enable
PowerID	Power ID Set to -1. See Section 6.7 "Command 22: Set power at antenna using calibration data" for Power ID mapping.
SignalBW	Signal bandwidth -1 = follows deviceBW as in in Section 6.26 "Command 111: Get channel bandwidth" and Section 6.27 "Command 112: Set channel bandwidth" (default) 0x0 = 20 MHz 0x1 = 40 MHz
BSSID	Basic Service Set ID The format is xx.xx.xx.xx.xx.xx. If is not set, all 0xFs will be used.

Examples

35 1 13 1 20 400 // Transmits a 1024-byte packet at 54 Mbps with a SIFS gap of 20 μ s.

35 1 22 1 45 200 // Transmits a 512-byte packet at HT_MCS7 with a SIFS gap of 45 μ s.

35 0 // Turns off transmission with SIFS Interval.

35 1 4 1 150 100 AA 1 3 0 0 0 0 0 0 -1 1.22.33.44.55.66 // Set duty cycle transmit with SIFS gap of 150 μ s at 11 Mbit/s and 256 bytes with data pattern "AA" and MAC is 11.22.33.44.55.66.

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

6.16 Command 38: Transmit unicast packet

This command transmits a specified number of unicast packets.

Syntax: 38 <Len> <Count> <Rate> <Pattern> <TxBfOn> <SLP>
<SignalBw> <PowerID> <BSSID>

Where:

Command parameter	Description
Len	Packet Length (in hexadecimal) Default is 0x400.
Count	Packet count (in hexadecimal) Default is 0x64.
Rate	Data rate See Section 8.2 "Data rates" for mapping. Some data rates are only available in some channel bandwidth modes. Default is 4.
Pattern	Pattern Default is 0xB496DEB6 for MFG testing
TxBfOn	Tx Beamform on 0 = disable (default) 1 = enable
SLP	Service location protocol (SLP) parameter used to enable/disable steering 0 = disable 1 = enable (default)
SignalBw	Signal bandwidth 0 = 20 MHz 1 = 40 MHz -1 = follow deviceBW as in Section 6.26 "Command 111: Get channel bandwidth" and Section 6.27 "Command 112: Set channel bandwidth" (default)
PowerID	Power ID Set to -1. See Section 6.7 "Command 22: Set power at antenna using calibration data" for Power ID mapping
BSSID	Basic Service Set ID The format is xx.xx.xx.xx.xx.xx. If is not set, all 0xFs will be used.

Example

38 400 64 4 AA 1 1 -1 -1 00.50.43.11.22.33 // Transmits 100 unicast packets with 1024-byte payload at data rate of 11 Mbps, data pattern "AA", enables SLP, and MAC is 00.50.43.11.22.

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

6.17 Command 44: Storage type get/set function

This command gets/sets the storage type for Read/Write during the Labtool session.

Syntax: 44 <Type>

Where:

Command parameter	Description
Type	Storage Type 01 = NO_EPPROM (see configuration calibration file) 10 = OTP

Examples

```
44 // Reads back storage type
```

```
44 1 // Sets the storage type to configuration file
```

Return data: Storage type if there is no option in the command.

6.18 Command 45: Read MAC address from OTP

This command returns the MAC address. Before this operation, the storage type must set to OTP.

Syntax: 45

Return data: MAC address

6.19 Command 46: Write MAC address to OTP

Command 46 writes the MAC address. Before this operation, the storage type must set to OTP.

Syntax: 46 <MAC Address>

Where:

Command parameter	Description
MAC Address	MAC address in xx.xx.xx.xx.xx.xx format

Example

```
46 C0.95.DA.00.43.61 // Writes MAC address C0.95.DA.00.43.61 to OTP
```

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

6.20 Command 53: Set calibration data to storage from text file

This command sets the calibration data to storage from the following calibration data text files:

- *CalWlanDataFile.txt*
- *CalBtDataFile.txt*
- *PwrTble_Path0.txt*

When the storage type is set to OTP, this command loads the calibration data generated from the text files into OTP.

Syntax: 53

Examples

```
44 1 // Set NO_EEPROM as storage type
53 // Generate calibration configuration file "WlanCalData_ext.conf"
    from the text files
```

```
44 2 // Set OTP as storage type
53 // Generate calibration configuration file "WlanCalData_ext.conf"
    from the text files and load into OTP memory
```

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

6.21 Command 54: Get calibration data from storage into file

This command gets the calibration data from storage and saves it to the following text files:

- *CalWlanDataFile_Upload.txt*
- *CalBtDataFile_Upload.txt*
- *PwrTble_Path0_Upload.txt*

These text files allow users to edit parameters, such as XTAL and FEM_Loss.

Syntax: 54

Example

```
44 1 // Set NO_EEPROM as storage type
54 // Generate text files from calibration configuration file
```

Return data:

- *CalWlanDataFile_Upload.txt*
- *CalBtDataFile_Upload.txt*
- *PwrTble_Path0_Upload.txt*

6.22 Command 88: Get firmware/hardware version

This command returns the firmware, hardware, and Labtool versions.

Syntax: 88

Return data:

- DLL Version: 1.0.0.10
- Labtool Version: 1.0.0.10
- FW Version: 16.80.10.127
- Mfg Version: 3.3.0.4
- SoC OR Version: 2.3 Customer ID: 0
- RF OR Version: 1.1 Customer ID: 0

6.23 Command 95: Get XTAL calibration offset

This command gets the 8-bit crystal calibration offset.

Syntax: 95

Return data XTAL: 80

6.24 Command 96: Set XTAL calibration offset

This command sets the 8-bit crystal calibration offset to adjust the frequency offset when viewed on a Vector Signal Analyzer (VSA), a spectrum analyzer, or a frequency counter.

Syntax: 96 <XTAL offset value>

Where:

Command parameter	Description
XTAL offset value	Crystal offset value comprised between 0x00 and 0xFF

Example(s)

96 AA // Sets crystal offset value to 0xAA.

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

6.25 Command 99: Exit Labtool application

This command exits either the Wi-Fi or Bluetooth menu. A second Command 99 will exit the Labtool and close the command prompt window.

Syntax: 99

Return data: --

6.26 Command 111: Get channel bandwidth

This command returns the channel bandwidth in use.

Syntax: 111

Return data: Channel bandwidth

- 0x0 = 20 MHz
- 0x1 = 40 MHz

6.27 Command 112: Set channel bandwidth

This command sets the channel bandwidth.

Syntax: 112 <Bandwidth>

Where:

Command parameter	Description
Bandwidth	Bandwidth 0x0 = 20 MHz 0x1 = 40 MHz

Examples

```
112 0 // Sets the channel bandwidth to 20 MHz
```

```
112 1 // Sets the channel bandwidth to 40 MHz
```

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

6.28 Command 144: Read OTP raw data

This command reads the OTP raw data.

Syntax: 144 <Line>

Where:

Command parameter	Description
Line	Specifies the line to read in OTP

Examples

```
144 0 // Reads all raw data in OTP
```

```
144 1 // Reads raw data of 16th line in OTP
```

Return data: Raw data in OTP

6.29 Command 146: Get the number of calibrations done on OTP

This command is used to check how many times the device was calibrated based on the number of calibration data sets stored in the on-chip OTP memory.

Syntax: 146

Example

```
146 // reads back the number of calibrations stored in the OTP
```

```
## ## // description of what the example does
```

Return data: Number of calibration DONE on OTP: X // (X is the number of calibrations performed)

6.30 Command 147: Get free lines in OTP

This command checks and returns the free lines in OTP.

Syntax: 147

Return data: Free lines on OTP

6.31 Command 148: Write patch block to OTP

This command writes the special binary file patch into OTP. For example, the regulatory power table bin file is programmed into OTP using this command.

Syntax: 148 <Bin File>

Where:

Command parameter	Description
Bin File	Name of the binary file to be written into OTP If left blank, default patch block file "PatchBlockFileOTP.bin" is used.

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

6.32 Command 149: Write user data to OTP

This command writes the user data bin file into OTP.

Syntax: 149 <User Data>

Where:

Command parameter	Description
User Data	User Bin File to be Written into OTP If left blank, default user data file "UserDataFileOTP.bin" is used.

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

6.33 Command 198: Start RSSI data collection

This command is used to start RSSI measurement

Syntax: 198

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

6.34 Command 199: Stop RSSI data collection and report result

This command is used to stop RSSI measurement and report the RSSI result. The RSSI measurement report includes the number of packets received, the measured RSSI value, and the measured noise floor (NF) value.

Syntax: 199

Return data:

- RSSI_packet_count
- RSSI_Val
- RSSI_NF

6.35 Wi-Fi RF test examples

This section shows some manual test examples using the Labtool command sequences for various Wi-Fi RF performance tests.

6.35.1 802.11b test sequences

6.35.1.1 Tx, 2.4 GHz, 20 MHz bandwidth, 11 Mbit/s data rate, Ch 6 at 10 dBm, CCK

Table 4. 802.11b test sequence - Tx, 2.4 GHz, 20 MHz bandwidth, 11 Mbit/s data rate, Ch 6 at 10 dBm, CCK

Command	Description
35	Stop Tx
30 0	Set to 2.4 GHz band
112 0	Set to 20 MHz bandwidth
12 6	Set to Ch 6
22 6 10 1	Set target power level to 10 dBm using calibration data on Ch 6
35 1 4 1 100 400	Tx at 11 Mbps with 100 μ s burst gap and 1024 bytes PSDU length
35	Stop Tx

6.35.1.2 Rx, 2.4 GHz, 20 MHz Bandwidth, Ch 6

Table 5. 802.11b test sequence - Rx, 2.4 GHz, 20 MHz Bandwidth, Ch 6

Command	Description
35	Stop Tx
30 0	Set to 2.4 GHz band
112 0	Set to 20 MHz bandwidth
12 6	Set to Ch 6
31	Clear received packet count
Transmit Wi-Fi packets from tester	
32	Get Rx packet count and clear Rx packet counter

6.35.1.3 RSSI, 2.4 GHz, 20 MHz bandwidth, Ch6

Table 6. 802.11b test sequence - RSSI, 2.4 GHz, 20 MHz Bandwidth, Ch 6

Command	Description
35	Stop Tx
30 0	Set to 2.4 GHz band
112 0	Set to 20 MHz bandwidth
12 6	Set to Ch 6
198	Start RSSI data collection
Transmit Wi-Fi packets from tester	
199	Stop RSSI data collection and report the result

6.35.2 802.11g test sequences

6.35.2.1 Tx, 2.4 GHz, 20 MHz bandwidth, 54 Mbit/s data rate, Ch 6 at 10 dBm, OFDM

Table 7. 802.11g test sequence - Tx, 2.4 GHz, 20 MHz bandwidth, 54 Mbit/s data rate, Ch 6 at 10 dBm, OFDM

Command	Description
35	Stop Tx
30 0	Set to 2.4 GHz band
112 0	Set to 20 MHz bandwidth
12 6	Set to Ch 6
22 6 10 1	Set target power level to 10 dBm using calibration data on Ch 6
35 1 13 1 100 908	Tx at 54 Mbit/s with 100 μ s burst gap and 2312 bytes PSDU length
35	Stop Tx

6.35.2.2 Rx, 2.4 GHz, 20 MHz bandwidth, Ch 6

Table 8. 802.11g test sequence - Rx, 2.4 GHz, 20 MHz Bandwidth, Ch 6

Command	Description
35	Stop Tx
30 0	Set to 2.4 GHz band
112 0	Set to 20 MHz bandwidth
12 6	Set to Ch 6
31	Clear received packet count
Transmit Wi-Fi packets from tester	
32	Get Rx packet count and clear Rx packet counter

6.35.2.3 RSSI, 2.4 GHz, 20 MHz bandwidth, Ch 6

Table 9. 802.11g test sequence - RSSI, 2.4 GHz, 20 MHz Bandwidth, Ch 6

Command	Description
35	Stop Tx
30 0	Set to 2.4 GHz band
112 0	Set to 20 MHz bandwidth
12 6	Set to Ch 6
198	Start RSSI data collection
Transmit Wi-Fi packets from tester	
199	Stop RSSI data collection and report the result

6.35.3 802.11a test sequences

6.35.3.1 Tx, 5 GHz, 20 MHz bandwidth, 54 Mbit/s data rate, Ch 36 at 10 dBm, OFDM

Table 10. 802.11a test sequence - Tx, 5 GHz, 20 MHz bandwidth, 54 Mbit/s data rate, Ch 36 at 10 dBm, OFDM

Command	Description
35	Stop Tx
30 1	Set to 5 GHz band
112 0	Set to 20 MHz bandwidth
12 36	Set to Ch 36
22 6 10 1	Set target power level to 10 dBm using calibration data on Ch 6
35 1 13 1 100 908	Tx at 54 Mbps with 100 μ s burst gap and 2312 bytes PSDU length
35	Stop Tx

6.35.3.2 Rx, 5 GHz, 20 MHz bandwidth, Ch 36

Table 11. 802.11a test sequence - Rx, 5 GHz, 20 MHz bandwidth, Ch 36

Command	Description
35	Stop Tx
30 1	Set to 5 GHz band
112 0	Set to 20 MHz bandwidth
12 36	Set to Ch 36
31	Clear received packet count
Transmit Wi-Fi packets from tester	
32	Get Rx packet count and clear Rx packet counter

6.35.3.3 RSSI, 5 GHz, 20 MHz bandwidth, Ch 36

Table 12. 802.11a test sequence - RSSI, 5 GHz, 40 MHz Bandwidth, Ch 36

Command	Description
35	Stop Tx
30 1	Set to 5 GHz band
112 0	Set to 20 MHz bandwidth
12 36	Set to Ch 36
198	Start RSSI data collection
Transmit Wi-Fi packets from tester	
199	Stop RSSI data collection and report the result

6.35.4 802.11n test sequences

6.35.4.1 Tx, 2.4 GHz, 20 MHz bandwidth, MCS7 data rate, Ch 6 at 10 dBm

Table 13. 802.11n test sequence - Tx, 2.4 GHz, 20 MHz bandwidth, MCS7 data rate, Ch 6 at 10 dBm

Command	Description
35	Stop Tx
30 0	Set to 2.4 GHz band
112 0	Set to 20 MHz bandwidth
12 6	Set to Ch 6
22 6 10 2	Set target power level to 10 dBm using calibration data on Ch 6
35 1 22 1 100 F00	Tx at MCS7 with 100 μ s burst gap and 3840 bytes PSDU length
35	Stop Tx

6.35.4.2 Tx, 2.4 GHz, 40 MHz bandwidth, MCS7 data rate, Ch 6/10 (bonded pair) at 10 dBm

Table 14. 802.11n test sequence - Tx, 2.4 GHz, 40 MHz bandwidth, MCS7 data rate, Ch 6/10 (bonded pair) at 10 dBm

Command	Description
35	Stop Tx
30 0	Set to 2.4 GHz band
112 1	Set to 40 MHz bandwidth
12 6	Set to Ch 6 Ch 6 is lower bonded pair. Ch 10 is higher bonded pair. Set lower channel in 40 MHz mode.
22 6 10 2	Set target power level to 10 dBm using calibration data on Ch 6
35 1 22 1 100 F00	Tx at MCS7 with 100 μ s burst gap and 3840 bytes PSDU length
35	Stop Tx

6.35.4.3 Tx, 5 GHz, 20 MHz bandwidth, MCS7 data rate, Ch 36 at 10 dBm

Table 15. 802.11n test sequence - Tx, 5 GHz, 20 MHz bandwidth, MCS7 data rate, Ch 36 at 10 dBm

Command	Description
35	Stop Tx
30 1	Set to 5 GHz band
112 0	Set to 20 MHz bandwidth
12 36	Set to Ch 36
22 6 10 2	Set target power level to 10 dBm using calibration data on Ch 6
35 1 22 1 100 F00	Tx at MCS7 with 100 μ s burst gap and 3840 bytes PSDU length
35	Stop Tx

6.35.4.4 Tx, 5 GHz, 40 MHz bandwidth, MCS7 data rate, Ch 36/40 (bonded pair) at 10 dBm**Table 16. 802.11n test sequence - Tx, 5 GHz, 40 MHz bandwidth, MCS7 data rate, Ch 36/40 (bonded pair) at 10 dBm**

Command	Description
35	Stop Tx
30 1	Set to 5 GHz band
112 1	Set to 40 MHz bandwidth
12 36	Set to Ch 36 Ch 36 is lower bonded pair. Ch 40 is higher bonded pair. Set lower channel in 40 MHz mode.
22 6 10 2	Set target power level to 10 dBm using calibration data on Ch 6
35 1 22 1 100 F00	Tx at MCS7 with 100 μ s burst gap and 3840 bytes PSDU length
35	Stop Tx

6.35.4.5 Rx, 2.4 GHz, 20 MHz bandwidth, Ch 6**Table 17. 802.11n test sequence - Rx, 2.4 GHz, 20 MHz bandwidth, Ch 6**

Command	Description
35	Stop Tx
30 0	Set to 2.4 GHz band
112 0	Set to 20 MHz bandwidth
12 6	Set to Ch 6
31	Clear received packet count
Transmit Wi-Fi packets from tester	
32	Get Rx packet count and clear Rx packet counter

6.35.4.6 RSSI, 2.4 GHz, 20 MHz bandwidth, Ch 6**Table 18. 802.11n test sequence - RSSI, 2.4 GHz, 20 MHz Bandwidth, Ch 6**

Command	Description
35	Stop Tx
30 0	Set to 2.4 GHz band
112 0	Set to 20 MHz bandwidth
12 6	Set to Ch 6
198	Start RSSI data collection
Transmit Wi-Fi packets from tester	
199	Stop RSSI data collection and report the result

6.35.4.7 Rx, 2.4 GHz, 40 MHz bandwidth, Ch 6/10 (bonded pair)**Table 19. 802.11n test sequence - Rx, 2.4 GHz, 40 MHz bandwidth, Ch 6/10 (bonded pair)**

Command	Description
35	Stop Tx
30 0	Set to 2.4 GHz band
112 1	Set to 40 MHz bandwidth
12 6	Set to Ch 6 Ch 6 is lower bonded pair. Ch 10 is higher bonded pair. Set lower channel in 40 MHz mode.
31	Clear received packet count
Transmit Wi-Fi packets from tester	
32	Get Rx packet count and clear Rx packet counter

6.35.4.8 RSSI, 2.4 GHz, 40 MHz bandwidth, Ch6/10 (bonded pair)**Table 20. 802.11n test sequence - RSSI, 2.4 GHz, 40 MHz Bandwidth, Ch 6/10 (bonded pair)**

Command	Description
35	Stop Tx
30 0	Set to 2.4 GHz band
112 1	Set to 40 MHz bandwidth
12 6	Set to Ch 6 Ch 6 is the lower bonded pair and Ch 10 is the higher bonded pair. Set the lower channel in 40 MHz mode
198	Start RSSI data collection
Transmit Wi-Fi packets from tester	
199	Stop RSSI data collection and report the result

6.35.4.9 Rx, 5 GHz, 20 MHz bandwidth, Ch 36**Table 21. 802.11n test sequence - Rx, 5 GHz, 20 MHz bandwidth, Ch 36**

Command	Description
35	Stop Tx
30 1	Set to 5 GHz band
112 0	Set to 20 MHz bandwidth
12 36	Set to Ch 36
31	Clear received packet count
Transmit Wi-Fi packets from tester	
32	Get Rx packet count and clear Rx packet counter

6.35.4.10 RSSI, 5 GHz, 20 MHz bandwidth, Ch 36**Table 22. 802.11n test sequence - RSSI, 5 GHz, 40 MHz Bandwidth, Ch 36**

Command	Description
35	Stop Tx
30 1	Set to 5 GHz band
112 0	Set to 20 MHz bandwidth
12 36	Set to Ch 36
198	Start RSSI data collection
Transmit Wi-Fi packets from tester	
199	Stop RSSI data collection and report the result

6.35.4.11 Rx, 5 GHz, 40 MHz bandwidth, Ch 36/40 (bonded pair)**Table 23. 802.11n test sequence - Rx, 5 GHz, 40 MHz bandwidth, Ch 36/40 (bonded pair)**

Command	Description
35	Stop Tx
30 1	Set to 5 GHz band
112 1	Set to 40 MHz bandwidth
12 36	Set to Ch 36 Ch 36 is lower bonded pair. Ch 40 is higher bonded pair. Set lower channel in 40 MHz mode.
31	Clear received packet count
Transmit Wi-Fi packets from tester	
32	Get Rx packet count and clear Rx packet counter

6.35.4.12 RSSI, 5 GHz, 40 MHz bandwidth, Ch 36/40 (bonded pair)**Table 24. 802.11n test sequence - RSSI, 5 GHz, 40 MHz Bandwidth, Ch 36/40 (bonded pair)**

Command	Description
35	Stop Tx
30 1	Set to 5 GHz band
112 1	Set to 40 MHz bandwidth
12 36	Set to Ch 36 Ch 36 is the lower bonded pair and Ch 40 is the higher bonded pair. Set the lower channel in 40 MHz mode
198	Start RSSI data collection
Transmit Wi-Fi packets from tester	
199	Stop RSSI data collection and report the result

7 Bluetooth Labtool commands

[Table 25](#) shows a summary of the commands available.

Table 25. Bluetooth Labtool command summary

Command
Command 11: Get Bluetooth channel
Command 12: Set Bluetooth channel
Command 15: Get power level value
Command 16: Set power level value
Command 17: Set continuous modulated Tx
Command 21: Step power level
Command 31: Get Rx result report
Command 32: Set Rx test
Command 45: Read BD address from storage
Command 46: Write BD address to storage
Command 78: Set test mode
Command 80: Reset Bluetooth hardware
Command 88: Get firmware/hardware version
Command 99: Exit Labtool application
Command 113: Get power control class
Command 114: Set power control class
Command 115: Get disable Bluetooth baseband unit power control
Command 116: Set disable Bluetooth baseband unit power control
Command 125: Set Bluetooth LE Tx test
Command 126: Get Bluetooth LE Tx test packet count
Command 127: Set Bluetooth LE Rx test
Command 129: Stop Bluetooth LE test
Command 133: Set Bluetooth LE Tx power
Command 225: Set Tx duty cycle
Command 234: Reload Bluetooth calibration data

7.1 Command 11: Get Bluetooth channel

This command gets the Bluetooth channel in use.

Syntax: 11

Return data: Channel in use

7.2 Command 12: Set Bluetooth channel

This command places the device on a specific channel.

Syntax: 12 <Channel>

Where:

Command parameter	Description
Channel	Channel number (0 to 78)

Example

```
12 7 // Sets Ch 7 (desired channel for testing)
```

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

7.3 Command 15: Get power level value

This command returns the power level value in 0.5 dB steps.

Syntax: 15

Return data: Power level value (in 0.5 dB steps)

7.4 Command 16: Set power level value

This command sets the power level value in 0.5 dB steps.

Syntax: 16 <pwr> <isEDR>

Where:

Command parameter	Description
pwr	Power Level (in 0.5 dB step)
isEDR	Data rate flag 0 = BDR/Bluetooth LE 1 = EDR

Examples

16 2.5 0 // Sets BDR power as 2.5 dBm

16 4 1 // Sets EDR power as 4 dBm for Bluetooth Class 2 and 1 dBm for Bluetooth Class 1.5

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

Note:

The result of this command depends on the Bluetooth Class, FE_Loss, and initial power level set in the calibration data file.

For Bluetooth Class 1.5, Enhanced Data Rate (EDR) Tx power is 3 dBm less than Basic Data Rate (BDR) Tx power.

For Bluetooth Class 2, EDR Tx power is same as BDR Tx power.

7.5 Command 17: Set continuous modulated Tx

This command transmits the continuous modulated signal.

Syntax: 17 <Enable> <DataRate> <PayloadPattern>

Where:

Command parameter	Description
Enable	Mode enable 0 = disable (default) 1 = enable
DataRate	Data Rate 0x1 = 1 Mbit/s (GFSK) (default) 0x2 = 2 Mbit/s (DQPSK) 0x3 = 3 Mbit/s (8PSK)
PayloadPattern	Pattern 00 = 11110000 01 = 0101 10 = PN9

Example

17 1 3 2 // Enables the device to transmit continuous modulated signal with 3 Mbit/s data rate, PN9 payload pattern.

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

7.6 Command 21: Step power level

This command increases/decreases the power level in steps.

Syntax: 21 <Step>

Where:

Command parameter	Description
Step	Step power level (in 0.5 dBm step)

Example

21 -2.5 // Steps power level as -2.5 dBm. After this command, the power level decreases by 2.5 dBm

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

7.7 Command 31: Get Rx result report

This command returns the Rx result report including Bit Error Rate (BER) and Packet Error Rate (PER).

Syntax: 31

Return data:

- BER 0%
- PER 0%

7.8 Command 32: Set Rx test

This command sets the Rx test.

Syntax: 32 <RxChannel> <FrameCount> <PayloadLength> <PacketType>
<PayloadPattern> <TxBdAddress>

Where:

Command parameter	Description
RxChannel	Rx Channel. Default is 10.
FrameCount	Number of frames to Rx. Default is 1000.
PayloadLength	Length of Payload (in bytes). Default is -1 (maximum for PacketType)
PacketType	Packet Type 0x01 = DM1 (GFSK, 1M FEC) 0x03 = DM3 (GFSK, 1M FEC) 0x05 = DM5 (GFSK, 1M FEC) 0x11 = DH1 (GFSK, 1M) 0x13 = DH3 (GFSK, 1M) 0x15 = DH5 (GFSK, 1M) 0x21 = 2-DH1 (DQPSK, 2M) 0x23 = 2-DH3 (DQPSK, 2M) 0x25 = 2-DH5 (DQPSK, 2M) 0x31 = 3-DH1 (8PSK, 3M) 0x33 = 3-DH3 (8PSK, 3M) 0x35 = 3-DH5 (8PSK, 3M) (default)
PayloadPattern	Payload Pattern 0x0 = all 0x01 = all 0x2 = PN9 (default) 0x3 = 0xAA 0x4 = 0xF0
TxBdAddress	BD Address of Tx Default is 00.00.88.C0.FF.EE.

Example

```
32 10 10 -1 35 2 00.00.88.C0.FF.EE
```

Sets Rx Test in Ch 10, 10 packets with maximum payload (-1) in packet type 3-DH5, with pattern PN9, to BD address 00.00.88.C0.FF.EE.s

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

7.9 Command 45: Read BD address from storage

This command returns the Bluetooth Device (BD) address from OTP or a configuration file.

Syntax: 45

Return data: BD address

7.10 Command 46: Write BD address to storage

This command writes the BD address to storage or a configuration file.

Syntax: 46 <BD Address>

Where:

Command parameter	Description
BD Address	Bluetooth device (BD) address in xx.xx.xx.xx.xx.xx format

Example

```
46 C0.95.DA.00.43.61 // Writes BD address into storage/configuration file
```

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

7.11 Command 78: Set test mode

This command enables/disables Bluetooth loopback test mode (link mode).

Syntax: 78 <Enable>

Where:

Command parameter	Description
Enable	Mode enable 0 = disable 1 = enable

Example(s)

```
78 1 // Enables Bluetooth device "in loopback" test mode
```

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

7.12 Command 80: Reset Bluetooth hardware

This command resets the Bluetooth RF block.

Syntax: 80

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

7.13 Command 88: Get firmware/hardware version

This command returns the firmware, hardware, and Labtool versions.

Syntax: 88

Return data:

- DLL version: 1.0.0.10
- Labtool version: 1.0.0.10
- Firmware version: 16.80.10.127
- Mfg Version: 1.0.0.10

7.14 Command 99: Exit Labtool application

This command exits either the Wi-Fi or Bluetooth menu. Enter the command 99 a second time to exit the Labtool application and close the command prompt window.

Syntax: 99

Return data: --

7.15 Command 113: Get power control class

This command gets the power control class in use.

Syntax: 113

Example(s)

```
114 0 // Sets the power control class to Class 2
```

Return data: Value for the power control class

- 0 = Class 2
- 1 = Class 1

Note: For Class 1 operation, IW416 max transmit power is 13 dBm at pin.

7.16 Command 114: Set power control class

This command sets the power control class.

Syntax: 114 <Mode>

Where:

Command parameter	Description
Mode	Power control class mode 0 = Class2 1 = Class 1.5 ^[1]

[1] Class 1.5 refers to Bluetooth class 1 operation. However in this mode, IW416 max transmit power is 13 dBm at pin.

Example

```
114 0 // Sets power control class to Class2
```

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

7.17 Command 115: Get disable Bluetooth baseband unit power control

This command returns Bluetooth baseband unit power control status (enabled/disabled).

Syntax: 115

Return data: Bluetooth baseband unit power control status (enabled/disabled)

7.18 Command 116: Set disable Bluetooth baseband unit power control

This command sets disable Bluetooth baseband unit power control.

Syntax: 116 <Mode>

Where:

Command parameter	Description
Mode	Mode enable 0 = disable (default) 1 = enable

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

7.19 Command 125: Set Bluetooth LE Tx test

This command sets the Bluetooth Low Energy (LE) Tx test.

Syntax: 125 <FreqIndex> <Len> <Pattern> <Phy>

Where:

Command parameter	Description
FreqIndex	Frequency index 0x00 = 2042 MHz 0x01 = 2404 MHz ... 0x39 = 2480 MHz
Len	Payload data length Range: 0 to 37. Default is 37.
Pattern	Payload data pattern 0x0 = PN9 0x1 = 0xF0 0x2 = 0xAA 0x3 = PN15 0x4 = all 1 0x5 = all 0 0x6 = 0x0F 0x7 = 0x55
Phy	Data rate 1 = 1M 2 = 2M 3 = LR8 4 = LR2

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

7.20 Command 126: Get Bluetooth LE Tx test packet count

This command gets the Tx test packet counts after the Bluetooth LE Tx test.

Syntax: 126

Return data: Tx packet count

7.21 Command 127: Set Bluetooth LE Rx test

This command sets Bluetooth Low Energy (LE) Rx test.

Syntax: 127 <FreqIndex>

Where:

Command parameter	Description
FreqIndex	Frequency Index 0x00 = 2042 MHz 0x01 = 2404 MHz ... 0x39 = 2480 MHz

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

7.22 Command 129: Stop Bluetooth LE test

This command stops the Bluetooth LE Tx/Rx test. It is always used after the Bluetooth LE Tx/Rx test ([Section 7.19 "Command 125: Set Bluetooth LE Tx test"](#) and [Section 7.21 "Command 127: Set Bluetooth LE Rx test"](#), respectively).

Syntax: 129

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

7.23 Command 133: Set Bluetooth LE Tx power

This command sets the Bluetooth LE Tx power level value.

Syntax: 133 <pwr>

Where:

Command parameter	Description
pwr	Tx Power (dBm) - Default is 0.

Example(s)

133 6 // Sets Bluetooth LE power level as 6 dBm

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

7.24 Command 225: Set Tx duty cycle

This command sets the transmit duty cycle.

Syntax: 225 <Enable> <PacketType> <PayloadPattern>
<PayloadLenInByte> <HopMode> <Interval> <Whitening>
<ChannelAccessMode>

Where:

Command parameter	Description
Enable	Mode enable 0 = disable (default) 1 = enable
PacketType	Packet type Test Pattern and ACL: 0x01 = DM1 (GFSK, 1M FEC) 0x03 = DM3 (GFSK, 1M FEC) 0x05 = DM5 (GFSK, 1M FEC) 0x11 = DH1 (GFSK, 1M) 0x13 = DH3 (GFSK, 1M) 0x15 = DH5 (GFSK, 1M) 0x21 = 2-DH1 (DQPSK, 2M) 0x23 = 2-DH3 (DQPSK, 2M) 0x25 = 2-DH5 (DQPSK, 2M) 0x31 = 3-DH1 (8PSK, 3M) 0x33 = 3-DH3 (8PSK, 3M) 0x35 = 3-DH5 (8PSK, 3M) SCO: 0x11 = HV1 (GFSK, 1M) (default) 0x12 = HV2 (GFSK, 1M) 0x13 = HV3 (GFSK, 1M) eSCO: 0x13 = EV3 (DQPSK, 1M) 0x14 = EV4 (DQPSK, 1M) 0x15 = EV5 (DQPSK, 1M) 0x23 = 2-EV3 (DQPSK, 2M) 0x25 = 2-EV5 (DQPSK, 2M) 0x33 = 3-EV3 (8PSK, 2M) 0x35 = 3-EV5 (8PSK, 2M)
PayloadPattern	Payload data pattern 0x0 = all 0 0x1 = all 1 0x2 = PN9 (default) 0x3 = 0xAA 0x4 = 0xF0 0x5 = PRBS 0x6 = PRBS SCO 0x7 = PRBS eSCO
PayloadLenInByte	Packet type dependent Default is -1 (maximum possible)

Command parameter	Description
HopMode	0 = fixed channel (default) 1 = random hopping
Interval	User-defined test interval. The default is 1
Whitening	Whitening whole packet 0 = disable (default) 1 = enable
ChannelAccessMode	Channel access mode Specify if a channel hopped into a hop mode. Default is 0x7FFFFFFFFFFFFFFFFFFFFF (all on) Bit[78]: Ch 78 ... Bit[0]: Ch 0 0 = off 1 = on

Return data: xx or

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

7.25 Command 234: Reload Bluetooth calibration data

This command reloads the Bluetooth calibration data to make the modified Bluetooth calibration data valid after the Bluetooth calibration data in “*WlanCalData_ext.conf*” is modified.

Syntax: 234

Return data:

- Successful command: all-0 status byte (0x00000000)
- Failed command: non-0 status byte (0x00000001 to 0xFFFFFFFF)

7.26 Bluetooth RF test examples

This section shows some examples of Labtool command sequences for various Bluetooth RF tests.

7.26.1 Bluetooth BDR test sequences

7.26.1.1 BDR Tx, Ch 0 at 4 dBm, DH1 packet type

Table 26. Bluetooth test sequence - BDR Tx, Ch 0 at 4 dBm, DH1 packet type

Command	Description
234	Reload Bluetooth calibration data
80	Reset Bluetooth RF block
116 1	Set disable Bluetooth baseband power control
114 1	Set to Class 1.5
16 4 0	Set to BDR power to 4 dBm
12 0	Set to Ch 0
225 1 11	Tx with DH1 packet type
225	Stop Tx

7.26.1.2 BDR Rx, Ch 10

Table 27. Bluetooth BDR test sequence - BDR Rx, Ch 10

Command	Description
234	Reload Bluetooth calibration data
80	Reset Bluetooth RF block
Connect system to Bluetooth tester:	
<ul style="list-style-type: none"> • Set generator file • Set Bluetooth channel to Ch 10 • Set signal level at -70 dBm 	
32 10 10 -1 15 2 00.00.88.C0.FF.EE	
Receive 10 packets of DH5 with maximum payload length, PN9 pattern on Ch 10, BD address is 00.00.88.C0.FF.EE	
Transmit packets from Bluetooth tester	
31	Return Rx result report

7.26.2 Bluetooth EDR test sequences

7.26.2.1 EDR Tx, Ch 78 at 4 dBm, 3-DH5 packet type

Table 28. Bluetooth test sequence - EDR Tx, Ch 78 at 4 dBm, 3-DH5 packet type

Command	Description
234	Reload Bluetooth calibration data
80	Reset Bluetooth RF block
116 1	Set disable Bluetooth baseband power control
114 1	Set to Class 1.5
16 7 1	Set to EDR power to 4 dBm
12 78	Set to Ch 78
225 1 35	Tx with 3-DH5 packet type
225	Stop Tx

7.26.2.2 EDR Rx, Ch 10

Table 29. Bluetooth test sequence - EDR Rx, Ch 10

Command	Description
234	Reload Bluetooth calibration data
80	Reset Bluetooth RF block
Connect system to Bluetooth tester:	
<ul style="list-style-type: none"> • Set generator file • Set Bluetooth channel to Ch 10 • Set signal level at -70 dBm 	
32 10 10 -1 35 2 00.00.88.C0.FF.EE	
Receive 10 packets of 3-DH5 with maximum payload length, PN9 pattern on Ch 10, BD address is 00.00.88.C0.FF.EE	
Transmit packets from Bluetooth tester	
31	Return Rx result report

7.26.3 Bluetooth LE test sequences

7.26.3.1 Bluetooth LE Tx, Ch 39 at 6 dBm

Table 30. Bluetooth test sequence - Bluetooth LE Tx, Ch 39 at 6 dBm, 1M

Command	Description
234	Reload Bluetooth calibration data
80	Reset Bluetooth RF block
133 6	Set LE power to 6 dBm
125 39 37 0 1	Tx on Ch 39, packet length 37, packet pattern PN9, data rate 1M
129	Stop Tx
126	Get Tx packet count

Table 31. Bluetooth test sequence - Bluetooth LE Tx, Ch 39 at 6 dBm, 2M

Command	Description
234	Reload Bluetooth calibration data
80	Reset Bluetooth RF block
133 6	Set LE power to 6 dBm
125 39 37 0 2	Tx on Ch 39, packet length 37, packet pattern PN9, data rate 2M
129	Stop Tx
126	Get Tx packet count

Table 32. Bluetooth test sequence - Bluetooth LE Tx, Ch 39 at 6 dBm, LR8

Command	Description
234	Reload Bluetooth calibration data
80	Reset Bluetooth RF block
133 6	Set LE power to 6 dBm
125 39 37 0 3	Tx on Ch 39, packet length 37, packet pattern PN9, data rate LR8
129	Stop Tx
126	Get Tx packet count

Table 33. Bluetooth test sequence - Bluetooth LE Tx, Ch 39 at 6 dBm, LR2

Command	Description
234	Reload Bluetooth calibration data
80	Reset Bluetooth RF block
133 6	Set LE power to 6 dBm
125 39 37 0 4	Tx on Ch 39, packet length 37, packet pattern PN9, data rate LR2
129	Stop Tx
126	Get Tx packet count

7.26.3.2 Bluetooth LE Rx, Ch 39

Table 34. Bluetooth test sequence - Bluetooth LE Rx, Ch 39, 1M

Command	Description
234	Reload Bluetooth calibration data
80	Reset Bluetooth RF block
127 39 1	Rx on Ch 39, 1M
Configure Bluetooth tester to transmit x number of packets	
129	Stop Rx test
126	Get Rx test error

Table 35. Bluetooth test sequence - Bluetooth LE Rx, Ch 39, 2M

Command	Description
234	Reload Bluetooth calibration data
80	Reset Bluetooth RF block
127 39 2	Rx on Ch 39, 2M
Configure Bluetooth tester to transmit x number of packets	
129	Stop Rx test
126	Get Rx test error

Table 36. Bluetooth test sequence - Bluetooth LE Rx, Ch 39, LR8

Command	Description
234	Reload Bluetooth calibration data
80	Reset Bluetooth RF block
127 39 3	Rx on Ch 39, LR8
Configure Bluetooth tester to transmit x number of packets	
129	Stop Rx test
126	Get Rx test error

Table 37. Bluetooth test sequence - Bluetooth LE Rx, Ch 39, LR2

Command	Description
234	Reload Bluetooth calibration data
80	Reset Bluetooth RF block
127 39 4	Rx on Ch 39, LR2
Configure Bluetooth tester to transmit x number of packets	
129	Stop Rx test
126	Get Rx test error

8 Conversion tables

This section provides the conversion tables for RF channels and data rates.

8.1 RF channels

[Table 38](#) shows the RF conversion values for 2.4 GHz and 5 GHz channels.

Table 38. RF channel conversion

Channel	Frequency	Channel	Frequency	Channel	Frequency
2.4 GHz channels					
1	2412 MHz	2	2417 MHz	3	2442 MHz
4	2427 MHz	5	2432 MHz	6	2437 MHz
7	2442 MHz	8	2447 MHz	9	2452 MHz
10	2457 MHz	11	2462 MHz	12	2467 MHz
13	2472 MHz	—	—	—	—
5 GHz channels					
8 (JP)	5040 MHz	12 (JP)	5060 MHz	16 (JP)	5080 MHz
34 (JP)	5170 MHz	38 (JP)	5190 MHz	42 (JP)	5210 MHz
46 (JP)	5230 MHz	184 (JP)	5920 MHz	188 (JP)	4940 MHz
192 (JP)	4960 MHz	196 (JP)	4980 MHz	—	—
36	5180 MHz	40	5200 MHz	44	5220 MHz
48	5240 MHz	52	5260 MHz	56	5280 MHz
60	5300 MHz	64	5320 MHz	100	5500 MHz
104	5520 MHz	108	5540 MHz	112	5560 MHz
116	5580 MHz	120	5600 MHz	124	5620 MHz
128	5640 MHz	132	5660 MHz	136	5680 MHz
140	5700 MHz	149	5645 MHz	153	5765 MHz
157	5785 MHz	161	5805 MHz	165	5825 MHz

8.2 Data rates

[Table 39](#) provides the data rate values.

Table 39. Data rate values

ID	Data rate	ID	Data rate	ID	Data rate	ID	Data rate
1	1 Mbit/s	7	9 Mbit/s	13	54 Mbit/s	19	HT_MCS4
2	2 Mbit/s	8	12 Mbit/s	14	Reserved	20	HT_MCS5
3	5.5 Mbit/s	9	18 Mbit/s	15	HT_MCS0	21	HT_MCS6
4	11 Mbit/s	10	24 Mbit/s	16	HT_MCS1	22	HT_MCS7
5	Reserved	11	36 Mbit/s	17	HT_MCS2	—	—
6	6 Mbit/s	12	48 Mbit/s	18	HT_MCS3	—	—

9 Acronyms and abbreviations

Table 40. Acronyms and abbreviations

Acronym	Definition
ACL	Access Control List
API	Application Programming Interface
BCC	Block Check Character
BD	Bluetooth Device
BDR	Basic Data Rate
BER	Bit Error Rate
BSS	Basic Service Set
BSSID	Basic Service Set ID
CCK	Complementary Code Keying
CLI	Command Line Interface
CW	Continuous Wave
DPD	Deep Power Down
DQPSK	Differential Quadrature Phase Shift Keying
DUT	Device Under Test
EDR	Enhanced Data Rate
EEPROM	Electrically Erasable Programmable Read Only Memory
eSCO	Extended Synchronous Connection
FAE	Field Application Engineer
FER	Frame Error Rate
GCC	GNU Compiler Collection
GFSK	Gaussian Frequency Shift Keying
GI	Guard Interval
GNU	Gnu's Not Unix
IP	Internet Protocol
LDPC	Low-Density Parity Check
MAC	Media/Medium Access Controller
MCS	Modulation and Coding Scheme
MFG	Manufacturing
NF	Noise floor
OFDM	Orthogonal Frequency Division Multiplexing
OTP	One Time Programmable
PC	Personal Computer
PCIe	Peripheral Component Interconnect Express
PER	Packet Error Rate

Table 40. Acronyms and abbreviations...continued

Acronym	Definition
PLCP	Physical Layer Convergence Protocol
PRBS	Pseudo-Random Binary Sequence
PSDU	PLCP Service Data Unit
PSK	Phase Shift Keying
RF	Radio Frequency
RSSI	Received Signal Strength Indicator
Rx	Receive
SCO	Synchronous Connection Oriented
SDIO	Secure Digital Input/Output
SIFS	Short Interframe Space
SLP	Service location protocol
SoC	System-on-Chip
STBC	Space-Time Block Code
TCP	Transmission Control Protocol
Tx	Transmit
UART	Universal Asynchronous Receive/Transmitter
UDP	User Datagram Protocol
USB	Universal Serial Bus
VHT	Very High Throughput
VSA	Vector Signal Analyzer
Wi-Fi	Hardware implementation of IEEE 802.11 for wireless connectivity
WLAN	Wireless Local Area Network
XTAL	Crystal

10 Legal information

10.1 Definitions

Draft — A draft status on a document indicates that the content is still under internal review and subject to formal approval, which may result in modifications or additions. NXP Semiconductors does not give any representations or warranties as to the accuracy or completeness of information included in a draft version of a document and shall have no liability for the consequences of use of such information.

10.2 Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. NXP Semiconductors takes no responsibility for the content in this document if provided by an information source outside of NXP Semiconductors. In no event shall NXP Semiconductors be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory. Notwithstanding any damages that customer might incur for any reason whatsoever, NXP Semiconductors' aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the Terms and conditions of commercial sale of NXP Semiconductors.

Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors and its suppliers accept no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification. Customers are responsible for the design and operation of their applications and products using NXP Semiconductors products, and NXP Semiconductors accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the NXP Semiconductors product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products. NXP Semiconductors does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or

the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using NXP Semiconductors products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). NXP does not accept any liability in this respect.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

Evaluation products — This product is provided on an "as is" and "with all faults" basis for evaluation purposes only. NXP Semiconductors, its affiliates and their suppliers expressly disclaim all warranties, whether express, implied or statutory, including but not limited to the implied warranties of non-infringement, merchantability and fitness for a particular purpose. The entire risk as to the quality, or arising out of the use or performance, of this product remains with customer. In no event shall NXP Semiconductors, its affiliates or their suppliers be liable to customer for any special, indirect, consequential, punitive or incidental damages (including without limitation damages for loss of business, business interruption, loss of use, loss of data or information, and the like) arising out of the use of or inability to use the product, whether or not based on tort (including negligence), strict liability, breach of contract, breach of warranty or any other theory, even if advised of the possibility of such damages. Notwithstanding any damages that customer might incur for any reason whatsoever (including without limitation, all damages referenced above and all direct or general damages), the entire liability of NXP Semiconductors, its affiliates and their suppliers and customer's exclusive remedy for all of the foregoing shall be limited to actual damages incurred by customer based on reasonable reliance up to the greater of the amount actually paid by customer for the product or five dollars (US\$5.00). The foregoing limitations, exclusions and disclaimers shall apply to the maximum extent permitted by applicable law, even if any remedy fails of its essential purpose.

Translations — A non-English (translated) version of a document is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

Security — Customer understands that all NXP products may be subject to unidentified or documented vulnerabilities. Customer is responsible for the design and operation of its applications and products throughout their lifecycles to reduce the effect of these vulnerabilities on customer's applications and products. Customer's responsibility also extends to other open and/or proprietary technologies supported by NXP products for use in customer's applications. NXP accepts no liability for any vulnerability. Customer should regularly check security updates from NXP and follow up appropriately. Customer shall select products with security features that best meet rules, regulations, and standards of the intended application and make the ultimate design decisions regarding its products and is solely responsible for compliance with all legal, regulatory, and security related requirements concerning its products, regardless of any information or support that may be provided by NXP. NXP has a Product Security Incident Response Team (PSIRT) (reachable at PSIRT@nxp.com) that manages the investigation, reporting, and solution release to security vulnerabilities of NXP products.

10.3 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

NXP — wordmark and logo are trademarks of NXP B.V.

Tables

Tab. 1.	References	3	Tab. 19.	802.11n test sequence - Rx, 2.4 GHz, 40 MHz bandwidth, Ch 6/10 (bonded pair)	41
Tab. 2.	Wi-Fi Labtool command summary	17	Tab. 20.	802.11n test sequence - RSSI, 2.4 GHz, 40 MHz Bandwidth, Ch 6/10 (bonded pair)	41
Tab. 3.	RF data rates	20	Tab. 21.	802.11n test sequence - Rx, 5 GHz, 20 MHz bandwidth, Ch 36	42
Tab. 4.	802.11b test sequence - Tx, 2.4 GHz, 20 MHz bandwidth, 11 Mbit/s data rate, Ch 6 at 10 dBm, CCK	36	Tab. 22.	802.11n test sequence - RSSI, 5 GHz, 40 MHz Bandwidth, Ch 36	42
Tab. 5.	802.11b test sequence - Rx, 2.4 GHz, 20 MHz Bandwidth, Ch 6	36	Tab. 23.	802.11n test sequence - Rx, 5 GHz, 40 MHz bandwidth, Ch 36/40 (bonded pair)	42
Tab. 6.	802.11b test sequence - RSSI, 2.4 GHz, 20 MHz Bandwidth, Ch 6	36	Tab. 24.	802.11n test sequence - RSSI, 5 GHz, 40 MHz Bandwidth, Ch 36/40 (bonded pair)	43
Tab. 7.	802.11g test sequence - Tx, 2.4 GHz, 20 MHz bandwidth, 54 Mbit/s data rate, Ch 6 at 10 dBm, OFDM	37	Tab. 25.	Bluetooth Labtool command summary	44
Tab. 8.	802.11g test sequence - Rx, 2.4 GHz, 20 MHz Bandwidth, Ch 6	37	Tab. 26.	Bluetooth test sequence - BDR Tx, Ch 0 at 4 dBm, DH1 packet type	57
Tab. 9.	802.11g test sequence - RSSI, 2.4 GHz, 20 MHz Bandwidth, Ch 6	37	Tab. 27.	Bluetooth BDR test sequence - BDR Rx, Ch 10	57
Tab. 10.	802.11a test sequence - Tx, 5 GHz, 20 MHz bandwidth, 54 Mbit/s data rate, Ch 36 at 10 dBm, OFDM	38	Tab. 28.	Bluetooth test sequence - EDR Tx, Ch 78 at 4 dBm, 3-DH5 packet type	58
Tab. 11.	802.11a test sequence - Rx, 5 GHz, 20 MHz bandwidth, Ch 36	38	Tab. 29.	Bluetooth test sequence - EDR Rx, Ch 10	58
Tab. 12.	802.11a test sequence - RSSI, 5 GHz, 40 MHz Bandwidth, Ch 36	38	Tab. 30.	Bluetooth test sequence - Bluetooth LE Tx, Ch 39 at 6 dBm, 1M	59
Tab. 13.	802.11n test sequence - Tx, 2.4 GHz, 20 MHz bandwidth, MCS7 data rate, Ch 6 at 10 dBm	39	Tab. 31.	Bluetooth test sequence - Bluetooth LE Tx, Ch 39 at 6 dBm, 2M	59
Tab. 14.	802.11n test sequence - Tx, 2.4 GHz, 40 MHz bandwidth, MCS7 data rate, Ch 6/10 (bonded pair) at 10 dBm	39	Tab. 32.	Bluetooth test sequence - Bluetooth LE Tx, Ch 39 at 6 dBm, LR8	59
Tab. 15.	802.11n test sequence - Tx, 5 GHz, 20 MHz bandwidth, MCS7 data rate, Ch 36 at 10 dBm	39	Tab. 33.	Bluetooth test sequence - Bluetooth LE Tx, Ch 39 at 6 dBm, LR2	60
Tab. 16.	802.11n test sequence - Tx, 5 GHz, 40 MHz bandwidth, MCS7 data rate, Ch 36/40 (bonded pair) at 10 dBm	40	Tab. 34.	Bluetooth test sequence - Bluetooth LE Rx, Ch 39, 1M	60
Tab. 17.	802.11n test sequence - Rx, 2.4 GHz, 20 MHz bandwidth, Ch 6	40	Tab. 35.	Bluetooth test sequence - Bluetooth LE Rx, Ch 39, 2M	60
Tab. 18.	802.11n test sequence - RSSI, 2.4 GHz, 20 MHz Bandwidth, Ch 6	40	Tab. 36.	Bluetooth test sequence - Bluetooth LE Rx, Ch 39, LR8	60
			Tab. 37.	Bluetooth test sequence - Bluetooth LE Rx, Ch 39, LR2	61
			Tab. 38.	RF channel conversion	62
			Tab. 39.	Data rate values	62
			Tab. 40.	Acronyms and abbreviations	63

Figures

Fig. 1.	Labtool Test Setup	4	Fig. 6.	Labtool start window	14
Fig. 2.	FwImage directory content	8	Fig. 7.	Command 88 execution	15
Fig. 3.	Labtool Repository Content	11	Fig. 8.	Status – Successful command execution	16
Fig. 4.	Calibration data file (.conf)	13	Fig. 9.	Status – Failed command execution	16
Fig. 5.	WlanCalData_Ext.conf in Labtool directory	13			

Contents

1	Introduction	3			
1.1	Purpose and scope	3	6.21	Command 54: Get calibration data from storage into file	31
1.2	References	3	6.22	Command 88: Get firmware/hardware version	31
2	Labtool test setup	4	6.23	Command 95: Get XTAL calibration offset	31
3	Device under test setup	5	6.24	Command 96: Set XTAL calibration offset	32
3.1	Linux Ubuntu installation	5	6.25	Command 99: Exit Labtool application	32
3.2	Linux bridge computer configuration	6	6.26	Command 111: Get channel bandwidth	32
3.3	Software download	6	6.27	Command 112: Set channel bandwidth	33
3.3.1	Production software release package	6	6.28	Command 144: Read OTP raw data	33
3.3.2	MFG software release package	6	6.29	Command 146: Get the number of calibrations done on OTP	33
3.4	Building IW416 drivers	7	6.30	Command 147: Get free lines in OTP	34
3.5	Building MFG bridge application and copying MFG firmware	8	6.31	Command 148: Write patch block to OTP	34
3.6	Loading IW416 driver and executing the firmware and bridge	9	6.32	Command 149: Write user data to OTP	34
4	Windows PC setup	11	6.33	Command 198: Start RSSI data collection	35
4.1	Labtool setup on Windows PC	11	6.34	Command 199: Stop RSSI data collection and report result	35
4.2	Calibration data	13	6.35	Wi-Fi RF test examples	36
5	Labtool usage	14	6.35.1	802.11b test sequences	36
5.1	Starting Labtool	14	6.35.1.1	Tx, 2.4 GHz, 20 MHz bandwidth, 11 Mbit/s data rate, Ch 6 at 10 dBm, CCK	36
5.2	Running commands	16	6.35.1.2	Rx, 2.4 GHz, 20 MHz Bandwidth, Ch 6	36
5.3	Closing Labtool	16	6.35.1.3	RSSI, 2.4 GHz, 20 MHz bandwidth, Ch6	36
5.4	Getting help	16	6.35.2	802.11g test sequences	37
6	Wi-Fi Labtool commands	17	6.35.2.1	Tx, 2.4 GHz, 20 MHz bandwidth, 54 Mbit/s data rate, Ch 6 at 10 dBm, OFDM	37
6.1	Command 9: Get Tx/Rx antenna configuration (valid when Antenna diversity is supported)	18	6.35.2.2	Rx, 2.4 GHz, 20 MHz bandwidth, Ch 6	37
6.2	Command 10: Set Tx/Rx antenna configuration (valid when Antenna diversity is supported)	18	6.35.2.3	RSSI, 2.4 GHz, 20 MHz bandwidth, Ch 6	37
6.3	Command 11: Get RF channel configuration	19	6.35.3	802.11a test sequences	38
6.4	Command 12: Set RF channel configuration	19	6.35.3.1	Tx, 5 GHz, 20 MHz bandwidth, 54 Mbit/s data rate, Ch 36 at 10 dBm, OFDM	38
6.5	Command 13: Get RF data rate	20	6.35.3.2	Rx, 5 GHz, 20 MHz bandwidth, Ch 36	38
6.6	Command 18: Set transmitter in CW mode	21	6.35.3.3	RSSI, 5 GHz, 20 MHz bandwidth, Ch 36	38
6.7	Command 22: Set power at antenna using calibration data	21	6.35.4	802.11n test sequences	39
6.8	Command 25: Transmit with duty cycle Tx mode	22	6.35.4.1	Tx, 2.4 GHz, 20 MHz bandwidth, MCS7 data rate, Ch 6 at 10 dBm	39
6.9	Command 29: Get RF band configuration	23	6.35.4.2	Tx, 2.4 GHz, 40 MHz bandwidth, MCS7 data rate, Ch 6/10 (bonded pair) at 10 dBm	39
6.10	Command 30: Set RF band configuration	23	6.35.4.3	Tx, 5 GHz, 20 MHz bandwidth, MCS7 data rate, Ch 36 at 10 dBm	39
6.11	Command 31: Clear Rx packet count	23	6.35.4.4	Tx, 5 GHz, 40 MHz bandwidth, MCS7 data rate, Ch 36/40 (bonded pair) at 10 dBm	40
6.12	Command 32: Get and clear Rx packet count	23	6.35.4.5	Rx, 2.4 GHz, 20 MHz bandwidth, Ch 6	40
6.13	Command 33: Transmit multicast packets	24	6.35.4.6	RSSI, 2.4 GHz, 20 MHz bandwidth, Ch 6	40
6.14	Command 34: Enable/disable BSSID filter	25	6.35.4.7	Rx, 2.4 GHz, 40 MHz bandwidth, Ch 6/10 (bonded pair)	41
6.15	Command 35: Transmit with SIFS gap	26	6.35.4.8	RSSI, 2.4 GHz, 40 MHz bandwidth, Ch6/10 (bonded pair)	41
6.16	Command 38: Transmit unicast packet	28	6.35.4.9	Rx, 5 GHz, 20 MHz bandwidth, Ch 36	42
6.17	Command 44: Storage type get/set function	29	6.35.4.10	RSSI, 5 GHz, 20 MHz bandwidth, Ch 36	42
6.18	Command 45: Read MAC address from OTP	29	6.35.4.11	Rx, 5 GHz, 40 MHz bandwidth, Ch 36/40 (bonded pair)	42
6.19	Command 46: Write MAC address to OTP	30	6.35.4.12	RSSI, 5 GHz, 40 MHz bandwidth, Ch 36/40 (bonded pair)	43
6.20	Command 53: Set calibration data to storage from text file	30	7	Bluetooth Labtool commands	44

7.1	Command 11: Get Bluetooth channel	45
7.2	Command 12: Set Bluetooth channel	45
7.3	Command 15: Get power level value	45
7.4	Command 16: Set power level value	46
7.5	Command 17: Set continuous modulated Tx	47
7.6	Command 21: Step power level	47
7.7	Command 31: Get Rx result report	48
7.8	Command 32: Set Rx test	49
7.9	Command 45: Read BD address from storage	50
7.10	Command 46: Write BD address to storage	50
7.11	Command 78: Set test mode	50
7.12	Command 80: Reset Bluetooth hardware	51
7.13	Command 88: Get firmware/hardware version	51
7.14	Command 99: Exit Labtool application	51
7.15	Command 113: Get power control class	51
7.16	Command 114: Set power control class	52
7.17	Command 115: Get disable Bluetooth baseband unit power control	52
7.18	Command 116: Set disable Bluetooth baseband unit power control	52
7.19	Command 125: Set Bluetooth LE Tx test	53
7.20	Command 126: Get Bluetooth LE Tx test packet count	53
7.21	Command 127: Set Bluetooth LE Rx test	54
7.22	Command 129: Stop Bluetooth LE test	54
7.23	Command 133: Set Bluetooth LE Tx power	54
7.24	Command 225: Set Tx duty cycle	55
7.25	Command 234: Reload Bluetooth calibration data	56
7.26	Bluetooth RF test examples	57
7.26.1	Bluetooth BDR test sequences	57
7.26.1.1	BDR Tx, Ch 0 at 4 dBm, DH1 packet type	57
7.26.1.2	BDR Rx, Ch 10	57
7.26.2	Bluetooth EDR test sequences	58
7.26.2.1	EDR Tx, Ch 78 at 4 dBm, 3-DH5 packet type	58
7.26.2.2	EDR Rx, Ch 10	58
7.26.3	Bluetooth LE test sequences	59
7.26.3.1	Bluetooth LE Tx, Ch 39 at 6 dBm	59
7.26.3.2	Bluetooth LE Rx, Ch 39	60
8	Conversion tables	62
8.1	RF channels	62
8.2	Data rates	62
9	Acronyms and abbreviations	63
10	Legal information	65

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.

© NXP B.V. 2021.

All rights reserved.

For more information, please visit: <http://www.nxp.com>

For sales office addresses, please send an email to: salesaddresses@nxp.com

Date of release: 2 February 2021
Document identifier: UM11434