

FIKRATAK DIGITAL · TECH ENTREPRENEURSHIP 2026

Nazrah

Remediation & Hardening Plan

A phased, copy-paste-ready execution plan for Claude Code (with Gemini Pro as verification helper) to fix every finding from the Impeccable audit and lift the score from **12/20** → **19/20**.

PROJECT

nazrah-main.algarni.online

STACK

Next.js (App Router) · TypeScript · Tailwind · next-intl · Framer Motion

ISSUE BUDGET

P0: 1 · P1: 6 · P2: 7 · P3: 4

PREPARED FOR

Mohammed Abotargah · Lead Engineer

Executive Summary

This plan converts your Impeccable audit (12/20) into a sequential, Claude-Code-driven repair pipeline. Each finding maps to a single prompt block you can paste directly into Claude Code inside the Antigravity IDE. Where verification is risky or repetitive (e.g. confirming every form input has matching `htmlFor/id` pairs), a follow-up Gemini Pro verification prompt is provided.

#	Dimension	Current	After Plan	Δ
1	Accessibility	2 / 4	4 / 4	+2
2	Performance	2 / 4	4 / 4	+2
3	Theming	3 / 4	4 / 4	+1
4	Responsive Design	3 / 4	4 / 4	+1
5	Anti-Patterns	2 / 4	3 / 4	+1
	TOTAL	12 / 20	19 / 20	+7

How to use this document

Work through the phases in order. Each fix block contains: **(1) Context** — what / why, **(2) Claude Code prompt** — paste verbatim, **(3) Verification** — usually a Gemini Pro prompt or a manual smoke-test.

Phase	Title	Scope	Time
Phase 0	Pre-flight	Branch, baseline, lock dependencies.	5 min
Phase 1	P0 — Critical fix	React hook violation in HeroSection.	10 min
Phase 2	P1 — Accessibility	Labels, focus-visible, skip link, ARIA.	60 min
Phase 3	P1 — Performance	Replace <code></code> with <code>next/image</code> .	25 min
Phase 4	P2 — Theming	WhatsApp token + dot-grid <code>theme()</code> call.	15 min
Phase 5	P2 — Responsive	Footer breakpoint + hero h1 mobile sizing.	15 min
Phase 6	P2 — Polish	Emoji → SVG icons, form success role.	25 min
Phase 7	P3 — Anti-patterns	Trim stagger, GPU-promote blur blob.	20 min
Phase 8	Verification	Re-run Impeccable + Gemini Pro sweep.	20 min

Phase 0 • Pre-flight

Before any edits, create a dedicated branch so each fix can be cherry-picked or reverted. Also baseline the current bundle so you can prove the wins.

Claude Code prompt — open the workspace

You are working inside the repository for nazrah-main.algarni.online.
The stack is Next.js App Router + TypeScript + Tailwind + next-intl + Framer Motion.

Task: prepare the repository for an Impeccable audit fix pass.

1. Confirm the current git branch and working tree state.
2. Create and switch to a new branch named: fix/impeccable-audit-pass-1
3. Run a baseline build with: pnpm build (or npm run build if pnpm is missing)
4. Print: the Node version, the Next.js version from package.json, and the list of files under apps/web/src/components/sections and apps/web/src/app/[locale].
5. Do NOT modify any source file yet. Just report.

When finished, give me a single-paragraph summary of what you observed and flag anything that already looks broken or unusual.

Verification (manual)

- ✓ git status is clean on the new branch.
- ✓ Build completes with the same warnings you already see in production.
- ✓ You have the file inventory in your scrollbar before Phase 1.

Phase 1 · P0 — Critical React Hook Violation

P0 Hook called inside .map() — HeroSection.tsx:135

File: apps/web/src/components/sections/HeroSection.tsx

Why it matters: `useTranslations('home.stats')` is being called inside a `.map()` callback. This breaks the Rules of Hooks — in React Strict Mode it throws; in production it produces inconsistent renders and can corrupt the next-intl cache.

Goal: Hoist the hook to the component body and reference the returned `t()` function inside the loop.

Claude Code prompt

Open `apps/web/src/components/sections/HeroSection.tsx`.

Audit finding (P0): on line ~135, `useTranslations('home.stats')` is being called inside a `.map()` callback. This violates the React Rules of Hooks.

Fix it precisely as follows:

1. At the very top of the `HeroSection` component body (above the `return /` above any JSX), add EXACTLY one new line:
`const ts = useTranslations('home.stats');`
2. Inside the `stats.map()` callback, replace every call that looks like
`useTranslations('home.stats')(labelKey as never)`
or
`useTranslations('home.stats')(labelKey)`
with:
`ts(labelKey as never)`
3. Do NOT change any other line. Keep all existing imports, animation wrappers, and class names exactly as they are.
4. After editing, run: `pnpm tsc --noEmit`
Paste any TypeScript errors you see. If clean, run: `pnpm lint` and paste the result.
5. Show me a clean unified diff of the file before you finish.

Gemini Pro verification (paste in Gemini)

Act as a senior React/Next.js reviewer.

Below is a diff for `HeroSection.tsx` after a fix for "hook called inside `.map()`".
Verify:

- (a) `useTranslations` is called exactly once at the top level of the component (not inside any callback, loop, conditional, or nested function).
- (b) The returned `t`-function (named ``ts``) is the only thing used inside `.map()`.
- (c) No other hooks were accidentally moved or duplicated.
- (d) TypeScript types of the `.map()` arguments are preserved.

If anything is wrong, return a corrected diff. If everything is correct, reply with: "VERIFIED: hook hoisted correctly."

<paste the diff here>

Phase 2 · P1 — Accessibility Hardening

Five accessibility findings share one mega-prompt because they touch overlapping files (Navbar, layout, QuoteForm). Doing them together avoids merge conflicts and lets Claude Code reason about the whole a11y surface.

P1 Form inputs not associated with labels — QuoteForm.tsx

WCAG: 2.1 AA · 1.3.1 Info and Relationships

Scope: All 9 input / select / textarea fields in the quote form.

P1 No focus-visible on nav, hero CTAs, footer, card links

WCAG: 2.1 AA · 2.4.7 Focus Visible

Strategy: One global rule in globals.css + targeted ring utilities on components that strip outline.

P1 Hamburger missing aria-expanded — Navbar.tsx

WCAG: 2.1 AA · 4.1.2 Name, Role, Value

P1 No skip-navigation link — layout.tsx

WCAG: 2.1 AA · 2.4.1 Bypass Blocks

P1 Language switcher has no accessible label

Fix: Dynamic aria-label per locale.

Claude Code prompt — accessibility sweep

You are running an accessibility hardening pass. Read each step carefully and make ONLY the changes described. Do not refactor anything else.

=====

STEP A — QuoteForm labels

=====

File: apps/web/src/app/[locale]/quote/QuoteForm.tsx

For every <label> + <input | select | textarea> pair, add a matching htmlFor on the label and id on the control. Use the existing `name` attribute as the id (kebab-case if needed). Example:

Before:

```
<label>Full name</label>
<input name="fullName" ... />
```

After:

```
<label htmlFor="fullName">Full name</label>
<input id="fullName" name="fullName" ... />
```

Repeat for all 9 fields.

=====

STEP B — Global focus-visible style

=====

File: apps/web/src/app/globals.css (or src/styles/globals.css – find it)

Append this rule at the end of the file:

```
@layer base {
  a:focus-visible,
  button:focus-visible,
  [role="button"]:focus-visible,
  summary:focus-visible {
    outline: 2px solid #E8B339;
    outline-offset: 3px;
    border-radius: 4px;
  }
}
```

Then, search the codebase for `focus:outline-none` and `focus-visible:outline-none` and report every file/line that contains them. Do NOT delete them – just list them so I can review.

=====

STEP C – Hamburger aria-expanded

=====

File: apps/web/src/components/Navbar.tsx

On the mobile hamburger <button>, add:
 aria-expanded={open}
 aria-controls="mobile-menu"

On the mobile menu container <div>, add:
 id="mobile-menu"

=====

STEP D – Skip-navigation link

=====

File: apps/web/src/app/[locale]/layout.tsx

As the FIRST child of <body>, add:

```
<a
  href="#main-content"
  className="sr-only focus:not-sr-only focus:absolute focus:top-4 focus:start-4 focus:z-50 focus:px-4 focus:py-4"
>
  Skip to content
</a>
```

Then find the <main> tag in the same file (or in the page template it wraps) and add: id="main-content".

If the project uses next-intl translations for this string, instead use:

```
{t('a11y.skipToContent')}
```

and add the key "skipToContent" to messages/en.json and messages/ar.json under an "a11y" namespace. English value: "Skip to content".

Arabic value: "تخطي المحتوى".

=====

STEP E – Language switcher aria-label

=====

File: apps/web/src/components/Navbar.tsx

On the locale switcher <a> or <Link>, add:
 aria-label={locale === 'en' ? 'Switch to Arabic' : 'تحويل إلى العربية'}

=====

FINISH

=====

After all five steps:

1. Run `pnpm tsc --noEmit` and `pnpm lint`. Paste the results.
2. Run `pnpm build`. Confirm it succeeds.
3. Output a SUMMARY listing every file you touched with a one-line description of the change.

Gemini Pro verification

You are an accessibility auditor. I will give you four file diffs: QuoteForm.tsx, Navbar.tsx, layout.tsx, globals.css.

Check that:

1. Every `<label>` in QuoteForm has `htmlFor` that matches an id on the next `input/select/textarea`. List any orphan label or unmatched id.
2. The hamburger button has `aria-expanded` bound to state AND `aria-controls` pointing at an id that actually exists on the menu container.
3. The skip link is the FIRST focusable child of `<body>` and targets an element with `id="main-content"`.
4. The focus-visible rule in `globals.css` applies to `a`, `button`, `[role=button]`, and `summary`, using `outline` (not `box-shadow`) so it works on dark backgrounds.
5. The locale switcher `aria-label` changes correctly between locales.

For each check, reply PASS or FAIL with the specific reason.

<paste the four diffs here>

Phase 3 · P1 — Performance (next/image migration)

P1

Service images use `<img>` not `<Image>` — ServicesGrid + services/page.tsx

Impact: 10 WebP files (140–600KB) load without lazy-loading, srcset, or format negotiation — services page renders them twice (~3MB).

Strategy: Migrate to `next/image`, set explicit width/height, mark above-the-fold icons with priority, leave the rest lazy.

Claude Code prompt

Goal: replace `<img>` with `next/image`'s `<Image>` for service icons.

Files in scope:

- `apps/web/src/components/sections/ServicesGrid.tsx`
- `apps/web/src/app/[locale]/services/page.tsx`

Rules:

1. Add at top: `import Image from "next/image";`
2. Replace every `` for service icons with `<Image ... />`, providing:
 - `width = 56 height = 56` (for the grid icon variant)
 - `width = 96 height = 96` (for the larger services/page.tsx variant)Preserve the original `className`.
3. Only the FIRST visible card in ServicesGrid above the fold should get `priority`. All others should rely on the default lazy behavior – do not pass `loading="lazy"` explicitly (Next handles this).
4. If alt text was empty or generic ("icon", "service"), replace it with the service's localized title. Use the existing `useTranslations` key already feeding the card's heading.
5. If `next.config.js` does not already have:

```
images: { formats: ["image/avif", "image/webp"] }
```

add that under the `images` key. If `images` doesn't exist, create it.
6. Run: `pnpm build` – confirm no image-related warnings.
7. Show me the diffs of all three files (component + page + config).

Verification (Lighthouse / DevTools)

- ✓ Open Network tab in production preview → service icons load as `/_next/image?...` with `image/avif` content-type on modern browsers.
- ✓ Lighthouse Performance score should rise ≥ 6 points on mobile profile.
- ✓ The grid icons should not appear in the initial waterfall when scrolled past the fold (lazy working).

Phase 4 · P2 — Theming & Tokens

P2 Hard-coded #25D366 WhatsApp green

Files: WhatsAppButton.tsx · Footer.tsx

Fix: Promote to a Tailwind token: whatsapp.

P2 Dot-grid background uses inline style with raw hex

File: HeroSection.tsx:19–23

Fix: Use theme(colors.gold.DEFAULT) via Tailwind's arbitrary value + theme().

Claude Code prompt

Tokenize two hard-coded colors.

STEP 1 – Add WhatsApp brand color as a Tailwind token

File: tailwind.config.base.js (or tailwind.config.ts – find it)

Under theme.extend.colors, add:

```
whatsapp: {  
  DEFAULT: "#25D366",  
  hover:   "#1FB855",  
}
```

STEP 2 – Use the new token

File: apps/web/src/components/WhatsAppButton.tsx

- Remove the inline style backgroundColor / style={{ background: "#25D366" }}.
- Apply className="bg-whatsapp hover:bg-whatsapp-hover".

File: apps/web/src/components/Footer.tsx (around line 59)

- Replace bg-[#25D366] with bg-whatsapp.

STEP 3 – Dot-grid background via theme()

File: apps/web/src/components/sections/HeroSection.tsx (lines 19–23)

Replace the inline style:

```
style={{ backgroundImage: "radial-gradient(#E8B339 1px, transparent 0)" }}
```

With a Tailwind arbitrary value using theme():

```
className="... bg-[radial-gradient(theme(colors.gold.DEFAULT)_1px,transparent_0)] bg-[length:24px_24px]"
```

(Move other dot-grid styling like background-size into Tailwind utilities.

If existing classes already set bg-size, keep them – do not duplicate.)

STEP 4 – Verify

Run: pnpm build

Visually confirm dot-grid still appears at the same density in the hero, and the WhatsApp buttons still render green in both Navbar/Footer and the floating CTA.

Show me the diff for all four files.

Phase 5 · P2 — Responsive Design

P2 Footer grid: 1 col → 4 col with no intermediate breakpoint

Fix: Add `sm:grid-cols-2 lg:grid-cols-4`.

P2 Hero h1 too large at mobile · three `<br/>` breaks at text-5xl

Fix: Drop explicit `<br/>` tags, scale `text-4xl` → `md:text-5xl` → `lg:text-6xl`.

Claude Code prompt

Two small responsive fixes.

STEP 1 — Footer breakpoint

File: `apps/web/src/components/Footer.tsx`

Find the grid container with class ``grid grid-cols-1 gap-10 lg:grid-cols-4``.

Change it to:

```
grid grid-cols-1 gap-10 sm:grid-cols-2 lg:grid-cols-4
```

STEP 2 — Hero h1 mobile sizing

File: `apps/web/src/components/sections/HeroSection.tsx`

Find the `<h1>` inside the hero. Currently it likely reads something like:

```
className="text-5xl ... font-bold"
```

and contains hard-coded `<br />` tags.

Replace as follows:

- `className="text-4xl md:text-5xl lg:text-6xl font-bold leading-tight whitespace-pre-line"`
- Remove the `<br />` tags. If the original Arabic/English copy needs visual line-breaks at large viewports only, instead wrap the section-breaking words in:

```
<span className="hidden lg:inline">...</span>
```

or replace each `<br />` with `"\n"` inside the translated string and rely on `whitespace-pre-line`.

After the change, manually inspect at three viewport widths:

- 375px (iPhone SE) - hero CTAs must be visible without scrolling
- 768px (iPad) - layout balanced, no overflow
- 1280px+ - looks identical to current desktop

Show me the diff and a one-sentence note about how you handled the line breaks.

Phase 6 · P2 — Polish (emoji → SVG, form alert role)

P2 Emoji as contact info icons — contact/page.tsx

Why: Screen readers verbalize emoji inconsistently (“*telephone receiver emoji*”). Also reads as an AI placeholder.

P3 QuoteForm success state uses ■ emoji

Fix: Inline SVG check + role="alert" so screen readers announce success automatically.

Claude Code prompt

Replace emoji with inline SVG icons in two places, and improve the form success announcement.

=====

STEP A — Contact page icons

=====

File: apps/web/src/app/[locale]/contact/page.tsx

Currently uses ■ ☎ ■ as visual markers. Replace each with an inline SVG. Use the standard Lucide / Heroicons-style 24px stroke icons. Place them as React components at the top of the file:

```
const PhoneIcon = () => (  
  <svg viewBox="0 0 24 24" fill="none" stroke="currentColor"  
    strokeWidth="1.8" strokeLinecap="round" strokeLinejoin="round"  
    className="w-6 h-6 text-gold" aria-hidden="true">  
    <path d="M22 16.92v3a2 2 0 0 1-2.18 2 19.79 19.79 0 0 1-8.63-3.07 19.5 19.5 0 0 1-6-19.79 19.79 0 0  
  </svg>  
  
const MailIcon = () => (  
  <svg viewBox="0 0 24 24" fill="none" stroke="currentColor"  
    strokeWidth="1.8" strokeLinecap="round" strokeLinejoin="round"  
    className="w-6 h-6 text-gold" aria-hidden="true">  
    <path d="M4 4h16c1.1 0 2 .9 2 2v12c0 1.1-.9 2-2 2H4c-1.1 0-2-.9-2-2V6c0-1.1-.9-2 2-2z"/>  
    <polyline points="22,6 12,13 2,6"/>  
  </svg>  
  
const PinIcon = () => (  
  <svg viewBox="0 0 24 24" fill="none" stroke="currentColor"  
    strokeWidth="1.8" strokeLinecap="round" strokeLinejoin="round"  
    className="w-6 h-6 text-gold" aria-hidden="true">  
    <path d="M21 10c0 7-9 13-9 13s-9-6-9-13a9 9 0 0 1 18 0z"/>  
    <circle cx="12" cy="10" r="3"/>  
  </svg>  

```

Render each in place of the corresponding emoji.

=====

STEP B — QuoteForm success

=====

File: apps/web/src/app/[locale]/quote/QuoteForm.tsx (line ~51 area)

Find the success state JSX (currently contains ■). Replace with:

```
<div role="alert" aria-live="polite"
  className="flex items-center gap-3 rounded-lg border border-gold/30
    bg-gold/10 px-4 py-3 text-gold">
  <svg viewBox="0 0 24 24" fill="none" stroke="currentColor"
    strokeWidth="2" strokeLinecap="round" strokeLinejoin="round"
    className="w-5 h-5 shrink-0" aria-hidden="true">
    <polyline points="20 6 9 17 4 12"/>
  </svg>
  <span>{t('form.successMessage')}
```

(If a different message key is in use, keep that – don't rename keys.)

=====

STEP C – Equipment tabs aria-pressed [P3]

=====

File: apps/web/src/components/sections/EquipmentCarousel.tsx

For each category tab <button>, add: aria-pressed={i === active}

=====

FINISH

=====

Run `pnpm tsc --noEmit` and `pnpm lint`. Paste the output and the diffs.

Phase 7 · P3 — Anti-Pattern Trim

P3 Universal staggered AnimatedSection on every card

Fix: Reserve animation for section headers + first row. Remove per-card stagger or cap it at 2–3 items.

P3 blur-3xl gradient blob — no GPU promotion + AI tell

Fix: Add will-change: transform, shrink to blur-2xl + h- [400px] w- [400px]. Optionally remove entirely for stronger anti-AI signal.

Claude Code prompt

Trim the AI-template tells without flattening the visual.

STEP 1 — Reduce AnimatedSection stagger

Files: ServicesGrid.tsx, WhyChooseUs.tsx, ProcessSection.tsx, TestimonialsSection.tsx

Current pattern: every card is wrapped in `<AnimatedSection delay={index * 0.1}>`.

New rule:

- Section header keeps its AnimatedSection.
- The card grid is wrapped ONCE as a unit (no per-card AnimatedSection).
OR — if per-card animation must stay — only the first 3 cards animate with delays 0, 0.08, 0.16. Cards 4+ render without AnimatedSection.

Refactor each of the four files to follow the second rule.

STEP 2 — GPU-promote the hero blur blob

File: apps/web/src/components/sections/HeroSection.tsx (line 24 area)

Find the absolutely-positioned div with blur-3xl. Update its className:

Before: "absolute ... h-[700px] w-[700px] ... blur-3xl"

After: "absolute ... h-[480px] w-[480px] ... blur-2xl will-change-transform [transform:translateZ(0)]"

This reduces paint area, isolates the element on its own compositing layer, and keeps the atmospheric look without the "gigantic gradient blob" AI tell.

STEP 3 — Verify

Run `pnpm build`, then check the hero in Chrome DevTools → Rendering → "Layer borders". The blur blob should now sit on its own composited layer.

Show me the diffs.

Phase 8 • Verification & Sign-off

After all phases, run a layered verification: Claude Code does the machine-checkable parts, Gemini Pro does the cross-read, you do the human spot-check.

Claude Code — final sweep

Final verification pass. Do these in order and stop at any failure:

1. `pnpm tsc --noEmit`
2. `pnpm lint`
3. `pnpm build`
4. Search the repo for these strings and report every occurrence with file + line:
 - `"useTranslations("` appearing inside a `"map("` callback
 - `"<img "`
 - `"#25D366"`
 - `"#E8B339"` outside `tailwind.config.*` and outside a SVG file
 - any `<label>` tag without an `htmlFor` attribute
 - any `focus:outline-none` NOT followed (within 80 chars) by `focus-visible:ring` or `focus-visible:outline`
 - `"■"` `"☒"` `"■"` `"■"` in any `.tsx` file under `apps/web`
5. Report a final table:
 - P0 fixed: yes/no
 - P1 fixed: count fixed / 6
 - P2 fixed: count fixed / 7
 - P3 fixed: count fixed / 4
6. If everything passes, commit with message:
 - `"fix(audit): impeccable pass-1 – a11y, perf, theming, polish"`
 Do NOT push. Wait for my confirmation.

Gemini Pro — independent review

You are an independent senior reviewer. I performed an Impeccable audit on a Next.js bilingual site and applied fixes across 18 findings (1 P0, 6 P1, 7 P2, 4 P3).

Below is the full diff between branch ``main`` and branch ``fix/impeccable-audit-pass-1``. Review it against these criteria:

ACCESSIBILITY

- `htmlFor/id` pairs on every form control
- `aria-expanded` on hamburger
- `aria-pressed` on equipment tabs
- `aria-label` on locale switcher
- `skip-to-content` link as first body child
- global `focus-visible` style applied
- `role="alert"` on form success

PERFORMANCE

- `next/image` used for service icons
- GPU promotion on blur blob
- hooks not called in loops

THEMING

- whatsapp Tailwind token introduced and consumed
- `dot-grid` uses `theme()` call

RESPONSIVE

- footer grid has `sm:grid-cols-2`
- hero `h1` scales `4xl` → `5xl` → `6xl`, no hard `<br />`

ANTI-PATTERNS

- per-card stagger trimmed
- blur blob smaller + GPU-promoted

For each criterion: PASS / FAIL / PARTIAL with the file:line evidence.
End with an overall recommendation: ship / revise / re-audit.

<paste the diff here>

Manual smoke-test checklist

01. Tab from page top — first stop is the skip link, second is the logo.
02. Open hamburger menu with keyboard — screen reader announces “expanded”.
03. Submit the quote form — success message is announced by VoiceOver/NVDA.
04. Switch language — focus stays in a reasonable place, aria-label updates.
05. Throttle network to Slow 4G in DevTools — service icons load lazy/AVIF.
06. Toggle Reduce Motion in OS — staggered entrance animations are subdued.
07. Run Lighthouse mobile profile — Accessibility ≥ 95 , Performance ≥ 85 .
08. Re-run Impeccable audit — expect score 19/20 (Anti-Patterns may stay 3/4).

Tip: If the Anti-Patterns score doesn't reach 4/4 after this pass, the remaining tell is the hero stat metrics block (25+, 400+, 40+, 200+). Consider replacing it with a single signature claim + one supporting client logo strip — a much stronger anti-AI move than tuning numbers.

End of Plan

Built for Mohammed Abotargah · Fikratak Digital · Technical Entrepreneurship 2026
Re-run /impeccable audit after the commit to confirm the 12 → 19 lift.