

# Assignment 9.1\_BasitAbdul

October 28, 2022

## 0.1 Assignment 9.1

```
[1]: import os
import shutil
import json
from pathlib import Path

import pandas as pd

from kafka import KafkaProducer, KafkaAdminClient
from kafka.admin.new_topic import NewTopic
from kafka.errors import TopicAlreadyExistsError

from pyspark.sql import SparkSession
from pyspark.streaming import StreamingContext
from pyspark import SparkConf
from pyspark.sql.functions import window, from_json, col
from pyspark.sql.types import StringType, TimestampType, DoubleType, \
    StructField, StructType
from pyspark.sql.functions import udf

[2]: current_dir = Path(os.getcwd()).absolute()
checkpoint_dir = current_dir.joinpath('checkpoints')
locations_checkpoint_dir = checkpoint_dir.joinpath('locations')
accelerations_checkpoint_dir = checkpoint_dir.joinpath('accelerations')

if locations_checkpoint_dir.exists():
    shutil.rmtree(locations_checkpoint_dir)

if accelerations_checkpoint_dir.exists():
    shutil.rmtree(accelerations_checkpoint_dir)

locations_checkpoint_dir.mkdir(parents=True, exist_ok=True)
accelerations_checkpoint_dir.mkdir(parents=True, exist_ok=True)
```

### 0.1.1 Configuration Parameters

**TODO:** Change the configuration parameters to the appropriate values for your setup.

```
[3]: config = dict(
    bootstrap_servers=['kafka.kafka.svc.cluster.local:9092'],
    first_name='Abdul',
    last_name='Basit'
)

config['client_id'] = '{}-{}'.format(
    config['last_name'],
    config['first_name']
)
config['topic_prefix'] = '{}-{}'.format(
    config['last_name'],
    config['first_name']
)

config['locations_topic'] = '{}-locations'.format(config['topic_prefix'])
config['accelerations_topic'] = '{}-accelerations'.
    ↪format(config['topic_prefix'])
config['simple_topic'] = '{}-simple'.format(config['topic_prefix'])

config
```

```
[3]: {'bootstrap_servers': ['kafka.kafka.svc.cluster.local:9092'],
      'first_name': 'Abdul',
      'last_name': 'Basit',
      'client_id': 'BasitAbdul',
      'topic_prefix': 'BasitAbdul',
      'locations_topic': 'BasitAbdul-locations',
      'accelerations_topic': 'BasitAbdul-accelerations',
      'simple_topic': 'BasitAbdul-simple'}
```

### 0.1.2 Create Topic Utility Function

The `create_kafka_topic` helps create a Kafka topic based on your configuration settings. For instance, if your first name is *John* and your last name is *Doe*, `create_kafka_topic('locations')` will create a topic with the name `DoeJohn-locations`. The function will not create the topic if it already exists.

```
[4]: def create_kafka_topic(topic_name, config=config, num_partitions=1,
    ↪replication_factor=1):
    bootstrap_servers = config['bootstrap_servers']
    client_id = config['client_id']
    topic_prefix = config['topic_prefix']
    name = '{}-{}'.format(topic_prefix, topic_name)

    admin_client = KafkaAdminClient(
        bootstrap_servers=bootstrap_servers,
```

```

        client_id=client_id
    )

    topic = NewTopic(
        name=name,
        num_partitions=num_partitions,
        replication_factor=replication_factor
    )

    topic_list = [topic]
    try:
        admin_client.create_topics(new_topics=topic_list)
        print('Created topic "{}"'.format(name))
    except TopicAlreadyExistsError as e:
        print('Topic "{}" already exists'.format(name))

create_kafka_topic('simple')

```

Topic "BasitAbdul-simple" already exists

```

[5]: spark = SparkSession\
      .builder\
      .appName("Assignment09")\
      .getOrCreate()

df_locations = spark \
    .readStream \
    .format("kafka") \
    .option("kafka.bootstrap.servers", "kafka.kafka.svc.cluster.local:9092") \
    .option("subscribe", config['locations_topic']) \
    .load()

```

**TODO:** Create a data frame called `df_accelerations` that reads from the `accelerations` topic you published to in assignment 8. In order to read data from this topic, make sure that you are running the notebook you created in assignment 8 that publishes acceleration and location data to the `LastNameFirstname-simple` topic.

```

[6]: df_accelerations = spark.readStream.format("kafka")\
      .option("kafka.bootstrap.servers", "localhost:9092")\
      .option("subscribe", config['accelerations_topic'])\
      .option("startingOffsets", "earliest")\
      .option("includeHeaders", "true")\
      .load()

```

**TODO:** Create two streaming queries, `ds_locations` and `ds_accelerations` that publish to the `LastNameFirstname-simple` topic. See <http://spark.apache.org/docs/latest/structured-streaming-programming-guide.html#starting-streaming-queries> and <http://spark.apache.org/docs/latest/structured-streaming-kafka->

integration.html for more information.

```
[7]: ds_locations = df_locations.writeStream \
      .format("kafka") \
      .option("checkpointLocation", locations_checkpoint_dir) \
      .option("kafka.bootstrap.servers", config['bootstrap_servers'][0]) \
      .option("topic", config['simple_topic']) \
      .start()

      ds_accelerations = df_locations.writeStream \
      .format("kafka") \
      .option("checkpointLocation", locations_checkpoint_dir) \
      .option("kafka.bootstrap.servers", config['bootstrap_servers'][0]) \
      .option("topic", config['simple_topic']) \
      .start()
      try:
          ds_locations.awaitTermination()
          ds_accelerations.awaitTermination()
      except KeyboardInterrupt:
          print("STOPPING STREAMING DATA")
```

STOPPING STREAMING DATA

```
[ ]:
```